#### PARALLEL TOPOLOGICAL SORTING

Design of High Performance Computing, Fall 2015

Kevin Wallimann Johannes Baum Matthias Untergassmair

ETH Zürich

November 2, 2015

### PROBLEM DESCRIPTION

INPUT Directed acyclic graph (DAG) with N nodes Output Topological Sortings of DAG


# "Efficient" Parallel and Distributed Topological Sort Algorithms

- Runtime:  $\mathcal{O}(\log^2 N)$
- Reduces to matrix-matrix multiplication problem

#### PROBLEM:

 $\mathcal{O}(N^3)$  execution units required

#### UML DIAGRAM



### SERIAL CODE


```
std::list<Node*> currentnodes;
Node* parent;
Node* child;
unsigned childcount = 0;
unsigned currentvalue = 0;
```

### SERIAL CODE

```
std::list<Node*> currentnodes;
Node* parent;
Node* child:
unsigned childcount = 0:
unsigned currentvalue = 0:
while(!currentnodes.empty()) { // stop when queue is empty
    parent = currentnodes.front();
    currentnodes.pop_front(): // remove current node - already visited
    currentvalue = parent->getValue():
    ++currentvalue: // increase value for child nodes
    childcount = parent->getChildCount();
    for(unsigned i=0: i<childcount: ++i) {</pre>
        child = parent->getChild(i);
        currentnodes.push_back(child); // add child node at end of queue
        child->setValue(currentvalue): // set value of child node to parentvalue+1
```


### PARALLELIZATION IDEAS

- Start in parallel at source nodes
- Spawn a new thread for every child node
- Synchronization needed when a node has multiple parents
- Performance dependent on topology of graph. Worst case  $\mathcal{O}(n)$



#### SYNCHRONIZATION IDEAS

- Each thread enumerates the nodes it visits.
- If a node already has a number, take the higher number
- Problem: Multiple threads might "follow" each other.
- Idea: Only last thread arriving at a node may continue.



# HARDWARE / TOOLS

- Shared memory parallelization
- OpenMP or C++11 threads.
- On Euler: 12-core Intel Xeon E5
- Intel Xeon Phi

### CHALLENGES

- Task queue
- Find a way to cope with chain-like graphs.
- Optional goal: Find all possible topological sortings.

# QUESTIONS

- Up to how many execution units should we parallelize at least?
- From your experience, what are the main time-consuming, maybe unexpected obstacles when running on Intel Xeon Phi?