

Dimensionality Reduction: SVD and its applications


Viet-Trung Tran

Credits

- Mining of Massive Datasets
 - Jure Leskovec, Anand Rajaraman, Jeff Ullman Stanford University
 - <http://www.mmds.org>
- Data mining coursera


Motivation

- Data compression
 - Redundancy features
 - Combine features



Reduce features from 2D to 1D

Reduce data from 3D to 2D



Speed up learning algorithms


Better data visualization

Country	GDP (trillions of US\$)	Per capita GDP (thousands of intl. \$)	Human Develop- ment Index	Life expectancy	Poverty Index (Gini as percentage)	Mean household income (thousands of US\$)	...
Canada	1.577	39.17	0.908	80.7	32.6	67.293	...
China	5.878	7.54	0.687	73	46.9	10.22	...
India	1.632	3.41	0.547	64.7	36.8	0.735	...
Russia	1.48	19.84	0.755	65.5	39.9	0.72	...
Singapore	0.223	56.69	0.866	80	42.5	67.1	...
USA	14.527	46.86	0.91	78.3	40.8	84.3	...
...


[resources from en.wikipedia.org]

Reduce to 2D

Country		
Canada	1.6	1.2
China	1.7	0.3
India	1.6	0.2
Russia	1.4	0.5
Singapore	0.5	1.7
USA	2	1.5
...



Dimensionality Reduction



- **Assumption:** Data lies on or near a low d -dimensional subspace
- **Axes of this subspace are effective representation of the data**

Rank of a Matrix


- **Q:** What is **rank** of a matrix **A**?
- **A:** Number of **linearly independent** columns of **A**
- **For example:**
 - Matrix **A** = $\begin{bmatrix} 1 & 2 & 1 \\ -2 & -3 & 1 \\ 3 & 5 & 0 \end{bmatrix}$ has rank **r=2**
 - **Why?** The first two rows are linearly independent, so the rank is at least 2, but all three rows are linearly dependent (the first is equal to the sum of the second and third) so the rank must be less than 3.
- **Why do we care about low rank?**
 - We can write **A** as two “basis” vectors: $[1 \ 2 \ 1] \ [-2 \ -3 \ 1]$
 - And new coordinates of : $[1 \ 0] \ [0 \ 1] \ [1 \ 1]$

Rank is “Dimensionality”

- **Cloud of points 3D space:**

- Think of point positions as a matrix:

1 row per point:
$$\begin{bmatrix} 1 & 2 & 1 \\ -2 & -3 & 1 \\ 3 & 5 & 0 \end{bmatrix} \begin{matrix} \mathbf{A} \\ \mathbf{B} \\ \mathbf{C} \end{matrix}$$




- **We can rewrite coordinates more efficiently!**

- Old basis vectors: $[1 \ 0 \ 0] \ [0 \ 1 \ 0] \ [0 \ 0 \ 1]$
- **New basis vectors:** $[1 \ 2 \ 1] \ [-2 \ -3 \ 1]$
- Then **A** has new coordinates: $[1 \ 0]$. **B**: $[0 \ 1]$, **C**: $[1 \ 1]$
 - Notice: We reduced the number of coordinates!

Dimensionality Reduction

- Goal of dimensionality reduction is to discover the axis of data!




Rather than representing every point with 2 coordinates we represent each point with 1 coordinate (corresponding to the position of the point on the red line).

By doing this we incur a bit of **error** as the points do not exactly lie on the line

Sum up

Why reduce dimensions?

- **Discover hidden correlations/topics**
 - Words that occur commonly together
- **Remove redundant and noisy features**
 - Not all words are useful
- **Interpretation and visualization**
- **Easier storage and processing of the data**



SVD - Definition

$$\mathbf{A}_{[m \times n]} = \mathbf{U}_{[m \times r]} \mathbf{\Sigma}_{[r \times r]} (\mathbf{V}_{[n \times r]})^T$$

- **A: Input data matrix**
 - $m \times n$ matrix (e.g., m documents, n terms)
- **U: Left singular vectors**
 - $m \times r$ matrix (m documents, r concepts)
- **Σ : Singular values**
 - $r \times r$ diagonal matrix (strength of each 'concept')
(r : rank of the matrix **A**)
- **V: Right singular vectors**
 - $n \times r$ matrix (n terms, r concepts)


SVD - Properties

It is **always** possible to decompose a real matrix **A** into **$A = U \Sigma V^T$** , where

- **U, Σ, V** : unique
- **U, V** : column orthonormal
 - $U^T U = I; V^T V = I$ (I : identity matrix)
 - (Columns are orthogonal unit vectors)
- **Σ** : diagonal
 - Entries (**singular values**) are positive, and sorted in decreasing order ($\sigma_1 \geq \sigma_2 \geq \dots \geq 0$)

SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example: Users to Movies



SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example: Users to Movies

Matrix

Alien

Serenity

Casablanca

Amelie

SciFi

Romnce

$$\begin{bmatrix}
 1 & 1 & 1 & 0 & 0 \\
 3 & 3 & 3 & 0 & 0 \\
 4 & 4 & 4 & 0 & 0 \\
 5 & 5 & 5 & 0 & 0 \\
 0 & 2 & 0 & 4 & 4 \\
 0 & 0 & 0 & 5 & 5 \\
 0 & 1 & 0 & 2 & 2
 \end{bmatrix}
 =
 \begin{bmatrix}
 0.13 & 0.02 & -0.01 \\
 0.41 & 0.07 & -0.03 \\
 0.55 & 0.09 & -0.04 \\
 0.68 & 0.11 & -0.05 \\
 0.15 & -0.59 & 0.65 \\
 0.07 & -0.73 & -0.67 \\
 0.07 & -0.29 & 0.32
 \end{bmatrix}
 \times
 \begin{bmatrix}
 12.4 & 0 & 0 \\
 0 & 9.5 & 0 \\
 0 & 0 & 1.3
 \end{bmatrix}
 \times
 \begin{bmatrix}
 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\
 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\
 0.40 & -0.80 & 0.40 & 0.09 & 1.09
 \end{bmatrix}$$

SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example: Users to Movies

Diagram illustrating the SVD decomposition of a User-Movie rating matrix A into three matrices: U , Σ , and V^T .

Matrix A (User-Movie Ratings):

	Matrix	Alien	Serenity	Casablanca	Amelie
SciFi	1	1	1	0	0
	3	3	3	0	0
	4	4	4	0	0
	5	5	5	0	0
Romnce	0	2	0	4	4
	0	0	0	5	5
	0	1	0	2	2

Matrix U (User-Concept Loadings):

	SciFi-concept	Romance-concept	
SciFi	0.13	0.02	-0.01
	0.41	0.07	-0.03
	0.55	0.09	-0.04
	0.68	0.11	-0.05
Romnce	0.15	-0.59	0.65
	0.07	-0.73	-0.67
	0.07	-0.29	0.32

Matrix Σ (Singular Values):

12.4	0	0
0	9.5	0
0	0	1.3

Matrix V^T (Movie-Concept Loadings):

0.56	0.59	0.56	0.09	0.09
0.12	-0.02	0.12	-0.69	-0.69
0.40	-0.80	0.40	0.09	16.09

The decomposition is shown as:

$$A = U \Sigma V^T$$

SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example: U is “user-to-concept” similarity matrix

Matrix Alien Serenity Casablanca Amelie

SciFi ↑ ↓ ↑ ↓ ↑ ↓

Romnce ↑ ↓ ↑ ↓ ↑ ↓

$$\begin{bmatrix}
 1 & 1 & 1 & 0 & 0 \\
 3 & 3 & 3 & 0 & 0 \\
 4 & 4 & 4 & 0 & 0 \\
 5 & 5 & 5 & 0 & 0 \\
 0 & 2 & 0 & 4 & 4 \\
 0 & 0 & 0 & 5 & 5 \\
 0 & 1 & 0 & 2 & 2
 \end{bmatrix}
 =
 \begin{bmatrix}
 0.13 & 0.02 & -0.01 \\
 0.41 & 0.07 & -0.03 \\
 0.55 & 0.09 & -0.04 \\
 0.68 & 0.11 & -0.05 \\
 0.15 & -0.59 & 0.65 \\
 0.07 & -0.73 & -0.67 \\
 0.07 & -0.29 & 0.32
 \end{bmatrix}
 \times
 \begin{bmatrix}
 12.4 & 0 & 0 \\
 0 & 9.5 & 0 \\
 0 & 0 & 1.3
 \end{bmatrix}
 \times
 \begin{bmatrix}
 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\
 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\
 0.40 & -0.80 & 0.40 & 0.09 & 1.09
 \end{bmatrix}$$

SciFi-concept Romance-concept

SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example:

Diagram illustrating the SVD decomposition of a user-movie rating matrix A into U , Σ , and V^T .

Matrix A (User-Movie Ratings):

	Matrix	Alien	Serenity	Casablanca	Amelie
SciFi	1	1	1	0	0
	3	3	3	0	0
	4	4	4	0	0
	5	5	5	0	0
	0	2	0	4	4
Romnce	0	0	0	5	5
	0	1	0	2	2

Matrix U (User-Concepts):

	SciFi-concept		
SciFi	0.13	0.02	-0.01
	0.41	0.07	-0.03
	0.55	0.09	-0.04
	0.68	0.11	-0.05
	0.15	-0.59	0.65
Romnce	0.07	-0.73	-0.67
	0.07	-0.29	0.32

Matrix Σ (Singular Values):

12.4	0	0
0	9.5	0
0	0	1.3

Matrix V^T (Movie-Concepts):


0.56	0.59	0.56	0.09	0.09
0.12	-0.02	0.12	-0.69	-0.69
0.40	-0.80	0.40	0.09	1.09

Annotations:

- Green arrows on the left indicate the **SciFi** (up) and **Romnce** (down) dimensions for the matrix A .
- A blue arrow points to the **SciFi-concept** column in matrix U .
- A blue circle highlights the value **12.4** in matrix Σ , with a label "strength" of the SciFi-concept pointing to it.
- Green 'X' marks are placed between matrix U and matrix Σ , and between matrix Σ and matrix V^T .

SVD – Example: Users-to-Movies

- $A = U \Sigma V^T$ - example:



SVD - Interpretation #1

‘**movies**’, ‘**users**’ and ‘**concepts**’:

- U : user-to-concept similarity matrix
- V : movie-to-concept similarity matrix
- Σ : its diagonal elements:
‘strength’ of each concept


"Simple" concept

Matrix	Alien	Serenity	Casablanca	Amelie		sci-fi	romance	
1	1	1	0	0	user 1	.14	0	$\begin{bmatrix} 12.4 & 0 \\ 0 & 9.5 \end{bmatrix} \begin{bmatrix} .58 & .58 & .58 & 0 & 0 \\ 0 & 0 & 0 & .71 & .71 \end{bmatrix}$
3	3	3	0	0	user 2	.42	0	
4	4	4	0	0	user 3	.56	0	
5	5	5	0	0	user 4	.70	0	
0	0	0	4	4	user 5	0	.60	
0	0	0	5	5	user 6	0	.75	
0	0	0	2	2	user 7	0	.30	

M
 U
 Σ
 V^T

Dimensionality Reduction with SVD

SVD – Dimensionality Reduction



- Instead of using two coordinates to describe point locations, let's use only one coordinate
- Point's position is its location along vector
- **How to choose ? Minimize reconstruction error**

SVD - Interpretation #2


- **$A = U \Sigma V^T$ - example:**

- **V** : “movie-to-concept” matrix
- **U** : “user-to-concept” matrix

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} = \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times$$

$$\begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & 1.3 \end{bmatrix} \times$$

$$\begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 0.09 \end{bmatrix}$$



SVD - Interpretation #2


- $A = U \Sigma V^T$ - example:

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} = \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times$$

$$\begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & 1.3 \end{bmatrix} \times$$

$$\begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 0.09 \end{bmatrix}$$

variance ('spread')
on the v_1 axis




SVD - Interpretation #2

$A = U \Sigma V^T$ - example:

- $U \Sigma$: Gives the coordinates of the points in the projection axis

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix}$$

Projection of users
on the “Sci-Fi” axis
($U \Sigma$)^T:



1.61	0.19	-0.01
5.08	0.66	-0.03
6.82	0.85	-0.05
8.43	1.04	-0.06
1.86	-5.60	0.84
0.86	-6.93	-0.87
0.86	-2.75	0.41

SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} = \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times \begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & 1.3 \end{bmatrix} \times \begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 0.09 \end{bmatrix}$$

SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?
- **A:** Set smallest singular values to zero

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} = \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times \begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & \cancel{1.3} \end{bmatrix} \times \begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 0.09 \end{bmatrix}$$



SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?
- **A:** Set smallest singular values to zero

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} \approx \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times \begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & \cancel{1.3} \end{bmatrix} \times \begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 20.09 \end{bmatrix}$$

SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?
- **A:** Set smallest singular values to zero

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} \approx \begin{bmatrix} 0.13 & 0.02 & -0.01 \\ 0.41 & 0.07 & -0.03 \\ 0.55 & 0.09 & -0.04 \\ 0.68 & 0.11 & -0.05 \\ 0.15 & -0.59 & 0.65 \\ 0.07 & -0.73 & -0.67 \\ 0.07 & -0.29 & 0.32 \end{bmatrix} \times \begin{bmatrix} 12.4 & 0 & 0 \\ 0 & 9.5 & 0 \\ 0 & 0 & 1.3 \end{bmatrix} \times \begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\ 0.40 & -0.80 & 0.40 & 0.09 & 0.09 \end{bmatrix}$$

The diagram illustrates the SVD decomposition of a matrix. The first matrix is a 7x5 matrix. The second matrix is a 7x3 matrix, with its third column crossed out by a red 'X'. The third matrix is a 3x3 diagonal matrix, with its third row and column crossed out by a red 'X'. The fourth matrix is a 3x5 matrix, with its third row and column crossed out by a red 'X'. The result of the multiplication is a 7x5 matrix, with its third row and column crossed out by a red 'X'.

SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?
- **A:** Set smallest singular values to zero

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} \approx \begin{bmatrix} 0.13 & 0.02 \\ 0.41 & 0.07 \\ 0.55 & 0.09 \\ 0.68 & 0.11 \\ 0.15 & -0.59 \\ 0.07 & -0.73 \\ 0.07 & -0.29 \end{bmatrix} \times \begin{bmatrix} 12.4 & 0 \\ 0 & 9.5 \end{bmatrix} \times \begin{bmatrix} 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\ 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \end{bmatrix}$$

SVD - Interpretation #2

More details

- **Q:** How exactly is dim. reduction done?
- **A:** Set smallest singular values to zero

$$\begin{bmatrix} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{bmatrix} \approx \begin{bmatrix} 0.92 & 0.95 & 0.92 & 0.01 & 0.01 \\ 2.91 & 3.01 & 2.91 & -0.01 & -0.01 \\ 3.90 & 4.04 & 3.90 & 0.01 & 0.01 \\ 4.82 & 5.00 & 4.82 & 0.03 & 0.03 \\ 0.70 & 0.53 & 0.70 & 4.11 & 4.11 \\ -0.69 & 1.34 & -0.69 & 4.78 & 4.78 \\ 0.32 & 0.23 & 0.32 & 2.01 & 2.01 \end{bmatrix}$$

SVD - Interpretation #2

Q: How many σ_s to keep?

A: Rule-of-a thumb:

keep 80-90% of 'energy'

$$\sum_i d_i^2$$

$$\begin{array}{c} \updownarrow n \\ \left[\begin{array}{ccccc} 1 & 1 & 1 & 0 & 0 \\ 3 & 3 & 3 & 0 & 0 \\ 4 & 4 & 4 & 0 & 0 \\ 5 & 5 & 5 & 0 & 0 \\ 0 & 2 & 0 & 4 & 4 \\ 0 & 0 & 0 & 5 & 5 \\ 0 & 1 & 0 & 2 & 2 \end{array} \right] \end{array} \begin{array}{c} \leftarrow m \rightarrow \\ \\ \\ \\ \\ \\ \end{array} = \sigma_1 \mathbf{u}_1 \mathbf{v}_1^T + \sigma_2 \mathbf{u}_2 \mathbf{v}_2^T + \dots$$

Assume: $\sigma_1 \geq \sigma_2 \geq \sigma_3 \geq \dots$

SVD - Conclusions so far

- **SVD:** $A = U \Sigma V^T$: **unique**
 - **U**: user-to-concept similarities
 - **V**: movie-to-concept similarities
 - Σ : strength of each concept
- **Dimensionality reduction:**
 - keep the few largest singular values (80-90% of 'energy')
 - SVD: picks up linear correlations

Example of SVD & Conclusion

Case study: How to query?

- **Q: Find users that like 'Matrix'**
- **A: Map query into a 'concept space' – how?**

Diagram illustrating the mapping of a query into a concept space for finding users that like 'Matrix'.

Matrix (Query) is mapped to a concept space using the following matrix:

$$\begin{bmatrix}
 1 & 1 & 1 & 0 & 0 \\
 3 & 3 & 3 & 0 & 0 \\
 4 & 4 & 4 & 0 & 0 \\
 5 & 5 & 5 & 0 & 0 \\
 0 & 2 & 0 & 4 & 4 \\
 0 & 0 & 0 & 5 & 5 \\
 0 & 1 & 0 & 2 & 2
 \end{bmatrix}$$

The matrix is annotated with vertical labels: **SciFi** (up arrow) and **Romnce** (down arrow) on the left, and **Matrix**, **Alien**, **Serenity**, **Casablanca**, and **Amelie** on the right.

This matrix is multiplied by the following matrix:

$$\begin{bmatrix}
 0.13 & 0.02 & -0.01 \\
 0.41 & 0.07 & -0.03 \\
 0.55 & 0.09 & -0.04 \\
 0.68 & 0.11 & -0.05 \\
 0.15 & -0.59 & 0.65 \\
 0.07 & -0.73 & -0.67 \\
 0.07 & -0.29 & 0.32
 \end{bmatrix}$$

The result is multiplied by the following matrix:

$$\begin{bmatrix}
 12.4 & 0 & 0 \\
 0 & 9.5 & 0 \\
 0 & 0 & 1.3
 \end{bmatrix}$$

The final result is a 7x5 matrix:

$$\begin{bmatrix}
 0.56 & 0.59 & 0.56 & 0.09 & 0.09 \\
 0.12 & -0.02 & 0.12 & -0.69 & -0.69 \\
 0.40 & -0.80 & 0.40 & 0.09 & 0.09
 \end{bmatrix}$$


The value **36** is highlighted in yellow in the bottom right corner of the final matrix.

Case study: How to query?

- **Q: Find users that like 'Matrix'**
- **A: Map query into a 'concept space' – how?**

$$\mathbf{q} = \begin{bmatrix} \text{Matrix} \\ 5 \\ \text{Alien} \\ 0 \\ \text{Serenity} \\ 0 \\ \text{Casablanca} \\ 0 \\ \text{Amelie} \\ 0 \end{bmatrix}$$

Project into concept space:
Inner product with each
'concept' vector \mathbf{v}_i




Case study: How to query?

- **Q: Find users that like 'Matrix'**
- **A: Map query into a 'concept space' – how?**

$$\mathbf{q} = \begin{bmatrix} \text{Matrix} \\ 5 \\ \text{Alien} \\ 0 \\ \text{Serenity} \\ 0 \\ \text{Casablanca} \\ 0 \\ \text{Amelie} \\ 0 \end{bmatrix}$$

Project into concept space:
Inner product with each
'concept' vector \mathbf{v}_i



Case study: How to query?

Compactly, we have:

$$\mathbf{q}_{\text{concept}} = \mathbf{q} \mathbf{V}$$

E.g.:

$$\mathbf{q} = \begin{matrix} & \begin{matrix} \text{Matrix} \\ \text{Alien} \\ \text{Serenity} \\ \text{Casablanca} \\ \text{Amelie} \end{matrix} \\ \begin{bmatrix} 5 & 0 & 0 & 0 & 0 \end{bmatrix} \end{matrix} \times \begin{matrix} \begin{bmatrix} 0.56 & 0.12 \\ 0.59 & -0.02 \\ 0.56 & 0.12 \\ 0.09 & -0.69 \\ 0.09 & -0.69 \end{bmatrix} \\ \text{movie-to-concept} \\ \text{similarities (V)} \end{matrix} = \begin{matrix} \text{SciFi-concept} \\ \downarrow \\ \begin{bmatrix} 2.8 & 0.6 \end{bmatrix} \end{matrix}$$

Case study: How to query?

- How would the user d that rated ('Alien', 'Serenity') be handled?

$$\mathbf{d}_{\text{concept}} = \mathbf{d} \mathbf{V}$$

E.g.:


$$\mathbf{q} = \begin{bmatrix} \text{Matrix} \\ 0 & 4 & 5 & 0 & 0 \end{bmatrix} \mathbf{x} \begin{bmatrix} 0.56 & 0.12 \\ 0.59 & -0.02 \\ 0.56 & 0.12 \\ 0.09 & -0.69 \\ 0.09 & -0.69 \end{bmatrix} = \begin{bmatrix} 5.2 & 0.4 \end{bmatrix}$$

movie-to-concept
similarities (V)

SciFi-concept
↓

Case study: How to query?

- Observation:** User d that rated ('*Alien*', '*Serenity*') will be **similar** to user q that rated ('*Matrix*'), although d and q have **zero ratings in common!**



SVD in Latent semantic indexing and analysis

Latent Semantic Indexing

- Term-document matrices are very large
- But the number of topics that people talk about is small (in some sense)
 - Clothes, movies, politics, ...
- Can we represent the term-document space by a lower dimensional latent space?

Idea

- From term-doc matrix A , we compute the approximation A_k .
- There is a row for each term and a column for each doc in A_k
- Thus docs live in a space of $k \ll r$ dimensions
 - These dimensions are not the original axes
- But why?

Image compression using SVD

Image as matrix

- Reduced SVD applied to keep most features



300 terms (rank)



Original image




10 terms





50 terms

Principle component analysis

Problem formulation



Problem formulation



$$\begin{aligned} 3D &\rightarrow 2D \\ K &= 2 \end{aligned}$$

Reduce from 2-dimension to 1-dimension: Find a direction (a vector $u^{(1)} \in \mathbb{R}^n$) onto which to project the data so as to minimize the projection error.

Reduce from n -dimension to k -dimension: Find k vectors $u^{(1)}, u^{(2)}, \dots, u^{(k)}$ onto which to project the data, so as to minimize the projection error.

PCA algorithm

Reduce data from n -dimensions to k -dimensions

Compute “covariance matrix”:

$$\frac{1}{m} \sum_{i=1}^m (x^{(i)})(x^{(i)})^T$$

Compute “eigenvectors” of matrix Σ :

$[U, S, V] = \text{svd}(\text{Sigma})$;

From $[U, S, V] = \text{svd}(\text{Sigma})$, we get:

$$U = \begin{bmatrix} | & | & & | \\ u^{(1)} & u^{(2)} & \dots & u^{(n)} \\ | & | & & | \end{bmatrix} \in \mathbb{R}^{n \times n}$$