

Blog Reference

<https://mattvarghese-cs.blogspot.com/2022/01/minimal-typescript-react-project.html>

Why?

I've seen developers commit entire `node_modules` folders into source control!! And I have also realized that the `create-react-app` template is somewhat mysterious and a bit bloated?

What I am trying to do

In this exercise, I explain the process of creating a TypeScript React app, plugged into Visual Studio Code, and supporting active debugging in Visual Studio Code, from scratch, and which works both in Linux and Windows.

I have seen developers commit entire `node_modules` folders into source control. That is terrifying! And I think the mystery behind “`create-react-app`” is part of what contributes to this kind of behavior(?). So I figured, I'll learn how to do this from scratch, and having done that, I am documenting my observations in this tutorial / blog post / document.

License

This project template and all documentation is released under GNU GPL v3:

<https://www.gnu.org/licenses/gpl-3.0.en.html>

Git Repository

If all you care is to get a minimal TypeScript React Template setup for use with Visual Studio Code in both Linux and Windows, you can get the result of this exercise from

<https://github.com/mattvarghese/minimal-typescript-react-template>

Downloading code

Have Git installed. Then

\$ git clone <https://github.com/mattvarghese/minimal-typescript-react-template.git>

Open the resulting `minimal-typescript-react-template` folder in Visual Studio Code

To run development server

In Visual Studio Code (VSCode) > Terminal > Run Task > *npm: start*

This will pull node_modules and do necessary compilation and start development server. It will also open your default browser and navigate to the App

Be sure once you're done to use CTRL+C in the VSCode terminal to exit out of the development server.

To debug with VSCode

You have to be running development server to debug using VSCode. Follow steps above. Then,

Open App.tsx, and put a breakpoint inside the App function, or wherever you desire.

In VSCode, on the left margin, Click the tab/button for "Run and Debug (CTRL+SHIFT+D)"

On the top, just below the menu bar, click the green "Launch Chrome" button

Chrome will launch to the App URL, and your breakpoint will hit. When you click continue for your breakpoint, the App loads inside Chrome.

As called out, be sure to close the development server using CTRL+C in the VSCode terminal

Other browsers for debugging

Chromium browser has been added for support for raspberry pi where neither chrome nor edge are available. You must have chromium-browser installed to use this

```
sudo apt install chromium-browser
```

Microsoft Edge has also been added, because why not?

To Build and Run production

Do VSCode > Terminal menu > Run Build Task, **or** VSCode > Terminal Menu > Run Task > *npm: build*

This builds the code into ~/dist folder.

If you haven't installed "serve" yet, do so by

```
$ sudo npm install -g serve
```

Then, to actually run the production server, do VSCode > Terminal Menu > Run Task > *npm: serve*, or \$ `serve -s dist` Inside the root folder of the app / from the VSCode terminal.

On newer windows versions, this might give you an error related to execution policy.

If so, run this command in the terminal before running serving

```
Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
```

Clean Everything

To delete the node_modules folder, dist folder etc. and thereby do a cleanup of build, VSCode > Terminal menu > Run Task > *npm: clean*

Using without Visual Studio Code

Even though this project template is developed with the perspective of using with Visual Studio Code, you can still use it without VSCode. Do the following steps

- Download code. Then do the below commands from the root folder.
- Do `npm run start`, **or** `npm start`, to run the development server
- Do `npm run build` to build production
- Do `npm run serve`, **or** `serve -s dist` to serve production locally
- Do `npm run clean` to clean up everything

Part 0: The “black-box” way to do this

To create a starter React Typescript project, use the command

```
$ npx create-react-app my-app --template typescript
```

Or

```
$ yarn create react-app my-app --template typescript
```

Reference: <https://create-react-app.dev/docs/adding-typescript/>

To make a minimal typescript app

```
$ npx create-react-app my-app --template minimal-typescript
```

Or

```
$ yarn create react-app my-app --template minimal-typescript
```

Reference: <https://www.npmjs.com/package/cra-template-minimal-typescript>

The difference is not actually in the node_modules used, but just the code organization, and skipping CSS etc

Issues

Permission Denied

This happens if NPM and NodeJS are installed globally.

In the user (not root), home folder, there is a .npm folder. However, this ends up with root ownership.

So the fix can be

- `$ rm -rf ~/.npm`
- Or `$ sudo chown -R $USER:$USER '/home/REPLACE_WITH_YOUR_USERNAME/.npm/'`

Reference: <https://www.google.com/search?client=firefox-b-1-d&q=sh%3A+1%3A+create-react-app%3A+Permission+denied>

NodeJS version is old in Linux

To update nodejs in linux, `apt update nodejs` doesn't fix this. Instead do

- `$ npm cache clean -f`
- `$ sudo npm install -g n`
- `$ sudo n stable` or `$ sudo n latest`

Reference: <https://exerror.com/create-react-app-requires-node-14-or-higher-please-update-your-version-of-node/>

Sample Output

Only important lines retained

```
ubuntu@mate-2110x64-play:~/Desktop/projects/react-typescript$ npx
create-react-app my-app --typescript
Installing react, react-dom, and react-scripts with cra-template...
Inside that directory, you can run several commands:
```

```
npm start
```

```
Starts the development server.
```

```
npm run build
```

```
Bundles the app into static files for production.
```

```
npm test
```

```
Starts the test runner.
```

```
npm run eject
```

```
Removes this tool and copies build dependencies, configuration
files and scripts into the app directory. If you do this, you
can't go back!
```

We suggest that you begin by typing:

```
cd my-app
```

```
npm start
```

npm notice Run `npm install -g npm@8.4.0` to update!

If you do `$ npm run build`, you see this about serving locally

- `$ sudo npm install -g serve`
- `$ serve -s build`

Prerequisites

NodeJS

In Linux, you can

```
$ sudo apt install npm nodejs
```

In Windows, download from <https://nodejs.org/en/download/>

Visual Studio Code

Download from: <https://code.visualstudio.com/download>

In Linux, install .deb using `$ dpkg -configure filename.deb`

Part 1: Creating a JavaScript React app

In this section, I am shamelessly copying from <https://dev.to/riddhiagrawal001/create-react-app-without-create-react-app-2l9d> Refer to that page for more explanations etc.

\$ npm init -y

- This creates package.json
- holds important information which is required before publishing to NPM, and also defines attributes of a project that is used by npm to install dependencies, run scripts, and identify the entry point of the project.

\$ npm install react react-dom

- React-DOM is a glue between React and browser DOM
- Creates node_modules and package.lock.json

\$ npm install --save-dev @babel/core @babel/preset-env @babel/preset-react babel-loader

- Babel is a JS compiler / JSX compiler
- Babel-loader transpiles JS files using Babel and webpack

Create .babelrc file

```
{
  "presets": [
    "@babel/preset-react",
    "@babel/preset-env"
  ]
}
```

\$ npm install --save-dev webpack webpack-cli webpack-dev-server

- Webpack compiles / bundles JavaScript modules
- Webpack-CLI provides interface of options webpack uses

\$ npm install --save-dev html-webpack-plugin style-loader css-loader file-loader

- More stuff for Webpack

Create webpack.config.js file

```

const HtmlWebpackPlugin = require("html-webpack-plugin");
const path = require("path");

module.exports = {
  entry: "./src/index.js",
  output: {
    filename: "bundle.[hash].js",
    path: path.resolve(__dirname, "dist"),
  },
  plugins: [
    new HtmlWebpackPlugin({
      template: "./src/index.html",
    }),
  ],
  resolve: {
    modules: [__dirname, "src", "node_modules"],
    extensions: ["*", ".js", ".jsx", ".tsx", ".ts"],
  },
  module: {
    rules: [
      {
        test: /\.jsx?$/,
        exclude: /node_modules/,
        loader: require.resolve("babel-loader"),
      },
      {
        test: /\.css$/,
        use: ["style-loader", "css-loader"],
      },
      {
        test: /\.png|svg|jpg|gif$/,
        use: ["file-loader"],
      },
    ],
  },
};

```

Create "src" folder, and create "src/App.js"

```

import React from "react";

const App = () => (
  <div>
    <h1>Hello React</h1>
  </div>
);

export default App;

```

Create "src/index.js"

```

import React from "react";
import ReactDOM from "react-dom";
import App from "./App";

```

```
ReactDOM.render(<App/>, document.querySelector("#root"));
```

Create "src/index.html"

```
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <title>React</title>
</head>

<body>
  <div id="root"></div>
</body>

</html>
```

In package.json, replace scripts with this

```
"scripts": {
  "start": "webpack serve --mode development --hot --open",
  "build": "webpack --config webpack.config.js --mode
production"
}
```

Run the App

Either npm start, or npm run start work - npm start seems to be a shortcut

```
$ npm start
```

Build the App

- \$ npm run build
- \$ sudo npm install -g serve
- \$ serve -s dist

On newer windows versions, this might give you an error related to execution policy. If so, run this command in the terminal before running serve -s dist

```
Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
```

Part 2: Adding TypeScript

Install relevant types

```
$ npm install --save typescript @types/node @types/react
@types/react-dom @types/jest
```

Setup tsconfig.json

```
$ npx tsc --init --rootDir src --outDir build --esModuleInterop --
resolveJsonModule --module commonjs --allowJs true --noImplicitAny
true --sourceMap true --jsx react -t ES2016 --lib "ES2016", "DOM"
```

Next, the tsconfig.json file created by the above command contains only the top level "compilerOptions" property. We need to also add another top level property "include" to tell typescript to only try to compile stuff inside the "src" folder. So at the end of compilerOptions, but not outside the main object, add:

```
,
  "include": [
    "src"
  ]
```

Note: the comma on first line is to start next property after "compilerOptions"

Rename files

- src/index.js to src/index.tsx
- Src/App.js to src/App.tsx

Add TypeScript build task

In VSCode, Terminal > Configure Tasks

- Select "tsc: build - tsconfig.json"

This will compile .tsx files in "./src" to .js files in "./build"

The tasks.json file is generated inside folder .vscode

Update webpack.config.js to look in build

Our webpack.config.js right now looks in "src" for the .js files.

We need to update it to look in build folder, since that's where the TS compiler puts stuff.

There are three "src" references in webpack.config.js that need to be converted.

These are highlighted in the above code listing

Add NPM Build task

In VSCode, Terminal > Configure Tasks

- Select "npm: build / webpack --config webpack.config.js --mode production"
- In the new task that gets created in tasks.json, add a dependency on our Typescript build task
"dependsOn": ["tsc: build - tsconfig.json"]

At this point, if you do VSCode > Terminal > Run Task..., webpack will complain that there is no index.html in build folder. This is because, while the typescript compiler created the .js files in build, index.html is still in src.

Add an additional task to copy files

In tasks.json, add another task to copy index.html from src, to build.

Note that because "build folder is created by the TypeScript build task, we need a dependency.

```
{
  "label": "Copy Additional Files",
  "type": "shell",
  "command": "cp ./src/index.html ./build/",
  "windows": {
    "command": "copy .\\src\\index.html .\\build\\"
  },
  "dependsOn": ["tsc: build - tsconfig.json"]
}
```

Add a dependency to this task for npm: build.

You may also want to create a similar npm: start task from VSCode > Terminal > Configure Tasks

Your tasks.json will look like this

```
{
  "version": "2.0.0",
  "tasks": [
    {
      "type": "typescript",
      "tsconfig": "tsconfig.json",
      "problemMatcher": [
        "$tsc"
      ],
      "group": "build",
      "label": "tsc: build - tsconfig.json"
    },
    {
      "label": "Copy Additional Files",
      "type": "shell",
      "command": "cp ./src/index.html ./build/",
      "windows": {
        "command": "copy .\\src\\index.html .\\build\\"
      },
      "dependsOn": [
        "tsc: build - tsconfig.json"
      ]
    },
    {
      "type": "npm",
      "script": "build",
      "group": {
        "kind": "build",
        "isDefault": true
      },
      "problemMatcher": [],
      "label": "npm: build",
      "detail": "webpack --config webpack.config.js --mode production",
      "dependsOn": [
        "tsc: build - tsconfig.json",
        "Copy Additional Files"
      ]
    }
  ]
}
```

```

    },
    {
      "type": "npm",
      "script": "start",
      "problemMatcher": [],
      "label": "npm: start",
      "detail": "webpack serve --mode development --hot --open",
      "dependsOn": [
        "tsc: build - tsconfig.json",
        "Copy Additional Files"
      ]
    }
  ]
}

```

Update code to use TypeScript features

src/App.tsx

```

import React from "react";

interface IProps {
  heading: string;
  body: string;
}

const App: React.FunctionComponent<IProps> = (props: IProps):
JSX.Element | null => {
  const { heading, body } = props;
  return (
    <div>
      <h1>{heading}</h1>
      <p>{body}</p>
    </div>
  );
};

export default App;

```

src/index.tsx

```

import React from "react";
import ReactDOM from "react-dom";
import App from "../App";

ReactDOM.render(
  <App heading="Hello React" body="Hope you have a ton of
fun!" />,
  document.querySelector("#root")
)

```

```
);
```

Part 3: Fixing TypeScript build

Right now, we're using as separate TypeScript compile step, and then chaining that through webpack as JavaScript. This has a problem that it doesn't work well with debugging.

Remove TypeScript Build Tasks

In tasks.json, remove the tasks

- tsc: build - tsconfig.json
- Copy Additional Files

We have also added a "Clean" task to this, and a Restore Node Modules task.

The two npm tasks now depend on "Restore Node Modules" and not the ones we removed.

Your tasks.json should look like this:

```
{
  "version": "2.0.0",
  "tasks": [
    {
      "type": "npm",
      "script": "build",
      "group": {
        "kind": "build",
        "isDefault": true
      },
      "problemMatcher": [],
      "label": "npm: build",
      "detail": "webpack --config webpack.config.js --mode production",
      "dependsOn": ["Restore Node Modules"]
    },
    {
      "type": "npm",
      "script": "start",
      "problemMatcher": [],
      "label": "npm: start",
      "detail": "webpack serve --mode development --hot --open",
      "dependsOn": ["Restore Node Modules"]
    },
    {
      "label": "Clean All",
      "type": "shell",
      "command": "rm -rf dist/ node_modules/",
      "windows": {
```

```

        "command": "Remove-Item -Path dist -Force -
Recurse; Remove-Item -Path node_modules -Force -
Recurse"
    },
    "problemMatcher": []
  },
  {
    "label": "Restore Node Modules",
    "type": "shell",
    "command": "./restore-node-modules.sh",
    "windows": {
      "command": ".\\restore-node-modules.bat"
    },
    "problemMatcher": []
  }
]
}

```

The Restore Scripts are

restore-node-modules.sh

```

if [ ! -d "./node_modules" ]; then
  npm install react react-dom
  npm install --save-dev @babel/core @babel/preset-env
  @babel/preset-react babel-loader
  npm install --save-dev webpack webpack-cli webpack-dev-server
  npm install --save-dev html-webpack-plugin style-loader css-
loader file-loader
  npm install --save typescript @types/node @types/react
  @types/react-dom @types/jest
  npm install --save-dev ts-loader
fi

```

resotre-node-modules.bat

```

if not exist "node_modules" (
  npm install react react-dom
  npm install --save-dev @babel/core @babel/preset-env
  @babel/preset-react babel-loader
  npm install --save-dev webpack webpack-cli webpack-dev-server
  npm install --save-dev html-webpack-plugin style-loader css-
loader file-loader
  npm install --save typescript @types/node @types/react
  @types/react-dom @types/jest
  npm install --save-dev ts-loader
)

```

Install ts-loader

```
$ npm install --save-dev ts-loader
```

Update webpack.config.js to support TypeScript

In webpack.config.js,

- Change all build references back to src
- Update entry property to ./src/index.tsx
- In module/rules, add an entry for tsx:

```
{
  test: /\.tsx?$/,
  exclude: /node_modules/,
  use: "ts-loader",
},
```

Your webpack.config.js should now look like this.

```
const HtmlWebpackPlugin = require("html-webpack-plugin");
const path = require("path");
```

```
module.exports = {
  entry: "./src/index.tsx",
  output: {
    filename: "bundle.[hash].js",
    path: path.resolve(__dirname, "dist"),
  },
  plugins: [
    new HtmlWebpackPlugin({
      template: "./src/index.html",
    }),
  ],
  resolve: {
    modules: [__dirname, "src", "node_modules"],
    extensions: ["*", ".js", ".jsx", ".tsx", ".ts"],
  },
  module: {
    rules: [
      {
        test: /\.tsx?$/,
        exclude: /node_modules/,
        use: "ts-loader",
      },
      {
        test: /\.jsx?$/,
        exclude: /node_modules/,
        loader: require.resolve("babel-loader"),
      },
      {
        test: /\.css$/,
        use: ["style-loader", "css-loader"],
      },
      {
        test: /\.png|svg|jpg|gif$/,
```

```

        use: ["file-loader"],
      },
    ],
  },
};

```

At this point, the "npm: build" task, and the "npm: start" task should work correctly.

Part 4: Debugging

launch.json

In order to debug, go to the debugging tab on the far left of VSCode

Click "Run and Debug" button. This suggests you to pick what debugging type - choose Chrome.

This introduces a launch.json in your .vscode folder.

Note: in the github version of this project, additional configurations have been added for launching edge, and for launching chromium browser – the latter to support raspberry pi, where neither chrome nor edge are available.

Reference: <https://askubuntu.com/questions/1048540/using-vs-code-with-chromium-snap>

First try

At this point, you can put a breakpoint in your App.tsx

Now, run the "npm: start" task. This launches dev server and firefox. Keep dev server running.

Then go to debugging tab, hit the green run button which should say "Launch Chrome"

The app runs correctly, but our breakpoint doesn't hit. This is because, our webpack bundled javascript doesn't include source maps.

Add sourcemap to webpack.config.js

Note - we only want to add sourcemap when running development server. So we do this. Also note that we're changing the port on which webpack serves from automatic (8080) to 3000.

```

const HtmlWebpackPlugin = require("html-webpack-plugin");
const path = require("path");

```

```

var config = {
  entry: "./src/index.tsx",
  devServer: {
    port: 3000
  },
  output: {
    filename: "bundle.[hash].js",
    path: path.resolve(__dirname, "dist"),
  },

```

```

plugins: [
  new HtmlWebpackPlugin({
    template: "./src/index.html",
  }),
],
resolve: {
  modules: [__dirname, "src", "node_modules"],
  extensions: ["*", ".js", ".jsx", ".tsx", ".ts"],
},
module: {
  rules: [
    {
      test: /\.tsx?$/,
      exclude: /node_modules/,
      use: "ts-loader",
    },
    {
      test: /\.jsx?$/,
      exclude: /node_modules/,
      loader: require.resolve("babel-loader"),
    },
    {
      test: /\.css$/,
      use: ["style-loader", "css-loader"],
    },
    {
      test: /\.png|svg|jpg|gif$/,
      use: ["file-loader"],
    },
  ],
},
},
};

module.exports = (env, argv) => {
  if (argv.mode === "development") {
    config.devtool = "inline-source-map"
  }

  if (argv.mode === "production") {
    // Nothing special
  }

  return config;
};

```

This adding of properties based on mode works, because if you look at your tasks.json, you'll see that mode is a parameter in each task. The build task specifies production, the start task specifies development.

Update your launch.json

Because we changed the port, we need to update the port from 8080 to 3000 in your launch.json. The launch.json should look like this.

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "type": "pwa-chrome",
      "request": "launch",
      "name": "Launch Chrome against localhost",
      "url": "http://localhost:3000",
      "webRoot": "${workspaceFolder}"
    }
  ]
}
```

Second Try

Now,

- Set a breakpoint in App.tsx
- Terminal > Run Task > npm: start
 - Leave the development server running. Up to you if you close firefox or not
- Go to the debug tab on the left, hit the green "Launch Chrome" button

This time, your breakpoint should hit!

Part 5: Using a consistent build model

After all of the above, I realized that I'm using a mix of different things for the VSCode tasks vs. the npm scripts. I want this project to be usable with and without VSCode. So I decided to make the following updates to the tasks.json and package.json, so everything is managed by npm/node, and VSCode just calls into these.

npm install

We don't really need .sh files and .bat files for restoring node modules. So delete these two files. Rather, running `npm install` from the command line will do this for us, since all necessary information is already in the package.json.

Add a clean-all.js

There doesn't seem to be a quick command for cleaning everything. So we do still need some custom handling. And we need OS specific handling for linux vs. windows. For this, we add a file named clean-all.js at the root folder, that looks like this:


```

var console = require('console');
var exec = require('child_process').exec;
var os = require('os');

function puts(error, stdout, stderr) { console.log(stdout) }

// Run command depending on the OS
if (os.type() === 'Linux')
  exec("rm -rf dist node_modules", puts);
else {
  exec("Remove-Item -Path dist -Force -Recurse", puts);
  exec("Remove-Item -Path node_modules -Force -Recurse", puts);
}

```

Updated package.json

See this updated package.json. We have scripts for start, build, serve, and clean

```

{
  "name": "my-app2",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1",
    "start": "npm install && webpack serve --mode development --hot --open",
    "build": "npm install && webpack --config webpack.config.js --mode production",
    "serve": "npm run build && serve -s dist",
    "clean": "node clean-all.js"
  },
  "keywords": [],
  "author": "",
  "license": "ISC",
  "dependencies": {
    "@types/jest": "^27.4.0",
    "@types/node": "^17.0.13",
    "@types/react": "^17.0.38",
    "@types/react-dom": "^17.0.11",
    "react": "^17.0.2",
    "react-dom": "^17.0.2",
    "typescript": "^4.5.5"
  },
  "devDependencies": {
    "@babel/core": "^7.16.12",
    "@babel/preset-env": "^7.16.11",

```

```

    "@babel/preset-react": "^7.16.7",
    "babel-loader": "^8.2.3",
    "css-loader": "^6.5.1",
    "file-loader": "^6.2.0",
    "html-webpack-plugin": "^5.5.0",
    "style-loader": "^3.3.1",
    "ts-loader": "^9.2.6",
    "webpack": "^5.67.0",
    "webpack-cli": "^4.9.2",
    "webpack-dev-server": "^4.7.3"
  }
}

```

Using this from the command line

Now once you git clone the repository, you can directly run the dev server by

```
$ npm start or $ npm run start
```

And you can directly run the production app by

```
$ npm run serve
```

You can also build production without running by

```
$ npm run build
```

Updated tasks.json

Now that we have updated, npm scripts, the VSCode > Terminal > Configure Tasks option will allow you to create wrapper tasks around these – you will see these options, if you clear out your existing task.json before trying.

So using that, we update our tasks.json to look like this:

```

{
  // Reference: https://code.visualstudio.com/docs/editor/tasks
  "version": "2.0.0",
  "tasks": [
    {
      "type": "npm",
      "script": "install",
      "problemMatcher": [],
      "label": "npm: install",
      "detail": "install dependencies from package"
    },
    {
      "type": "npm",
      "script": "serve",

```

```

        "problemMatcher": [],
        "label": "npm: serve",
        "detail": "npm run build && serve -s dist"
    },
    {
        "type": "npm",
        "script": "clean",
        "problemMatcher": [],
        "label": "npm: clean",
        "detail": "node clean-all.js"
    },
    {
        "type": "npm",
        "script": "build",
        "group": {
            "kind": "build",
            "isDefault": true
        },
        "problemMatcher": [],
        "label": "npm: build",
        "detail": "npm install && webpack --config
webpack.config.js --mode production"
    },
    {
        "type": "npm",
        "script": "start",
        "problemMatcher": [],
        "label": "npm: start",
        "detail": "npm install && webpack serve --mode
development --hot --open"
    }
]
}

```

Using this in VSCode

Now, to run the development server, do

VSCode > Terminal > Run Task > npm: start

After you have development server running, you can debug using Chrome/Edge/Chromium as before.

To serve the production build, do

VSCode > Terminal > Run Task > npm: serve

To build production without serving

VSCode > Terminal > Run Task > npm: build

To clean everything

VSCode > Terminal > Run Task > npm: clean

References

Webpack with TypeScript: <https://webpack.js.org/guides/typescript/>

JavaScript App: <https://dev.to/riddhiagrawal001/create-react-app-without-create-react-app-2lgd>

VSCode tasks: <https://code.visualstudio.com/docs/editor/tasks>

Debugging: <https://www.youtube.com/watch?v=tC91t9OvVHA>

Resolving "document" reference / DOM APIs in TypeScript:

<https://stackoverflow.com/questions/41336301/typescript-cannot-find-name-window-or-document>

- `tsc -t ES2016 --lib "ES2016","DOM" ./your_file.ts`

Using VSCode with Chromium Snap: <https://askubuntu.com/questions/1048540/using-vs-code-with-chromium-snap>

OS Specific NPM Scripts: <https://stackoverflow.com/questions/45082648/npm-package-json-os-specific-script> and https://bugzilla.redhat.com/show_bug.cgi?id=1735361

NPM Notes

If you don't know the specific version, you can do @latest to the package

To update react-scripts in the app

- `$ npm install react-scripts@latest`

To list all globally installed stuff

- `$ npm ls -g`

Example

```
root@mate-2110x64-play:/home/ubuntu# npm ls -g
/usr/local/lib
├─ @types/node@17.0.10
├─ corepack@0.10.0
├─ n@8.0.2
├─ npm@8.4.0
├─ serve@13.0.2
└─ yarn@1.22.17
```