

An automated triple modular redundancy EDA flow for Yosys

REIT4882 Thesis Draft Project Proposal

Matt Young

46972495

m.young2@student.uq.edu.au

August 2024

Contents

1. Introduction and background	1
2. Aims	2
2.1. Engineering requirements	2
3. Literature review	4
4. Milestones	4
References	4

1. Introduction and background

For safety-critical sectors such as aerospace and defence, silicon ICs and FPGA gateware must be designed to be fault tolerant. In the context of digital electronics, *fault tolerant* means that the design is able to gracefully recover and continue operating in the event of a fault, or upset. A Single Event Upset (SEU) occurs when ionising radiation strikes a transistor on a digital circuit, causing it to transition from a 1 to a 0, or vice versa. This type of upset is most common in space, where the Earth's atmosphere is not present to dissipate the ionising particles. On an unprotected system, an unlucky SEU may corrupt the system's state to such a severe degree that it may cause destruction or loss of life - particularly important given the safety-critical nature of most space-fairing systems (satellites, crew capsules, missiles, etc).

One common fault-tolerant design technique is Triple Modular Redundancy (TMR), which mitigates SEUs by triplicating key parts of the design and using voter circuits to select a non-corrupted result if an SEU occurs. Typically, TMR is manually designed at the Hardware Description Language (HDL) level, for example, by manually instantiating three copies of the target module, designing a voter circuit, and linking them all together. However, this approach is an additional time-consuming and potentially error-prone step in the already complex design pipeline.

To address these issues, I propose TaMaRa: a novel fully automated TMR flow for the open source Yosys EDA tool [1].

Modern digital ICs and FPGAs are described using Hardware Description Languages (HDLs), such as SystemVerilog or VHDL. The process of transforming this high level description into a photolithography mask (for ICs) or bitstream (for FPGAs) is achieved through the use of Electronic Design Automation (EDA) tools. This generally comprises of the following stages:

- **Synthesis:** The transformation of a high-level textual HDL description into a lower level synthesisable netlist.

- Elaboration
- Optimisation
- Technology mapping
- **Placement:** The process of optimally placing the netlist onto the target device. For FPGAs, this involves choosing which logic elements to use. For digital ICs, this is much more complex and manual - usually done by dedicated layout engineers who design a *floorplan*.
- **Routing:** The process of optimally connecting all the placed logic elements (FPGAs) or standard cells (ICs).

Due to their enormous complexity and cutting-edge nature, most IC EDA tools are commercial proprietary software sold by the big three vendors: Synopsys, Cadence and Siemens. These are economically infeasible for almost all researchers, and even if they could be licenced, would not be possible to extend to implement custom synthesis passes. The major FPGA vendors, AMD and Intel, also develop their own EDA tools for each of their own devices, which are often cheaper or free. However, these tools are still proprietary software and cannot be modified by researchers. Until recently, there was no freely available, research-grade, open-source EDA tool available for study and improvement. That changed with the introduction of Yosys and Nextpnr [1]. Yosys is a capable synthesis tool that can emit optimised netlists for various FPGA families as well as a few silicon process nodes (e.g. Skywater 130nm). Nextpnr is a place and route tool that targets various FPGA families. Together, they provide a fully open-source, end-to-end EDA toolchain. Importantly, for this thesis, Yosys can be modified either by changing the source code or by developing modular plugins that can be dynamically loaded at runtime. Due to specific advice from the Yosys development team [2], TaMaRa will be developed as a loadable C++ plugin.

2. Aims

This thesis is governed by two overarching aims:

- To design a C++ plugin for the Yosys synthesis tool that, when presented with any Yosys-compatible HDL input, will apply an algorithm to turn the selected HDL module(s) into a triply modular redundant design, suitable for space.
- To design and implement a comprehensive verification process for the above pass, including the use of formal methods, HDL simulation, fuzzing and potential real-life radiation exposure.

Much like designing a pass for a compiler, designing a pass for an EDA tool is no light undertaking. It needs to handle all possible designs the user may provide as input, and provide a high degree of assurance of correctness. This is particularly important given the safety-critical nature of the designs users may provide to TaMaRa. I do not undertake this lightly, and the rigorous verification methodology is a necessity to produce a pass worth using.

These two major aims can be broken down into smaller aims. Under the design pipeline:

- Research the applications of graph theory to

2.1. Engineering requirements

Due to the large and complex nature of the TaMaRa development process, I decided it beneficial to apply the MoSCoW engineering requirements system. I present the requirements and their justifications. The capitalised keywords are to be interpreted according to RFC 2119 [3].

TMR pass requirements

Requirement	Justification
Tamara SHALL be implemented as a C++ pass for the Yosys synthesis tool	Yosys is certainly going to be the synthesis tool used, and the C++ plugin API is the most stable.
Tamara SHALL process the design in such a way that triple modular redundancy (TMR) is applied to the selected HDL module(s), protecting it from SEUs	This is the overarching goal of the thesis.
Tamara MAY operate at any desired level of granularity - anywhere from RTL code level, to elaboration, to techmapping - but it SHALL operate on at least one level of granularity	As long as the TMR is implemented correctly, it doesn't matter what level of granularity the algorithm uses. Each level of granularity has different tradeoffs which still require research at this stage.
Tamara SHOULD be capable of handling large designs, up to and including picorv32, in reasonable amounts of time and memory	Also supports the overarching goal of the thesis, but left as a SHOULD in case of major unforeseen implementation issues with the performance.
Tamara MAY handle FPGA primitives like SRAMs and DSP slices	Most likely will not handle these primitives as there's no reliable way to replicate them across all FPGA vendors supported by Yosys.
Tamara MAY make the voters themselves redundant	Could be added for extra assurance, but not typically considered necessary in industry.
Tamara SHOULD NOT be timing driven	Timing is best left up to the P&R tool (Nextpnr). Although some EDA synthesis tools are timing driven, Yosys currently is not.
Tamara SHOULD have a clean codebase through the use of tools like clang-tidy	Easy to implement and highly desirable but not strictly necessary for correct functioning.

Verification requirements

Requirement	Justification
Verification simulation SHALL be performed using one or more of: Verilator, Icarus Verilog, cxxrtl	These are the best open-source simulation tools, and each have different trade-offs (e.g. Verilator is fast, but not sub-cycle accurate).
Verification SHOULD involve a complex design (e.g. picorv32 CPU) in a simulated SEU environment	This is an important final test, but is left as a SHOULD requirement in case of major unforeseen issues applying TMR to large designs.
Verification SHALL involve equivalence checking (formally proving that a design acts the same before and after TMR) using <i>SymbiYosys</i> and <i>eqy</i>	Equivalence checking is necessary to formally prove that the TMR pass does not modify the behaviour of the design, only that it adds TMR.
Verification MAY involve fuzzing equivalence checking (generating random RTL modules, applying TMR, and checking they're identical)	It's not clear at the time of writing whether a fully end-to-end, automated fuzzing approach for equivalence checking is possible.

Requirement	Justification
Verification SHALL involve mutation coverage (injecting faults into the design and formally proving that TaMaRa mitigates them) using <i>mcy</i>	Mutation coverage is necessary to formally prove that the TMR pass correctly mitigates SEUs.
Verification MAY involve fuzzing mutation coverage, if such a thing is possible	Early research indicates that the generation of random RTL <i>as well as</i> random testbenches is still under active research in academia.
Verification MAY involve a physical, real-life radiation test whereby an FPGA with a Tamara bitstream on it is exposed to radiation	It's not known at the time of writing whether UQ has the facilities to perform this test, or whether the risks caused by radiation exposure are worth the investigation.

3. Literature review

4. Milestones

References

- [1] D. Shah, E. Hung, C. Wolf, S. Bazanski, D. Gisselquist, and M. Milanovic, "Yosys+nextpnr: an Open Source Framework from Verilog to Bitstream for Commercial FPGAs," *CoRR*, 2019, [Online]. Available: <http://arxiv.org/abs/1903.10407>
- [2] N. Engelhardt, "Jitsi meeting with author." May 2024.
- [3] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," Mar. 1997. [Online]. Available: <https://www.ietf.org/rfc/rfc2119.txt>