

Lecture 12

Public-key Cryptography

- **Benefit:** No longer need to assume that Alice and Bob already share a secret
- **Drawback:** Much slower than symmetric-key cryptography
 - Number theory calculations are much slower than XORs and bit-shifts

Reading materials

- [Encryption: Strengths and Weaknesses of Public-key Cryptography](#)
- [Public-key cryptography is a public invention due to Whitfield Diffie & Martin Hellman at Stanford Uni in 1976](#)

Public-key cryptography


- **public-key/two-key/asymmetric** cryptography involves the use of **two** keys:
 - a **public-key**, which may be known by anybody, and can be used to **encrypt messages**, and **verify signatures**
 - a **private-key**, known only to the recipient, used to **decrypt messages**, and **sign** (create) **signatures**
- is **asymmetric** because
 - Not the same key
 - those who encrypt messages or verify signatures **cannot** decrypt messages or create signatures

Public-Key Encryption

- Everybody can encrypt with the public key
- Only the recipient can decrypt with the private key



Public-Key Cryptography - Encryption




Encryption steps

- step1: generate a pair of keys
- step2: keep the private key / secret key (SK) and distribute the public key (PK) – place PK in a public register or other accessible file
- step3: Bob encrypts the message with Alice's PK
- step4: upon receiving the ciphertext (CT), Alice decrypt CT with SK


Public-Key Encryption: Definition

- Three parts:
 - $\text{KeyGen}() \rightarrow PK, SK$: Generate a public/private keypair, where PK is the public key, and SK is the private (secret) key
 - $\text{Enc}(PK, M) \rightarrow C$: Encrypt a plaintext M using public key PK to produce ciphertext C
 - $\text{Dec}(SK, C) \rightarrow M$: Decrypt a ciphertext C using secret key SK
- Properties
 - **Correctness**: Decrypting a ciphertext should result in the message that was originally encrypted
 - $\text{Dec}(SK, \text{Enc}(PK, M)) = M$ for all $PK, SK \leftarrow \text{KeyGen}()$ and M
 - **Efficiency**: Encryption/decryption should be fast
 - **Security**: 1. Alice (the challenger) just gives Eve (the adversary) the public key, and Eve doesn't request encryptions. Eve cannot guess out anything; 2. computationally infeasible to recover M with PK and ciphertext

Public-Key Cryptography - Signature



Review



Public-Key application

- can classify uses into 3 categories:
 - **encryption/decryption** (provide secrecy)
 - **digital signatures** (provide authentication)
 - **key exchange** (of session keys)
- some algorithms are suitable for all uses; others are specific to one
- Either of the two related keys can be used for encryption, with the other used for decryption

Algorithm	Encryption/Decryption	Digital Signature	Key Exchange
RSA	Yes	Yes	Yes
Diffie–Hellman	No	No	Yes
DSS	No	Yes	No
Elliptic curve	Yes	Yes	Yes