

▽ FOR ALL DATA IN THE TABLE			RUN CAPACITOR 50/60Hz 2253262TAB "ROHS FREE"											CABLE/CAPACITOR CONFIGURATION (SEE VIEW)	INTERNAL DISCHARGE RESISTOR	GENERAL (FOR EMBRACO INT. USE ONLY)
MODEL			REQUIREMENTS		DIMENSIONS			CABLE LENGTH		APPROVAL MARKS						
CODE	TERMINALS VERSION	µF	SAFETY CLASS	LIFE EXPECTANCY /TENSIONE VOLTAGE	ØD	H	A	L	E	CE	VDE	CURUS OR UR+CSA	CQC			
2253106	Y	2.5	S2	CL.B/450V	30	45		400	50	X	X	X	X	SIDE	-	
2253108	Y	3	S2	CL.B/450V	30	45		400	50	X	X	X	X	SIDE	-	
2253110	Y	4	S2	CL.B/450V	30	50		400	50	X	X	X	X	SIDE	-	
2253111	Y	5	S2	CL.B/450V	35	50		400	50	X	X	X	X	SIDE	-	
2253295	-	15	S2	CL.B/450V	35	80	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253296	-	17.5	S2	CL.B/450V	35	80	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253297	-	20	S2	CL.B/450V	40	80	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253298	-	25	S2	CL.B/450V	40	80	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253299	-	30	S2	CL.B/450V	40	90	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253300	-	35	S2	CL.B/450V	45	80	24	-	-	X	X	X	X	VERSION "X"	-	
2253301	-	10	S2	CL.B/450V	30	70	17.5	-	-	X	X	X	X	VERSION "X"	-	
2253304	Y	2	S2	CL.B/450V	30	45		400	50	X	X	X	X	SIDE	-	
2253306	W	17.5	S2	CL.B/450V	40	80		400	50	X	X	X	X	SIDE	-	
2253307	-	40	S2	CL.B/450V	45	90	24	-	-	X	X	X	X	VERSION "X"	-	
2253310	Z	15	S2	CL.B/450V	35	90		200	85	X	X	X	X	AXIAL	-	
2253311	Z	17,5	S2	CL.B/450V	40	80		200	85	X	X	X	X	AXIAL	-	
2253312	Z	20	S2	CL.B/450V	40	90		200	85	X	X	X	X	AXIAL	-	
2253313	Z	25	S2	CL.B/450V	40	94		200	85	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253314	Z	30	S2	CL.B/450V	40	104		200	85	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253315	Z	35	S2	CL.B/450V	45	94		200	85	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253316	Z	10	S2	CL.B/450V	35	70		200	85	X	X	X	X	AXIAL	-	
2253318	Z	12.5	S2	CL.B/450V	35	80		200	85	X	X	X	X	AXIAL	-	
2253320	Z	7,5	S2	CL.B/450V	35	58		200	85	X	X	X	X	AXIAL	-	
2253321	Z	40	S2	CL.B/450V	45	104		200	85	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253323	Z	8	S2	CL.B/450V	35	58		200	85	X	X	X	X	AXIAL	-	
2253324	Z	7	S2	CL.B/450V	35	58		200	85	X	X	X	X	AXIAL	-	
2253325	Z	5	S2	CL.B/450V	35	50		200	85	X	X	X	X	AXIAL	-	
2253326	Y	4	S2	CL.B/450V	30	63		400	50	X	X	X	X	FULL ALUMINIUM AXIAL	-	NO
2253327	Y	2	S2	CL.B/450V	30	58		400	50	X	X	X	X	FULL ALUMINIUM AXIAL	-	NO
2253328	Y	8	S2	CL.B/450V	35	58		400	50	X	X	X	X	AXIAL	-	
2253330	W	12.5	S2	CL.B/450V	35	80		400	50	X	X	X	X	SIDE	-	
2253331	Y	3	S2	CL.B/450V	30	58		400	50	X	X	X	X	FULL ALUMINIUM AXIAL	-	NO
2253332	Y	25	S2	CL.B/450V	40	94		400	50	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253333	Y	12.5	S2	CL.B/450V	35	80		400	50	X	X	X	X	SIDE	-	
2253334	Y	17.5	S2	CL.B/450V	40	80		400	50	X	X	X	X	SIDE	-	
2253335	W	25	S2	CL.B/450V	40	94		400	50	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253336	W	15	S2	CL.B/450V	35	90		400	50	X	X	X	X	SIDE	-	
2253337	W	8	S2	CL.B/450V	35	58		400	50	X	X	X	X	SIDE	-	
2253338	Z	15	S2	CL.B/450V	35	90		200	85	X	X	X	X	AXIAL	-	NO
2253339	Z	17,5	S2	CL.B/450V	40	80		200	85	X	X	X	X	AXIAL	-	NO
2253340	Z	20	S2	CL.B/450V	40	90		200	85	X	X	X	X	AXIAL	-	NO
2253341	Z	10	S2	CL.B/450V	35	70		200	85	X	X	X	X	AXIAL	-	NO
2253342	Y	25	S2	CL.B/450V	40	90		400	50	X	X	X	X	SIDE	-	NO
2253343	Z	12,5	S2	CL.B/450V	35	80		200	85	X	X	X	X	AXIAL	-	NO
2253344	Z	7,5	S2	CL.B/450V	35	58		200	85	X	X	X	X	AXIAL	-	NO
2253345	W	12,5	S2	CL.B/450V	35	80		400	50	X	X	X	X	SIDE	-	NO
2253346	W	25	S2	CL.B/450V	40	90		400	50	X	X	X	X	SIDE	-	NO
2253347	W	30	S2	CL.B/450V	40	104		200	85	X	X	X	X	FULL ALUMINIUM AXIAL	-	
2253351	W	10	S2	CL.B/450V	35	70		400	50	X	X	X	X	SIDE	-	NO
2253352	Y	10	S2	CL.B/450V	35	70		400	50	X	X	X	X	SIDE	-	NO
2253354	W	20	S2	CL.B/450V	40	90		200	85	X	X	X	X	SIDE	-	NO
2253355	W	5	S2	CL.B/450V	35	50		200	85	X	X	X	X	SIDE	-	NO
2253356	W	10	S2	CL.B/450V	35	70		200	85	X	X	X	X	SIDE	-	NO
2464089	U	12,5	S2	CL.B/450V	35	70		220	42	X	X	X	X	SIDE	100k Ohm 1W	
2464093	U	10	S2	CL.B/450V	35	70		220	42	X	X	X	X	SIDE	100k Ohm 1W	

MATERIAL :				GEN. TOL. : --	
SEE NOTES				ANG. TOL. : --	
				SCALE : 1:1 (1:2)	
				UNIT : mm  A2	
CODE :		TITLE, DOCUMENT TYPE SUPPLIER NAME 50/60Hz		REPLACE: --	
DRAWN : Peter TEPLICA		RUN CAPACITOR		No.	
APP. : Robert REICH				2253262TAB	
ECM : 517090	DATE : 2011.MAR.02	THIS MATERIAL IS CONFIDENTIAL AND PROPRIETARY TO EMBRACO, AND MAY NOT BE REPRODUCED, DISCLOSED, DISTRIBUTED OR USED WITHOUT PERMISSION		SHEET NUMBER: 2 OF 2	