



- 1 - DRAWING ACCORDING TO ISO STANDARDS, SEE TSS 002513.
- 2 - DIMENSIONS AND SPECIFICATIONS SIGNED WITH $\nabla\nabla\oplus$, SEE TSS 002470.
- 3 - REQUIREMENTS ABOUT HAZARDOUS SUBSTANCES ACCORDING TO TSS 002420. $\oplus$
- 4 - HFC MANDATORY REQUIREMENTS ACCORDING TO TSS 002369. ∇
- 5 - VARIATION IS ADMITTED OF ± 3 MICROMETERS IN THE LIMITS OF SPECIFICATION OF THE THICKNESS BETWEEN GASKET GROUPS.
- 6 - IDENTIFY THE THICKNESS CLASS.
FORMAT: "X"-THICKNESS CLASS, FOR EXAMPLE: 19,9-13
LETTERING HEIGHT: 2,5 , COLOR: WHITE OR BLACK.
- 7 - GEOMETRIC REQUIREMENTS ACCORDING TO TSS 002605.
- 8 - $\boxed{\oplus} \boxed{\varnothing 0,1}$ AND $\boxed{\curvearrowright} \boxed{0,2}$ AND ANGLE TOLERANCE $\pm 1^\circ$ FOR MEASUREMENT BY POLYESTER GASKET, $\boxed{\oplus} \boxed{\varnothing 0,3}$ AND $\boxed{\curvearrowright} \boxed{0,3}$ AND ANGLE TOLERANCE $\pm 2^\circ$ FOR MEASUREMENT BY CARDBOARD GASKET.
- 9 - FOR CN PLANT, VARIATION IS ADMITTED OF ± 3 MICROMETERS IN THE LIMITS OF SPECIFICATION OF THE THICKNESS BETWEEN GASKET GROUPS.

13958120 / 8139	24,9
13958040 / 8059	19,9
13958020 / 8039	21,9
13958000 / 8019	23,4
CODE	"X"

MATERIAL : NI-2085-G (ALTERNATIVE: GZL-2002)		embraco Nidec		GEN. TOL. : ±0,2	
				ANG. TOL. : ±2°	
				SCALE : 5:2	
				UNIT: mm	
CODE : TSS 002259		TITLE, DOCUMENT TYPE GASKET - VALVE PLATE		REPLACE: 01.395.8000 REV. E	
DRAWN : ALEXANDRE PEREIRA				No. 13958000	
APP.: JOSE C. TISSEI					
ECM : 43007	DATE : 2016.JUL.18	THIS MATERIAL IS CONFIDENTIAL AND PROPRIETARY TO EMBRACO, AND MAY NOT BE REPRODUCED, DISCLOSED, DISTRIBUTED OR USED WITHOUT PERMISSION		SHEET NUMBER: 1 OF 1	