

# HTML NEWSLETTER AND MJML

# WHY IS CREATING HTML NEWSLETTERS SO WEIRD?

- Many render engines with different capabilities
- Rarely get updated for new requirements
- Webmailers are picky and remove a lot of styles

# BASIC LAYOUT TECHNIQUES

- Use deeply nested tables for all layouts
- Use inline CSS for general styling and style-tags for responsive overrides
- Don't use body tag for styling
- Avoid html-attributes like cellpadding or cellspacing
- Avoid padding and width/height on the same element
- Avoid floats or modern layout methods
- Use conditional commands to target Outlook
- Font-tags, center-tags are not necessary anymore

# EXAMPLE

```
template-ticketyboo.html
```

# COMMON EMAIL CLIENTS

# OUTLOOK

- Since Outlook 2007 Word is used as render engine
- Engine hasn't been updated since then
- Support for margin, padding, width and height spotty
- No media queries or other modern CSS-features
- No support for background images
- Outlook for Mac uses Webkit

# OUTLOOK.COM

- Uses render engine of browser
- Didn't support CSS margins for a while
- Background images don't repeat
- Media queries support was supposed to be introduced in 2019
- Can be targeted in CSS via `[owa] .test {}`

# GMAIL

- Support of style-tags in the head since late 2016
- No support for style-element in the body
- Messages larger than 1024kb are clipped
- Doesn't support attribute selectors
- Ignores style-elements larger than 16,384 characters (used to be 8,192)
- Removes entire style-tag when encountering an error
- Numbers and URLs are automatically converted to links



# APPLE MAIL

- Very good support due to Webkit rendering engine
- Dark mode is not applied to HTML emails automatically
- Media queries can be used to add support for dark mode @media (prefers-color-scheme: dark)
- Numbers and URLs are automatically converted to links

# STATISTICS

- 4 of 5 used email clients are either from Apple or Google (Apple Mail and Gmail)
- Standalone Outlook much more popular than Outlook.com
- <https://www.kevinmandeville.com/blog/email-client-market-share-trends-2018>

**TOOLS**

# CSS-INLINER

- Convert style-tags to inline styles
- No support for media queries
- Usually applied before deployment
- Circumvent issues of lack of support of embedded or external styles
- Popular tools: Premailer, PutsMail, MailChimp Inliner

# SENDING TOOLS

- Can be used to send the unmodified html source code to email addresses
- Usually require email verification to avoid abuse
- Some services provide APIs for automated testing
- Popular tools: MailGun, SendGrid

# FRAMEWORKS & BOILERPLATE TEMPLATES

- MJML
- Foundation for Emails 2 (formerly Zurb Ink)
- Cerberus
- Blueprints by Mailchimp

# TESTING

- Litmus Email (\$99 per month)
- Email on Acid (\$44 per month)

**MJML**



# BASICS

- Open source framework for responsive HTML mails
- First release in January 2016
- Uses Mailjet Markup Language DSL
- Comes with library of components out of the box
- Supports creation of custom components
- Used by The New York Times and Ryan Air

# TECHNICAL DETAILS

- Version 4 was rewritten in vanillaJS
- Plugins for common editors like VSCode
- Supported by module bundlers like Webpack and task runners like Gulp
- Provides quality of life improvements like watch tasks and linter
- Can be used with React and template engines
- Can be used standalone via npx

# ADVANTAGES

- Fixes a lot of the common issues with render engines
- Automatically inlines styles during compilation and adds Outlook specific overrides
- Gives errors about incorrect usage at compile time
- Allows splitting up into partials/components
- MJML DSL is fairly close to HTML
- Mobile first

# DISADVANTAGES

- No support for variables, loops, template inheritance etc.
- Requires use of template engines to enable parameterization
- Imposes restrictions on email design
- No way to configure render engine support
- Outdated guides and tips that reference MJML version 3 can be confusing

# BUILDING BLOCKS

## BUILDING BLOCKS - BODY

```
<mj-body>  
  . . .  
</mj-body>
```

- Acts similar to body-element in HTML
- Sets background color and max-width of email
- Used to be called container in MJML 3

## BUILDING BLOCKS - SECTION

```
<mj-section>  
  ...  
</mj-section>
```

- Similar to rows in grid systems like Bootstrap or Foundation
- Cannot contain sections themselves
- Multiple sibling sections are okay

# BUILDING BLOCKS - COLUMN

```
<mj-column>  
  ..  
</mj-column>
```

- Similar to columns in grid systems like Bootstrap or Foundation
- Must be a direct children of sections
- Cannot contain other columns or sections
- Fill up row automatically, e.g. 1 column 100% width, 2 columns 50% width etc.
- Columns become stacked on small viewports



# CREATING A BASIC GRID LAYOUT

```
<mj-section>
  <mj-column>
    Full-width column
  </mj-column>
</mj-section>
<mj-section>
  <mj-column>
    Column 50%
  </mj-column>
  <mj-column>
    Column 50%
  </mj-column>
</mj-section>
```

# USING IMAGES

```
<mj-image  
  width="250px"  
  src="image.png"  
  padding="0"  
  align="center"  
  href="#"  
  fluid-on-mobile  
>
```

- Helper to deal with images
- Images can be used as links
- SrcSet is supported
- Can be full width on mobile and fixed width on desktop

# STYLING ELEMENTS - INLINE STYLES

```
<mj-text color="red" font-size="16px">  
  Cat  
</mj-text>
```

- Not reusable
- Inline style override global styles
- Make changes more difficult

# STYLING ELEMENTS - GLOBAL STYLES

```
<mj-attributes>
  <mj-class name="font-size-base" font-size="16px" />
  <mj-class name="color-primary" color="red" />
</mj-attributes>

<mj-text mj-class="font-size-base color-primary">
  Cat
</mj-text>
```

- Reusable
- Easily changeable
- Get inlined during compilation
- Can be overridden by inline styles

# OTHER ELEMENTS

- Buttons
- Hero component
- Media elements
- Navbar
- Accordion
- Social icons
- Data tables

# WORKING WITH PARTIALS

```
// base
<mj-body background-color="#4e4096">
  <mj-include path="./child-component.mjml" />
</mj-body>
```

```
// child-component.mjml
<mjml>
  <mj-body>
    <mj-text>
      Hello
    </mj-text>
  </mj-body>
</mjml>
```

- Watch task also works on partials since v4
- No way to pass variables to a partial

# PARAMETERIZE MJML TEMPLATES

- Not possible out of the box
- Can be achieved via template engines like handlebars, twig etc.
- Generate MJML markup via template engine and then compile to HTML
- Parameters are handled by template engine when MJML markup is generated

---