How to Operate the Orchestration Pipeline

Created by Johnson, Maurice, last modified yesterday at 7:31 PM

What you are looking at is a successful deployment out on the Orchestration Pipeline. The Orchestration Pipeline is presently comprised of **37** Stages. Each equating to the **37** Docker Images and or Configurations necessary to stand up and host the EIS Application out on the Cloud. Quite an interesting feat if you ask me. Cloud Technology was something we normally just discussed at the Water Cooler or within our favorite forum. Industry seems to have grabbed the Cloud Technology Stack by the Horns, and Allstate is no exception. It truly is fascinating to witness the shifts in technology, especially these last 20 years. No matter, fore I have gotten slightly sidetracked. Let us begin our journey on "How to Operate the Orchestration Pipeline"

In order to Interact with the Orchestration Pipeline the reader must navigate to the "**Build with Parameters**" Menu Item on the Left-hand-side; 

The page will refresh and display the Orchestration Pipeline Interface based upon the Configurations & Parameterizations that we just finished discussing. A Screen shot of it's current state follows below the reference table. With our EIS Project still within it's infancy, the Orchestration Pipeline has been set up with **Default Values**, that meet our current needs. In other words, whoever is operating the Orchestration Pipeline will not have to alter many of the settings outside of the "**allNameSpaces**", "**imageTags**", and or the "**imageTagOverride**" sections.

For example we are presently pulling and Docker Docker Images that are being built by the vendor EIS. Knowing this, the Docker Repository required to meet this pipeline demand is the value "**eis-central-remote.artifactory.allstate.com**"; which is also the default value. Another example is that our first Kubernetes Namespace for deployment is "**dev1**"; which is might have it, is also the default value. Hopefully you get the idea.

As the project matures, I am confident the Orchestration Pipeline will continue to be rather fluid, will change with the needs at that moment in time.

What follows is a reference table discussing your options at time of deployment

Section	Description	Options	Default Value
dockerRepository	Dropdown with 2 Docker Repository Options,	eis-central-remote.artifactory.allstate.com, abeis.artifactory.allstate.com	eis-central-remote.artifactory.allstate.com
allNameSpaces	A Radio Button Group with 8 total single select options	dev, int, uat,dev1, dev2, commit, manualtest, staging	dev1
eisCoreDependency	Represents a Group of Parameterized Multi-Select CheckBoxes. There are a total of 2 Multi-Select Checkboxes.	Core-Dependency, Core-Configurations	All Components are Selected with the Exception of "Core-Dependency"
eisStaticReference	Represents a Group of Parameterized Multi-Select CheckBoxes. There are a total of 5 Multi-Select Checkboxes.	Infra-Core, Security-Core, Registry, OrgStruct, RefData,	All Components are Selected by default
eisBase	Represents a Group of Parameterized Multi-Select CheckBoxes. There are a total of 10 Multi-Select Checkboxes.	CRM, Census, Policy-Generic, Policy-Acc, Policy-OpenL, Infra-Aux, Policy-hi, UI, Tooling, Dxp	All Components are Selected by default
imageTagOverride	This value **supersedes** any **Docker Image Tag Values** entered within the next section "**imageTags**". As the name implies, it is to provide an Override so that the entire Suite of Application Components may be installed at the same identical base Docker Image Tag Version.		BLANK
imageTags	Series of Individual Single Entry Textboxes each catered towards the individual EIS Components. There are a total of 37 Single Entry Textboxes.	`[5.5.1, 8.6.3, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, b72cb69a, b72cb69a, 94fc30dd, 94fc30dd, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 21.9, 8b049882, 21.9, 21.9, 26adccb5, 26adccb5, 26adccb5, 26adccb5, b401dd11, b401dd11, 21.8, 21.9, 21.9, 03966e70]`	Last Docker Image Tag Value Deployed

	It is worth noting here, when looking at the Orchestration Pipeline Deployment Interface , some of the Textboxes have a **Light Blue Background Color**. This is to signify that the Vender EIS has provided a Customized Docker Image that is unique to Allstate's Requirements/needs.		
Build	Jenkins Button that allows the user to Kick Off or Start the Pipeline Deployment Process		

Pipeline AB-Nightly-Deploy-Orchestration

This build requires parameters:

dockerRepository: eis-central-remote.artifactory.allstate.com

allNameSpaces — **Allstate Namespaces:**
(●) dev1 ( ) dev ( ) int ( ) uat ( ) staging ( ) dev2 ( ) dev3 ( ) dev4 ( ) commit ( ) manualtest ( ) int2 ( ) uat2

eisCoreDependency — **Core-Dependency Components:**
[ ] core-dependency [x] core-configurations

eisStaticReference — **Static REF Components:**
[x] infra-core [x] security-core [x] registry [x] orgstruct [x] refdata

eisBase — **Base Components:**
[x] crm [x] census [x] policy-generic [x] policy-acc [x] policy-openl
[x] infra-aux [x] policy-hi [x] ui [x] tooling [x] dxp

engageSleep — **Engage Sleep Time:**
[ ] engageSleep

Engage Sleep Times Between Deployers & Associative APPs. CAUTION this adds 79mins - (StaticRef Comps: 8min Deployers & 3min APPs, Base Comps: 2min Deployers & 0min APPs)

imageTagOverride:

To Provide a Value Here will Override all Subsequent Docker Image Tag Values that are referenced below in the next section

imageTags

Core Dependency:

eis-zookeeper	5.5.1	eis-solr	8.6.3

Infra-Core:

infra-deployer	21.9	infra-app	21.9

Security-Core:

security-deployer	21.9	security-app	21.9	sso-provider	21.9

Registry:

party-deployer	21.9	party-app	21.9

OrgStruct:

org-deployer	21.9	org-app	21.9

RefData:

infra-lookups-deployer	a79ccd41	security-domain-deployer	a79ccd41

CRM:

crm-deployer	94fc30dd	crm-app	94fc30dd

Census:

census-deployer	21.9	census-app	21.9

Policy-Generic:

policy-generic-deployer	21.9	policy-generic-app	21.9

Policy-Acc:

acc-master-deployer	21.9	acc-master-app	21.9	acc-cert-deployer	21.9	acc-cert-app	21.9

Policy-OpenL:

openl-policy-app	21.9	openl-rating-app	8b049882

Infra-Aux:

infra-aux-deployer	21.9	infra-aux-app	21.9

Policy-Hi:

hi-cert-deployer	26adccb5	hi-cert-app	26adccb5	hi-master-deployer	26adccb5	hi-master-app	26adccb5

UI:

admin-ui	21.9	cssr-app	4211000b

Tooling:

configuration-server-deployer	21.8	configuration-server	21.9	product-catalog	21.9

DXP:

dxp-gateway	03966e70

Provides the Jenkins Operator/Systems Engineer/DEVOps Engineer the means of manually entering the necessary pipeline configurations for this job.

Build

No labels