REQUIREMENTS SPECIFICATION REPORT

PROJECT: Traduce Señas

TEAM MEMBERS:
Luis Alejandro Duarte Aldana
Juan Mauricio Suaza Solorzano
Juan Camilo Fierro Esquivel

NATIONAL LEARNING SERVICE – SENA
Software Analysis and Development

2026

Table of Contents

Introduction 3
General project information 3
Problem statement 3
Justification 4
General objective 4
Specific objectives 4
Scope 4
Personnel involved 5
Definitions, acronyms, and abbreviations 5
Overall description 6
Product perspective 6
User characteristics 6
Constraints 6
Assumptions and dependencies 7
Specific requirements 7
Common interface requirements 7
User interfaces 7
Hardware interfaces 7
Software interfaces 7
Communication interfaces 8
Functional requirements 8
Identity module (iam-service) 8
Authorization module (iam-service) 9
Profile and notifications module (profile-service) 9
Lexicon module (lexicon-service) 9
Translation and AI module (recognition-service) 10
Usage, achievements, audit, and configuration module 10
Nonfunctional requirements 11
Use case requirements 12
UML use case diagram 12
Use case characterization 12
Traceability 14
Conclusions 14
References 16

Introduction

This report presents the requirements specification for the Traduce Señas software, developed as a training project for the Technologist in Software Analysis and Development program at the National Learning Service (SENA). Its purpose is to document, in a verifiable and unambiguous way, what the system must do and at what quality level, so that it serves as an agreement among the development team, the instructor, and future users.

This document follows the structure recommended by the IEEE 830-1998 standard (Institute of Electrical and Electronics Engineers [IEEE], 1998): it first presents the project context, then describes the product in general terms, and finally details the functional requirements, nonfunctional requirements, and use cases. The requirements described here are the basis for the analysis, design, testing, and implementation documents that accompany this deliverable.

General project information

Problem statement

Deaf people and people with hearing disabilities face persistent barriers when communicating with the hearing population. In Colombia, the number of certified LSC interpreters is far below demand, and availability is even lower in rural areas, public entities, and unplanned everyday situations (Instituto Nacional para Sordos [INSOR], 2020). As a result, deaf people lose autonomy, and their participation in education, employment, and health services is reduced.

In response to this situation, there is a need for a low-cost technological solution, accessible on a smartphone, that translates signs into text or speech without requiring an interpreter in everyday interactions.

Justification

The project promotes social inclusion and equal opportunities for deaf people, in line with Ley 982 de 2005, which recognizes LSC and requires the elimination of communication barriers. It also leverages mature computer vision technologies, such as MediaPipe Hands (Zhang et al., 2020), which make it possible to detect the hand in real time from the camera of a common device, making development feasible for a small team.

General objective

Design and implement a mobile and web application that translates Colombian Sign Language into text or audio in real time, using computer vision and artificial intelligence, to reduce the communication barriers faced by deaf people in everyday settings.

Specific objectives

1. Build a tool that recognizes LSC signs and delivers the translation immediately.
2. Convert the recognized signs into written or spoken words that any hearing person can understand.
3. Enable communication between deaf and hearing people in situations such as the classroom, a store, or a service counter.
4. Validate the tool in real-world scenarios to confirm that it is accurate and useful.
5. Contribute to a more inclusive society in which hearing ability does not determine who can communicate.

Scope

The system comprises an application for Android, iOS, and web browsers that recognizes signs through the camera and delivers the translation as text or audio. It includes account management with roles and permissions, translation history, sign language alphabet lookup (with 3D models), visual notifications, an achievements module, usage statistics for administrators, sample capture and recognition training, an audit trail, error logging, and a configurable password policy.

The following are out of scope for this version: reverse translation (from text or speech to signs), full coverage of the LSC vocabulary, and offline use without an internet connection.

Personnel involved

Table 1
Project team

Name	Role	Responsibility	Contact
Juan Mauricio Suaza Solórzano	Technical lead, Scrum Master, analyst, and developer	Analysis, design, backend programming (lexicon and recognition), and coordination	suazasolorzano@gmail.com
Luis Alejandro Duarte Aldana	Analyst and developer	Analysis, interface design, and programming	aleosea777@gmail.com
Juan Camilo Fierro Esquivel	Analyst and developer	Analysis, product documentation, and programming	fierroesquiveljuancamilo@gmail.com

Note. Apprentices in the Technologist in Software Analysis and Development program at SENA.

Definitions, acronyms, and abbreviations

Table 2
Project glossary

Term	Definition
LSC	Colombian Sign Language, officially recognized by Ley 982 de 2005.
API Gateway	Single entry point to the backend: routes requests, validates the JWT, and limits the request rate.
Microservice	Small, independent service with its own database that handles a single business domain.
JWT	JSON Web Token. Signed credential that identifies the user and their roles in each request.
MediaPipe	Google library that detects the hand in the image and returns 21 anatomical points (landmarks).
Landmark	Each of the 21 hand points, with x, y, z coordinates.
DTW	Dynamic Time Warping. Algorithm that compares two sequences even when they have different speeds.
Template	Saved example of a sign against which the camera input is compared.
Threshold	Maximum accepted distance for displaying a sign as recognized (currently 1.1).
RabbitMQ	Message broker that carries domain events between microservices.
Domain event	Message that reports that something occurred, for example "TranslationProduced".
RBAC	Role-based access control (USER, ADMIN, LINGUIST).
Expo	Platform that allows compiling the same React Native application for Android, iOS, and web.
RF / RNF	Functional requirement / nonfunctional requirement.
CU	Use case.

Overall description

Product perspective

Traduce Señas is a new, independent product. It is designed to be educational, accessible, and easy to use, so that anyone, even without prior knowledge, can interact with the deaf community.

Technically, the system consists of a client built with React Native and Expo (running on Android, iOS, and web browsers) and a microservices backend in Node.js, Express, and TypeScript: an API Gateway and five domain services (iam, recognition, lexicon, analytics, and profile), each with its own PostgreSQL database, MongoDB for training samples, and RabbitMQ for asynchronous event-based communication.

User characteristics

Table 3
User profiles

Profile	Training	Main activities
Deaf user or user with hearing loss	No technical training required	Performs signs in front of the camera, reviews their history and the alphabet, and configures theme and language
Hearing user	No LSC knowledge required	Reads or listens to the translation and learns basic signs with the alphabet
Administrator	Technologist in Software Analysis and Development	Monitors recognition accuracy, manages the lexicon and users, captures samples, reviews statistics and audit logs

Constraints

- **Limited vocabulary:** recognition initially covers the alphabet and a reduced set of words; it does not cover the full LSC.
- **Connectivity:** registration, sign-in, history, and statistics require an internet connection.
- **Hardware:** the device must have a camera and the capacity to process video in real time.
- **Personal data:** the system must comply with Ley 1581 de 2012 and Decreto 1377 de 2013, especially for video samples and hand points.
- **Team and timeline:** three apprentices working part-time and following the SENA

academic calendar.

Assumptions and dependencies

- Deaf and hearing people are willing to use the application to communicate.
- Institutional support is available for pilot testing in real-world settings.
- Public LSC data, such as the LSC-54 dataset (Mora-Zarate et al., 2025), is available to build the recognition templates.
- Users have access to a smartphone or a computer with a camera.
- The system depends on external services: MediaPipe, an SMTP mail server, and, in the future, Firebase Cloud Messaging.

Specific requirements

Common interface requirements

User interfaces

The interface is inclusive, intuitive, and accessible: large buttons (minimum 48 × 48 dp), clear iconography, a minimum contrast of 4.5:1 in light and dark themes, and no information conveyed by sound alone. It contains a live video area for recognition, a translation panel, accessibility controls, and an alphabet section.

Hardware interfaces

- Device camera with a minimum resolution of 720p.
- Speaker or audio output for voice mode.
- Stable internet connection.
- Processor capable of running computer vision inference in real time.

Software interfaces

- Android 9 (API 28) or later.
- iOS 14 or later.
- Up-to-date desktop browsers with WebAssembly and camera access support (Chrome, Edge, Firefox).
- Server with Docker and Docker Compose for the backend.

Communication interfaces

- HTTPS for all client-server connections.
- REST API with data exchange in JSON format.
- JWT authentication in the "Authorization: Bearer" header.
- AMQP messaging (RabbitMQ) between microservices, only within the internal network.

Functional requirements

Table 4 summarizes the eleven functional requirements of the system and their specifications (ERF). The detailed catalog follows, dividing each requirement into atomic, verifiable functions numbered by module.

Table 4
System functional requirements

Code	Requirement	Specifications	Priority
RF1	User management	ERF1.1 Registration · ERF1.2 Sign-in (own account, Google, Facebook) · ERF1.3 Password recovery	High
RF2	Site navigation	ERF2.1 Navigation bar visible on all devices	High
RF3	Sign language translation	ERF3.1 Translation mode activation · ERF3.2 Conversion of signs to text/audio	High
RF4	Visual notifications	ERF4.1 On-screen notifications	Medium
RF5	Profile management	ERF5.1 View profile · ERF5.2 Light/dark theme · ERF5.3 Change password · ERF5.4 Language · ERF5.5 Recent translations	High
RF6	Usage statistics (administrator only)	ERF6.1 Access to statistics	Medium
RF7	Sign language alphabet	ERF7.1 Alphabet display	High
RF8	Gamification	ERF8.1 Achievement catalog and progress · ERF8.2 Achievement unlock and notice	Low
RF9	Internal audit	ERF9.1 Audit trail query	Medium
RF10	Error handling	ERF10.1 Error classification and query	Medium
RF11	Password policy	ERF11.1 Policy configuration	Medium

Identity module (iam-service)

Table 5
Detailed requirements — Identity (iam-service)

ID	Description	Source	Priority
FR-001	Register a user with name, date of birth, username, email, and a valid password; the account is created as INACTIVE until the email is verified	RF1	Must
FR-002	Reject registration unless the terms are accepted, and store the accepted date and version	RF1	Must

ID	Description	Source	Priority
FR-003	Verify the email with a 6-digit code	RF1	Must
FR-004	Store codes only as hashes, with expiration, single use, and an attempt counter	RF1	Must
FR-005	Authenticate with email and password	RF1	Must
FR-006	Temporarily lock the account after failed attempts (1, 5, and 10 minutes)	RF1	Must
FR-007	Permanently lock the account when the escalation is exhausted; only the administrator can restore it	RF1	Must
FR-008	Registration and sign-in with Google and Facebook	RF1	Must
FR-010	Recover the password with a single-use code that expires	RF1	Must
FR-012	Rotate refresh tokens and detect their reuse	RF1	Must
FR-014	Delete the account by anonymizing the data (Ley 1581 de 2012)	RF1, RF5	Should
FR-015	The administrator lists, locks, restores, and deactivates accounts	RF1, RF6	Should

Note. MoSCoW priority (Must, Should, Could). The complete catalog contains 79 requirements (04-requirements/functional.md); these tables show the representative ones for each module.

Authorization module (iam-service)

Table 6

Detailed requirements — Authorization (iam-service)

ID	Description	Source	Priority
FR-101	Role-based access control for USER, ADMIN, and LINGUIST	RF6	Must
FR-102	Permissions are assigned to roles, never directly to users	RF6	Must
FR-103	Deny administration functions to anyone without the permission	RF6	Must
FR-104	Do not allow deleting a role that is assigned to a user	RF6	Must

Profile and notifications module (profile-service)

Table 7

Detailed requirements — Profile and notifications (profile-service)

ID	Description	Source	Priority
FR-201	View and edit profile data	RF5	Must
FR-202	Change the password in compliance with the current policy	RF5	Must
FR-203	Choose a light or dark theme	RF5	Should
FR-204	Choose the interface language (Spanish / English)	RF5	Should
FR-205	Enable or disable all notifications with a single toggle	RF4, RF5	Must
FR-502	Deliver notifications only through visual channels (push, in-app, email)	RF4	Must
FR-507	Mark a notification as read	RF4	Must

Lexicon module (lexicon-service)

Table 8

Detailed requirements — Lexicon (lexicon-service)

ID	Description	Source	Priority
FR-301	Present the sign catalog organized by category	RF7	Must

ID	Description	Source	Priority
FR-302	Search signs by name	RF7	Must
FR-303	Show the details of a sign with its multimedia resources	RF7	Must
FR-304	Present the alphabet (A–Z and Ñ) without repeated letters	RF7	Must
FR-305	Each sign has a stable code that does not change when published	RF7	Must
FR-307	The administrator creates, edits, publishes, and withdraws signs	RF7	Must
FR-310	Only ACTIVE signs are visible to the end user	RF7	Must

Translation and AI module (recognition-service)

Table 9
Detailed requirements — Translation and AI (recognition-service)

ID	Description	Source	Priority
FR-401	Capture signs with the camera and translate them into text in real time	RF3	Must
FR-402	Provide audio output, always accompanied by visible text	RF3	Should
FR-403	Record the model that produced each translation and its confidence	RF3	Must
FR-405	Visually warn when a sign is not recognized, instead of showing an incorrect translation	RF3	Must
FR-406	View one's own translation history, from most recent to oldest	RF3, RF5	Must
FR-407	Delete history entries (logical deletion)	RF5	Should
FR-601	Capture gesture samples grouped by capture session	RF3	Must
FR-602	Do not store any sample without verifiable consent	—	Must
FR-605	Maintain a registry of models with their training metrics	RF3	Must

Usage, achievements, audit, and configuration module

Table 10
Detailed requirements — Usage, achievements, audit, and configuration

ID	Description	Source	Priority
FR-701	Record an event each time the user enters a section	RF6	Must
FR-703	Show the administrator the most visited sections	RF6	Must
FR-706	Statistics are aggregated and require permission	RF6	Must
FR-801	Maintain an achievements catalog with a target greater than zero	RF8	Could
FR-803	An achievement is unlocked only once per user	RF8	Could
FR-901	Maintain an audit trail with values before and after each change	RF9	Must
FR-904	Classify errors by type (validation, authentication, permission, database, etc.)	RF10	Must
FR-905	Configure the password policy; only one policy may be active	RF11	Should

Nonfunctional requirements

Table 11

Nonfunctional requirements and their acceptance metric


Code	Attribute	Requirement and metric
RNF1	Performance	End-to-end response of 5 s or less; P95 latency < 300 ms in critical services (login, translations, lexicon) with 50 requests per second; ≥ 15 frames per second during capture
RNF2	Usability	Simple interface; a new user completes a translation without help in less than 2 minutes
RNF3	Compatibility	Android 9+, iOS 14+, and up-to-date desktop browsers
RNF4	Security	Passwords hashed with bcrypt; mandatory JWT with a secret of 32+ characters; progressive lockout; request rate limit on /api/auth; HTTPS in production
RNF5	Adaptability / scalability	500 concurrent users and 5,000 registered; each microservice scales independently
RNF6	Documentation	Technical, installation, and user manuals; OpenAPI contracts for each service
RNF7	Fault tolerance	A failure in one service does not stop the others; the event bus reconnects automatically
RNF8	Personal data protection	Explicit authorization with date and version; right of erasure; samples disassociated from identity
RNF9	Accessibility	WCAG 2.1 Level AA as the target; no information conveyed by sound alone; contrast 4.5:1; touch targets of 48 dp
RNF10	Observability	GET /health endpoint in each service; structured logs and classified errors
RNF11	Maintainability	Hexagonal architecture; unit test coverage ≥ 80%; commit and branch conventions
RNF12	Disaster recovery	Daily database backups; documented restoration in less than 4 hours

Note. Accessibility is treated as a primary constraint because the primary users are deaf people (World Wide Web Consortium [W3C], 2018).

Use case requirements

UML use case diagram

Figure 1
General use case diagram



Note. Own elaboration.

Use case characterization

Table 12
Characterization of use case CU-01 Sign in

Element	Description
Actors	End user, Administrator
Requirement	RF1 / ERF1.2
Precondition	The account exists and is ACTIVE
Main flow	1. The user opens the app and selects "Sign in". 2. Enters email and password. 3. The system validates the credentials. 4. The system displays the main dashboard.

Element	Description
Alternative flows	3a. Invalid credentials: displays an error and adds a failed attempt. 3b. Attempts are exceeded: the account is temporarily locked.
Postcondition	The user has an active session with their token

Table 13

Characterization of use case CU-02 Sign up

Element	Description
Actors	End user
Requirement	RF1 / ERF1.1
Precondition	The email is not registered
Main flow	1. The user selects "Sign up". 2. Fills out the form and accepts the terms. 3. The system creates the account and sends a code. 4. The user enters the code and the account becomes active.
Alternative flows	2a. Invalid data or terms not accepted: the system displays the errors. 4a. Expired code: the user requests that it be resent.
Postcondition	ACTIVE account, profile, and preferences created

Table 14

Characterization of use case CU-03 Translate signs to text

Element	Description
Actors	End user
Requirement	RF3 / ERF3.1, ERF3.2
Precondition	Signed-in session and camera permission
Main flow	1. The user opens "Translation" and taps "Start camera". 2. Performs the sign in front of the camera. 3. The system recognizes the sign and displays the text. 4. Optionally plays the voice output. 5. The system saves the translation to the history.
Alternative flows	1a. No camera permission: the system requests it. 3a. Sign not recognized: visual notice; no word is displayed.
Postcondition	The translation is stored in the user's history

Table 15

Characterization of use case CU-04 Consult LSC alphabet

Element	Description
Actors	End user
Requirement	RF7 / ERF7.1
Precondition	None (also available in the demo)
Main flow	1. The user opens "Alphabet". 2. The system displays the letters. 3. The user selects a letter and views its 3D model and description.
Alternative flows	2a. No connection: the letters saved in the cache are displayed.
Postcondition	The user views the selected sign

Table 16
Characterization of use case CU-05 Consult usage statistics

Element	Description
Actors	Administrator
Requirement	RF6 / ERF6.1
Precondition	Session with ADMIN role
Main flow	1. The administrator opens "Statistics". 2. The system displays translations per day, the most visited sections, and the most used signs.
Alternative flows	1a. User without ADMIN role: the system denies access (403).
Postcondition	Aggregated statistics visible

Table 17
Characterization of use case CU-06 Capture samples and train

Element	Description
Actors	Administrator
Requirement	RF3 / FR-601…606
Precondition	Session with ADMIN role and signer consent
Main flow	1. The administrator opens "Training". 2. Selects the sign and captures samples. 3. The system saves the samples. 4. The administrator generates and publishes the templates.
Alternative flows	3a. No consent: the sample is rejected. 2a. Discards the entire capture session.
Postcondition	New templates available for recognition

Traceability

Each functional requirement is linked to the user story that plans it and to the tables that persist it. The complete traceability matrix is maintained in the documentation repository (04-requirements/traceability-matrix.md). Table 18 summarizes the current coverage.

Table 18
Traceability coverage summary

Relationship	Coverage
SRS requirements with at least one detailed requirement	15 of 15
Detailed requirements with user story	79 of 79
Detailed requirements persisted in the data model	74 of 79 (the remaining 5 do not persist data)
Data model tables used by at least one requirement	25 of 29

Conclusions

The specification defines eleven functional requirements, broken down into 79 detailed requirements, and twelve nonfunctional requirements with measurable metrics. Accessibility and

personal data protection are established as primary constraints due to the nature of the users and of the biometric information the system handles.

This document is the baseline for analysis, design, and testing; any change in scope must be recorded here and in the traceability matrix before it is implemented.

References

Congreso de la República de Colombia. (2005, August 2). *Ley 982 de 2005, por la cual se establecen normas tendientes a la equiparación de oportunidades para las personas sordas y sordociegas*. Diario Oficial No. 45.995.

Congreso de la República de Colombia. (2012, October 17). *Ley Estatutaria 1581 de 2012, por la cual se dictan disposiciones generales para la protección de datos personales*. Diario Oficial No. 48.587.

Institute of Electrical and Electronics Engineers. (1998). *IEEE recommended practice for software requirements specifications* (IEEE Std 830-1998). IEEE. https://doi.org/10.1109/IEEESTD.1998.88286

Instituto Nacional para Sordos. (2020). *Observatorio social de la población sorda colombiana*. INSOR. https://www.insor.gov.co/observatorio/

Mora-Zarate, J. E., Garzón-Castro, C. L., & Castellanos Rivillas, J. A. (2025). LSC-54: A landmark-based dataset for Colombian Sign Language. *Data in Brief*. https://doi.org/10.1016/j.dib.2025.112145

Presidencia de la República de Colombia. (2013, June 27). *Decreto 1377 de 2013, por el cual se reglamenta parcialmente la Ley 1581 de 2012*. Diario Oficial No. 48.834.

Pressman, R. S., & Maxim, B. R. (2020). *Software engineering: A practitioner's approach* (9th ed.). McGraw-Hill Education.

Sommerville, I. (2016). *Software engineering* (10th ed.). Pearson.

World Wide Web Consortium. (2018). *Web Content Accessibility Guidelines (WCAG) 2.1*. W3C. https://www.w3.org/TR/WCAG21/

Zhang, F., Bazarevsky, V., Vakunov, A., Tkachenka, A., Sung, G., Chang, C.-L., & Grundmann, M. (2020). *MediaPipe Hands: On-device real-time hand tracking* (arXiv:2006.10214). arXiv. https://doi.org/10.48550/arXiv.2006.10214