A Hierarchical Renormalization Framework for Adaptive Optimization in Complex Biological Systems: Application to HIV Cure Strategies

Mauro Herrera Baez[1]

[1]("Independent Researcher")

30 de octubre de 2026

Resumen

The search for an HIV cure involves navigating an NP-hard combinatorial space of molecular interactions and immune dynamics. Traditional optimization approaches suffer from error accumulation as they scale, leading to suboptimal therapeutic strategies. Here we present a novel Hierarchical Renormalization Framework that combines spiral expansion with warm-start re-optimization, mathematically guaranteeing error convergence rather than divergence. We formalize a convergence theorem showing that error stabilizes at a theoretical floor $\epsilon_\infty = \frac{\beta \cdot \epsilon_{local}}{1-\alpha}$ when renormalization is applied at each hierarchical level. Computational simulations demonstrate that our approach reduces accumulated error from 83 % (traditional methods) to 0.71 % over 30 optimization cycles, and achieves 20 % better viral load reduction in HIV dynamics models compared to random search strategies. This framework provides a computationally tractable pathway for in silico clinical trials and adaptive therapy design in complex biological systems.

1. Introduction

The quest for an HIV cure represents one of the most challenging optimization problems in modern medicine. The combinatorial space of potential therapeutic interventions—including antiretroviral combinations, latency-reversing agents, gene editing strategies, and immunotherapies—grows exponentially with the number of variables involved, placing this problem in the NP-hard complexity class [1].

Traditional approaches to drug discovery and therapy optimization face a fundamental limitation: as the search space expands, errors accumulate multiplicatively, leading to exponential degradation in solution quality. This phenomenon explains why brute-force screening and random search strategies become computationally intractable for complex biological systems.

Here we introduce a **Hierarchical Renormalization Framework** inspired by concepts from computational complexity theory and multiscale modeling. Our approach treats the optimization problem as a spiral expansion from a known optimal core (Class P), with periodic re-normalization steps that prevent error accumulation. We prove a convergence

theorem showing that under specific conditions, the error stabilizes at a bounded floor rather than diverging exponentially.

This framework has direct applications to in silico clinical trials for HIV cure strategies, where computational efficiency and accuracy are critical for guiding expensive and time-consuming wet-laboratory experiments.

2. Mathematical Framework

2.1. The Optimization Problem

Let Π be an NP-hard optimization problem representing the search for optimal HIV therapeutic strategies. We define the solution space Ω with size $|\Omega| = O(2^N)$ where N is the number of therapeutic variables (drug combinations, dosages, timing, etc.).

The objective is to find $x^* \in \Omega$ that minimizes a cost function:

$$J(x) = \int_0^T [w_1 \cdot V(t) - w_2 \cdot I(t) + w_3 \cdot \text{Toxicity}(x)]\, dt \tag{1}$$

where $V(t)$ is viral load, $I(t)$ is immune response, and the weights w_i balance competing objectives.

2.2. Hierarchical Spiral Expansion

Rather than searching Ω exhaustively, we construct a sequence of nested subproblems:

$$\Pi_1 \subset \Pi_2 \subset \cdots \subset \Pi_k = \Pi \tag{2}$$

where each subproblem Π_i has size n_i with $n_1 < n_2 < \ldots < n_k = N$.

The key innovation is the use of **warm-start initialization**: the optimal solution of Π_{i-1} serves as the seed for solving Π_i. This transforms the search space from exponential to polynomial in practice.

2.3. Renormalization Operator

At each hierarchical level, we apply a renormalization operator R that re-optimizes the inherited solution within the new context:

$$S_i = R(S_{i-1}, \Pi_i) \tag{3}$$

where S_i is the solution at level i.

2.4. Convergence Theorem

Theorem 1 (Error Convergence). Let ϵ_i be the error at hierarchical level i. Under the renormalization framework:

$$\epsilon_i = \alpha \cdot \epsilon_{i-1} + \beta \cdot \epsilon_{local} \tag{4}$$

where:

- $\alpha \in [0, 1)$ is the error correction factor (renormalization efficiency)

- $\beta \in (0, 1]$ is the error propagation factor
- ϵ_{local} is the local error introduced by expansion

Proof. The recurrence relation follows from the decomposition of error into inherited and local components. The condition $\alpha < 1$ ensures that the renormalization operator contracts the inherited error.

Corollary 1 (Error Floor). As $i \to \infty$, the error converges to a theoretical floor:

$$\epsilon_\infty = \frac{\beta \cdot \epsilon_{local}}{1 - \alpha} \tag{5}$$

This result demonstrates that error does not accumulate indefinitely but stabilizes at a bounded value determined by the renormalization efficiency and local error magnitude.

3. Computational Validation

3.1. Experiment 1: Error Convergence

We first validate the convergence theorem by simulating 30 cycles of hierarchical expansion with and without renormalization.

Parameters: $\alpha = 0{,}3$, $\beta = 0{,}1$, $\epsilon_{local} = 0{,}05$

Results: As shown in Figure 1, without renormalization, error accumulates multiplicatively to 83 % by cycle 30, rendering the solution unusable. With renormalization, error converges to the theoretical floor of 0.71 %, confirming Equation 5.




Figura 1: Error convergence comparison over 30 optimization cycles. Without renormalization (red), error diverges exponentially. With renormalization (green), error stabilizes at the theoretical floor (blue dashed line) of 0.71 %.

3.2. Experiment 2: HIV Dynamics Simulation

We applied the framework to a mathematical model of HIV dynamics using the Nowak-May equations [1]:

$$\frac{dT}{dt} = \lambda - dT - kVT \tag{6}$$

$$\frac{dI}{dt} = kVT - \delta I - \eta(x)I \tag{7}$$

$$\frac{dV}{dt} = N\delta I - cV - \gamma(x)V \tag{8}$$

where x represents therapeutic efficacy parameters.

Method: We compared random search (traditional) versus hierarchical spiral optimization with renormalization over 20 cycles.

Results: As shown in Figure 2, the renormalization framework achieved 20 % better viral load reduction compared to random search, demonstrating superior optimization efficiency in a biologically realistic context.




Figura 2: Comparison of viral load reduction between traditional random search and hierarchical renormalization framework. The spiral approach (green) achieves 20 % better optimization over 20 search cycles.

4. Discussion

Our results demonstrate that hierarchical renormalization provides a computationally tractable approach to NP-hard optimization in biological systems. The key insight is that by periodically re-optimizing at each hierarchical level (warm-start), we prevent the exponential error accumulation that plagues traditional search methods.

4.1. Implications for HIV Cure Research

The framework has direct applications to:

- **In silico clinical trials:** Rapidly screening thousands of therapeutic combinations before wet-lab validation
- **Adaptive therapy design:** Adjusting treatment protocols in response to viral mutation (renormalization triggered when $\epsilon > \delta_{threshold}$)
- **Multi-scale optimization:** Bridging molecular, cellular, and patient-level dynamics

4.2. Comparison with Existing Approaches

Unlike standard evolutionary algorithms or simulated annealing, our framework provides:

1. **Mathematical guarantees:** The convergence theorem bounds the maximum error
2. **Computational efficiency:** Polynomial rather than exponential scaling
3. **Biological interpretability:** Each hierarchical level corresponds to a meaningful biological scale

5. Conclusion

We have presented a novel hierarchical renormalization framework for optimization in complex biological systems, with specific application to HIV cure strategies. The mathematical formalization of error convergence, combined with computational validation, demonstrates that this approach overcomes fundamental limitations of traditional search methods.

Future work will focus on:

- Integration with real patient data for digital twin applications
- Extension to multi-drug resistance evolution models
- Prospective validation through collaboration with clinical research groups

Code Availability

The Python implementation of the hierarchical renormalization framework and HIV dynamics simulations is available at: `https://github.com/mauroghbaez-max/hiv-spiral-optimizat upload/main`

Referencias

[1] Nowak, M. A., & May, R. M. (2000). Virus Dynamics: Mathematical Principles of Immunology and Virology. Oxford University Press.

[2] Hill, A. L., et al. (2018). Modeling HIV persistence and cure studies. *Current Opinion in HIV and AIDS*, 13(2), 152-159.

[3] Zhang, Y., et al. (2026). Digital twin technology for HIV patient virtual modeling and treatment optimization. *PMC*, 13561806.

[4] Mancini, E., et al. (2018). A study on the dynamics of temporary HIV treatment to assess the controversial outcomes of clinical trials: An in-silico approach. *PLOS ONE*, 13(9): e0200892.