

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

**Institute of Computer Technology**  
**B. Tech Computer Science and Engineering**

**Sub: Algorithm Analysis and Design**

**Practical 3**

NextMid Technology is an American food company that manufactures, markets, and distributes spices, seasoning mixes, condiments, and other flavoring products for the industrial, restaurant, institutional, and home markets, they are having some number quantity of different categories item food, kindly help them to sort data using any three sorting methods and determine the time required to sort the elements. Repeat the experiment for different values of n, the number of elements in the list to be sorted and plot a graph of the comparison between them.

Design the algorithm for the same and implement using the programming language of your choice. Make comparative analysis for various use cases & input size.

CODE :

```
from flask import Flask, request, render_template_string, send_file
```

```
import time
```

```
import matplotlib.pyplot as plt
```

```
import io
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014  
import random

```
app = Flask(__name__)
```

```
def bubble_sort(arr):
```

```
    n = len(arr)
```

```
    start_time = time.time()
```

```
    for i in range(n):
```

```
        for j in range(0, n-i-1):
```

```
            if arr[j] > arr[j+1]:
```

```
                arr[j], arr[j+1] = arr[j+1], arr[j]
```

```
    end_time = time.time()
```

```
    return (end_time - start_time) * 1000 # Convert to milliseconds
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014

```
def quick_sort(arr):
```

```
    start_time = time.time()
```

```
    def partition(low, high):
```

```
        i = low - 1
```

```
        pivot = arr[high]
```

```
        for j in range(low, high):
```

```
            if arr[j] < pivot:
```

```
                i += 1
```

```
            arr[i], arr[j] = arr[j], arr[i]
```

```
        arr[i+1], arr[high] = arr[high], arr[i+1]
```

```
    return i + 1
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014

```
def quick_sort_recursive(low, high):
```

```
    if low < high:
```

```
        pi = partition(low, high)
```

```
        quick_sort_recursive(low, pi - 1)
```

```
        quick_sort_recursive(pi + 1, high)
```

```
quick_sort_recursive(0, len(arr) - 1)
```

```
end_time = time.time()
```

```
return (end_time - start_time) * 1000 # Convert to milliseconds
```

```
def merge_sort(arr):
```

```
    start_time = time.time()
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014

```
def merge(left, right):  
  
    result = []  
  
    i = j = 0  
  
    while i < len(left) and j < len(right):  
  
        if left[i] < right[j]:  
  
            result.append(left[i])  
  
            i += 1  
  
        else:  
  
            result.append(right[j])  
  
            j += 1  
  
    result.extend(left[i:])  
  
    result.extend(right[j:])
```

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

return result

```
def merge_sort_recursive(arr):
```

```
    if len(arr) <= 1:
```

```
        return arr
```

```
    mid = len(arr) // 2
```

```
    left = merge_sort_recursive(arr[:mid])
```

```
    right = merge_sort_recursive(arr[mid:])
```

```
    return merge(left, right)
```

```
arr[:] = merge_sort_recursive(arr)
```

```
end_time = time.time()
```

```
return (end_time - start_time) * 1000 # Convert to milliseconds
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014

```
def measure_sort_times(size):  
  
    arr = [random.randint(0, 10000) for _ in range(size)]  
  
    bubble_time = bubble_sort(arr.copy())  
  
    quick_time = quick_sort(arr.copy())  
  
    merge_time = merge_sort(arr.copy())  
  
    return bubble_time, quick_time, merge_time
```

```
def plot_sorting_times():  
  
    sizes = [10, 50, 100, 200, 300, 400, 500]  
  
    bubble_times = []  
  
    quick_times = []  
  
    merge_times = []
```

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014

for size in sizes:

bubble\_time, quick\_time, merge\_time = measure\_sort\_times(size)

bubble\_times.append(bubble\_time)

quick\_times.append(quick\_time)

merge\_times.append(merge\_time)

plt.figure(figsize=(10, 6))

plt.plot(sizes, bubble\_times, label='Bubble Sort', marker='o')

plt.plot(sizes, quick\_times, label='Quick Sort', marker='o')

plt.plot(sizes, merge\_times, label='Merge Sort', marker='o')

plt.xlabel('Number of Elements')

plt.ylabel('Time (milliseconds)')



NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

plt.title('Sorting Algorithm Performance')

plt.legend()

plt.grid(True)

img = io.BytesIO()

plt.savefig(img, format='png')

img.seek(0)

plt.close()

return img

@app.route("/", methods=["GET", "POST"])

def index():

if request.method == "POST":

try:

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

```
elements = request.form["elements"]
```

```
arr = list(map(int, elements.split()))
```

```
bubble_arr = arr.copy()
```

```
bubble_time = bubble_sort(bubble_arr)
```

```
quick_arr = arr.copy()
```

```
quick_time = quick_sort(quick_arr)
```

```
merge_arr = arr.copy()
```

```
merge_time = merge_sort(merge_arr)
```

```
return render_template_string("""
```

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

<h1>Sorted Lists</h1>

<p><strong>Original List:</strong> {{ original }}</p>

<p><strong>Bubble Sorted List:</strong> {{ bubble }}</p>

<p><strong>Bubble Sort Time:</strong> {{ bubble\_time }}  
milliseconds</p>

<p><strong>Quick Sorted List:</strong> {{ quick }}</p>

<p><strong>Quick Sort Time:</strong> {{ quick\_time }}  
milliseconds</p>

<p><strong>Merge Sorted List:</strong> {{ merge }}</p>

<p><strong>Merge Sort Time:</strong> {{ merge\_time }}  
milliseconds</p>

<a href="/">Try Again</a>

<h2>Performance Graph</h2>



""", original=arr, bubble=bubble\_arr, bubble\_time=bubble\_time,

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

```
        quick=quick_arr, quick_time=quick_time, merge=merge_arr,  
merge_time=merge_time)
```

```
except ValueError:
```

```
    return "Invalid input. Please enter a space-separated list of integers."
```

```
return ""
```

```
<h1>Sorting Algorithm Demo</h1>
```

```
<form method="post">
```

```
<label for="elements">Enter numbers:</label><br>
```

```
<input type="text" id="elements" name="elements" required><br><br>
```

```
<input type="submit" value="Sort">
```

```
</form>
```

```
<h2>Performance Graph</h2>
```

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014



"""

@app.route("/plot")

def plot():

img = plot\_sorting\_times()

return send\_file(img, mimetype='image/png')

if \_\_name\_\_ == "\_\_main\_\_":

app.run(debug=True)

NAME : MAURYA PATEL  
BATCH : 51  
BRANCH : CBA  
EN NO: 22162101014  
OUTPUT :

---

### Sorting Algorithm Demo

Enter numbers:

Sort

### Performance Graph

Sorting Algorithm Performance

## Sorted Lists

**Original List:** [12, 8, 9, 78]

**Bubble Sorted List:** [8, 9, 12, 78]

**Bubble Sort Time:** 0.0 milliseconds

**Quick Sorted List:** [8, 9, 12, 78]

**Quick Sort Time:** 0.0 milliseconds

**Merge Sorted List:** [8, 9, 12, 78]

**Merge Sort Time:** 0.0 milliseconds

[Try Again](#)

### Performance Graph

NAME : MAURYA PATEL

BATCH : 51


BRANCH : CBA

EN NO: 22162101014

Merge Sort Time: 0.0 milliseconds

[Try Again](#)

### Performance Graph



### Questions:

What is the best, average and worst case analysis of algorithms?

ANS : The best case analysis of an algorithm provides the minimum time or space required for the algorithm to complete, given the most favorable input scenario.

The average case analysis provides the expected time or space complexity of an algorithm over all possible inputs, assuming a certain distribution of inputs.

The worst case analysis provides the maximum time or space required for the algorithm to complete, given the most unfavorable input scenario.

Which are different asymptotic notations? What is their use?

ANS : Big-O Notation ( $O$ ):

Use: To express the maximum time complexity and to ensure the algorithm's performance does not exceed a certain bound.

Omega Notation ( $\Omega$ ):

Use: To express the minimum time complexity and to ensure the algorithm's performance is not better than a certain bound.

Theta Notation ( $\Theta$ ):

NAME : MAURYA PATEL

BATCH : 51

BRANCH : CBA

EN NO: 22162101014

Use: To express the exact growth rate of the algorithm's time complexity.

What is the time complexity of above 3 sorting algorithms in all cases?

ANS : Best Case:

$O(n)$

Average Case:

$O(n^2)$

Worst Case:

$O(n^2)$

Quick Sort:

Best Case:

$O(n \log n)$

Average Case:

$O(n \log n)$

Worst Case:

$O(n^2)$

Merge Sort:

Best Case:

$O(n \log n)$

Average Case:

$O(n \log n)$

Worst Case:

$O(n \log n)$