Minerva: Reinforcement Learning with Verifiable Rewards for Cyber Threat Intelligence LLMs

Md Tanvirul Alam *ma8235@rit.edu*
Rochester Institute of Technology, Rochester, NY, USA

Aritran Piplai *apiplai@utep.edu*
University of Texas at El Paso, El Paso, TX, USA

Ionut Cardei *icardei@fau.edu*
Florida Atlantic University, Boca Raton, FL, USA

Nidhi Rastogi *nxrvse@rit.edu*
Rochester Institute of Technology, Rochester, NY, USA

Peter J Worth Jr *pworth2022@fau.edu*
Florida Atlantic University, Boca Raton, FL, USA

Reviewed on OpenReview: *https://openreview.net/forum?id=w1IMu9exKC*

Abstract

Cyber threat intelligence (CTI) analysts routinely convert noisy, unstructured security artifacts into standardized, automation-ready representations. Although large language models (LLMs) show promise for this task, existing approaches remain brittle when producing structured CTI outputs and have largely relied on supervised fine-tuning (SFT). In contrast, CTI standards and community-maintained resources define canonical identifiers and schemas that enable deterministic verification of model outputs. We leverage this structure to study reinforcement learning with verifiable rewards (RLVR) for CTI tasks. We introduce *Minerva*, a unified dataset and training pipeline spanning multiple CTI subtasks, each paired with task-specific verifiers that score structured outputs and identifier predictions. To address reward sparsity during rollout, we propose *MinervaRL*, an auxiliary self-training mechanism that generates additional verified trajectories and distills them back into the model. Averaged across four backbones and 12 CTI benchmarks, MinervaRL improves the mean score by 15.8 percentage points over the corresponding base models and by 4.3 points over GRPO.

1 Introduction

Cyber threat intelligence (CTI) often requires mapping free-text security information into standardized labels, scores, and structured records that downstream tools can use (Xu et al., 2024). In practice, analysts map unstructured inputs such as vulnerability descriptions, detection rules, and incident narratives to standardized frameworks and identifiers, including MITRE ATT&CK (Adversarial Tactics, Techniques, and Common Knowledge) for adversary behavior, Common Vulnerabilities and Exposures (CVE) identifiers, Common Weakness Enumeration (CWE) labels, and Common Vulnerability Scoring System (CVSS) vectors and scores (MITRE Corporation, 2026d; Byers et al., 2022; MITRE Corporation, 2026c; FIRST.org, Inc., 2019). These standards enable consistent reporting and large-scale exchange through formats and protocols such as Structured Threat Information Expression (STIX) and Trusted Automated Exchange of Intelligence Information (TAXII) (Strom et al., 2020; OASIS Cyber Threat Intelligence (CTI) Technical Committee, 2021a;b). Figure 1 illustrates this setting with a public vulnerability description mapped to canonical CWE and CVSS outputs. These standards also make correctness critical: a CTI system must ground outputs to

evolving taxonomies, preserve evidence from noisy text, and produce syntactically valid structured artifacts. Even small identifier, schema, or formatting errors can break downstream automation or propagate incorrect intelligence.

Large language models (LLMs) are a natural fit for CTI because they can read long-form security narratives and generate structured analyst-facing outputs. Prior work shows growing use of LLMs across cybersecurity, and domain-adapted models such as CTI-BERT demonstrate that security-specific pretraining improves CTI-oriented extraction and representation learning (Xu et al., 2024; Park & You, 2023). However, existing CTI benchmarks reveal uneven reliability. Models can often follow analyst-style instructions and recover surface facts, but still fail on workflow-critical outputs such as ATT&CK technique mapping, mitigation recommendation, and vulnerability root-cause identification (Ji et al., 2024; Alam et al., 2024; Liu et al., 2024). These failures are especially problematic for deployment, where CTI systems must produce canonical identifiers, valid schemas, and grounded structured predictions, often under constraints that favor smaller specialized models.

A key observation behind this work is that many CTI tasks are directly verifiable. Unlike open-ended preference tasks, CTI outputs often have canonical targets: an ATT&CK technique ID, a CWE label, a CVSS vector, a mitigation set, or a structured extraction schema. This makes CTI well-suited to reinforcement learning with verifiable rewards (RLVR), where deterministic programmatic verifiers score model outputs without requiring a learned reward model or human preference labels. RLVR has recently improved reasoning and structured generation in LLMs (Shao et al., 2024; DeepSeek-AI et al., 2025; Wen et al., 2025), while avoiding the cost and subjectivity of RLHF-style preference collection (Ouyang et al., 2022). However, under a small rollout budget, hard prompts may produce no fully verified completion (Wu et al., 2025). This finite-budget detectability issue is common in CTI, especially for long-tail identifiers and strict structured outputs.

We introduce **Minerva**, a unified CTI training suite and RLVR pipeline for specializing open-weight LLMs to verifier-checkable CTI workflows. Minerva-CTI contains 16 training tasks spanning three broad families: vulnerability-centric mapping, such as CVE → CWE/CVSS/ATT&CK; detection-centric mapping, such as Sigma, Microsoft Sentinel, and Splunk rules → ATT&CK; and procedure-oriented mapping, such as scenarios or behaviors → techniques, tactics, mitigations, or threat actors. All tasks are normalized to canonical target spaces and paired with deterministic verifiers.

To train reliably under sparse verifier feedback, we propose **MinervaRL**. MinervaRL augments the standard GRPO-based RLVR loop with hardness-gated answer-conditioned rationale generation. When the current policy fails to produce a fully verified rollout for a prompt, MinervaRL temporarily reveals the gold label during training to elicit a short rationale trace, filters the generated candidates for correctness and quality, and distills accepted traces back onto the original answer-free prompt. At evaluation time, MinervaRL uses the same answer-free prompts as GRPO and receives no label hints.

Our contributions are:

- We curate **Minerva-CTI**, a unified 16-task CTI training suite with deterministic, verifier-checkable targets spanning vulnerability, detection, and procedure-oriented CTI workflows.
- We propose **MinervaRL**, an RLVR extension that mitigates sparse verifier feedback by leveraging hardness-gated, answer-conditioned rationale generation and periodic distillation onto the original answer-free prompts.
- We evaluate across 12 CTI benchmarks and four open-weight backbones. MinervaRL improves the mean CTI score by 15.8 percentage points over matched base checkpoints and by 4.3 points over GRPO, while outperforming controlled SFT, rejection-finetuning, and off-policy RLVR baselines on average.

Representative CTI mapping

Input: CVE description
CVE-2024-20092. In vdec, there is a possible out of bounds write due to a missing bounds check. This could lead to local escalation of privilege with System execution ...

Structured output
CWE: `CWE-787`
CVSS: `AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H`
Score/severity: `7.8 / High`

Figure 1: Representative CTI mapping from a CVE description to structured labels and scores.

2 Related Work

LLMs for cyber threat intelligence. LLMs have increasingly been applied to CTI workflows that require extracting, normalizing, and grounding security-relevant information from unstructured reports. A central task is mapping tactics, techniques, and procedures (TTPs) from natural-language threat reports to MITRE ATT&CK. TRAM demonstrates an applied LLM pipeline for automated technique identification, motivated by the cost and brittleness of manual ATT&CK mapping (Center for Threat-Informed Defense, 2023). A recent systematization of automated TTP extraction methods, including generative LLMs, highlights persistent comparability challenges arising from heterogeneous ontologies, datasets, and evaluation protocols (Büchel et al., 2025). Expert-annotated resources such as AnnoCTR provide more controlled supervision and evaluation for ATT&CK-labeled CTI text (Lange et al., 2024). Beyond report-level extraction, LLMs have been used to bootstrap structured CTI artifacts such as knowledge graphs (Hu et al., 2024), and hybrid knowledge-graph/LLM systems have been proposed for producing actionable intelligence from heterogeneous evidence (Fieblinger et al., 2024). Other work maps vulnerability descriptions into standardized taxonomies, where prompting alone remains unreliable but instruction templating and fine-tuning can improve grounding (Liu et al., 2023; Zhang et al., 2024). Instruction-tuned security models such as CyberPal and CyberPal 2.0 further improve cybersecurity-oriented behavior, while also illustrating the limitations of supervised fine-tuning for robust CTI reasoning and structured output generation (Levi et al., 2024; 2025). Complementary efforts study data-efficient ATT&CK technique identification, including active learning (Rahman et al., 2024), and LLM pipelines for mapping detection artifacts, such as Sigma rules and SIEM analytics, to ATT&CK via prompt chaining and retrieval (Wudali et al., 2025).

CTI and cybersecurity benchmarks. A growing set of benchmarks evaluates LLMs on CTI and cybersecurity workflows beyond general NLP tasks. CTIBench and AthenaBench target CTI-specific capabilities such as CVE→CWE mapping, CVSS prediction, ATT&CK technique extraction, mitigation recommendation, and threat-actor attribution (Alam et al., 2024; 2025). SEvenLLM introduces a bilingual cybersecurity instruction corpus and benchmark with incident-analysis and response-oriented CTI tasks (Ji et al., 2024). Broader cybersecurity evaluations include SECURE, which measures LLM performance across multiple cybersecurity tasks (Bhusal et al., 2024); CyberMetric, which evaluates broad cybersecurity knowledge through 10,000 questions (Tihanyi et al., 2024); and CyberBench, which aggregates datasets for cybersecurity-language understanding tasks such as entity recognition, summarization, and classification (Liu et al., 2024). These benchmarks expose recurring failure modes, including hallucination, mis-grounding, brittle identifier mapping, and schema errors.

Reinforcement learning with verifiable rewards. Reinforcement learning with verifiable rewards (RLVR) has become a prominent post-training approach for tasks where correctness can be checked programmatically, especially mathematical reasoning and code generation (Shao et al., 2024; DeepSeek-AI et al., 2025). Instead of relying on learned preference models, RLVR uses deterministic verifiers to assign rewards, making it attractive for domains with canonical answers and structured outputs. Recent work shows that RLVR can improve reasoning behavior, reliability, and calibration relative to supervised baselines (Wen et al., 2025), while other studies examine whether RLVR elicits new capabilities or primarily amplifies behaviors already present in the base model (Yue et al., 2025; Cheng et al., 2025; Wu et al., 2025). Related analyses further suggest that supervised fine-tuning can overfit or memorize solution traces, whereas reinforcement learning may encourage more generalizable behavior under verifiable feedback (Chu et al., 2025). Follow-up work studies how RLVR gains depend on task difficulty, rollout budget, and exploration strategy (Yang et al.,

2025), and shows that verifiable-reward formulations can transfer beyond math and code to other structured domains (Lu et al., 2025; Su et al., 2025). Our work brings this paradigm to CTI, where many targets are canonical identifiers, label sets, or structured strings, and addresses the sparse-reward regime through hardness-gated answer-conditioned rationale generation and original-prompt distillation.

3 Minerva-CTI Dataset

We introduce **Minerva-CTI**, a unified CTI training suite curated from standards, knowledge bases, and community-maintained security resources, including MITRE ATT&CK (MITRE Corporation, 2026d;a), MITRE CAPEC (MITRE Corporation, 2026b), the National Vulnerability Database (NVD) (Byers et al., 2022; MITRE Corporation, 2026c), Mappings Explorer (Center for Threat-Informed Defense, 2026), and detection or emulation corpora such as Sigma, Atomic Red Team, Microsoft Sentinel, and Splunk Security Content (SigmaHQ, 2026; Red Canary, 2026; Microsoft, 2026; Splunk, 2026). From these sources, we define 16 verifier-checkable tasks spanning vulnerability mapping, detection-rule mapping, and procedure-oriented CTI reasoning. Tasks include predicting ATT&CK techniques, tactics, and mitigations; mapping CVEs to CWE labels and CVSS v3.1 vectors; attributing threat actors based on observed behaviors; and linking CAPEC examples to attack patterns or weaknesses. The dataset contains 32,000 training instances and 1,200 validation instances; Appendix A provides full task definitions, sources, and split statistics.

Each instance consists of an analyst-style prompt x, a canonical target $y^\star$, and task metadata used by the verifier. Targets include single identifiers, unordered identifier sets, and structured strings such as CVSS v3.1 vectors. During construction, we normalize labels against fixed taxonomy snapshots, map aliases to canonical forms when applicable, and deduplicate set-valued targets before scoring. This yields stable verifier targets despite heterogeneous surface forms across CTI sources. Minerva-CTI is intentionally heterogeneous: examples are allocated per task so that low-resource mappings remain represented alongside larger CVE- and scenario-derived tasks. The held-out Minerva validation split is used for checkpoint selection and diagnostics, while the 12-task suite in Section 5.1 evaluates both training-aligned performance and transfer to benchmarks not used as Minerva-CTI training objectives.

4 Methodology

4.1 Reinforcement Learning with Verifiable Rewards

We train CTI models using reinforcement learning with verifiable rewards (RLVR). Let $x \in \mathcal{X}$ denote a prompt, $y \in \mathcal{Y}$ a model-generated output sequence, and $y^\star \in \mathcal{A}$ the canonical target answer for x. Each training task is paired with a deterministic programmatic verifier $R_{\text{MINERVA}} : \mathcal{X} \times \mathcal{Y} \times \mathcal{A} \to [0, 1]$, which extracts the final answer from y, normalizes it, and scores it against $y^\star$. Rewards are instantiated as exact identifier matching for single-label outputs, structured partial credit for hierarchical labels such as ATT&CK techniques and sub-techniques, or set-based overlap for multi-label targets such as tactics, mitigations, and CWE sets. This formulation is well suited to CTI because many analyst-facing outputs are structured, canonicalized, and automatically auditable. It therefore enables scalable optimization without a learned reward model or human preference labels. Appendix B describes answer extraction, normalization, and task-specific verification. Unless otherwise stated, we do not add a separate format reward.

We optimize the policy π_θ, parameterized by θ, with Group Relative Policy Optimization (GRPO) (Shao et al., 2024; DeepSeek-AI et al., 2025), a PPO-style objective (Schulman et al., 2017) that avoids training a value critic by estimating advantages from multiple completions sampled for the same prompt. For each training pair $(x, y^\star)$, we sample a group of N completions $\{y_j\}_{j=1}^N$ from the behavior policy $\pi_{\theta_{\text{old}}}(\cdot \mid x)$, score them with the verifier to obtain rewards $r_j = R_{\text{MINERVA}}(x, y_j, y^\star)$, and compute group-normalized advantages

$$\hat{A}_j = \frac{r_j - \text{mean}(\{r_h\}_{h=1}^N)}{\text{std}(\{r_h\}_{h=1}^N) + \epsilon}. \tag{1}$$

Here $\epsilon > 0$ is a small numerical stabilizer. The policy is then updated with the clipped GRPO surrogate

$$\mathcal{L}_{\text{GRPO}}(\theta) = -\mathbb{E}\left[\frac{1}{N}\sum_{j=1}^{N}\min\left(\rho_j(\theta)\hat{A}_j,\ \text{clip}(\rho_j(\theta), 1-\varepsilon, 1+\varepsilon)\,\hat{A}_j\right)\right], \quad \rho_j(\theta) = \frac{\pi_\theta(y_j \mid x)}{\pi_{\theta_{\text{old}}}(y_j \mid x)}. \tag{2}$$

Here $\rho_j(\theta)$ is the likelihood ratio between the updated policy and the behavior policy for completion y_j, and ε is the clipping radius. The expectation is over sampled training pairs and their completion groups. This critic-free objective uses only verifier scores and within-prompt relative comparisons, making it a natural optimizer for structured CTI tasks with automatically checkable outputs.

4.2 MinervaRL

Minerva-CTI tasks are verifier-checkable, but they are not uniformly easy for on-policy RLVR. Many tasks require selecting an exact identifier, or a small set of identifiers, from a large, finite, and long-tailed label space. For example, our January 2026 snapshots contain 944 CWE identifiers and 44 MITRE Enterprise mitigation identifiers, with many labels appearing rarely in public pretraining data compared to more common schemas, such as ATT&CK techniques. Under a small rollout budget, the policy may therefore fail to sample any fully verified completion for hard prompts. This finite-budget no-full-success regime motivates an auxiliary mechanism that can generate verified training traces while preserving the original answer-free inference setting.

MinervaRL augments the standard GRPO-based RLVR loop with hardness-gated answer-conditioned self-training. The central idea is simple: when the current policy cannot solve a prompt within the available rollout budget, we temporarily reveal the ground-truth label during training to elicit a short rationale that justifies it. We call the resulting trace an *answer-conditioned rationale* (ACR). Importantly, the label-revealing prompt is used only to generate candidate training traces. Before distillation, each candidate is checked by the task verifier and filtered for leakage and rationale quality. Accepted traces are then distilled back into the actor using the original task prompt, without any label hint. Thus, MinervaRL uses labels to construct additional verified supervision during training, but all reported evaluations use the same answer-free prompts as the GRPO baseline.

The procedure runs on two coupled timescales. At every training step, the actor performs the ordinary on-policy GRPO update on verifier-scored rollouts from the original prompts, so the primary RLVR objective is unchanged. In parallel, MinervaRL identifies hard prompts whose rollout group contains no fully verified completion, i.e., prompts with maximum verifier reward below 1. These prompts are added to an ACR buffer $\mathcal{P}$ together with a label-conditioned generation prompt. Every I steps, an exponential moving average (EMA) teacher samples ACR candidates for the buffered prompts. Candidates that are verifier-correct and pass the filtering pipeline are stored in a distillation buffer $\mathcal{Q}$ as pairs of the original prompt and the accepted trace. The actor then receives a lightweight supervised update on samples from $\mathcal{Q}$, after which the buffers are reset. In this way, MinervaRL preserves on-policy RLVR as the main training signal while periodically adding verified original-prompt training examples for selected hard prompts.

Notation. Let $\mathcal{D} = \{(x_i, y_i^\star)\}_{i=1}^n$ be the Minerva-CTI training set, where $x_i \in \mathcal{X}$ is the original answer-free prompt and $y_i^\star \in \mathcal{A}$ is the ground-truth structured target. The actor π_θ and EMA teacher π_ϕ both generate output sequences $y \in \mathcal{Y}$, including ordinary RLVR responses and ACR traces. The buffers $\mathcal{P}$ and $\mathcal{Q}$ store ACR-generation prompts and accepted original-prompt distillation pairs, respectively. We write $x_i \oplus b(y_i^\star, d_i)$ for concatenating x_i with a label-conditioned ACR suffix $b(\cdot)$, where d_i denotes optional canonical reference details, and $\text{task}(x_i)$ for the task type of prompt x_i. The instance-specific heuristic filter $\text{Filter}_i : \mathcal{Y} \to \{0, 1\}$ returns 1 when a candidate passes the deterministic leakage and quality checks using the prompt and reference context; the TextCNN score is applied separately. Below, $r_{i,j}$ is the reward r_j from Section 4.1 with the prompt index made explicit.

Step 1 (Algorithm 1): RLVR rollouts and GRPO update. At step t, we sample a batch $\mathcal{B}_t \subset \mathcal{D}$. For each $(x_i, y_i^\star) \in \mathcal{B}_t$, the actor samples $N = 8$ completions from the original prompt,

$$y_{i,j}^{\text{rlvr}} \sim \pi_\theta(\cdot \mid x_i), \qquad j = 1, \ldots, N, \tag{3}$$




Figure 2: MinervaRL overview separating the standard GRPO loop from the auxiliary ACR path. Solid arrows show the synchronous training flow, while dashed arrows show the periodic ACR distillation pass.

which are scored by the verifier:

$$r_{i,j} = R_{\text{MINERVA}}\left(x_i, y_{i,j}^{\text{rlvr}}, y_i^{\star}\right). \tag{4}$$

The actor is updated with GRPO using only these on-policy, original-prompt trajectories, matching the standard GRPO baseline.

Step 2 (Algorithm 1): Hard-prompt buffering. For each prompt, compute the best rollout reward

$$m_i = \max_{j \in \{1,\ldots,N\}} r_{i,j}. \tag{5}$$

We call x_i hard at step t if $m_i < 1$, i.e., none of the sampled completions is fully verified. This gate is broader than the zero-solve statistic in Section 7.1: $m_i = 0$ denotes an all-zero group with no within-prompt GRPO contrast, whereas $0 < m_i < 1$ denotes a partial-credit group that may still contribute relative GRPO signal. For each hard prompt, excluding CVSS, we construct an answer-conditioned rationale prompt

$$x_i^{\text{acr}} = x_i \oplus b(y_i^{\star}, d_i), \tag{6}$$

where $b(\cdot)$ reveals the gold target and asks for a short rationale, and d_i optionally contains truncated canonical reference details. We add $(x_i, x_i^{\text{acr}}, y_i^{\star})$ to the ACR buffer $\mathcal{P}$. This gate is dynamic: a prompt stops entering $\mathcal{P}$ once the actor begins producing fully verified rollouts, focusing ACR generation on prompts without a fully verified rollout. We exclude CVSS because its verifier already provides dense graded feedback through CVSS base-score distance, unlike long-tail identifier tasks where incorrect IDs often yield no useful signal.

Step 3 (Algorithm 1): ACR generation and filtering. Every $I = 10$ steps, the EMA teacher samples $K = 4$ ACR candidates for each buffered prompt:

$$y_{i,k}^{\text{acr}} \sim \pi_{\phi}(\cdot \mid x_i^{\text{acr}}), \qquad k = 1, \ldots, K, \tag{7}$$

Algorithm 1 MinervaRL

Require: $\mathcal{D} = \{(x_i, y_i^\star)\}_{i=1}^n$; actor π_θ; verifier R_{MINERVA}; RLVR rollouts N; ACR rollouts K; interval I; EMA decay α; distill cap M; threshold τ_q; SFT scale γ
Ensure: Trained actor π_θ

Initialize: $\phi \leftarrow \theta$; $\mathcal{P}, \mathcal{Q} \leftarrow \emptyset$
for training step $t = 1, 2, \ldots$ **do**
  Step 1: RLVR rollouts and GRPO update
  $\mathcal{B}_t \leftarrow \textsc{SampleBatch}(\mathcal{D})$
  for all $(x_i, y_i^\star) \in \mathcal{B}_t$ **do**
    $Y_i^{\text{rlvr}} \leftarrow \{y_{i,j}^{\text{rlvr}} \sim \pi_\theta(\cdot \mid x_i)\}_{j=1}^N$
    $\mathbf{r}_i \leftarrow \{r_{i,j} = R_{\text{MINERVA}}(x_i, y_{i,j}^{\text{rlvr}}, y_i^\star)\}_{j=1}^N$
    $m_i \leftarrow \max_j r_{i,j}$
  $\theta \leftarrow \text{GRPO}\big(\theta, \mathcal{B}_t, \{Y_i^{\text{rlvr}}, \mathbf{r}_i\}_i\big)$; $\phi \leftarrow \alpha\phi + (1-\alpha)\theta$
  Step 2: Buffer hard prompts for ACR
  $\mathcal{P} \leftarrow \mathcal{P} \cup \{(x_i,\, x_i^{\text{acr}},\, y_i^\star) : (x_i, y_i^\star) \in \mathcal{B}_t,\ x_i^{\text{acr}} = x_i \oplus b(y_i^\star, d_i), m_i < 1,\ \text{task}(x_i) \neq \text{CVSS}\}$
  if $t \bmod I = 0$ **then**
    Step 3: ACR generation and filtering
    for all $(x_i, x_i^{\text{acr}}, y_i^\star) \in \mathcal{P}$ **do**
      $Y_i^{\text{acr}} \leftarrow \{y_{i,k}^{\text{acr}} \sim \pi_\phi(\cdot \mid x_i^{\text{acr}})\}_{k=1}^K$
      $\mathbf{q}_i \leftarrow \{q_{i,k} = \textsc{TextCNNGood}(y_{i,k}^{\text{acr}})\}_{k=1}^K$
      $\mathcal{E}_i \leftarrow \{k : R_{\text{MINERVA}}(x_i, y_{i,k}^{\text{acr}}, y_i^\star) = 1 \wedge \text{Filter}_i(y_{i,k}^{\text{acr}}) = 1 \wedge q_{i,k} \geq \tau_q\}$
      if $\mathcal{E}_i \neq \emptyset$ **then**
        $k^\star \leftarrow \arg\max_{k \in \mathcal{E}_i} q_{i,k}$; $\mathcal{Q} \leftarrow \mathcal{Q} \cup \{(x_i, y_{i,k^\star}^{\text{acr}})\}$
    Step 4: Distill accepted traces on original prompts
    if $\mathcal{Q} \neq \emptyset$ **then**
      $\mathcal{S} \leftarrow \textsc{Sample}(\mathcal{Q}, M)$; $\theta \leftarrow \text{SFT}(\theta, \mathcal{S}, \gamma\, \text{lr}_{\text{rlvr}})$
    $\mathcal{P}, \mathcal{Q} \leftarrow \emptyset$

using temperature 0.7 and nucleus sampling with $p = 0.9$. We retain only candidates that are verifier-correct and pass the filtering pipeline in Appendix C, which removes leakage, degeneration, insufficiently grounded rationales, and low-quality traces. The eligible set is

$$\mathcal{E}_i = \left\{k : R_{\text{MINERVA}}\left(x_i, y_{i,k}^{\text{acr}}, y_i^\star\right) = 1 \ \wedge\ \text{Filter}_i\left(y_{i,k}^{\text{acr}}\right) = 1 \ \wedge\ q_{i,k} \geq \tau_q\right\}, \tag{8}$$

where $q_{i,k}$ is the separate TextCNN GOOD probability and $\tau_q = 0.5$. If $\mathcal{E}_i \neq \varnothing$, we select

$$k^\star = \arg\max_{k \in \mathcal{E}_i} q_{i,k} \tag{9}$$

and enqueue the original-prompt distillation pair $(x_i, y_{i,k^\star}^{\text{acr}})$ into $\mathcal{Q}$. Keeping at most one trace per prompt per interval prevents repeated generations from dominating the supervised update.

Step 4 (Algorithm 1): Original-prompt distillation. At each distillation interval, if $\mathcal{Q} \neq \varnothing$, we sample up to $M = 256$ pairs $\mathcal{S} \subseteq \mathcal{Q}$ and apply one supervised update:

$$\mathcal{L}_{\text{sft}}(\theta) = -\mathbb{E}_{(x,y)\sim\mathcal{S}}\left[\log \pi_\theta(y \mid x)\right]. \tag{10}$$

The update uses learning rate $\gamma \cdot \text{lr}_{\text{rlvr}}$ with $\gamma = 0.05$. The buffers $\mathcal{P}$ and $\mathcal{Q}$ are then reset. Because distillation is performed on the original prompt x_i, not on x_i^{acr}, the actor learns from verified traces without relying on label hints at inference time.

4.3 A Stylized Finite-Budget Detectability View

Let $a^\star$ denote the ground-truth structured target for prompt x. Because Minerva's task verifiers include extraction, normalization, alias handling, structured partial credit, and set-valued scoring, we define full success through the verifier itself:

$$S(x, y; a^\star) := \mathbb{1}\{R_{\text{MINERVA}}(x, y, a^\star) = 1\}, \qquad p_\theta(a^\star \mid x) := \Pr_{y\sim\pi_\theta(\cdot|x)}[S(x, y; a^\star) = 1]. \tag{11}$$

With k independent rollouts, the probability that the rollout group contains no fully verified completion is

$$\Pr[\text{no full success in } k \text{ rollouts}] = (1 - p_\theta(a^\star \mid x))^k . \tag{12}$$

For a failure tolerance $\zeta \in (0, 1)$, define the detectability threshold

$$\varepsilon_{k,\zeta} := 1 - \zeta^{1/k} \approx \frac{-\log \zeta}{k}. \tag{13}$$

When $p_\theta(a^\star \mid x) \geq \varepsilon_{k,\zeta}$, the probability of missing a fully verified completion in k rollouts is at most ζ. Conversely, below this threshold, full success is not reliably observed under the available rollout budget.

The no-full-success event $m_i = \max_j r_{i,j} < 1$ is the condition used by the ACR gate.

For a gated prompt, the answer-conditioned prompt $x^{\text{acr}} = x \oplus b(a^\star, d)$ can produce a fully verified trace, which is filtered and distilled back onto the original prompt x. This step aims to raise $p_\theta(a^\star \mid x)$ above the finite-budget detectability threshold. Appendix J states a conditional finite-sampling formalization: if accepted ACR traces occur with nonzero probability and each successful original-prompt distillation update increases the log success probability by a fixed amount, repeated updates cross the threshold in finite expected time. These assumptions posit the effect of distillation rather than derive it from joint GRPO/SFT optimization, so the result is a stylized conditional argument, not an optimization guarantee or independent evidence for the method. It also assumes $p_{\theta_0}(a^\star \mid x) > 0$ and therefore concerns finite-budget detectability rather than expansion of mathematical support.

5 Experiments

5.1 Evaluation Benchmarks

We evaluate on the 12 CTI evaluation tasks in Table 1, covering multiple-choice cybersecurity and CTI knowledge, structured taxonomy prediction, SOC-style reasoning, and information extraction. These tasks include **CKT** (Alam et al., 2025), a five-option CTI knowledge QA benchmark; **CyberMetric** (Tihanyi et al., 2024), a four-option cybersecurity knowledge QA benchmark; **SOCEval** (Deason et al., 2025), multi-select SOC-style reasoning over threat-intelligence reports; **RCM** (Alam et al., 2025), CVE-to-CWE root-cause mapping; **VSP** (Alam et al., 2025), CVSS v3.1 base-vector prediction; **ATE** (Alam et al., 2025), ATT&CK technique identification from attack scenarios; **RMS** (Alam et al., 2025), ATT&CK mitigation recommendation; **ElasticRule** (Elastic, 2026), Elastic detection-rule to ATT&CK technique mapping; **APTNER** (Wang et al., 2022), APT-focused named-entity recognition; **LANCE** (Froudakis et al., 2025), IoC identification over IP, URL, domain, and hash candidates; **AnnoCTR** (Lange et al., 2024), STIX-style entity and relation extraction; and **AZERG** (Lekssays et al., 2025), STIX-style entity and relation extraction from CTI text. Full task definitions, output formats, and sample counts are provided in Appendix E.

Contamination and overlap considerations. Because CTI benchmarks often draw on shared public standards and threat intelligence resources, fully eliminating train-test overlap is difficult. We therefore design Minerva-CTI to minimize direct leakage where possible. We exclude multiple-choice formats during training to reduce overlap with CKT and CyberMetric. SOCEval is derived from threat-intelligence reports that are not used as training targets. For CVE-based tasks, Minerva-CTI uses pre-2025 CVEs, while AthenaBench RCM and VSP evaluations emphasize 2025-era entries. For ATT&CK scenario tasks, Minerva-CTI uses ATT&CK-derived training scenarios, whereas ATE and RMS evaluation use independently curated model-generated scenarios conditioned on technique descriptions. Finally, ElasticRule, APTNER, LANCE, AnnoCTR, and AZERG are used only for evaluation and are not included as supervised training objectives.

5.2 Experimental Settings

RLVR and MinervaRL training. All RLVR models use GRPO with batch size 128, $N = 8$ on-policy rollouts per prompt, 2048-token prompt truncation, 1024-token response truncation, actor learning rate 1×10^{-6}, and 500 training steps. Checkpoints for GRPO, MinervaRL, and the controlled trained baselines

Table 1: Benchmark results across 12 CTI evaluation tasks. We compare MinervaRL with matched base models, GRPO, public security-SFT baselines, and STaR-CTI, DART-CTI, and LUFFY-CTI baselines. Underlined values indicate the best score within each backbone group.

Model	CKT	CyberMetric	SOCEval	RCM	VSP	ATE	RMS	ElasticRule	APTNER	LANCE	AnnoCTR	AZERG	Avg.
Llama-3.1-8B-Instruct	67.6	83.2	64.8	48.4	76.0	17.4	6.7	14.4	33.5	78.2	50.7	42.8	48.6
Llama-Primus-Merged	76.5	85.9	68.0	56.0	72.6	33.6	7.8	27.3	22.0	59.4	51.8	40.9	50.2
Foundation-Sec-8B-Instruct	77.1	81.3	67.9	61.0	65.8	39.2	15.4	33.6	34.0	59.5	43.5	44.4	51.9
Llama-3.1-8B-STaR-CTI	70.0	81.8	61.7	57.4	73.8	29.2	9.6	21.3	33.1	80.0	46.5	32.1	49.7
Llama-3.1-8B-DART-CTI	71.3	82.4	61.5	64.0	73.0	37.8	27.7	31.0	34.0	74.8	47.1	39.3	53.7
Llama-3.1-8B-GRPO	71.9	85.4	63.0	66.3	82.6	32.0	30.9	32.2	32.7	86.2	49.5	39.5	56.0
Llama-3.1-8B-LUFFY-CTI	73.9	83.7	63.3	63.8	79.6	40.6	34.3	33.8	35.4	82.4	49.7	43.1	57.0
Llama-3.1-8B-MinervaRL	73.9	84.2	64.7	68.8	87.6	48.4	42.1	40.5	34.1	84.6	50.3	43.7	60.2
Llama-3.2-3B-Instruct	71.6	77.0	55.7	15.2	2.8	1.0	0.4	1.2	25.4	77.8	35.9	32.8	33.1
Llama-3.2-3B-STaR-CTI	64.3	70.5	50.3	36.4	53.4	4.2	7.0	1.9	21.4	76.3	33.8	28.0	37.3
Llama-3.2-3B-DART-CTI	73.0	78.2	54.5	54.9	61.2	16.8	17.8	11.6	22.5	73.8	38.7	25.7	44.0
Llama-3.2-3B-GRPO	71.2	77.8	58.3	48.9	56.5	5.2	15.4	5.3	27.5	70.6	38.5	29.7	42.1
Llama-3.2-3B-LUFFY-CTI	70.6	78.5	55.4	43.8	71.6	19.4	24.2	20.4	15.0	68.0	46.0	32.1	45.4
Llama-3.2-3B-MinervaRL	71.0	78.1	54.6	57.2	77.1	21.8	29.3	20.1	16.7	82.2	37.9	33.7	48.3
Qwen3-8B-Base	71.7	69.3	63.8	52.6	69.0	13.4	6.5	9.0	31.3	45.1	9.8	9.8	37.6
Qwen3-8B-STaR-CTI	37.9	49.3	65.1	36.8	68.7	15.6	3.5	4.9	37.9	55.7	40.0	26.4	36.8
Qwen3-8B-DART-CTI	39.2	55.7	65.2	47.1	72.7	14.0	6.5	16.4	37.9	76.4	46.5	36.6	42.9
Qwen3-8B-GRPO	69.8	72.7	69.0	60.5	68.8	23.6	8.2	18.1	37.7	66.1	37.8	31.1	47.0
Qwen3-8B-LUFFY-CTI	78.6	88.3	64.8	65.3	73.2	29.4	25.8	32.4	34.3	74.5	45.1	26.8	53.2
Qwen3-8B-MinervaRL	77.8	88.2	67.5	64.8	79.4	32.0	20.1	22.0	37.4	74.9	43.0	33.1	53.4
Qwen3-4B-Base	45.6	50.1	56.1	45.6	76.5	4.2	6.5	4.6	1.2	18.0	16.6	6.5	27.6
Qwen3-4B-STaR-CTI	76.1	88.2	66.1	21.1	80.2	5.8	6.6	12.3	31.8	62.0	46.9	47.7	45.4
Qwen3-4B-DART-CTI	45.4	42.1	60.0	54.6	73.8	20.6	5.8	17.1	27.6	47.5	43.2	35.1	39.4
Qwen3-4B-GRPO	74.2	85.8	63.9	60.8	88.1	20.2	3.8	20.4	32.4	58.2	39.6	24.0	47.6
Qwen3-4B-LUFFY-CTI	54.1	56.5	60.9	59.9	72.6	17.6	10.3	23.4	29.2	60.4	46.7	36.2	44.0
Qwen3-4B-MinervaRL	70.0	80.0	64.0	59.9	80.0	25.4	5.1	27.5	28.0	56.7	50.4	29.1	48.0

are selected using the same validation criterion: average performance on the held-out Minerva validation split (Minerva-Dev) and AthenaBench-Mini (Alam et al., 2025). MinervaRL uses the same GRPO loop, but for hard prompts with no fully verified rollout, an EMA teacher ($\alpha = 0.995$) samples $K = 4$ ACR traces at temperature 0.7 and nucleus sampling $p = 0.9$ using a 4096-token ACR context. Every $I = 10$ steps, up to $M = 256$ accepted traces are distilled onto the original answer-free prompts with learning rate $\gamma \cdot \mathrm{lr}_{\mathrm{rlvr}}$, where $\gamma = 0.05$. Full implementation details are in Appendix K.

Checkpoint-selection overlap. AthenaBench-Mini is not instance-disjoint from the final CKT, RCM, VSP, ATE, and RMS evaluations: its 950 examples are contained in those five evaluation sets. Appendix F.1 reports a sensitivity analysis excluding them.

LLM backbones. We evaluate four open-weight backbones: **Llama-3.1-8B-Instruct** (Meta, 2024a), **Llama-3.2-3B-Instruct** (Meta, 2024b), **Qwen3-4B-Base** (Qwen Team, 2025a), and **Qwen3-8B-Base** (Qwen Team, 2025b). For each backbone, we report the unadapted base model, a GRPO-trained RLVR model, and a MinervaRL model trained with the same GRPO setup plus hardness-gated ACR generation and original-prompt distillation.

Baselines. We compare against three controlled baselines using the same Minerva-CTI training split and verifiers: **STaR-CTI**, which iteratively bootstraps verifier-correct traces and retrains with SFT (Zelikman et al., 2022); **DART-CTI**, a rejection-finetuning baseline with a fixed verifier-filtered trace corpus (Tong et al., 2024); and **LUFFY-CTI**, an off-policy RLVR baseline using one accepted guidance trace per prompt (Yan et al., 2025). We also include two external Llama-3.1-8B security-SFT reference models, **Llama-Primus-Merged** and **Foundation-Sec-8B-Instruct** (Llama-Primus Team, 2025; Foundation AI, 2025). Baseline construction details are provided in Appendix H.

Evaluation metrics. We use each benchmark's official or task-specific metric. Multiple-choice tasks use exact-match accuracy; taxonomy and mapping tasks use exact match on extracted ATT&CK or CWE labels; APTNER uses micro-F1 over JSON entities; RMS uses multi-label F1 over mitigation sets; and LANCE, AnnoCTR, and AZERG report averages over subtasks. For VSP, we follow the benchmark verifier and report

the normalized CVSS score $1 - \text{MAD}/7.7$, where MAD is the mean absolute deviation between predicted and gold CVSS v3.1 base scores.

Evaluation protocol. For the main single-sample results in Table 1, we use greedy decoding with temperature 0.0 and a maximum of 2048 new tokens. Each evaluation example is evaluated with its fixed task prompt, without model-specific prompt rewriting. The prompts specify the required output format, summarized in Table 15, such as a multiple-choice letter, CWE/ATT&CK/CVSS identifier, JSON object in `<json_object>` tags, or XML-like entity/relation tags. We score every system with the same task-specific parser, normalizer, and scoring script: the evaluator extracts the requested final answer or structured field using regex, JSON, or tag parsing as appropriate, canonicalizes identifiers where needed, and treats unparseable outputs as empty predictions. These rules are shared across all systems, including the external security-SFT baselines. The rollout-aware best-of-k analysis in Section 7.2 uses a separate sampled decoding protocol.

Uncertainty estimates. To quantify evaluation uncertainty, we compute paired bootstrap 95% confidence intervals over evaluation examples. For each task, backbone, and baseline comparison, we resample task examples with replacement, recompute the original task metric for MinervaRL and the baseline on the same resampled examples, and report the percentile interval of the paired difference, MinervaRL minus the baseline. These intervals quantify evaluation-example variation for fixed checkpoints; they do not estimate variation across independent training seeds. Dataset sizes for all evaluation tasks are listed in Table 15.

6 CTI Benchmark Results

6.1 Task-Level Results and Paired Comparisons

Aggregate task scores. Table 1 reports absolute scores across the 12 CTI evaluation tasks and four open-weight backbone families. Standard GRPO improves the average score over each matched base model, raising Llama-3.1-8B from 48.6 to 56.0, Llama-3.2-3B from 33.1 to 42.1, Qwen3-8B from 37.6 to 47.0, and Qwen3-4B from 27.6 to 47.6. These gains are largest on structured verifier-aligned tasks such as CWE mapping, CVSS prediction, ATT&CK technique identification, mitigation recommendation, and rule-to-technique mapping. MinervaRL further raises the average to 60.2, 48.3, 53.4, and 48.0 for the four backbones, respectively, obtaining the highest average score within each backbone group.

Comparison with controlled baselines. Compared with STaR-CTI and DART-CTI, MinervaRL has a higher average score for all four backbone groups. LUFFY-CTI is the closest controlled baseline: MinervaRL is higher by +3.2 points on Llama-3.1-8B, +2.9 on Llama-3.2-3B, +0.2 on Qwen3-8B, and +4.0 on Qwen3-4B. On Llama-3.1-8B, MinervaRL also exceeds the two external security-SFT reference models, reaching 60.2 average compared with 50.2 for Llama-Primus-Merged and 51.9 for Foundation-Sec-8B-Instruct.

Per-task paired uncertainty versus GRPO. To complement the aggregate scores, Table 2 reports per-task paired bootstrap 95% confidence intervals over evaluation examples for MinervaRL minus GRPO. Across the 48 backbone-task comparisons, MinervaRL has positive point deltas on 34/48 comparisons; the paired interval is entirely above zero on 28/48, entirely below zero on 7/48, and overlaps zero on 13/48. The strongest CI-separated gains are concentrated on structured verifier-aligned tasks including RCM, VSP, ATE, RMS, and ElasticRule. The Qwen3-4B comparison is the least separated: its average gain over GRPO is small, and several task-level intervals are negative or overlap zero.

Pairwise summary across baselines. Table 3 summarizes paired interval signs for MinervaRL against each baseline across all 48 backbone-task comparisons. MinervaRL is higher than the base models on 42/48 point comparisons, with 35/48 CI-positive intervals. It also has broad CI-positive majorities against STaR-CTI and DART-CTI, with 35/48 and 34/48 CI-positive intervals, respectively. Against LUFFY-CTI, the closest controlled baseline, MinervaRL has positive point deltas on 32/48 comparisons; the paired 95% interval is entirely above zero on 20/48, entirely below zero on 6/48, and overlaps zero on 22/48.

Table 2: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus GRPO, in percentage points. Positive intervals indicate tasks where MinervaRL is higher than GRPO under the paired bootstrap interval.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+2.0 [0.6, 3.5]	-0.2 [-1.6, 1.1]	+8.0 [6.5, 9.5]	-4.2 [-5.8, -2.6]
CyberMetric	-1.1 [-2.5, 0.3]	+0.3 [-1.1, 1.5]	+15.5 [13.5, 17.5]	-5.7 [-7.4, -4.0]
SOCEval	+1.7 [-0.4, 3.8]	-3.7 [-5.8, -1.4]	-1.4 [-2.7, -0.1]	+0.2 [-1.6, 2.1]
RCM	+2.4 [1.1, 3.8]	+8.3 [6.8, 9.8]	+4.3 [2.9, 5.8]	-0.9 [-2.1, 0.2]
VSP	+5.0 [4.3, 5.7]	+20.6 [18.9, 22.4]	+10.6 [9.7, 11.7]	-8.1 [-9.0, -7.3]
ATE	+16.4 [12.6, 20.4]	+16.6 [13.2, 20.2]	+8.4 [5.8, 11.4]	+5.2 [2.8, 7.6]
RMS	+11.2 [7.8, 14.4]	+13.9 [11.1, 16.9]	+12.0 [9.1, 14.8]	+1.3 [-0.7, 3.2]
ElasticRule	+8.3 [3.9, 12.7]	+14.8 [11.6, 18.3]	+3.9 [-0.2, 7.9]	+7.2 [3.7, 10.9]
APTNER	+1.4 [0.5, 2.4]	-10.8 [-12.3, -9.3]	-0.3 [-1.5, 1.0]	-4.4 [-5.9, -2.9]
LANCE	-1.5 [-5.7, 2.2]	+11.7 [2.7, 19.3]	+8.8 [0.8, 19.9]	-1.5 [-10.5, 9.3]
AnnoCTR	+0.7 [-1.6, 2.9]	-0.7 [-2.4, 1.1]	+5.2 [3.2, 8.1]	+10.7 [4.4, 12.9]
AZERG	+4.1 [2.3, 7.7]	+4.0 [1.5, 7.0]	+2.0 [0.1, 5.6]	+5.1 [0.3, 7.8]

Table 3: Pairwise task-count summary for MinervaRL versus each baseline across 48 backbone-task comparisons. CI Pos. and CI Neg. are counts of comparisons whose paired 95% confidence interval is entirely above or below zero.

Baseline	Point wins	Point losses	CI Pos.	CI Neg.	CI Overlap
Base	42/48	6/48	35/48	2/48	11/48
STaR	38/48	10/48	35/48	6/48	7/48
DART	38/48	10/48	34/48	3/48	11/48
GRPO	34/48	14/48	28/48	7/48	13/48
LUFFY	32/48	16/48	20/48	6/48	22/48

6.2 Task-Family Summary

To summarize the heterogeneous CTI evaluation tasks by output and scoring type, Table 4 groups the pairwise comparisons from Table 3 into four task families: QA/selection (CKT, CyberMetric, SOCEval), taxonomy mapping (RCM, ATE, RMS, ElasticRule), vulnerability scoring (VSP), and information extraction (APTNER, LANCE, AnnoCTR, AZERG). The denominators count task-by-backbone comparisons. By point wins, MinervaRL has a majority in every family-baseline block except QA/selection versus GRPO, where the comparison is tied at 6 wins and 6 losses. The same exception appears under CI-sign counts: CI-positive counts exceed CI-negative counts in every family-baseline block except QA/selection versus GRPO, where the signs are 3 positive, 4 negative, and 5 overlapping. The strongest interval-separated gains remain on taxonomy mapping and vulnerability scoring, while QA/selection and extraction tasks are more mixed.

6.3 Component Ablations

We report component ablations for Llama-3.1-8B only. We evaluate the resulting checkpoints on the two checkpoint-selection sets, Minerva-Dev and AthenaBench-Mini, and on the 12 CTI evaluation tasks from Table 1. Table 5 reports validation scores, 12-task averages, and paired bootstrap sign counts for Full MinervaRL minus each control across the 12 task metrics. Table 27 reports the corresponding per-task scores.

The full method has the highest 12-task average among the component controls. In Table 5, GRPO is the no-ACR control, GRPO 12 rollouts controls for additional rollout sampling, and in-loop answer SFT matches the auxiliary distillation schedule while replacing ACR traces with direct final-answer targets. GRPO is 4.2 points lower, indicating that the gain is not explained by verifier RL alone. GRPO with 12 rollouts does not close the gap despite additional rollout compute. Full MinervaRL also has a higher average than in-loop answer SFT (60.2 vs. 57.8). For Full MinervaRL minus this control, 6 paired task-level intervals are positive, 4 are negative, and 2 overlap zero. Thus, direct answer-only distillation does not recover the full method on average, but the advantage of ACR distillation is not uniform across tasks. Removing the EMA teacher or filtering components yields smaller drops in the 12-task average.

Table 4: Task-family count summary for MinervaRL versus each baseline. Counts are over backbone-task comparisons within each family. Point W/L reports MinervaRL point wins/losses; CI +/-/0 reports CI-positive, CI-negative, and CI-overlap counts.

	QA / selection (n=12)		Taxonomy mapping (n=16)		Vulnerability scoring (n=4)		Information extraction (n=16)	
Baseline	Point W/L	CI +/-/0	Point W/L	CI +/-/0	Point W/L	CI +/-/0	Point W/L	CI +/-/0
Base	9/3	7/0/5	15/1	15/1/0	4/0	4/0/0	14/2	9/1/6
STaR	9/3	9/2/1	15/1	15/1/0	3/1	3/0/1	11/5	8/3/5
DART	10/2	9/1/2	15/1	15/0/1	4/0	4/0/0	9/7	6/2/8
GRPO	6/6	3/4/5	15/1	13/0/3	3/1	3/1/0	10/6	9/2/5
LUFFY	8/4	4/0/8	10/6	8/3/5	4/0	4/0/0	10/6	4/3/9

Table 5: Llama-3.1-8B component ablations on validation splits and the 12 CTI evaluation tasks. Validation columns report Minerva-Dev and AthenaBench-Mini scores. Evaluation columns report the 12-task macro average and paired bootstrap interval sign counts across the 12 tasks. Underlined values indicate the best score in each validation or 12-task average column.

Ablation	Validation			12 CTI evaluation tasks			
	Minerva-Dev	AthenaBench-Mini	Avg.	Avg.	CI Pos.	CI Neg.	CI Overlap
GRPO	50.3	57.4	53.8	56.0	8	0	4
GRPO 12 rollouts	50.9	52.7	51.8	53.9	7	1	4
Answer-only SFT	58.6	38.7	48.7	52.6	7	3	2
In-loop answer SFT	58.3	57.8	58.0	57.8	6	4	2
No EMA teacher	63.1	62.2	62.6	57.2	8	0	4
No TextCNN filter	<u>64.2</u>	59.0	61.6	57.7	7	1	4
No filtering	63.0	61.4	62.2	57.8	7	0	5
Full MinervaRL	63.2	<u>63.3</u>	<u>63.3</u>	<u>60.2</u>	–	–	–




Figure 3: GPT-5.2 pairwise response-quality preferences for backbone-specific model groups. Each cell reports the probability that the row model is preferred over the column model, with ties retained in the denominator.

6.4 Response-Quality Preference Evaluation

Verifier-based scores measure structured CTI correctness, but analyst-facing usefulness also depends on readability, evidence use, and CTI concept precision. We therefore run a blind GPT-5.2 response-quality evaluation within each backbone family, comparing the base model, GRPO, MinervaRL, STaR-CTI, and DART-CTI. Responses are scored with a three-criterion rubric covering writing quality, prompt-evidence use, and CTI concept use; pairwise preferences are derived from total scores, with ties retained. Full prompts, rubrics, and validation details are in Appendix I.

Preference results. Figure 3 shows that MinervaRL is preferred over GRPO for all four backbones and is top-ranked for Llama-3.2-3B, Qwen3-4B, and Qwen3-8B. On Llama-3.1-8B, STaR-CTI and DART-CTI receive higher preference rates, suggesting that fixed-trace SFT and rejection-finetuning baselines can produce stronger prose for a strong instruction-tuned backbone. MinervaRL nevertheless remains preferred

over the base and GRPO variants and achieves the highest average task score in Table 1, indicating that its verifier-score gains generally coincide with improved judged response quality relative to standard GRPO.

Judge validation. We validate GPT-5.2 on a 100-example subset over the five Llama-3.1-8B-family variants, using two human annotators and Claude Sonnet 4.6. GPT-5.2 agrees substantially with the human annotator average (QWK 0.6313, Spearman 0.7722), close to human–human agreement (QWK 0.6514, Spearman 0.6461), and also agrees strongly with Claude Sonnet 4.6 (QWK 0.7634, Spearman 0.8266). Full validation results are in Appendix I.

6.5 Training-Aligned vs. Not-in-Training Tasks

We split the 12 CTI evaluation tasks into tasks that directly match Minerva-CTI training objectives and tasks that are not directly optimized during training. The training-aligned group contains RCM, VSP, ATE, and RMS, corresponding to CVE-to-CWE mapping, CVSS vector prediction, ATT&CK technique prediction, and mitigation recommendation. The not-in-training group contains CKT, CyberMetric, SOCEval, ElasticRule, APTNER, LANCE, AnnoCTR, and AZERG. Table 6 reports the mean score for each group.

MinervaRL delivers the largest gains on training-aligned tasks, improving over the base model by +24.6, +41.5, +13.7, and +9.4 points on Llama-3.1-8B, Llama-3.2-3B, Qwen3-8B, and Qwen3-4B, respectively. It also improves over GRPO on three of the four backbones in this group. On not-in-training tasks, MinervaRL improves over GRPO for every backbone in the group average, with gains of +2.0, +1.9, +5.2, and +0.9 points. The task-count summary in Table 7 shows the same pattern at the task level: gains over the base model remain broad even outside the training objectives, while gains over GRPO are positive on a majority of not-in-training comparisons but more mixed than on training-aligned tasks. Overall, the gains are largest on verifier-aligned structured tasks; outside the training objectives, improvements are broader relative to base models and more mixed relative to GRPO.

7 Training Dynamics and Additional Evaluations

7.1 Reward Sparsity and Validation Dynamics

A central challenge in CTI RLVR is reward sparsity: for some prompts, none of the sampled rollouts receives any verifier reward, leaving GRPO with no within-prompt reward contrast for that example. We track this failure mode using the zero-solve fraction, defined as the fraction of prompts whose rollout group has maximum verifier reward equal to 0. Unlike the ACR gate, which uses $m_i < 1$, this diagnostic excludes partial-credit groups with $0 < m_i < 1$. As shown in Figure 4, MinervaRL reduces the zero-solve fraction relative to GRPO across all four backbone families. For Llama-3.1-8B, increasing the GRPO rollout budget from $N = 8$ to $N = 12$ also reduces zero-solve frequency, but does not close the gap to MinervaRL. This suggests that MinervaRL's gains are not merely due to additional sampling; answer-conditioned trace generation and original-prompt distillation help the policy reach verifier-detectable outputs under the same sparse-reward setting.

Figure 5 shows that the reduction in zero-solve prompts is accompanied by improved validation performance. Across all four backbones, MinervaRL reaches the best GRPO validation accuracy during training and then continues improving beyond it. Taken together, these trends are consistent with MinervaRL supplying verified original-prompt supervision for zero-solve prompts, but they do not isolate the gate's causal contribution.

7.2 Rollout-Aware Best-of-k Evaluation

We further evaluate GRPO and MinervaRL on the 12 CTI evaluation tasks under matched rollout budgets: for each example, we sample eight responses from each model using temperature 0.7, top-p 0.95, and a 2048-token generation limit, then compute best-of-k scores for $k \in \{1, 2, 4, 8\}$. For exact-match, MCQ, and taxonomy tasks, best-of-k is the fraction of examples with at least one verified correct response. For graded, extraction, and multi-label tasks, we select the highest-scoring rollout for each example and then compute

Table 6: Average performance on training-aligned and not-in-training evaluation tasks.

	Llama-3.1-8B		Llama-3.2-3B		Qwen3-8B		Qwen3-4B	
Model	Aligned	Not-in-train	Aligned	Not-in-train	Aligned	Not-in-train	Aligned	Not-in-train
Base	37.1	54.4	4.9	47.2	35.4	38.7	33.2	24.8
GRPO	53.0	57.5	31.5	47.4	40.3	50.3	43.2	49.8
MinervaRL	61.7	59.5	46.4	49.3	49.1	55.5	42.6	50.7

Table 7: Task-count summary for training-aligned and not-in-training tasks among the 12 CTI evaluation tasks. Counts are over backbone-task comparisons. Aligned tasks are RCM, VSP, ATE, and RMS; not-in-training tasks are the remaining eight tasks. CI Pos./Neg./Overlap indicate whether the paired bootstrap 95% confidence interval for MinervaRL minus the comparison model is entirely above zero, below zero, or overlaps zero.

	Training-aligned					Not-in-training				
Comparison	Point wins	Point losses	CI Pos.	CI Neg.	CI Overlap	Point wins	Point losses	CI Pos.	CI Neg.	CI Overlap
MinervaRL vs Base	15/16	1/16	15/16	1/16	0/16	27/32	5/32	21/32	1/32	10/32
MinervaRL vs GRPO	14/16	2/16	13/16	1/16	2/16	20/32	12/32	15/32	6/32	11/32




Figure 4: Fraction of prompts whose rollout group has maximum verifier reward = 0. Each panel compares GRPO and MinervaRL; Llama-3.1-8B also includes GRPO-12 ($N = 12$). Curves use a 5-step rolling mean.

the task metric on those selected outputs. Table 8 summarizes paired comparisons across all backbone-task settings, Table 26 reports the full task scores, and Tables 22 to 25 report the per-task paired intervals.

MinervaRL improves over GRPO on 32/48, 36/48, 38/48, and 39/48 backbone-task comparisons for $k = 1, 2, 4, 8$, respectively. At $k = 8$, the paired bootstrap interval is entirely above zero for 31/48 comparisons, entirely below zero for 6/48, and overlaps zero for 11/48. As the rollout budget increases, MinervaRL's relative advantage over GRPO becomes slightly broader: point wins rise from 32/48 at $k = 1$ to 39/48 at $k = 8$, and CI-positive comparisons are highest at $k = 4$ and $k = 8$.

7.3 General Capability and Structured-Output Transfer

We include two auxiliary evaluations: general/cyber benchmarks for Llama-3.1-8B variants and a preliminary text-to-SQL transfer experiment. Table 9(a) shows that MinervaRL largely preserves MMLU-Pro (Wang et al., 2024) and IFEval (Zhou et al., 2023) performance, improves CanaryExploit (Bhatt et al., 2024) over the base and GRPO variants, and does not increase WMDP-Cyber (Li et al., 2024) relative to GRPO, where lower scores indicate lower measured cyber-risk.

Table 9(b) evaluates transfer to text-to-SQL, another structured-output setting with executable or verifier-style rewards. Starting from Qwen2.5-Coder-3B, we train GRPO and MinervaRL using the SQL-R1 (Ma et al., 2025) training/validation setup and compare against the base model and SQL-R1-3B. MinervaRL obtains the best average score (60.8) and leads on four of seven datasets, providing preliminary evidence that the MinervaRL training recipe can transfer to another structured-output setting with verifier-style rewards.




Figure 5: Validation accuracy over training. Curves are 5-step rolling means; dashed lines mark the best GRPO accuracy, and crosses mark the first MinervaRL step that reaches it.

Table 8: Rollout-aware task-count summary for MinervaRL versus GRPO across 48 backbone-task comparisons at each best-of-k budget. CI Pos. and CI Neg. are counts of comparisons whose paired 95% confidence interval is entirely above or below zero.

k	Point wins	Point losses	CI Pos.	CI Neg.	CI Overlap
1	32/48	16/48	27/48	10/48	11/48
2	36/48	12/48	26/48	6/48	16/48
4	38/48	10/48	31/48	4/48	13/48
8	39/48	9/48	31/48	6/48	11/48

Table 9: Additional evaluations: Llama-3.1-8B general/cyber benchmarks and Qwen2.5-Coder-3B text-to-SQL transfer. Higher is better except WMDP-Cyber. Underlined values indicate the best score in each column.

(a) Other benchmarks

Model	MMLU Pro ↑	IFEval ↑	Canary Exploit ↑	WMDP Cyber ↓
Llama-3.1-8B	44.1	72.3	10.9	46.7
Llama-Primus	41.5	68.2	<u>29.8</u>	46.3
Foundation-Sec	42.5	67.1	0.0	<u>45.3</u>
Llama-3.1-8B-GRPO	<u>45.6</u>	72.3	0.0	47.1
Llama-3.1-8B-MinervaRL	43.6	<u>73.8</u>	28.4	47.1

(b) Text-to-SQL transfer

Model	Spider Dev	Spider Test	BIRD Dev	BIRD DK	BIRD Syn	BIRD Real.	BIRD Live	BIRD Avg
Qwen2.5-Coder	77.4	77.6	50.3	65.6	67.2	<u>69.7</u>	3.7	58.8
SQL-R1-3B	77.1	77.4	53.3	<u>70.5</u>	67.5	66.5	6.3	59.8
GRPO	77.5	78.5	<u>54.2</u>	69.0	67.9	68.7	6.3	60.3
MinervaRL	<u>78.2</u>	<u>79.3</u>	52.5	69.2	<u>70.7</u>	69.3	<u>6.7</u>	<u>60.8</u>

7.4 Hyperparameter Sensitivity

Table 10 shows sensitivity to the distillation learning-rate scale γ used in the supervised update, with learning rate $\gamma \cdot \mathrm{lr}_{\mathrm{rlvr}}$. Performance is best around $\gamma = 0.05$: smaller values under-use accepted traces, while a larger value degrades both validation splits. We therefore use $\gamma = 0.05$ in the main experiments.

8 Limitations and Future Work

Our study has several limitations. **Uncertainty and training variation.** Our paired bootstrap confidence intervals capture variation over evaluation examples for fixed checkpoints, not variation across independent training seeds. Multi-seed RLVR experiments would provide a stronger estimate of training stability but were not computationally feasible across four post-trained backbones. **Compute and ablations.** Because RLVR training is expensive, the component controls in Table 5 are limited to Llama-3.1-8B, and we sweep only the distillation learning-rate scale γ. Broader backbone-level ablations and hyperparameter sweeps, including the distillation interval I, per-interval cap M, and EMA decay α, remain future work. The current experiments evaluate the complete hard-prompt allocation policy but do not isolate the gate from always-on, random-prompt, or strict-zero-only ACR allocation. These alternatives change the eligible prompt pool: holding the $M = 256$ distillation cap fixed changes buffer composition or fill rate, whereas matching accepted-trace exposure may require different ACR-generation compute or update timing. **Data coverage.** Minerva-CTI and our evaluation suite are primarily English-centric; multilingual CTI, regional reporting styles, and non-English security artifacts remain important extensions. **Trace filtering.** Miner-

Table 10: Distillation scale γ sensitivity.

γ	Minerva-Dev	Athena-Mini	Avg.
0.01	60.3	61.3	60.8
0.02	63.1	63.3	63.2
0.05	<u>63.2</u>	<u>63.3</u>	<u>63.3</u>
0.10	60.1	58.1	59.1

vaRL uses lightweight heuristics and a TextCNN filter for ACR trace selection. Stronger LLM-based filters may improve trace quality but would increase cost, motivating more scalable quality estimators. **Training overhead.** MinervaRL adds overhead from ACR generation, log-probability computation, and periodic distillation. Appendix K.4 reports a 39.3% increase in a 10-step Llama-3.1-8B timing study, although Figure 5 shows faster progress toward strong validation performance. Reducing this overhead while preserving finite-budget performance is an important direction.

9 Conclusion

We presented **Minerva**, a verifiable-reward training framework for cyber threat intelligence LLMs. Minerva-CTI provides verifier-checkable tasks across vulnerability, detection, and procedure-oriented workflows, while MinervaRL extends GRPO with hardness-gated answer-conditioned rationale generation and original-prompt distillation. Across 12 CTI benchmarks and four open-weight backbones, MinervaRL improves the average score over matched base models, standard GRPO, controlled SFT/rejection-finetuning baselines, and an off-policy RL baseline. Task-level paired analysis shows the clearest gains on verifier-aligned structured tasks, while improvements also extend to SOC reasoning and extraction evaluations. These results show that CTI's structured taxonomies and canonical identifiers are well suited to verifier-driven post-training, and that periodically distilling filtered answer-conditioned traces can improve finite-budget detectability under sparse rewards.

Data and Code Availability

We will release the Minerva codebase, data-construction pipeline, evaluation tools, and derived Minerva-CTI splits for research use. Minerva-CTI is built from public CTI sources with reuse-compatible terms, including MITRE ATT&CK/CWE/CAPEC, CVE/NVD, Mappings Explorer, Sigma, Atomic Red Team, Microsoft Sentinel, and Splunk Security Content. Released artifacts will preserve required upstream notices, licenses, and attribution.

Broader Impact Statement

This work is intended to improve open-weight LLMs for defensive CTI analysis. Minerva-CTI is curated from public CTI and detection-engineering resources and targets analyst workflows such as indicator/entity extraction, vulnerability triage, ATT&CK/CWE/CVSS mapping, mitigation recommendation, and detection-rule interpretation. We do not train models for exploit generation, malware development, phishing, intrusion execution, or operational attack planning. Some evaluations, including exploit-related diagnostics, may nevertheless improve because stronger models better understand vulnerability semantics and attack-technique mappings; we treat such results as dual-use signals rather than deployment objectives. Potential misuse includes helping adversaries organize vulnerability knowledge, map attack techniques, prioritize targets, or automate threat analysis. We will therefore accompany released artifacts with defensive-use documentation, model/data cards, and cyber-safety review, and use staged release for model checkpoints or artifacts if review indicates elevated misuse risk. Finally, incorrect CWE labels, ATT&CK techniques, CVSS vectors, or mitigation recommendations can mislead downstream security decisions, so Minerva outputs should be treated as analyst-assistive signals rather than authoritative judgments.

References

Md Tanvirul Alam, Dipkamal Bhusal, Le Nguyen, and Nidhi Rastogi. CTIBench: A benchmark for evaluating LLMs in cyber threat intelligence. In *Advances in Neural Information Processing Systems (NeurIPS 2024), Datasets and Benchmarks Track*, 2024.

Md Tanvirul Alam, Dipkamal Bhusal, Salman Ahmad, Nidhi Rastogi, and Peter Worth. AthenaBench: A dynamic benchmark for evaluating LLMs in cyber threat intelligence. *Workshop on AI for Cyber Threat Intelligence (WAITI) 2025*, 2025. URL https://arxiv.org/abs/2511.01144.

Manish Bhatt, Sahana Chennabasappa, Yue Li, Cyrus Nikolaidis, Daniel Song, Shengye Wan, Faizan Ahmad, Cornelius Aschermann, Yaohui Chen, Dhaval Kapil, et al. CyberSecEval 2: A wide-ranging cybersecurity evaluation suite for large language models. *arXiv preprint arXiv:2404.13161*, 2024.

Dipkamal Bhusal, Md Tanvirul Alam, Le Nguyen, Ashim Mahara, Zachary Lightcap, Rodney Frazier, Romy Fieblinger, Grace Long Torales, Benjamin A. Blakely, and Nidhi Rastogi. SECURE: benchmarking large language models for cybersecurity. In *Annual Computer Security Applications Conference, ACSAC 2024, Honolulu, HI, USA, December 9-13, 2024*, pp. 15–30. IEEE, 2024. doi: 10.1109/ACSAC63791.2024.00019. URL https://doi.org/10.1109/ACSAC63791.2024.00019.

Marvin Büchel, Tommaso Paladini, Stefano Longari, Michele Carminati, Stefano Zanero, Hodaya Binyamini, Gal Engelberg, Dan Klein, Giancarlo Guizzardi, Marco Caselli, Andrea Continella, Maarten van Steen, Andreas Peter, and Thijs van Ede. SoK: Automated TTP extraction from CTI reports – are we there yet? In *Proceedings of the 34th USENIX Security Symposium (USENIX Security 2025)*, 2025. URL https://www.usenix.org/system/files/usenixsecurity25-buechel.pdf.

Robert Byers, Chris Turner, and Tanya Brewer. National Vulnerability Database. https://doi.org/10.18434/M3436, 2022. National Institute of Standards and Technology (NIST). Accessed: 2026-01-19.

Center for Threat-Informed Defense. Threat report ATT&CK mapper (TRAM). Project page, 2023. URL https://ctid.mitre.org/projects/threat-report-attck-mapper-tram/.

Center for Threat-Informed Defense. Mappings Explorer. https://github.com/center-for-threat-informed-defense/mappings-explorer, 2026. Accessed: 2026-01-19.

Daixuan Cheng, Shaohan Huang, Xuekai Zhu, Bo Dai, Wayne Xin Zhao, Zhenliang Zhang, and Furu Wei. Reasoning with exploration: An entropy perspective. *arXiv preprint arXiv:2506.14758*, 2025.

Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V. Le, Sergey Levine, and Yi Ma. SFT memorizes, RL generalizes: A comparative study of foundation model post-training. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, Proceedings of Machine Learning Research. PMLR / OpenReview.net, 2025. URL https://proceedings.mlr.press/v267/chu25c.html.

Lauren Deason, Adam Bali, Ciprian Bejean, Diana Bolocan, James Crnkovich, Ioana Croitoru, Krishna Durai, Chase Midler, Calin Miron, David Molnar, Brad Moon, Bruno Ostarcevic, Alberto Peltea, Matt Rosenberg, Catalin Sandu, Arthur Saputkin, Sagar Shah, Daniel Stan, Ernest Szocs, Shengye Wan, Spencer Whitman, Sven Krasser, and Joshua Saxe. CyberSOCEval: Benchmarking LLMs capabilities for malware analysis and threat intelligence reasoning. *arXiv preprint arXiv:2509.20166*, 2025.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025. doi: 10.48550/arXiv.2501.12948.

Elastic. Detection Rules. https://github.com/elastic/detection-rules, 2026. Accessed: 2026-01-19.

Romy Fieblinger, Md Tanvirul Alam, and Nidhi Rastogi. Actionable cyber threat intelligence using knowledge graphs and large language models. In *IEEE European Symposium on Security and Privacy Workshops, EuroS&PW 2024, Vienna, Austria, July 8-12, 2024*, pp. 100–111. IEEE, 2024. doi: 10.1109/EUROSPW61312.2024.00018. URL https://doi.org/10.1109/EuroSPW61312.2024.00018.

FIRST.org, Inc. Common Vulnerability Scoring System (CVSS) v3.1 Specification Document. https://www.first.org/cvss/v3-1/specification-document, 2019. Accessed: 2026-01-19.

Foundation AI. Foundation-Sec-8B-Instruct. Model card, 2025. URL https://huggingface.co/foundation-models/Foundation-Sec-8B-Instruct.

Evangelos Froudakis, Athanasios Avgetidis, Sean Tyler Frankum, Roberto Perdisci, Manos Antonakakis, and Angelos D Keromytis. Revealing the true indicators: Understanding and improving IoC extraction from threat reports. In *RAID*, 2025.

Yuelin Hu, Futai Zou, Jiajia Han, Xin Sun, and Yilei Wang. LLM-TIKG: Threat intelligence knowledge graph construction utilizing large language model. *Computers & Security*, 145:103999, 2024. doi: 10.1016/j.cose.2024.103999. URL https://www.sciencedirect.com/science/article/abs/pii/S0167404824003043.

Hangyuan Ji, Jian Yang, Linzheng Chai, Chaoren Wei, Liqun Yang, Yunlong Duan, Yunli Wang, Tianzhen Sun, Hongcheng Guo, Tongliang Li, Changyu Ren, and Zhoujun Li. SEvenLLM: Benchmarking, eliciting, and enhancing abilities of large language models in cyber threat intelligence. *arXiv preprint arXiv:2405.03446*, 2024. URL https://arxiv.org/abs/2405.03446.

Alexander Lange, Elie Herms, Rafael Hromada, Daniel D. Lai, Max Möller, Nikola Pester, Tim Schneider, Marius Witte, and Matthias Weidlich. Annoctr: A corpus of cyber threat reports annotated with MITRE ATT&CK techniques. In *Proceedings of LREC-COLING 2024*, 2024. URL https://arxiv.org/abs/2404.07765.

Ahmed Lekssays, Husrev Taha Sencar, and Ting Yu. From text to actionable intelligence: Automating STIX entity and relationship extraction. *arXiv preprint arXiv:2507.16576*, 2025.

Matan Levi, Yair Allouche, Daniel Ohayon, and Anton Puzanov. Cyberpal.ai: Empowering llms with expert-driven cybersecurity instructions. *arXiv preprint arXiv:2408.09304*, 2024. doi: 10.48550/arXiv.2408.09304. URL https://arxiv.org/abs/2408.09304.

Matan Levi, Daniel Ohayon, Ariel Blobstein, Ravid Sagi, Ian Molloy, and Yair Allouche. Toward cybersecurity-expert small language models. *arXiv preprint arXiv:2510.14113*, 2025. doi: 10.48550/arXiv.2510.14113. URL https://arxiv.org/abs/2510.14113.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, et al. The WMDP benchmark: Measuring and reducing malicious use with unlearning. *arXiv preprint arXiv:2403.03218*, 2024.

Xin Liu, Yuan Tan, Zhenghang Xiao, Jianwei Zhuge, and Rui Zhou. Not the end of story: An evaluation of chatgpt-driven vulnerability description mappings. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 3724–3731, 2023. URL https://aclanthology.org/2023.findings-acl.229/.

Zefang Liu, Jialei Shi, and John F Buford. CyberBench: A multi-task benchmark for evaluating large language models in cybersecurity. In *AAAI 2024 Workshop on Artificial Intelligence for Cyber Security*, 2024.

Llama-Primus Team. Llama-Primus-Merged. Model card, 2025. URL https://huggingface.co/Llama-Primus/Llama-Primus-Merged.

Brian Lu, Hongyu Zhao, Shuo Sun, Hao Peng, Rui Ding, and Hongyuan Mei. Generalization of rlvr using causal reasoning as a testbed. *arXiv preprint arXiv:2512.20760*, 2025.

Peixian Ma, Xialie Zhuang, Chengjin Xu, Xuhui Jiang, Ran Chen, and Jian Guo. SQL-R1: Training natural language to SQL reasoning model by reinforcement learning. In *Advances in Neural Information Processing Systems*, 2025. URL https://arxiv.org/abs/2504.08600.

Meta. Llama 3.1 8B Instruct. Model card, 2024a. URL https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct.

Meta. Llama 3.2 3B Instruct. Model card, 2024b. URL https://huggingface.co/meta-llama/Llama-3.2-3B-Instruct.

Microsoft. Microsoft Sentinel Content (GitHub Repository). https://github.com/Azure/Azure-Sentinel, 2026. Accessed: 2026-01-19.

MITRE Corporation. ATT&CK STIX Data. https://github.com/mitre-attack/attack-stix-data, 2026a. Accessed: 2026-01-19.

MITRE Corporation. CAPEC: Common Attack Pattern Enumeration and Classification. https://capec.mitre.org/, 2026b. Accessed: 2026-01-19.

MITRE Corporation. CWE: Common Weakness Enumeration. https://cwe.mitre.org/, 2026c. Accessed: 2026-01-19.

MITRE Corporation. MITRE ATT&CK. https://attack.mitre.org/, 2026d. Accessed: 2026-01-19.

OASIS Cyber Threat Intelligence (CTI) Technical Committee. STIX version 2.1. OASIS Standard, 2021a. URL https://www.oasis-open.org/standard/6426/. Approved 10 June 2021.

OASIS Cyber Threat Intelligence (CTI) Technical Committee. TAXII version 2.1. OASIS Standard, 2021b. URL https://www.oasis-open.org/standard/taxii-version-2-1/. Approved 10 June 2021.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

Youngja Park and Weiqiu You. A pretrained language model for cyber threat intelligence. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pp. 113–122. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.emnlp-industry.12.

Qwen Team. Qwen3 4B Base. Model card, 2025a. URL https://huggingface.co/Qwen/Qwen3-4B-Base.

Qwen Team. Qwen3 8B Base. Model card, 2025b. URL https://huggingface.co/Qwen/Qwen3-8B-Base.

Fariha Ishrat Rahman, Sagar Samtani, Saswati Singhal, and Latifur Khan. ALERT: A framework for efficient extraction of attack techniques from cyber threat intelligence reports using active learning. In *Data and Applications Security and Privacy XXXVIII (DBSec 2024)*, volume 14901 of *Lecture Notes in Computer Science*, pp. 13–32. Springer, 2024. URL https://tsapps.nist.gov/publication/get_pdf.cfm?pub_id=958028.

Red Canary. Atomic Red Team. https://github.com/redcanaryco/atomic-red-team, 2026. Accessed: 2026-01-19.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017. doi: 10.48550/arXiv.1707.06347.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. doi: 10.48550/arXiv.2402.03300.

SigmaHQ. Sigma Main Rule Repository. https://github.com/SigmaHQ/sigma, 2026. Accessed: 2026-01-19.

Splunk. Splunk Security Content. https://github.com/splunk/security_content, 2026. Accessed: 2026-01-19.

Blake E. Strom, Andy Applebaum, Doug P. Miller, Kathryn C. Nickels, Adam G. Pennington, and Cody B. Thomas. MITRE ATT&CK: Design and philosophy. Technical report, The MITRE Corporation, 2020. URL https://www.mitre.org/sites/default/files/2021-11/prs-19-01075-28-mitre-attack-design-and-philosophy.pdf. Originally published July 2018; revised March 2020.

Yi Su, Dian Yu, Linfeng Song, Juntao Li, Haitao Mi, Zhaopeng Tu, Min Zhang, and Dong Yu. Crossing the reward bridge: Expanding rl with verifiable rewards across diverse domains. *arXiv preprint arXiv:2503.23829*, 2025.

Norbert Tihanyi, Mohamed Amine Ferrag, Ridhi Jain, Tamas Bisztray, and Merouane Debbah. CyberMetric: A benchmark dataset based on retrieval-augmented generation for evaluating LLMs in cybersecurity knowledge. In *2024 IEEE International Conference on Cyber Security and Resilience (CSR)*, pp. 296–302, 2024. doi: 10.1109/CSR61664.2024.10679494.

Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. DART-Math: Difficulty-aware rejection tuning for mathematical problem-solving. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 7821–7846. Curran Associates, Inc., 2024. doi: 10.52202/079017-0251. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/0ef1afa0daa888d695dcd5e9513bafa3-Paper-Conference.pdf.

Xuren Wang, Songheng He, Zihan Xiong, Xinxin Wei, Zhengwei Jiang, Sihan Chen, and Jun Jiang. APTNER: A specific dataset for NER missions in cyber threat intelligence field. In *2022 IEEE 25th international conference on computer supported cooperative work in design (CSCWD)*, pp. 1233–1238. IEEE, 2022.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, et al. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *Advances in Neural Information Processing Systems*, 37:95266–95290, 2024.

Xumeng Wen, Zihan Liu, Shun Zheng, Shengyu Ye, Zhirong Wu, Yang Wang, Zhijian Xu, Xiao Liang, Junjie Li, Ziming Miao, et al. Reinforcement learning with verifiable rewards implicitly incentivizes correct reasoning in base llms. *arXiv preprint arXiv:2506.14245*, 2025.

Fang Wu, Weihao Xuan, Ximing Lu, Mingjie Liu, Yi Dong, Zaid Harchaoui, and Yejin Choi. The invisible leash: Why rlvr may or may not escape its origin. *arXiv preprint arXiv:2507.14843*, 2025.

Prasanna N. Wudali, Moshe Kravchik, Ehud Malul, Parth A. Gandhi, Yuval Elovici, and Asaf Shabtai. RuleATT&CK mapper (RAM): Mapping SIEM rules to TTPs using LLMs. *arXiv preprint arXiv:2502.02337*, 2025. URL https://arxiv.org/abs/2502.02337.

Hanxiang Xu, Shenao Wang, Ningke Li, Kailong Wang, Yanjie Zhao, Kai Chen, Ting Yu, Yang Liu, and Haoyu Wang. Large language models for cyber security: A systematic literature review. *arXiv preprint arXiv:2405.04760*, 2024. Accepted by ACM Transactions on Software Engineering and Methodology (TOSEM).

Jianhao Yan, Yafu Li, Zican Hu, Zhi Wang, Ganqu Cui, Xiaoye Qu, Yu Cheng, and Yue Zhang. Learning to reason under off-policy guidance. *arXiv preprint arXiv:2504.14945*, 2025. doi: 10.48550/arXiv.2504.14945. URL https://arxiv.org/abs/2504.14945.

Zhicheng Yang, Zhijiang Guo, Yinya Huang, Yongxin Wang, Dongchun Xie, Yiwei Wang, Xiaodan Liang, and Jing Tang. Depth-breadth synergy in rlvr: Unlocking llm reasoning gains with adaptive exploration. *arXiv preprint arXiv:2508.13755*, 2025.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*, 2025.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. Star: Bootstrapping reasoning with reasoning. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 15476–15488. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/639a9a172c044fbb64175b5fad42e9a5-Paper-Conference.pdf.

Chenhui Zhang, Le Wang, Dunqiu Fan, Junyi Zhu, Tang Zhou, Liyi Zeng, and Zhaohua Li. VTT-LLM: Advancing vulnerability-to-tactic-and-technique mapping through fine-tuning of large language model. *Mathematics*, 12(9):1286, 2024. doi: 10.3390/math12091286. URL https://www.mdpi.com/2227-7390/12/9/1286.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023.

A Minerva-CTI Dataset

Minerva-CTI comprises 16 tasks covering vulnerability descriptions, detection content, and structured threat knowledge bases. Each task is defined as an input–target prediction problem derived from a specific upstream source, with targets expressed as canonical identifiers (e.g., ATT&CK technique, tactic, or mitigation IDs). Across all tasks, the dataset contains 32,000 training instances and 1,200 validation instances. Table 11 summarizes the per-task sample counts for the training and validation splits in Minerva-CTI.

1. Mappings-Explorer CVE→ATT&CK Exploitation. This task maps vulnerability descriptions to the ATT&CK technique directly used for exploitation. Given a CVE description as input, the model predicts a single ATT&CK technique identifier (formatted as `Txxxx` or `Txxxx.yyy`). Ground-truth labels are obtained from the Center for Threat-Informed Defense Mappings Explorer CVE→ATT&CK mappings, with technique definitions aligned to the ATT&CK catalog (Center for Threat-Informed Defense, 2026; MITRE Corporation, 2026d).

2. Mappings-Explorer CVE→ATT&CK Primary Impact. This task focuses on the main adversarial impact resulting from successful exploitation. The input is the CVE description, and the target is a single ATT&CK technique identifier corresponding to the primary post-exploitation effect (e.g., credential access or privilege escalation). Labels are sourced from the Mappings Explorer and normalized using the ATT&CK technique taxonomy (Center for Threat-Informed Defense, 2026; MITRE Corporation, 2026d).

3. Mappings-Explorer CVE→ATT&CK Secondary Impact. This task predicts a subsequent impact enabled by the primary impact. The input consists of the CVE description concatenated with the given primary-impact technique ID, and the target is a single ATT&CK technique identifier representing the secondary effect. Ground-truth annotations are derived from the Mappings Explorer and mapped to canonical ATT&CK identifiers (Center for Threat-Informed Defense, 2026; MITRE Corporation, 2026d).

4. Sigma→ATT&CK Tactics. This task infers high-level adversary intent from detection logic. Given a Sigma rule excerpt—including the rule title, `logsource`, and `detection` fields—the model predicts a multi-label set of ATT&CK tactic identifiers (formatted as `TA000x`). Sigma rules are sourced from the public Sigma repository, and annotations are expressed using the ATT&CK tactic taxonomy (SigmaHQ, 2026; MITRE Corporation, 2026d).

5. Sigma→ATT&CK Technique. This task maps detection logic to the specific adversarial behavior it is designed to identify. Using the same Sigma rule excerpt as input, the model predicts a single ATT&CK technique identifier (formatted as `Txxxx` or `Txxxx.yyy`). Rules are drawn from the Sigma repository, with targets aligned to canonical ATT&CK technique identifiers (SigmaHQ, 2026; MITRE Corporation, 2026d).

6. Atomic Red Team→ATT&CK Technique. This task maps adversary procedure descriptions to their corresponding ATT&CK techniques. The input is an Atomic Red Team procedure snippet that includes execution steps or commands and platform context, and the target is a single ATT&CK technique identifier. Examples are drawn from the Atomic Red Team repository, which is natively aligned with the ATT&CK framework (Red Canary, 2026; MITRE Corporation, 2026d).

7. Microsoft Sentinel→ATT&CK Technique. This task links analytics rules to the ATT&CK techniques they are intended to detect. The input comprises the rule title, description, and associated KQL query, and the target is a single ATT&CK technique identifier. Rules are sourced from the Microsoft Sentinel content repository, with labels normalized to the ATT&CK taxonomy (Microsoft, 2026; MITRE Corporation, 2026d).

8. Splunk Security Content→ATT&CK Technique. This task maps SPL-based detection content to the ATT&CK technique it targets. The input consists of an SPL query, its detection narrative, and metadata, and the target is a single ATT&CK technique identifier. Content is obtained from Splunk Security Content,

with annotations expressed using canonical ATT&CK technique IDs (Splunk, 2026; MITRE Corporation, 2026d).

9. ATT&CK Scenario→Technique. This task identifies the ATT&CK technique that best corresponds to a described adversary scenario. The input is a scenario text derived from ATT&CK procedure examples, and the target is a single ATT&CK technique identifier. Scenarios and labels are sourced directly from the ATT&CK knowledge base and its machine-readable releases (MITRE Corporation, 2026d;a).

10. ATT&CK Scenario→Tactics. This task infers the adversary intent categories implied by a scenario. Given the same scenario text as input, the model predicts a multi-label set of ATT&CK tactic identifiers (`TA000x`) associated with the underlying behavior. Annotations are derived from the ATT&CK taxonomy and its structured releases (MITRE Corporation, 2026d;a).

11. ATT&CK Scenario→Mitigations. This task predicts mitigations relevant to the behaviors described in a scenario. The input is the ATT&CK scenario text, and the target is a multi-label set of ATT&CK mitigation identifiers (`Mxxxx`) associated with the corresponding techniques. Mitigation mappings are obtained from the ATT&CK knowledge base (MITRE Corporation, 2026d;a).

12. NVD CVE→CWE. This task maps vulnerability descriptions to their underlying weakness categories. The input is the CVE description text, and the target is a multi-label set of CWE identifiers (formatted as `CWE-xxx`). CVE records are obtained from the National Vulnerability Database, with labels aligned to the CWE taxonomy (Byers et al., 2022; MITRE Corporation, 2026c).

13. NVD CVE→CVSS v3.1. This task predicts the CVSS v3.1 base vector associated with a vulnerability. Given a CVE description as input, the model outputs the corresponding CVSS v3.1 base vector string (e.g., `CVSS:3.1/AV:N/...`). CVE entries are sourced from the National Vulnerability Database, and targets follow the official CVSS v3.1 specification (Byers et al., 2022; FIRST.org, Inc., 2019).

14. ATT&CK Threat Actor Attribution. This task performs threat actor attribution from observed behaviors expressed as procedure text. Examples are derived from MITRE ATT&CK Enterprise intrusion-set (group) entries by collecting each actor's *techniques used* relationships and extracting the associated procedure descriptions that characterize how the actor operates (MITRE Corporation, 2026d;a). Training instances are sampled from per-actor pools of procedures, with counts allocated roughly in proportion to available procedure coverage (e.g., binning by technique count and enforcing minimum coverage) to prevent a small number of well-documented actors from dominating the dataset. To reduce lexical leakage, prompts are anonymized by replacing explicit actor mentions with a generic placeholder (e.g., "A threat actor") and by generalizing other named entities by type (e.g., campaign, malware, tool) while preserving the remaining structure. The true actor name is retained only as the target label, and aliases are recorded in a lookup table for evaluation and reward scoring.

15. CAPEC Example→CAPEC. This task maps attack example narratives to the CAPEC attack pattern they exemplify. The input is a CAPEC example description, and the target is a single CAPEC identifier (formatted as `CAPEC-xxx`). Both example texts and pattern identifiers are sourced from the CAPEC catalog (MITRE Corporation, 2026b).

16. CAPEC Example→CWE. This task associates CAPEC attack examples with the underlying software weakness categories they exploit. The input is the same CAPEC example narrative, and the target is a multi-label set of CWE identifiers (formatted as `CWE-xxx`). Example descriptions are drawn from CAPEC, with labels aligned to the CWE taxonomy (MITRE Corporation, 2026b;c).

B Reward Functions for RLVR

Each Minerva-CTI task is paired with a deterministic verifier whose form depends on the task output type. Given a prompt x, a model completion c, and a ground-truth target t, the verifier first extracts a task-specific

Table 11: Minerva training datasets and split sizes.

Dataset	Target	Train	Val
Mappings-Explorer CVE→ATT&CK Exploitation	ATT&CK technique ID	245	20
Mappings-Explorer CVE→ATT&CK Primary Impact	ATT&CK technique ID	210	20
Mappings-Explorer CVE→ATT&CK Secondary Impact	ATT&CK technique ID	64	10
Sigma→ATT&CK Tactics	ATT&CK tactic IDs	950	50
Sigma→ATT&CK Technique	ATT&CK technique ID	950	50
Atomic Red Team→ATT&CK Technique	ATT&CK technique ID	950	50
Microsoft Sentinel→ATT&CK Technique	ATT&CK technique ID	950	50
Splunk Security Content→ATT&CK Technique	ATT&CK technique ID	280	20
ATT&CK Scenario→Technique	ATT&CK technique ID	7,780	220
ATT&CK Scenario→Tactics	ATT&CK tactic IDs	1,950	50
ATT&CK Scenario→Mitigations	ATT&CK mitigation IDs	7,780	220
NVD CVE→CWE	CWE IDs	6,696	220
NVD CVE→CVSS v3.1	CVSS v3.1 vector	1,900	100
ATT&CK Threat Actor Attribution	Threat actor name	779	60
CAPEC Example→CAPEC	CAPEC ID	340	40
CAPEC Example→CWE	CWE IDs	176	20
Total	–	32,000	1,200

prediction $\hat{y}$ from c and then assigns a reward $r \in [0, 1]$. Single-label tasks use exact identifier matching, hierarchical ATT&CK tasks use partial credit for base-technique matches, set-valued tasks use set-F_1, CVSS tasks use score-distance credit, and threat-actor attribution accepts known aliases. Thus, rewards measure task correctness after answer extraction and normalization rather than surface-form similarity.

System prompt and answer extraction. All Minerva-CTI training tasks use a shared system prompt that asks the model to reason step by step and place the final answer inside `\boxed{...}`:

Train System Prompt

You are given a cyber threat intelligence question. Solve it by reasoning step by step.
Present the final answer clearly inside \boxed{}.

For reward computation, we prioritize the final `\boxed{...}` span when present. During training, extraction is intentionally strict: if no boxed span is found, we accept only explicit answer lines such as `Answer:` or `Final answer:`, and require either one unambiguous identifier for single-label tasks or a well-formed identifier set for multi-label tasks. During validation and testing, extraction is more permissive: if no boxed answer is present, we try answer-line parsing, tagged answer spans, and the last non-empty line, then apply task-specific regular expressions to recover candidate identifiers.

Normalization. Before scoring, predictions and targets are canonicalized. The function $\mathrm{norm}_{\mathrm{id}}(\cdot)$ trims whitespace and uppercases identifiers. For ATT&CK technique IDs, we additionally normalize sub-technique notation by zero-padding suffixes when needed, e.g., `T1059.3` $\mapsto$ `T1059.003`. For threat-actor names, $\mathrm{norm}_{\mathrm{actor}}(\cdot)$ lowercases text, removes non-alphanumeric characters, and collapses repeated whitespace. Set-valued predictions are deduplicated after normalization.

Single identifier exact match. For tasks with a single canonical identifier, such as CAPEC Example→CAPEC, the extracted prediction $\hat{y}$ receives binary exact-match credit:

$$r = \mathbb{1}[\mathrm{norm}_{\mathrm{id}}(\hat{y}) = \mathrm{norm}_{\mathrm{id}}(t)] \,.$$

ATT&CK technique identifier. For tasks whose target is an ATT&CK technique ID, including CVE→ATT&CK, scenario→technique, and detection→technique tasks, we give full credit for an exact nor-

malized ID match and partial credit when the base technique matches but sub-technique specificity differs. Let $b(\cdot)$ return the base technique ID, e.g., `T1059`, and let $s(\cdot) \in \{0, 1\}$ indicate whether the ID includes a sub-technique suffix. The reward is

$$r = \begin{cases} 1.0, & \mathrm{norm}_{\mathrm{id}}(\hat{y}) = \mathrm{norm}_{\mathrm{id}}(t), \\ 0.5, & b(\hat{y}) = b(t) \ \wedge \ \big(s(\hat{y}) = 1 \ \vee \ s(t) = 1\big), \\ 0.0, & \text{otherwise.} \end{cases}$$

This credit reflects the fact that upstream CTI sources sometimes annotate the same behavior at different levels of ATT&CK granularity.

Multi-label identifier sets. For set-valued targets, including scenario→tactics, scenario→mitigations, NVD CVE→CWE, and CAPEC Example→CWE, we normalize the predicted and target identifier sets as P and T. Invalid identifiers are discarded and duplicates are removed. The reward is set-F_1:

$$r = \begin{cases} 1.0, & P = T = \varnothing, \\ 0.0, & (P = \varnothing) \oplus (T = \varnothing), \\ \dfrac{2|P \cap T|}{|P| + |T|}, & \text{otherwise,} \end{cases}$$

where $\oplus$ denotes exclusive-or. This penalizes both missing required labels and adding spurious labels.

CVSS v3.1 base vector. For NVD CVE→CVSS v3.1, the prediction must parse as a valid CVSS v3.1 base vector. We require each of the eight base metrics to appear exactly once:

$$\mathcal{M} = \{\mathrm{AV}, \mathrm{AC}, \mathrm{PR}, \mathrm{UI}, \mathrm{S}, \mathrm{C}, \mathrm{I}, \mathrm{A}\}.$$

Base metrics may appear in any order, and Temporal or Environmental metrics are ignored if present. If the prefix, version, metric set, or metric values are invalid, the reward is 0. Otherwise, we compute the CVSS v3.1 base score $s(\cdot) \in [0, 10]$ for the predicted and target vectors and assign distance-based credit:

$$r = \max\left(0,\, 1 - \frac{|s(\hat{y}) - s(t)|}{\delta}\right), \qquad \delta = 10.$$

Threat actor attribution. For ATT&CK threat-actor attribution, each target actor has an alias set $A(t)$ derived from ATT&CK group profiles, including the canonical name and known aliases. From the extracted answer span, we form a normalized candidate set Y by splitting on commas and semicolons and applying $\mathrm{norm}_{\mathrm{actor}}(\cdot)$. The reward is

$$r = \mathbb{1}[Y \cap A(t) \neq \varnothing].$$

This gives credit when the model predicts either the canonical actor name or a recognized alias.

C Answer-Conditioned Rationale (ACR) Filtering

C.1 ACR Generation

For hard prompts, MinervaRL generates answer-conditioned rationale (ACR) traces by augmenting the original training prompt with a label-revealing block. The ACR prompt provides the ground-truth label(s), optionally includes a truncated canonical reference, and asks the model to produce a short justification that ends in the same final-answer format required by the original task. The prompt explicitly discourages leakage language, such as stating that the answer was provided. Figure 6 shows the template.

ACR Generation Prompt

You are generating a reasoning trace for training.

GROUND_TRUTH_LABELS:
- <LABEL_1>
- <LABEL_2>

LABEL_REFERENCE:
<details_text>

Instructions:
- Write a short reasoning that would justify selecting the correct label(s) from the input.
- <TASK_OR_ENTITY_REASONING_HINT>
- Do NOT say or imply that the answer was provided (no phrases like "given the answer", "based on the provided label", "ground truth", etc.).
- End with the final answer in the same format required by the original task.

Figure 6: Answer-conditioned rationale (ACR) prompt template used to elicit training traces.

C.2 Candidate Filtering and Selection

For each buffered training prompt with unique identifier (UID) i, ACR generation produces K candidate traces $\{c_{i,k}\}_{k=1}^{K}$. MinervaRL retains at most one trace per UID for self-distillation. Filtering proceeds in three stages. First, each candidate is scored by the task-specific Minerva verifier, yielding a correctness score $s_{i,k} \in [0, 1]$; only candidates with $s_{i,k} = 1$ are considered for distillation. Second, verifier-correct candidates pass through heuristic filters that remove leakage and low-quality generations. Third, the remaining candidates are scored by a lightweight TextCNN quality classifier, and the highest-scoring eligible trace is selected.

Heuristic filters. We apply four heuristic checks before the ML filter. The leakage filter rejects candidates containing curated phrases or regex patterns that directly refer to provided labels, references, or ground-truth answers. The reasoning-length filter rejects candidates whose reasoning portion, excluding the final answer line, contains fewer than 100 characters. The grounding filter rejects candidates whose reasoning has Jaccard overlap below 0.05 with the task description plus label reference, computed over lowercased alphanumeric tokens after removing ID-like tokens. Finally, the degeneracy filter rejects repetitive responses when the response has at least 30 tokens. Degeneracy checks include n-gram repetition thresholds, repeated-window checks, and near-duplicate sentence checks. Specifically, we reject if $\text{rep}_3 \geq 0.70$ or $\text{rep}_4 \geq 0.75$; if repeated windows of size 24 and stride 12 are exact matches or have 3-gram Jaccard similarity at least 0.9; or if sentences within a 6-sentence window have SequenceMatcher similarity at least 0.75 when both sentences contain at least 6 words. These thresholds apply only to the heuristic repetition checks; the TextCNN acceptance threshold is $\tau_q = 0.5$.

TextCNN quality filter. Candidates that pass the heuristic filters are scored by the deployed response-only TextCNN classifier. The classifier tokenizes alphanumeric response tokens, truncates to at most 1024 tokens, and outputs a GOOD probability $q_{i,k} \in [0, 1]$. We keep candidates with $q_{i,k} \geq \tau_q$, where $\tau_q = 0.5$. Let $L_{i,k}$ and $D_{i,k}$ denote whether candidate k is rejected by leakage/quality heuristics or degeneracy heuristics, respectively. The eligible set is

$$\mathcal{E}_i = \{k \mid s_{i,k} = 1,\ L_{i,k} = 0,\ D_{i,k} = 0,\ q_{i,k} \geq \tau_q\}\,.$$

If $\mathcal{E}_i = \varnothing$, UID i contributes no distillation example in that interval. Otherwise, we select the highest-confidence candidate,

$$k^\star = \arg\max_{k \in \mathcal{E}_i} q_{i,k},$$

breaking ties uniformly at random. The selected distillation record pairs the original answer-free prompt with the accepted ACR response, i.e., $(x_i, c_{i,k^\star})$.

C.3 Filtering Dynamics

Figure 7 tracks the ACR filtering pipeline during training for Llama-3.1-8B-Instruct. We report the fraction of batches that pass the heuristic filter, pass the ML filter, and satisfy UID coverage, meaning that accepted traces span a sufficient number of distinct prompts. These rates increase over training, indicating that as the actor and EMA teacher improve, more ACR candidates are both verifier-correct and suitable for stable original-prompt distillation.

D Training the TextCNN Reasoning-Quality Classifier

MinervaRL uses a lightweight TextCNN classifier to filter verifier-correct ACR traces before distillation. The classifier is trained to identify rationale quality rather than answer correctness: all training examples are already verifier-correct, and labels distinguish useful traces from traces with leakage, incoherence, unsupported reasoning, or other quality failures.

D.1 Dataset Curation

We construct the TextCNN training data from Minerva-CTI prompts. For each prompt, we generate responses in two formats: *plain* responses from the original prompt, and *hinted* responses from an ACR-style prompt containing the ground-truth label, a label reference, and an explicit training-trace marker. Responses are generated with a diverse set of open or open-weight instruction-tuned LLMs using typical decoding settings of temperature 0.7 and maximum length 1024 new tokens.

To ensure that the classifier learns rationale quality rather than answer correctness, we first score all responses with the task verifier and retain only reward-correct responses with `reward` = 1. These responses are then labeled `GOOD` or `BAD` by a rubric-based LLM judge. The judge does not re-grade correctness; instead, it marks a response as `BAD` if it exhibits any quality failure, including leakage, incoherence, unsupported claims, mismatch between rationale and final answer, answer-only reasoning, refusals, prompt copying, or other artifacts. The judge is instructed to return a single JSON object, as shown in Figure 8.

To improve coverage of failure modes, we also synthesize additional `BAD` examples by conditioning a generator on randomly sampled rubric violations. These synthetic examples are retained only if they remain verifier-correct. We then build a balanced dataset by downsampling to 32k `GOOD` and 32k `BAD` examples, and split each class 80/20 into train and validation partitions.

D.2 TextCNN Model and Training

The deployed classifier uses response text only; prompt text is not concatenated to the input. Responses are tokenized with the regex tokenizer `[A-Za-z0-9_]+`, lowercased, and truncated to a maximum of 1024 tokens. The vocabulary is built from the training split with `max_vocab`=100,000 and `min_freq`=2, using `<pad>` and `<unk>` as special tokens.

The model is a standard TextCNN: an embedding layer followed by 1D convolutions with kernel widths 3, 4, and 5; ReLU activations; max-over-time pooling; feature concatenation; dropout; and a two-way linear classifier. We train with AdamW and cross-entropy loss for 5 epochs using batch size 128. Hyperparameters are selected by grid search over learning rate $\{3\times10^{-4}, 6\times10^{-4}, 10^{-3}, 2\times10^{-3}, 4\times10^{-3}\}$, filters per kernel $\{256, 384\}$, dropout $\{0, 0.25\}$, embedding dimension $\{200, 300\}$, and maximum response-token budget. The deployed model uses learning rate 6×10^{-4}, 384 filters per kernel, embedding dimension 300, dropout 0.25, maximum response length 1024 tokens, and threshold 0.5. On the balanced validation split, it achieves 0.826 accuracy and $F_1 = 0.828$.




Figure 7: Acceptance rates of the ACR self-distillation pipeline over training for Llama-3.1-8B-Instruct: fraction of batches passing the heuristic filter, passing the machine-learning (ML) filter, and meeting unique identifier (UID) coverage.

Table 12: Validation confusion matrix for the TextCNN reasoning-quality filter at threshold 0.5.

	Predicted GOOD	Predicted BAD
Actual GOOD	5,375	1,025
Actual BAD	1,206	5,194

D.3 Validation and Error Analysis

Table 12 reports the validation confusion matrix. False positives are `BAD` responses accepted by the TextCNN. As shown in Table 13, most false positives involve leakage: 738 of 1,206 false positives (61.2%) explicitly or implicitly reveal access to the provided answer or reference. Other common false-positive categories are ungrounded claims (17.7%) and rationale-answer mismatch (13.2%). These errors are often fluent and plausible, which makes them difficult for a lightweight lexical classifier to reject.

A representative `scenario_to_attack_technique` false positive received $p(\text{GOOD}) = 0.829$ from TextCNN, but the judge labeled it `BAD`/Leakage because it implies access to the provided reference techniques:

> A malware has installed a bootkit on the system to maintain persistence. A bootkit modifies the boot sectors of a hard drive, allowing malicious code to execute before the operating system has loaded. This behavior aligns with the definition of techniques that involve modifying the operating system or firmware to achieve persistence. The Master Boot Record (MBR) and Volume Boot Record (VBR) are key components involved in the boot process, and modifying these areas would allow an adversary to execute malicious code before the operating system loads. This is a common method used by bootkits to persist on systems.
> *Considering the provided techniques*, the most suitable ID is `T1542.003`, which directly corresponds to Bootkit, as it describes the use of a bootkit to persist on systems. Therefore, the selected technique ID is `T1542.003`.

False negatives are `GOOD` responses rejected by the TextCNN. Table 14 shows that these are concentrated in open-ended ATT&CK generation tasks, especially `scenario_to_attack_mitigations` and `scenario_to_attack_technique`. These tasks permit diverse valid rationales, so a compact response-only classifier can reject acceptable traces whose style differs from common `GOOD` examples. This error profile is consistent with the component ablations in Table 5: removing the full filtering pipeline or only the ML filter reduces AthenaBench-Mini and average performance relative to full MinervaRL, despite occasional TextCNN errors.

LLM Judge Prompt

You are an expert CTI evaluator. You will be given a Question and a Response.
The Question may include answer/reference text as hints.

Label the Response as GOOD or BAD. Mark BAD if any single criterion below is present;
otherwise mark GOOD. Do not grade correctness beyond these checks.

Return exactly one JSON object on a single line and nothing else.
- GOOD: {"label": "GOOD"}
- BAD: {"label": "BAD", "category_id": <number>, "category_title": "<title>"}

If multiple BAD criteria apply, choose the lowest-numbered category.

Criteria (one per bullet):
1. Leakage: says or implies the answer/label/options/reference were provided,
   or quotes/paraphrases provided reference text instead of reasoning from the prompt.
2. Incoherent: loops, repeated phrases/lines, templated filler, or gibberish.
3. Ungrounded: invents concrete details not in the question (extra CVEs,
   vendors, malware names, IOCs, dates, techniques, etc.).
4. Mismatch: reasoning supports a different label than the final answer,
   or directly contradicts it.
5. Unsupported: provides reasoning but does not use evidence from the prompt to
   justify the answer (hand-wavy or irrelevant justification), OR provides an
   answer with no reasoning at all (answer-only).
6. Other: refusals, policy/meta artifacts, generic CTI tutorials, or prompt copying.

Example outputs:
{"label": "GOOD"}
{"label": "BAD", "category_id": 1, "category_title": "Leakage"}

QUESTION:
{QUESTION}

RESPONSE:
{RESPONSE}

Figure 8: Prompt template used to label reward-correct responses as `GOOD/BAD` for training the TextCNN rationale-quality classifier.

Table 13: False positives by LLM-judge rubric category for the TextCNN filter at threshold 0.5.

Rubric category	Count	Share of FP
Leakage	738	61.2%
Ungrounded	214	17.7%
Mismatch	159	13.2%
Incoherent	77	6.4%
Unsupported	18	1.5%

E Evaluation Datasets

We evaluate on 12 CTI and cybersecurity benchmarks covering multiple-choice knowledge QA, SOC-style reasoning, structured taxonomy prediction, vulnerability assessment, and information extraction. Each benchmark is evaluated with task-specific answer extraction and the corresponding exact-match or structured metric described in Section 5.2. Meta tasks report the aggregate sample count over their constituent subtasks.

Table 14: False negatives by task for the TextCNN filter at threshold 0.5.

Task	Count	Share of FN
`scenario_to_attack_mitigations`	392	38.2%
`scenario_to_attack_technique`	194	18.9%
`cve_to_cwe`	173	16.9%
`scenario_to_attack_tactics`	64	6.2%
`sentinel_to_attack_technique`	35	3.4%
`sigma_to_attack_technique`	35	3.4%
`sigma_to_attack_tactics`	34	3.3%
`cve_to_cvss_v31`	28	2.7%
`threat_actor`	23	2.2%
`art_to_attack_technique`	20	2.0%
Other tasks	27	2.6%

Table 15: Evaluation datasets used for Table 1.

Task	# Samples	Output format and evaluation target
CKT (Alam et al., 2025)	3000	Five-option CTI knowledge QA; output a single option A–E.
CyberMetric (Tihanyi et al., 2024)	2000	Four-option cybersecurity knowledge QA; output a single option A–D.
SOCEval (Deason et al., 2025)	588	Multi-select SOC-style reasoning over threat-intelligence reports; output a JSON object in `<json_object>` tags with a `correct_answers` array.
RCM (Alam et al., 2025)	2000	Root-cause mapping from CVE description to a single CWE identifier, e.g., `CWE-####`.
VSP (Alam et al., 2025)	2000	Vulnerability severity prediction; output a full CVSS v3.1 base vector, e.g., `CVSS:3.1/AV:N/...`.
ATE (Alam et al., 2025)	500	ATT&CK technique extraction from an attack scenario; output a single technique or sub-technique ID, e.g., `T####` or `T####.###`.
RMS (Alam et al., 2025)	500	Risk mitigation recommendation; output a set of ATT&CK mitigation IDs, e.g., `M10xx`.
ElasticRule (Elastic, 2026)	432	Detection-rule mapping; map an Elastic rule and metadata to a single ATT&CK technique ID.
APTNER (Wang et al., 2022)	1505	APT-focused named-entity recognition; output a JSON object mapping entity types to extracted spans.
LANCE (Froudakis et al., 2025)	466	Indicator-of-compromise identification over candidate IPs, URLs, domains, and hashes; output candidate-level IoC labels.
AnnoCTR (Lange et al., 2024)	1230	STIX-style entity and relation extraction; meta task over entity extraction, entity typing, relation existence, and relation labeling with XML-like output tags.
AZERG (Lekssays et al., 2025)	1333	STIX-style entity and relation extraction; meta task over entity extraction, entity typing, relation existence, and relation labeling with XML-like output tags.

F Statistical Uncertainty Analysis

Bootstrap protocol. We use 2000 paired bootstrap resamples. For each task, backbone, and baseline comparison, examples are resampled within the task, both systems are evaluated on the same resampled examples, the original task metric is recomputed, and the percentile interval of MinervaRL minus the baseline is reported.

Table 16: Paired bootstrap 95% confidence intervals for MinervaRL minus each baseline on the 12-task macro average. The macro average is the unweighted mean over the 12 task metrics and is included for comparability with Table 1.

Baseline	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
Base	+11.6 [10.8, 12.5]	+15.2 [14.5, 16.0]	+15.7 [14.5, 17.1]	+20.4 [19.0, 21.3]
STaR	+10.5 [9.7, 11.3]	+11.0 [10.3, 11.8]	+16.5 [15.4, 17.6]	+2.6 [1.5, 3.6]
DART	+6.6 [5.7, 7.5]	+4.3 [3.5, 5.1]	+10.5 [9.5, 11.8]	+8.6 [7.4, 9.7]
GRPO	+4.2 [3.5, 5.1]	+6.2 [5.3, 7.1]	+6.4 [5.6, 7.6]	+0.4 [-0.8, 1.3]
LUFFY	+3.3 [2.5, 4.1]	+2.9 [2.1, 4.0]	+0.1 [-0.6, 0.8]	+4.0 [3.0, 4.7]

F.1 Checkpoint-Selection Sensitivity

AthenaBench-Mini is not instance-disjoint from the final CKT, RCM, VSP, ATE, and RMS evaluations; its 950 examples are contained in those five evaluation sets. After excluding those examples, the MinervaRL–GRPO five-task macro-average differences (paired 95% CIs) are +7.7 [6.4, 9.0], +11.9 [10.8, 13.1], +8.6 [7.6, 9.7], and −1.3 [−2.1, −0.5] points for Llama-3.1-8B, Llama-3.2-3B, Qwen3-8B, and Qwen3-4B, respectively. The first three remain positive, while Qwen3-4B is negative, consistent with our qualified claims.

F.2 Full Pairwise Confidence Intervals

Table 17: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus Base, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+6.3 [4.6, 8.0]	-0.6 [-1.9, 0.7]	+6.0 [4.5, 7.5]	+24.4 [22.4, 26.5]
CyberMetric	+1.1 [-0.3, 2.5]	+1.1 [-0.2, 2.4]	+18.9 [16.8, 21.0]	+29.9 [27.2, 32.5]
SOCEval	-0.1 [-1.9, 1.9]	-1.1 [-3.1, 0.9]	+3.8 [2.2, 5.4]	+7.9 [5.6, 10.1]
RCM	+20.4 [18.3, 22.5]	+42.0 [40.0, 44.2]	+12.2 [10.5, 14.0]	+14.3 [12.7, 16.1]
VSP	+11.6 [10.6, 12.7]	+74.3 [73.2, 75.5]	+10.4 [9.4, 11.3]	+3.5 [2.6, 4.4]
ATE	+31.0 [26.8, 35.4]	+20.8 [17.4, 24.2]	+18.6 [14.8, 22.6]	+21.2 [17.6, 24.8]
RMS	+35.4 [32.1, 38.9]	+28.9 [26.3, 31.7]	+13.6 [10.7, 16.5]	-1.5 [-2.8, -0.2]
ElasticRule	+26.2 [21.1, 30.8]	+19.0 [15.0, 22.9]	+13.0 [9.0, 17.4]	+22.9 [19.0, 27.1]
APTNER	+0.6 [-0.3, 1.6]	-8.8 [-10.3, -7.2]	+6.1 [4.7, 7.6]	+26.8 [25.0, 28.7]
LANCE	+6.4 [2.2, 10.1]	+4.5 [-0.0, 9.5]	+29.8 [18.7, 44.5]	+38.7 [28.9, 48.6]
AnnoCTR	-0.4 [-2.7, 2.0]	+1.9 [-0.2, 3.9]	+33.2 [29.1, 35.8]	+33.8 [27.7, 36.1]
AZERG	+0.8 [-1.9, 3.6]	+0.8 [-1.5, 3.0]	+23.3 [20.6, 26.0]	+22.6 [18.0, 24.8]

Table 18: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus STaR-CTI, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+3.9 [2.2, 5.5]	+6.7 [5.1, 8.3]	+39.8 [37.7, 41.9]	-6.1 [-7.8, -4.5]
CyberMetric	+2.4 [1.0, 3.9]	+7.6 [5.8, 9.5]	+38.9 [36.5, 41.3]	-8.2 [-10.0, -6.5]
SOCEval	+3.0 [1.3, 4.9]	+4.3 [2.1, 6.4]	+2.4 [1.0, 3.9]	-2.1 [-4.4, 0.2]
RCM	+11.4 [9.7, 13.2]	+20.8 [19.0, 22.7]	+28.1 [26.1, 30.3]	+38.8 [36.6, 41.0]
VSP	+13.8 [12.8, 15.0]	+23.7 [22.0, 25.4]	+10.7 [9.8, 11.6]	-0.2 [-1.2, 0.7]
ATE	+19.2 [14.6, 23.8]	+17.6 [14.0, 21.0]	+16.4 [12.8, 20.0]	+19.6 [16.2, 23.2]
RMS	+32.5 [29.2, 36.0]	+22.3 [19.5, 25.4]	+16.6 [13.8, 19.5]	-1.5 [-2.7, -0.2]
ElasticRule	+19.2 [14.8, 23.8]	+18.3 [14.8, 22.2]	+17.1 [13.2, 21.1]	+15.3 [11.3, 19.2]
APTNER	+1.0 [-0.1, 2.1]	-4.7 [-6.1, -3.3]	-0.5 [-2.0, 1.0]	-3.8 [-5.5, -2.1]
LANCE	+4.6 [1.5, 7.5]	+5.9 [1.9, 10.7]	+19.2 [9.9, 29.0]	-5.3 [-14.2, 3.3]
AnnoCTR	+3.8 [1.3, 6.3]	+4.1 [1.7, 6.6]	+3.0 [-1.1, 6.2]	+3.5 [-0.8, 5.7]
AZERG	+11.6 [9.1, 14.0]	+5.7 [3.1, 8.1]	+6.7 [4.3, 9.1]	-18.6 [-21.2, -16.1]

Table 19: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus DART-CTI, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+2.6 [1.2, 4.1]	-2.0 [-3.2, -0.7]	+38.6 [36.6, 40.6]	+24.6 [22.5, 26.8]
CyberMetric	+1.9 [0.6, 3.1]	-0.1 [-1.4, 1.2]	+32.5 [30.1, 34.9]	+37.9 [35.3, 40.5]
SOCEval	+3.3 [1.4, 5.2]	+0.1 [-1.8, 1.9]	+2.4 [1.1, 3.8]	+4.0 [2.0, 6.1]
RCM	+4.7 [3.2, 6.3]	+2.3 [1.1, 3.7]	+17.7 [15.8, 19.6]	+5.2 [3.9, 6.7]
VSP	+14.6 [13.6, 15.7]	+15.9 [14.9, 17.0]	+6.7 [5.8, 7.6]	+6.2 [5.3, 7.2]
ATE	+10.6 [6.2, 15.2]	+5.0 [2.2, 7.6]	+18.0 [14.0, 22.0]	+4.8 [1.6, 8.2]
RMS	+14.4 [11.0, 18.1]	+11.5 [8.6, 14.5]	+13.6 [10.9, 16.3]	-0.8 [-2.0, 0.4]
ElasticRule	+9.5 [5.3, 13.7]	+8.6 [5.5, 11.6]	+5.6 [1.4, 10.0]	+10.4 [7.2, 13.9]
APTNER	+0.1 [-0.9, 1.1]	-5.8 [-7.2, -4.5]	-0.5 [-1.8, 0.8]	+0.4 [-1.2, 2.1]
LANCE	+9.8 [3.9, 16.3]	+8.4 [1.7, 14.8]	-1.5 [-10.8, 8.5]	+9.2 [-0.5, 21.2]
AnnoCTR	+3.2 [0.9, 5.6]	-0.8 [-3.0, 1.3]	-3.5 [-6.2, 0.1]	+7.1 [2.0, 9.3]
AZERG	+4.4 [2.0, 7.0]	+8.0 [5.8, 10.1]	-3.4 [-5.3, 0.2]	-6.1 [-10.5, -3.2]

Table 20: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus GRPO, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+2.0 [0.6, 3.5]	-0.2 [-1.6, 1.1]	+8.0 [6.5, 9.5]	-4.2 [-5.8, -2.6]
CyberMetric	-1.1 [-2.5, 0.3]	+0.3 [-1.1, 1.5]	+15.5 [13.5, 17.5]	-5.7 [-7.4, -4.0]
SOCEval	+1.7 [-0.4, 3.8]	-3.7 [-5.8, -1.4]	-1.4 [-2.7, -0.1]	+0.2 [-1.6, 2.1]
RCM	+2.4 [1.1, 3.8]	+8.3 [6.8, 9.8]	+4.3 [2.9, 5.8]	-0.9 [-2.1, 0.2]
VSP	+5.0 [4.3, 5.7]	+20.6 [18.9, 22.4]	+10.6 [9.7, 11.7]	-8.1 [-9.0, -7.3]
ATE	+16.4 [12.6, 20.4]	+16.6 [13.2, 20.2]	+8.4 [5.8, 11.4]	+5.2 [2.8, 7.6]
RMS	+11.2 [7.8, 14.4]	+13.9 [11.1, 16.9]	+12.0 [9.1, 14.8]	+1.3 [-0.7, 3.2]
ElasticRule	+8.3 [3.9, 12.7]	+14.8 [11.6, 18.3]	+3.9 [-0.2, 7.9]	+7.2 [3.7, 10.9]
APTNER	+1.4 [0.5, 2.4]	-10.8 [-12.3, -9.3]	-0.3 [-1.5, 1.0]	-4.4 [-5.9, -2.9]
LANCE	-1.5 [-5.7, 2.2]	+11.7 [2.7, 19.3]	+8.8 [0.8, 19.9]	-1.5 [-10.5, 9.3]
AnnoCTR	+0.7 [-1.6, 2.9]	-0.7 [-2.4, 1.1]	+5.2 [3.2, 8.1]	+10.7 [4.4, 12.9]
AZERG	+4.1 [2.3, 7.7]	+4.0 [1.5, 7.0]	+2.0 [0.1, 5.6]	+5.1 [0.3, 7.8]

Table 21: Per-task paired bootstrap 95% confidence intervals for MinervaRL minus LUFFY-CTI, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+0.0 [-1.4, 1.3]	+0.4 [-0.8, 1.5]	-0.9 [-1.9, 0.2]	+16.0 [13.9, 18.0]
CyberMetric	+0.6 [-0.7, 1.8]	-0.4 [-1.6, 0.8]	-0.1 [-1.2, 1.0]	+23.6 [21.1, 25.9]
SOCEval	+1.5 [-0.0, 2.9]	-0.8 [-2.4, 0.9]	+2.7 [1.0, 4.4]	+3.1 [1.1, 5.1]
RCM	+4.9 [3.7, 6.2]	+13.4 [11.9, 14.9]	-0.5 [-1.6, 0.6]	-0.0 [-1.2, 1.0]
VSP	+8.0 [7.2, 8.8]	+5.5 [4.5, 6.6]	+6.2 [5.5, 7.0]	+7.4 [6.5, 8.2]
ATE	+7.8 [4.2, 11.6]	+2.4 [-0.4, 5.4]	+2.6 [0.0, 5.2]	+7.8 [4.6, 11.0]
RMS	+7.8 [4.4, 11.2]	+5.1 [2.3, 8.0]	-5.7 [-8.5, -3.0]	-5.2 [-6.9, -3.6]
ElasticRule	+6.7 [2.5, 10.6]	-0.2 [-3.0, 2.5]	-10.4 [-14.1, -6.5]	+4.2 [0.7, 7.6]
APTNER	-1.3 [-2.1, -0.5]	+1.7 [0.3, 3.0]	+3.1 [2.0, 4.2]	-1.1 [-2.7, 0.5]
LANCE	+2.2 [-3.1, 7.3]	+14.2 [5.2, 22.2]	+0.4 [-5.4, 5.2]	-3.7 [-10.5, 4.4]
AnnoCTR	+0.6 [-2.1, 3.1]	-8.1 [-10.2, -3.7]	-2.1 [-5.5, 0.2]	+3.7 [-0.7, 5.8]
AZERG	+0.5 [-2.2, 3.4]	+1.6 [-0.9, 5.1]	+6.4 [3.8, 8.8]	-7.1 [-10.1, -4.9]

F.3 Rollout-Aware Confidence Intervals

Tables 22 to 25 report per-task paired bootstrap intervals for the held-out rollout-aware comparisons in Section 7.2. Each cell is MinervaRL minus GRPO in percentage points under the corresponding best-of-k score.

Table 22: Per-task rollout-aware paired bootstrap 95% confidence intervals for MinervaRL minus GRPO at best-of-1, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+0.0 [-1.5, 1.6]	-0.4 [-2.0, 1.2]	+7.0 [5.3, 8.7]	+9.4 [7.6, 11.3]
CyberMetric	-0.5 [-1.9, 0.8]	+1.3 [0.0, 2.6]	+2.8 [1.4, 4.3]	+28.6 [26.0, 31.1]
SOCEval	+2.2 [0.0, 4.3]	-5.1 [-7.4, -3.1]	-2.3 [-4.6, -0.2]	-0.3 [-2.5, 1.8]
RCM	+0.7 [-0.8, 2.2]	+7.5 [6.0, 8.9]	+4.0 [2.6, 5.4]	-0.7 [-1.9, 0.6]
VSP	+5.0 [4.3, 5.7]	+20.0 [18.4, 21.8]	+9.3 [8.4, 10.2]	-8.2 [-9.0, -7.3]
ATE	+16.0 [12.0, 19.8]	+16.8 [13.4, 20.4]	+8.6 [5.6, 11.8]	+3.8 [1.0, 6.6]
RMS	+7.6 [4.3, 11.1]	+11.2 [8.2, 14.1]	+10.5 [7.3, 13.4]	-4.3 [-6.8, -1.8]
ElasticRule	+8.6 [4.4, 12.7]	+15.0 [11.3, 18.8]	+0.2 [-3.2, 3.7]	+4.6 [1.2, 8.3]
APTNER	-0.1 [-1.1, 0.8]	-11.7 [-13.0, -10.6]	-3.2 [-5.0, -1.4]	+10.3 [8.4, 12.3]
LANCE	-5.5 [-10.0, -1.6]	+10.2 [2.2, 18.6]	+2.8 [-7.0, 15.2]	+12.0 [0.0, 24.5]
AnnoCTR	-5.3 [-7.8, -1.0]	+5.6 [3.3, 7.5]	+0.2 [-2.7, 5.4]	-1.4 [-3.7, 3.0]
AZERG	+3.2 [1.0, 6.5]	+18.0 [15.4, 20.5]	-6.2 [-9.0, -3.3]	-4.6 [-7.1, -2.0]

Table 23: Per-task rollout-aware paired bootstrap 95% confidence intervals for MinervaRL minus GRPO at best-of-2, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+5.1 [3.7, 6.5]	+3.1 [1.8, 4.6]	+0.8 [-0.4, 2.1]	+1.0 [-0.4, 2.4]
CyberMetric	+0.7 [-0.5, 1.8]	+2.0 [0.8, 3.1]	+0.3 [-0.6, 1.4]	-0.3 [-1.7, 1.1]
SOCEval	+3.5 [1.4, 5.6]	-3.0 [-5.0, -0.9]	-0.7 [-2.4, 1.0]	+0.2 [-1.7, 2.1]
RCM	+3.1 [1.6, 4.6]	+9.1 [7.6, 10.7]	+5.5 [4.0, 7.1]	+1.0 [-0.1, 2.1]
VSP	+5.9 [5.3, 6.6]	+11.9 [10.6, 13.2]	+8.8 [7.9, 9.7]	-7.5 [-8.2, -6.6]
ATE	+19.4 [15.6, 23.2]	+20.2 [16.6, 24.2]	+8.6 [5.6, 11.8]	+4.6 [1.6, 7.4]
RMS	+13.2 [9.9, 16.6]	+11.2 [8.2, 14.4]	+16.9 [14.2, 19.7]	-5.3 [-8.1, -2.6]
ElasticRule	+12.7 [8.6, 17.1]	+14.6 [11.1, 18.3]	+4.2 [1.4, 6.9]	+4.2 [0.9, 7.4]
APTNER	+0.1 [-0.7, 1.0]	-15.7 [-16.9, -14.4]	-1.5 [-2.9, -0.2]	+5.0 [3.5, 6.5]
LANCE	-2.7 [-4.7, -0.7]	+5.7 [0.2, 10.7]	+4.6 [-3.8, 12.3]	+4.8 [-4.0, 12.6]
AnnoCTR	-2.8 [-5.4, 1.5]	+4.1 [2.9, 6.7]	+0.5 [-0.9, 4.1]	+4.6 [2.5, 10.8]
AZERG	-2.0 [-4.9, 1.5]	+4.4 [2.4, 6.5]	-1.3 [-4.0, 1.3]	-1.1 [-3.4, 1.3]

Table 24: Per-task rollout-aware paired bootstrap 95% confidence intervals for MinervaRL minus GRPO at best-of-4, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+8.1 [6.8, 9.5]	+4.2 [3.1, 5.3]	-0.3 [-1.4, 0.8]	+0.6 [-0.6, 1.8]
CyberMetric	+1.1 [0.1, 2.1]	+2.3 [1.2, 3.4]	-0.4 [-1.3, 0.4]	-0.8 [-1.8, 0.2]
SOCEval	+6.9 [4.8, 9.2]	-0.6 [-2.6, 1.6]	+0.2 [-1.2, 1.6]	+0.6 [-1.2, 2.2]
RCM	+4.5 [3.1, 6.0]	+10.5 [9.0, 12.2]	+7.2 [5.8, 8.7]	+2.3 [1.2, 3.3]
VSP	+6.2 [5.6, 6.8]	+7.0 [6.1, 7.9]	+4.4 [3.6, 5.2]	-5.8 [-6.6, -5.1]
ATE	+20.4 [16.4, 24.2]	+23.2 [19.6, 27.0]	+10.0 [6.8, 13.4]	+7.0 [4.0, 10.0]
RMS	+17.9 [14.6, 21.2]	+12.7 [9.5, 15.7]	+22.3 [19.3, 25.5]	-3.1 [-5.8, -0.3]
ElasticRule	+16.4 [12.3, 20.6]	+16.0 [12.5, 19.4]	+5.6 [2.8, 8.6]	+5.1 [1.9, 8.3]
APTNER	+1.4 [0.5, 2.2]	-16.3 [-17.6, -15.0]	-2.1 [-3.4, -0.8]	+4.8 [3.3, 6.2]
LANCE	-1.5 [-3.3, 0.6]	+6.2 [0.8, 10.8]	+2.0 [-6.5, 10.3]	+1.3 [-4.4, 8.0]
AnnoCTR	-1.4 [-3.6, 2.9]	+5.5 [4.0, 8.2]	+2.3 [0.9, 4.3]	+4.2 [2.3, 10.3]
AZERG	+1.1 [-2.3, 5.6]	+7.8 [5.6, 9.9]	+2.5 [-0.0, 4.9]	+5.9 [4.0, 7.8]

Table 25: Per-task rollout-aware paired bootstrap 95% confidence intervals for MinervaRL minus GRPO at best-of-8, in percentage points.

Task	Llama-3.1-8B	Llama-3.2-3B	Qwen3-8B	Qwen3-4B
CKT	+9.4 [8.1, 10.7]	+6.6 [5.7, 7.7]	-1.7 [-2.6, -0.8]	+2.0 [1.0, 2.9]
CyberMetric	+1.9 [1.0, 2.9]	+3.1 [2.0, 4.2]	-0.7 [-1.5, -0.0]	+0.3 [-0.5, 1.0]
SOCEval	+8.5 [6.4, 10.6]	+1.0 [-1.1, 3.1]	+1.1 [-0.1, 2.2]	+0.5 [-1.1, 2.1]
RCM	+5.6 [4.1, 7.0]	+12.5 [10.9, 14.2]	+8.7 [7.2, 10.1]	+2.6 [1.5, 3.6]
VSP	+6.3 [5.7, 6.8]	+4.6 [4.0, 5.3]	-3.2 [-3.9, -2.6]	-0.9 [-1.5, -0.3]
ATE	+23.6 [19.8, 27.8]	+25.4 [21.4, 29.6]	+11.6 [8.2, 14.8]	+10.2 [7.2, 13.6]
RMS	+22.4 [19.1, 25.6]	+15.3 [12.5, 18.2]	+26.7 [23.7, 29.5]	+0.6 [-2.3, 3.7]
ElasticRule	+18.1 [13.9, 22.2]	+17.8 [13.9, 21.8]	+8.3 [5.3, 11.3]	+6.5 [3.5, 9.7]
APTNER	+1.8 [1.0, 2.6]	-15.7 [-17.0, -14.4]	-1.3 [-2.6, -0.1]	+5.3 [3.9, 6.7]
LANCE	-1.2 [-3.4, 1.3]	+2.6 [-0.6, 5.3]	-0.5 [-3.9, 2.3]	-1.9 [-4.9, 2.4]
AnnoCTR	+2.7 [-1.5, 6.8]	+7.3 [5.7, 10.2]	+1.5 [0.1, 3.0]	+8.0 [5.1, 10.5]
AZERG	+2.5 [-1.0, 6.4]	+7.8 [5.8, 9.8]	+3.7 [1.2, 6.1]	+4.5 [2.8, 6.3]

G Additional Result Tables

G.1 Rollout-Aware Task Scores

Table 26: Full rollout-aware best-of-k task scores for GRPO and MinervaRL. Each task cell reports GRPO/MinervaRL in percent for the specified backbone and best-of-k budget.

Backbone	k	CKT	CyberMetric	SOCEval	RCM	VSP	ATE	RMS	ElasticRule	APTNER	LANCE	AnnoCTR	AZERG
Llama-3.1-8B	1	71.3/71.4	85.7/85.2	63.2/65.4	66.5/67.2	82.4/87.4	30.8/46.8	31.3/38.9	31.7/40.3	32.6/32.5	87.0/81.6	52.9/47.6	39.3/42.5
Llama-3.1-8B	2	75.4/80.5	89.0/89.7	65.8/69.3	67.2/70.3	83.9/89.9	32.2/51.6	33.8/47.1	32.4/45.1	36.0/36.2	88.0/85.3	55.7/52.9	47.8/45.8
Llama-3.1-8B	4	77.9/86.0	91.4/92.5	69.7/76.7	68.4/72.9	85.1/91.3	35.0/55.4	35.0/52.9	34.0/50.5	38.6/40.0	89.2/87.8	58.8/57.4	49.7/50.8
Llama-3.1-8B	8	80.0/89.4	92.9/94.8	71.6/80.1	69.2/74.8	86.0/92.3	35.4/59.0	36.0/58.4	34.3/52.3	41.0/42.8	90.1/88.8	61.8/64.5	51.4/53.9
Llama-3.2-3B	1	68.6/68.2	77.7/79.0	60.5/55.4	47.9/55.5	54.6/74.6	5.4/22.2	17.1/28.2	5.6/20.6	26.8/15.1	66.2/76.5	36.9/42.5	25.0/43.0
Llama-3.2-3B	2	73.1/76.2	80.5/82.5	63.0/60.0	48.9/58.0	70.0/81.9	5.6/25.8	22.3/33.4	6.5/21.1	30.7/15.1	77.6/83.3	43.5/47.6	47.9/52.3
Llama-3.2-3B	4	81.6/85.7	83.9/86.2	67.2/66.6	49.5/60.1	79.8/86.8	5.8/29.0	24.5/37.2	7.2/23.1	34.0/17.7	81.8/88.1	46.7/52.1	51.1/58.9
Llama-3.2-3B	8	82.9/89.5	85.7/88.8	68.8/69.8	50.3/62.8	85.1/89.7	5.8/31.2	26.3/41.6	7.9/25.7	37.0/21.3	87.1/89.7	51.6/58.9	55.2/63.0
Qwen3-8B	1	69.0/76.0	84.5/87.4	68.4/66.1	60.0/64.0	69.5/78.8	22.6/31.2	7.9/18.4	24.1/24.3	36.2/33.1	66.4/69.2	45.1/45.3	38.4/32.3
Qwen3-8B	2	82.3/83.1	92.1/92.5	74.7/74.0	61.5/67.0	73.8/82.6	24.6/33.2	8.3/25.2	26.6/30.8	45.1/43.6	74.7/79.3	53.5/53.9	49.2/47.9
Qwen3-8B	4	88.2/87.8	94.9/94.5	80.9/81.1	62.3/69.5	81.6/86.0	25.2/35.2	8.6/31.0	28.5/34.0	51.7/49.6	83.2/85.2	56.8/59.1	53.4/55.9
Qwen3-8B	8	92.8/91.1	96.8/96.0	83.7/84.8	62.8/71.5	91.6/88.4	25.8/37.4	9.0/35.7	29.4/37.7	55.3/53.9	92.3/91.8	59.5/60.9	58.1/61.8
Qwen3-4B	1	62.7/72.2	54.1/82.8	62.1/61.8	60.2/59.5	88.1/80.0	20.6/24.4	12.2/7.9	22.0/26.6	21.8/32.2	45.4/57.4	44.8/43.4	38.5/33.9
Qwen3-4B	2	80.4/81.4	90.6/90.3	69.2/69.5	61.5/62.5	89.6/82.1	22.0/26.6	14.7/9.4	25.0/29.2	34.4/39.3	64.2/69.0	54.3/58.9	48.6/47.5
Qwen3-4B	4	86.3/86.9	95.0/94.2	75.2/75.8	62.2/64.5	90.1/84.3	22.4/29.4	15.1/12.0	25.7/30.8	41.3/46.0	76.7/78.1	59.2/63.4	53.5/59.4
Qwen3-4B	8	89.9/91.9	96.3/96.5	80.0/80.5	62.8/65.4	90.8/89.9	22.4/32.6	15.9/16.5	26.4/32.9	46.0/51.3	89.7/87.8	65.6/73.5	58.4/62.9

G.2 Component Ablation Task Scores

Table 27: Full Llama-3.1-8B component ablation scores on the 12 CTI evaluation tasks. All entries are task scores in percent.

Ablation	CKT	CyberMetric	SOCEval	RCM	VSP	ATE	RMS	ElasticRule	APTNER	LANCE	AnnoCTR	AZERG	Avg.
GRPO	71.9	85.4	63.0	66.3	82.6	32.0	30.9	32.2	32.7	86.2	49.6	39.5	56.0
GRPO 12 rollouts	71.2	85.0	64.6	66.8	76.3	31.4	17.0	31.7	36.3	82.6	48.8	35.4	53.9
Answer-only SFT	76.3	85.9	65.2	64.7	64.8	36.6	17.2	34.7	40.7	56.5	45.3	43.2	52.6
In-loop answer SFT	75.6	84.5	66.8	65.8	79.2	38.4	28.6	33.3	38.7	78.1	53.9	50.5	57.8
No EMA teacher	72.5	83.7	62.4	65.3	85.9	42.2	43.0	39.8	33.1	75.1	43.7	40.2	57.2
No TextCNN filter	71.2	85.3	63.6	64.0	78.6	45.0	36.5	41.4	36.0	82.5	47.5	41.1	57.7
No filtering	73.1	84.3	63.3	67.2	83.9	40.0	37.2	38.2	34.2	81.2	45.9	44.6	57.8
Full MinervaRL	73.9	84.2	64.7	68.8	87.6	48.4	42.1	40.5	34.1	84.6	50.3	43.7	60.2

H Additional Baseline Construction Details

This appendix describes the three additional training-method baselines reported in Table 1. All baselines use the same 32,000-example Minerva-CTI train split, the same task verifiers, and the same 12-task evaluation protocol as MinervaRL unless stated otherwise. Training and sampling hyperparameters for these baselines are listed with the other implementation settings in Appendix K.

H.1 STaR-CTI

STaR-CTI adapts STaR (Zelikman et al., 2022) to verifier-scored CTI tasks. For each training example $(x, y^\star)$ in a round, we generate one *original* trace from the original prompt x and one *rationalization* trace from a prompt that additionally reveals the gold answer $y^\star$. Both traces are scored by the Minerva verifier. We keep the original trace if it is verifier-correct; otherwise, we keep the rationalization trace if it is verifier-correct; otherwise, the example contributes no trace in that round.

The selected traces form that round's SFT dataset. We train a fresh copy of the base model for each round rather than continuing from the previous SFT checkpoint. The resulting checkpoint is then used as the generator for the next round. Checkpoints are selected with the same validation criterion used for the RL baselines: the average of Minerva-Dev and AthenaBench-Mini validation performance. The validation suite contains 1,200 Minerva-Dev examples and 950 Athena CTI examples covering ATE, CKT, RCM, RMS, Threat Actor Attribution (TAA), and VSP.

H.2 DART-CTI

DART-CTI adapts DART-Math (Tong et al., 2024) as a fixed rejection-finetuning baseline. We build a teacher-generated trace corpus once, then train each student model with SFT on that fixed corpus. The target corpus contains two accepted traces per Minerva-CTI training prompt, for 64,000 traces total.

The final corpus is built in four stages. First, we run plain rejection sampling from the original prompt, with a target of two accepted traces per prompt and a cap of 32 attempts per prompt. This produces 16,807 accepted plain traces from 880,782 generated attempts. Second, for prompts still missing traces, we use answer-guided generation with the same ACR-style prompt used by MinervaRL and accept traces that pass the verifier plus the heuristic/TextCNN filters; this adds 38,868 traces. Third, for the remaining hard tail, we keep answer-guided generation but disable the heuristic/TextCNN filters and require only verifier success; this adds 8,296 traces. Finally, 29 remaining missing traces are filled with a deterministic boxed gold-answer completion that is still checked by the verifier. The final training corpus therefore contains 16,807 plain traces, 47,164 guided-fill traces, and 29 direct-answer tail traces.

H.3 LUFFY-CTI

LUFFY-CTI adapts LUFFY (Yan et al., 2025), an off-policy RLVR method that uses precomputed correct traces as off-policy guidance during RL training. We derive the off-policy guidance corpus from the DART-CTI trace corpus by selecting one accepted trace per training prompt, giving a 32,000-trace guidance set aligned with the Minerva-CTI train split.

We run LUFFY-CTI on the same four backbones used for GRPO and MinervaRL. This baseline is useful because it tests whether an off-policy trace-guided RL method closes the reward-sparsity gap without MinervaRL's online answer-conditioned rationale generation and periodic distillation. A practical distinction is that LUFFY-CTI requires the guidance corpus before RL begins: in our setup, constructing the 32,000-prompt trace corpus required 1,017,847 teacher attempts, or 31.8 attempts per prompt on average. By contrast, under the default MinervaRL schedule each prompt is seen about twice on average, with eight on-policy rollouts per visit and up to four additional ACR generations only for hard prompts, giving an upper bound of 24 generations per prompt across the full RL process.

I Response-Quality Evaluation Details

This appendix describes the response-quality evaluation summarized in Figure 3. The goal is to complement verifier-based task metrics with a separate assessment of analyst-facing response quality, including readability, evidence use, and CTI concept precision.

I.1 Evaluation Scope and Rubric

For each backbone family, we evaluate a shared set of 350 prompts: 50 prompts each from CKT, CyberMetric, RCM, VSP, ATE, RMS, and ElasticRule (Elastic, 2026). These tasks require justification or nontrivial CTI reasoning, making them suitable for prose-quality assessment. We exclude schema-heavy extraction and tagging tasks because their responses are dominated by format compliance and label recovery rather than explanatory quality.

Within each backbone family, we compare five variants: the base model, GRPO, MinervaRL, STaR-CTI, and DART-CTI. Model identities are hidden from the judge. GPT-5.2 scores each prompt-response pair independently using the three-criterion rubric in Figure 9. Each criterion is scored from 1 to 4, and the total response-quality score is the sum of writing quality, evidence use, and CTI concept use, giving a range of 3–12.

I.2 Pairwise Preference Construction

The heatmaps in Figure 3 are derived from the pointwise rubric scores. For each prompt and each unordered pair of models within the same backbone family, we compare the two total response-quality scores. The model with the higher total score receives one pairwise win; if the scores are equal, the outcome is counted as a tie. Each heatmap cell reports the row model's win count divided by the number of shared prompts, with ties retained in the denominator rather than discarded.

I.3 Human and Cross-Judge Agreement

We validate GPT-5.2 on a 100-example subset covering the five Llama-3.1-8B-family variants. Two human annotators independently score the same blind prompt-response items using the rubric in Figure 9. We also score the same subset with Claude Sonnet 4.6 as a cross-judge comparison. Agreement is measured on the total rubric score using quadratic weighted kappa (QWK) and Spearman correlation.

GPT-5.2 agrees with the human annotator average at a level close to human–human agreement, and Claude Sonnet 4.6 shows strong agreement with GPT-5.2. These results support using GPT-5.2 as a scalable response-quality judge for the full preference study, while treating the preference heatmaps as complementary to the verifier-based task metrics.

J Additional Support for MinervaRL

J.1 Target-Level Reward Sparsity

To characterize the sparsity that motivates hardness-gated answer-conditioned rationale generation, we analyze the DART-CTI stage-1 plain rejection-sampling traces with a maximum budget of 32 attempts per prompt. Figure 10 plots target-level aggregates for ATE and RCM. Question-weighted summaries from the target-level statistics show that ATE is sparser than RCM: ATE requires 26.7 attempts per question on average, yields 0.66 verifier-successful responses, and reaches the 32-attempt cap for 73.2% of questions, compared with 23.6 attempts, 0.86 verifier-successful responses, and a 61.5% cap rate for RCM. Both tasks also exhibit long target-level tails, with many identifiers clustered near the attempt cap and below one successful response per question.

J.2 A Stylized Finite-Budget Detectability Formalization

Verifier-level success. Consider a training instance $(x, a^\star)$, where $x \in \mathcal{X}$ is the original prompt and $a^\star \in \mathcal{A}$ is the ground-truth structured target, such as an ATT&CK technique ID, a set of mitigation IDs, or a CVSS vector. We define full success directly through the same task-specific Minerva verifier used during training:

$$S(x, y; a^\star) := \mathbb{1}\{R_{\text{MINERVA}}(x, y, a^\star) = 1\}\,. \tag{14}$$

Pointwise Response-Quality Judge Prompt

You are an expert cyber threat intelligence (CTI) analyst evaluating the quality of a single model response. Your job is to score the response using the rubric below.
Rubric: use a 1–4 scale for each criterion, where 1 = poor, 2 = fair, 3 = good, and 4 = excellent.

1. **Writing quality.** Is the response easy to read and efficiently structured?
   1: no rationale, or hard to follow because of rambling, disorganization, or awkward phrasing.
   2: understandable, but noticeably wordy, repetitive, or clunky.
   3: clear and easy to follow, with minor issues in concision or structure.
   4: very clear, concise, well structured, and easy to scan.
2. **Evidence use.** Does the response justify its answer using details from the prompt?
   1: mostly asserts the answer with little or no prompt-based support.
   2: uses some prompt evidence, but the justification is weak, generic, or incomplete.
   3: supports the main answer with relevant prompt details, with only minor gaps.
   4: directly justifies the answer using strong and specific prompt evidence.
3. **CTI concept use.** Does the response use the right CTI concepts correctly?
   1: uses no relevant CTI concepts, or uses irrelevant concepts.
   2: uses some relevant CTI concepts, but with important mistakes or vague distinctions.
   3: mostly uses the right CTI concepts correctly, with minor imprecision.
   4: uses the right CTI concepts precisely and consistently to support the answer.

Task: `{task}`
Subtask: `{subtask}`
Prompt: `{prompt}`
Model Response: `{response}`
Return JSON only with this exact schema:

```
{
"writing_quality_score": 1,
"evidence_use_score": 1,
"cti_concept_focus_score": 1,
"notes": "short explanation"
}
```

Rules: each score must be an integer from 1 to 4; use the rubric exactly; keep notes short and concrete; return JSON only.

Figure 9: Prompt template and rubric used for GPT-5.2 and Claude Sonnet 4.6 pointwise response-quality scoring.

Table 28: Agreement on the response-quality validation subset. QWK denotes quadratic weighted kappa.

Comparison	QWK	Spearman
Annotator 1 vs. Annotator 2	0.6514	0.6461
Annotator 1 vs. GPT-5.2	0.6019	0.7822
Annotator 2 vs. GPT-5.2	0.5680	0.6440
Annotator average vs. GPT-5.2	0.6313	0.7722
Claude Sonnet 4.6 vs. GPT-5.2	0.7634	0.8266

This definition incorporates the verifier's extraction, normalization, alias handling, structured partial credit, and set-valued scoring rules. A policy $\pi_\theta(\cdot \mid x)$ therefore induces the full-verification probability

$$p_\theta(a^\star \mid x) := \Pr_{y \sim \pi_\theta(\cdot|x)} [S(x, y; a^\star) = 1] \,. \tag{15}$$




Figure 10: Target-level reward sparsity for ATE and RCM in DART-CTI stage-1 plain-generation attempts. Each point is one target identifier; the x-axis is mean attempts per question, the y-axis is mean verifier-successful responses per question, and color indicates the fraction of questions that reached the 32-attempt cap.

Finite-budget detectability. With a rollout budget of k independent completions for the same prompt, the probability that the rollout group contains no fully verified completion is

$$\Pr[\text{no full success in } k \text{ rollouts}] = (1 - p_\theta(a^\star \mid x))^k . \tag{16}$$

For a failure tolerance $\zeta \in (0, 1)$, define the exact detectability threshold

$$\varepsilon_{k,\zeta} := 1 - \zeta^{1/k} \approx \frac{-\log \zeta}{k}. \tag{17}$$

This is the minimum full-verification probability needed to make the chance of missing a fully verified completion in k samples at most ζ.

Lemma J.1 (Finite-sample detectability)**.** *Fix a prompt-target pair $(x, a^\star)$ and a rollout budget k. If $p_\theta(a^\star \mid x) \geq \varepsilon_{k,\zeta}$, then*

$$\Pr[\textit{no full success in } k \textit{ rollouts}] \leq \zeta. \tag{18}$$

Proof. If $p_\theta(a^\star \mid x) \geq 1 - \zeta^{1/k}$, then

$$(1 - p_\theta(a^\star \mid x))^k \leq (\zeta^{1/k})^k = \zeta.$$

□

Small-budget no-full-success regime. The detectability threshold above characterizes when full verifier success is reliably observable. For $\eta \in (0, 1)$, define

$$\delta_{k,\eta} := 1 - (1 - \eta)^{1/k} \approx \frac{\eta}{k}. \tag{19}$$

If $p_\theta(a^\star \mid x) \leq \delta_{k,\eta}$, then the probability of seeing no fully verified completion in k rollouts is at least $1 - \eta$. Thus, when $p_\theta(a^\star \mid x) \ll 1/k$, the prompt can repeatedly produce no-full-success rollout groups.

Theorem J.2 (Small-budget full-success detectability)**.** *Fix a prompt x and rollout budget k. Suppose that, at iteration t, $p_t := p_{\theta_t}(a^\star \mid x) \leq \delta_{k,\eta}$. Then, with probability at least $1 - \eta$, the k on-policy rollouts for x contain no fully verified completion. On this event, an update rule whose direct positive signal for full verifier success comes only from observed fully verified rollouts receives no such direct positive example in that iteration.*

Proof sketch. The probability of no fully verified rollout is $(1-p_t)^k$. Since $p_t \le 1-(1-\eta)^{1/k}$, we have $(1-p_t)^k \ge 1-\eta$. Conditioning on this event, the sampled trajectories contain no fully verified example. This statement does not exclude relative GRPO signal from partial-credit differences. □

Relation to the ACR gate. For rollouts $y_1, \dots, y_k$, write $r_j = R_{\text{MINERVA}}(x, y_j, a^\star)$ and $m = \max_j r_j$. The no-full-success event analyzed above is exactly $m < 1$, the gate used by MinervaRL.

Conditional effect of the auxiliary update. When $m < 1$, MinervaRL constructs an answer-conditioned prompt

$$\tilde{x} = \text{ACR}(x, a^\star, \text{ref}(a^\star)),$$

which reveals the gold target and optionally includes a truncated canonical reference. The EMA teacher samples ACR candidates from $\pi_\phi(\cdot \mid \tilde{x})$. A candidate is accepted only if it is fully verified under the original task target and passes the leakage and quality filters. The accepted trace is then distilled onto the original prompt x, not onto $\tilde{x}$.

We model this mechanism through two finite-sampling assumptions. The first describes the probability that answer-conditioned generation yields an accepted verified trace; the second posits the effect of distilling that trace onto the original prompt.

Assumption J.3 (Answer-conditioned exposure)**.** For a gated instance $(x, a^\star)$, before the prompt reaches the detectability threshold $\varepsilon_{k,\zeta}$, each ACR-generation cycle has conditional probability at least $\alpha > 0$ of producing an accepted trace y_{acr} such that

$$S(x, y_{\text{acr}}; a^\star) = 1. \tag{20}$$

Assumption J.4 (Effective original-prompt distillation)**.** Let $p_\theta(a^\star \mid x) > 0$. Whenever MinervaRL performs an SFT update on an accepted pair (x, y_{acr}) with $S(x, y_{\text{acr}}; a^\star) = 1$, the full-verification probability under the original prompt increases by at least $\Delta > 0$ in log-space until the detectability threshold is reached:

$$\log p_{\theta^+}(a^\star \mid x) \ge \min\{\log \varepsilon_{k,\zeta},\, \log p_\theta(a^\star \mid x) + \Delta\}\,. \tag{21}$$

Theorem J.5 (Conditional finite-budget detectability)**.** *Fix a prompt-target pair $(x, a^\star)$, rollout budget k, and failure tolerance ζ. Let $\varepsilon_{k,\zeta} = 1-\zeta^{1/k}$ and $p_0 = p_{\theta_0}(a^\star \mid x) > 0$. Under Assumptions J.3 and J.4, MinervaRL raises $p_\theta(a^\star \mid x)$ to at least $\varepsilon_{k,\zeta}$ in a finite expected number of ACR-generation cycles. In particular, after*

$$L = \left\lceil \frac{[\log \varepsilon_{k,\zeta} - \log p_0]_+}{\Delta} \right\rceil \tag{22}$$

successful original-prompt distillation updates, we have

$$p_\theta(a^\star \mid x) \ge \varepsilon_{k,\zeta}. \tag{23}$$

The expected number of ACR-generation cycles needed to obtain these L accepted traces is at most L/α. Consequently, once this threshold is reached, the probability that k standard RLVR rollouts contain no fully verified completion is at most ζ.

Proof sketch. By Assumption J.4, each successful distillation update increases $\log p_\theta(a^\star \mid x)$ by at least Δ until the threshold $\varepsilon_{k,\zeta}$ is reached. Therefore L accepted distillation updates suffice. By Assumption J.3, each ACR-generation cycle produces an accepted trace with conditional probability at least α, so the expected number of cycles required to obtain L accepted traces is at most L/α. Finally, once $p_\theta(a^\star \mid x) \ge \varepsilon_{k,\zeta}$, Lemma J.1 gives the final miss-probability statement. □

Scope and limitations. This result is a stylized implication of its assumptions, not an optimization guarantee or independent evidence for MinervaRL. In particular, Assumption J.4 posits the probability increase that the calculation accumulates; the result does not derive that increase from interacting GRPO and SFT updates, shared-parameter language-model optimization, or cross-prompt effects. Because it assumes $p_{\theta_0}(a^\star \mid x) > 0$, it concerns finite-budget detectability rather than expansion of mathematical support. It also does not claim that ACR traces are faithful proofs or that answer conditioning improves general reasoning.

K Training Hyperparameters and Implementation Details

This appendix lists the training hyperparameters used for RLVR (GRPO), MinervaRL, and the controlled training baselines. We report only settings that directly affect optimization, sampling, or sequence truncation.

K.1 RLVR (GRPO) settings

- **Optimizer:** GRPO with actor learning rate 1×10^{-6}.
- **Batching:** 128 prompts per training step.
- **Rollouts:** $N = 8$ sampled completions per prompt per step.
- **Sequence lengths:** max prompt length 2048 tokens; max response length 1024 tokens.
- **Schedule:** 500 training steps.

K.2 MinervaRL (ACR + distillation) settings

- **Hard-example criterion:** mark a prompt "hard" if the best base-rollout reward is < 1.0 (CVSS prompts excluded).
- **ACR prompt context:** max ACR prompt length 4096 tokens; max response length 1024 tokens.
- **ACR sampling:** $K = 4$ traces per ACR prompt; temperature 0.7; nucleus sampling $p = 0.9$.
- **Deferred generation cadence:** generate/distill every $I = 10$ steps.
- **Teacher:** EMA teacher with decay $\alpha = 0.995$.
- **Distillation:** supervised fine-tuning on original prompts using up to 256 accepted traces per distillation interval; learning rate is scaled by $\gamma = 0.05$ relative to the RLVR learning rate.
- **Trace filtering:** a two-stage pipeline (heuristics + ML filter) is applied before distillation; the ML filter acceptance threshold is $\tau_q = 0.5$.

K.3 Controlled baseline settings

STaR-CTI.

- **Trace generation:** maximum generation length 2048 tokens; temperature 0.7; top-$p = 0.95$.
- **Trace selection:** one original trace and one rationalization trace per training example in each round; verifier success threshold 1.0.
- **SFT training:** one epoch per round; train batch size 128; maximum sequence length 3072 tokens; bfloat16 FSDP; gradient checkpointing.
- **Optimizer:** AdamW with learning rate 1×10^{-5}, betas $(0.9, 0.95)$, weight decay 0.01, gradient clipping 1.0, and cosine scheduling with warmup ratio 0.1.
- **Micro-batching:** micro-batch size 8 for Llama-3.1-8B, Llama-3.2-3B, and Qwen3-8B; micro-batch size 4 for Qwen3-4B.

DART-CTI.

- **Corpus generation:** Llama-3.1-8B-Instruct teacher; maximum generation length 1024 tokens; temperature 0.7; top-$p = 0.95$; verifier threshold 1.0.
- **Rejection sampling:** plain stage targets two accepted traces per prompt with a cap of 32 attempts.
- **Guided fill:** maximum prompt length 4096 tokens; at most 8096 label-reference characters.
- **Filtering:** when enabled, use the response-only TextCNN filter with threshold 0.5, filter batch size 128, and filter maximum length 1024 tokens.
- **Student SFT training:** one epoch; train batch size 128; micro-batch size 8; maximum sequence length 4096 tokens; bfloat16 FSDP; gradient checkpointing.
- **Optimizer and selection:** AdamW with learning rate 1×10^{-5}, betas $(0.9, 0.95)$, weight decay 0.01, gradient clipping 1.0, and cosine scheduling with warmup ratio 0.1; checkpoints selected by synthetic-validation loss.

LUFFY-CTI.

- **Guidance corpus:** 32,000-row one-trace-per-prompt off-policy corpus derived from DART-CTI.
- **RL training:** GRPO advantages with actor learning rate 1×10^{-6}; train batch size 128; PPO mini-batch size 128; PPO micro-batch size 16; 500 training steps.
- **Rollout sampling:** $N = 8$ completions per prompt; maximum prompt length 2048 tokens; maximum response length 1024 tokens; rollout temperature 1.0; validation temperature 0.6.
- **Distributed training:** gradient checkpointing, dynamic batching, FSDP, maximum actor token length 32768 per GPU, and four GPUs per run.
- **Off-policy objective:** token-level off-policy loss, no off-policy normalization, `p_div_p_0.1` reshape setting, KL loss disabled, KL coefficient 0, entropy coefficient 0, and reference model disabled.
- **Prefix guidance:** one random prefix per prompt with maximum prefix length 1024 tokens and min/max prefix ratio 1.0.

K.4 Timing overhead

To isolate per-step overhead, we ran a small-scale timing study on Llama-3.1-8B-Instruct for 10 training steps with validation disabled and one ACR/SFT interleave at step 10. Including end-to-end process time, GRPO took 469.8s and MinervaRL took 654.5s, a 39.3% increase. The measured MinervaRL components were: GRPO rollout 110.3s, GRPO reward 2.3s, ACR prompt construction 2.9s, ACR generation 36.4s, ACR reward 5.9s, and SFT distillation 9.3s. The remaining gap comes mainly from ACR log-prob computation (32.1s) and a modest increase in the shared actor update (+16.9s relative to GRPO). Thus, MinervaRL is not strictly Pareto-dominant at equal step count, but Figure 5 shows that the additional cost can be favorable in time-to-performance because MinervaRL reaches the best GRPO validation accuracy earlier and continues improving.