

09 — Architectural Character, Elevations and Renderings

Project: The Cottages at Arcade Springs — R-1 → R-2 rezoning, 4535 / 4537 / 4539 / 4541 Arcade Rd SW, Lilburn, GA 30047 (PINs R6123 033, 015, 014, 162; Land Lot 123, 6th District, Gwinnett County; 9.44 ac deeded / 9.577 ac GIS-calculated)

Answers: City of Lilburn 2026 *Application Instructions — Rezoning/Special Use Permit/Change In Condition, item (11)*

Architectural Renderings and Elevations; Lilburn Zoning Ordinance 2023-603 §1003-4 **Prepared:** 2026-09-03 (owner-applicant self-prepared; filing date 2026-09-__) **Status: DRAFT — ILLUSTRATIVE, NOT FOR CONSTRUCTION, NOT SEALED.** Every drawing and image named here is preliminary work of the owner-applicant, prepared with AI drafting tools, and is to be superseded by sealed drawings of a Georgia-registered architect before any building permit. See §8. **Geometry source:** data/plans.json (regenerated 2026-09-03 by tools/floorplans.py), data/layout.json (site-plan generator, corrected 2026-09-03 — **the lot count is now 41, not 43**; see §3), tools/elevations.py (Rev B, 2026-09-03) and tools/amenity.py (Sheet A-3.0, 2026-09-03). Every dimension below is read out of those files, not copied from the 2026-08-28 program brief in FACTS.md §4, which both plans have since departed from — see §5.2. **Sheet numbers** are those of the settled register in tools/transmittal.py SHEETS, and only those; python3 verify/check_sheet_refs.py fails on any number that is not in it.

1. What item (11) requires, and where each requirement is answered

Item (11) of the 2026 Application Instructions reads, verbatim (data/application-instructions-2026.txt, lines 49–52):

(11) Architectural Renderings and Elevations: Required for rezoning and special use permits where the applicant plans to erect or alter a building, sign, or other structure. An architectural rendering or elevation of each side of the structure visible from the street shall be submitted. The drawings shall be to scale or in proper perspective and shall include the color and materials of all structures and roofing and location and size of wall signs. Visual imagery may be used.

The instruction names five separate obligations. They are answered as follows.

#	What item (11) requires	Where it is answered	Status
a	An elevation or rendering of each side of each structure visible from the street	§2 structure-by-side table; Sheets A-2.1 (Plan A), A-2.2 (Plan B) and A-3.0 (clubhouse, mail kiosk, monument sign)	Complete. All four elevations of both cottage plans and of the clubhouse; the kiosk and the sign are drawn on A-3.0 — §2.4
b	To scale or in proper perspective	Elevations at 3/16" = 1'-0" on ARCH C (24 × 18 in), drawings/plan-a-elev.svg, plan-b-elev.svg; perspectives in renderings/	Cottages complete; see §7
c	The colour and materials of all structures and roofing	§4 schedule; Sheet A-2.3 material and colour board; the material key printed on each elevation sheet; Sheet A-3.0 draws the clubhouse, kiosk and sign in Scheme 1	Complete for the cottages and for the amenity structures
d	Location and size of wall signs	§6 — no wall signs are proposed anywhere in the development ; one ground-mounted monument entry sign is proposed, scheduled in §6.1 and drawn on Sheet A-3.0 with its area computation	Complete
e	"Visual imagery may be used"	§7 rendering index — twelve AI-generated illustrative perspectives, the scaled drawings governing	All 12 generated (files renderings/R-01...R-12); the R-00 contact index remains to be laid out

Nothing in this document asserts that any element meets a code or ordinance requirement. Every regulatory statement is made as **"appears consistent with"** and each carries its ordinance and edition.

1.1 Sheet numbering — settled

The numbering conflict this section reported on 2026-09-03 is closed. **The register in tools/transmittal.py SHEETS governs**, the generated title blocks have been reconciled to it, and verify/check_sheet_refs.py tests every "Sheet X-N.N" reference in every document in docs/ against it. The architectural sheets are:

Sheet	Content	File	Issued?
A-1.1	Plan A "The Springbrook" — floor and roof plan, 3/16" = 1'-0"	drawings/plan-a-sheet.svg	Issued
A-1.2	Plan B "The Laurel" — floor and roof plan, 3/16" = 1'-0"	drawings/plan-b-sheet.svg	Issued
A-2.1	Plan A — exterior elevations, four sides, 3/16" = 1'-0"	drawings/plan-a-elev.svg	Issued
A-2.2	Plan B — exterior elevations, four sides, 3/16" = 1'-0"	drawings/plan-b-elev.svg	Issued
A-2.3	Exterior colour schemes and materials	drawings/plan-colors.svg	Issued
A-3.0	Clubhouse, mail kiosk and entry monument sign — plans, elevations and details	drawings/amenity-sheet.svg	Issued

Sheet	Content	File	Issued?
A-4.0 / A-4.1	Typical lot — Plan A / Plan B, 1" = 10'	drawings/plan-a-lot.svg, plan-b-lot.svg	Issued

Two consequences for the rest of the package:

1. **Voluntary condition 8 has been conformed** (2026-09-03). It now binds the applicant to "floor plans, elevations and materials substantially as shown on the sheets submitted with the application — Sheets A-1.1 and A-1.2 (floor plans, Plans A and B), A-2.1 and A-2.2 (exterior elevations, Plans A and B), A-2.3 (exterior colour schemes and materials), A-3.0 (clubhouse, mail kiosk and entry monument sign) and A-4.0 and A-4.1 (typical lots)" (data/voluntary-conditions.md, generated from docs/02 §9). That is the register, and it matches this document. The earlier citation — A-1.1 (Plan A), A-2.1 (Plan B), A-3.0, A-4.0 — pointed at Plan A's *floor plan*, Plan A's *elevations* and the *typical-lot* sheet, and is superseded.

2. **Two generated title blocks still print pre-register numbers — this remains a defect to close before filing.**
drawings/amenity-sheet.svg titles itself

"A-3" rather than A-3.0 and cross-refers to "Sheet C-1" for the site plan (the register makes that C-2.0, with the entrance enlargement C-2.3); drawings/existing-conditions.svg titles itself "C-0" and cross-refers to "C-1, MASTER CONCEPT PLAN" (the register makes those C-1.0 and C-2.0). Correct tools/amenity.py and tools/existing_conditions.py and regenerate.

This document uses the register throughout.

2. Structures the applicant plans to erect, and which of their sides are visible

2.1 What "the street" means on this site

The only public street is **Arcado Road SW** (Gwinnett County minor collector, 35 mph, two lanes). Every dwelling stands on a **private lane**, and Lilburn Zoning Ordinance 2023-603 §319 requires every lot to abut at least 30 ft on a public street **or an approved private street**, with the City's Site Development Plan Review Checklist §4.s adding that "All components of private streets and alleys must meet minimum standards for public street." The applicant therefore reads "visible from the street" in item (11) to include the private lane, and provides elevations on that basis rather than arguing that 41 of 41 dwellings face no street at all.

2.2 Why all four elevations of both cottage plans are provided

On the typical lot the arithmetic leaves no side hidden:

Input	Value	Source
Lot	50'-0" × 100'-0" = 5,000 SF	data/layout.json (all 41 lots identical)
Body width, both plans	38'-0"	data/plans.json overall_body_dims
Side yard, each side	6'-0" (50'-0" – 38'-0" = 12'-0", centred)	data/plans.json lot_siting.side_yard_ft
Roof-to-roof width	39'-4" (38'-0" body + 2 × 0'-8" side overhang)	tools/elevations.py check_width()
Clear gap, wall to wall, between adjacent cottages	12'-0" (6'-0" + 6'-0")	derived
Clear gap, roof edge to roof edge	10'-8" (12'-0" – 2 × 0'-8")	derived

A 12'-0" gap between one-story houses set 15'-8" back from a 22'-0"-wide lane is a direct sight line: from the lane a passer-by sees the front elevation of the house in front of them and the full side elevation of both its neighbours. Every one of the 41 lots is also a **perimeter lot** — the **fourteen** south-west lots (numbered 1–14) back to the south-west property line at $v \approx -234.7$ to -235.1 and the **twenty-seven** north-east lots (15–41) back to the north-east line at $v \approx +1.4$ to $+8.7$ (data/layout.json lot polygons) — so **every rear elevation faces the 20'-0" undisturbed buffer and, beyond it, an occupied R-1 back yard** in Legends at Parkview, King David Manor or Nantucket.

All four elevations of both cottage plans are therefore submitted, not only the front. That is more than item (11)'s literal minimum, and it is the only honest reading of "each side visible from the street" on a 236–246-ft-wide strip where nothing is screened by distance.

2.3 Structure-by-side table

Local coordinates are those of FACTS.md §1 (**u** along the strip from Arcado Rd, **v** across it, feet).

#	Structure	Qty	Location	Sides	Which sides are visible from a street or the private lane	Elevation of each such side is at
1	Plan A "The Springbrook" cottage — 1 story, 38'-0" × 51'-10" body	21	odd-numbered lots 1, 3, 5 ... 41, both sides of the lane	4	All four. Front faces the lane; both sides face 12'-0" gaps open to the lane; rear faces the 20-ft buffer and an abutting R-1 rear yard	A-2.1 , four panels: FRONT ELEVATION — FACES THE PRIVATE LANE; RIGHT SIDE; LEFT SIDE; REAR (drawings/plan-a-elev.svg / .png, 3/16" = 1'-0")
2	Plan B "The Laurel" cottage — 1 story, 38'-0" × 57'-6" body	20	even-numbered lots 2, 4, 6 ... 40, both sides of the lane	4	All four , same reasoning	A-2.2 , four panels, same arrangement (drawings/plan-b-elev.svg / .png, 3/16" = 1'-0")
3	Clubhouse — 1 story, 60'-0" (parallel to the lane) × 40'-0" = 2,400 SF under roof (2,000 SF enclosed + a 400-SF covered porch; 1,831 SF of net rooms)	1	amenity tract, north-east of the lane, u 110–170 / v –74.3 to –34.3; 114.8 ft from the Arcade Rd right-of-way and 15.0 ft clear of the 20-ft buffer (tools/amenity.py)	4	All four. The 40'-0" south-east face fronts the 14,354-SF village green and is the face seen from Arcade Road ; the 60'-0" south-west face fronts the lane and the entry drive; the 40'-0" north-west face closes the lane view; the 60'-0" north-east face is seen across the 20-ft buffer from King David Manor	A-3.0 — ISSUED (drawings/amenity-sheet.svg / .png). Four elevations plus floor plan and roof plan; plate 10'-0" + 0'-10" raised heel → eave 10'-10" above the finished floor; 40'-0" span at 6:12 → ridge 20'-10" above the finished floor / 21'-6" above finished grade , against the 24'-0" of voluntary condition 3
4	Mail kiosk — USPS cluster-box shelter, 16'-0" × 10'-0" = 160 SF, roofed and three-sided	1	north-east of the lane, u 211.5–227.5 / v –85.8 to –75.8, opposite a 4-space kiosk bay at u 155.5–207.5 / v –106.9 to –88.9	4	All four — a freestanding shelter with a closed north-east wall, open to the lane	A-3.0 — ISSUED. 4:12 hip, ridge 11'-7" above finished grade ; 3 cluster box units = 48 compartments + 6 parcel lockers; four 9'-0" × 18'-0" stalls and a 4'-0" walk. The sheet carries the Site Development Plan Review Checklist §4.r note ("accessory structure details with protection from the elements")
5	Monument entry sign — ground-mounted; an 8'-0"-long × 1'-4"-thick masonry wall with a 1'-4" wing / planter return at each end, 4'-0" deep overall	1	in the front amenity tract on the Arcade Rd frontage, u –9.7 to –1.7 / v –171.9 to –167.9 — 19.0 ft from the Arcade Rd right-of-way, outside it	2 faces + ends	The face toward Arcade Road and the entry drive is the item-(11) side; the reverse face is seen from the village green. Both faces carry copy	A-3.0 — ISSUED. Elevation, plan and the area computation: whole structure face 8'-0" × 3'-9" = 30.0 SF against the 32-SF voluntary limit, overall height 3'-9" against the 6'-0" voluntary limit, cast-stone copy panel 6'-0" × 1'-9" = 10.5 SF. The sheet shows the 390-ft departure sight triangle: the sign stands 20'-6" behind the driver eye and its nearest corner is 20.1 ft clear of the nearer sight line — no part of the sign or its bed lies inside the triangle
6	Pickleball court enclosure — 10'-0" black PVC-coated chain-link fence around two 60'-0" × 30'-0" pads carrying 44'-0" × 20'-0" courts	2 pads	south-west of the lane, u 157.5–217.5 / v –212.7 to –152.7	—	Visible from the lane and the entry drive. A fence, not a building; no wall, roof or sign	C-8.0 civil details — NOT YET ISSUED (fence height, mesh, colour, post spacing). No court lighting is proposed (voluntary condition 11)
7	Detention basin outlet structures, headwalls, retaining walls (if any)	—	Ponds 1 and 2, south-west side	—	Not visible from Arcade Rd; below the lane grade	C-3.0 — NOT YET ISSUED (grading, drainage and stormwater concept). Not item-(11) structures

Structures the applicant does NOT propose: no attached dwellings, no multifamily building, no commercial or office building, no gate house, no entry gate, no clubhouse pool building, no maintenance building, no freestanding utility building, no billboard, no changeable-copy sign, and **no wall signs of any kind** (§6.2).

2.4 What is complete, and what is left

Complete and to scale. All four exterior elevations of Plan A (**A-2.1**) and all four of Plan B (**A-2.2**) at 3/16" = 1'-0" on ARCH C 24 × 18 in, each with the eave, plate, ridge, finished-floor and finished-grade lines drawn, every opening placed from the same exterior_openings list that generates the floor plans, a keyed material legend, the height statement, the grade statement and the wall-sign statement printed on the sheet; the floor and roof plans at **A-1.1** and **A-1.2**; the colour and material board at **A-2.3**; the typical-lot sheets at **A-4.0** and **A-4.1**; and — new on 2026-09-03 — the **clubhouse, mail kiosk and monument entry sign on A-3.0**, which is the item that this section previously recorded as the package's blocking gap. It is closed. tools/elevations.py check_massing() and check_width() now pass for both plans.

What is left, and none of it is an item-(11) elevation:

1. **C-2.3 entry, frontage and amenity enlargement — NOT YET ISSUED.** Sheet A-3.0 already computes and draws the 390-ft departure sight triangle at the entrance and shows the sign clear of it by 20.1 ft, so the substantiation exists; but the civil enlargement that will be sealed by the PE has not been drawn, and the sign's plan footprint, the curb returns and the landscape strip belong on it.
2. **C-8.0 civil details — NOT YET ISSUED.** The pickleball fence section (height, mesh, colour, post spacing) is the only item-(11)-adjacent content on it.
3. **A-2.3 colour-key plan.** The distribution rule in §4.2 is deterministic but data/layout.json still carries no scheme field on the lot records, so the tinted key plan cannot yet be generated.
4. **Architect's seal.** Every sheet above is owner-prepared and illustrative (§8).

3. The architectural character of the community

The Cottages at Arcade Springs is a community of **41 one-story detached houses** on fee-simple 50'-0" × 100'-0" lots, all of them served by one private lane and all of them backing onto a 20'-0" undisturbed perimeter buffer. There is no second storey anywhere in the development, no attached unit, no dormer and no basement. The tallest thing proposed on the site is a roof ridge **18'-6" above finished grade** on Plan A and **19'-8"** on Plan B (§5) — lower than the two-storey houses that surround the property on three sides.

Massing. Each cottage reads as three simple gabled masses stepping back from the lane. Seen from the lane, left to right: a **two-car garage wing 21'-0" wide** under a front-facing **6:12** gable; then the **living wing 17'-0" wide** under a front-facing **8:12** gable; and behind both of them the **main body**, an 8:12 gable whose ridge runs left-to-right, parallel to the lane. The two front-facing gables and the long ridge behind them give the small house a hip-and-gable silhouette rather than the single blank ridge of a builder box, and each front-facing gable carries a single 2'-0" × 1'-4" louvered vent centred in the field with a cedar knee-brace bracket under each end of the living-wing rake.

The porch is the front of the house. The living-wing gable is **carried forward 6'-0" over the porch** — an integral gable porch, not an add-on. The porch is **17'-0" wide × 6'-0" deep = 102 SF**, with a flat beadboard ceiling at 9'-0", carried on three **8×8 nominal Western Red Cedar posts** standing on 20-in-square masonry piers 2'-0" tall with sloped cast-stone caps, with a painted header beam between them. It is a porch two people can sit on, which is the point of the product; a 6'-0" depth is also the minimum the applicant offers as voluntary condition 8.

The garage is subordinate, and can be shown to be. The garage door sits **26'-8" from the front lot line**, its face **5'-0" behind the front wall of the dwelling**, which appears consistent with Lilburn Zoning Ordinance 2023-603 Table 4.2 ("if they must be located in the front of the dwelling, garages must be recessed back at least five feet behind the front wall of the dwelling so that it is subordinate rather than dominant when viewed from the city street on which the dwelling fronts"). The recess alone would not have achieved that: at the 8:12 pitch first drawn, the 21'-0"-wide garage gable would have risen to **16'-6"** above the finished floor and stood **1'-4" above** the 15'-2" ridge of the house's own living-wing gable — dominant, exactly what Table 4.2 forbids in words. Dropping the garage roof to **6:12** brings its ridge to **14'-9"**, which is **0'-5" below** the living-wing gable. The garage is now subordinate in plan *and* in silhouette (§5.2).

Grade and entry. The finished floor sits **0'-8" above finished grade** at the front porch, not the 1'-6" a slab house usually carries. That is a deliberate accessibility decision: the 4'-0"-wide entry walk runs **15'-8"** from the lane to the porch slab, so a 0'-8" rise is a slope of **1:23.5** (4.3 %) — flatter than the 1:20 at which a walking surface becomes a ramp under ICC A117.1-2017 §403.3 (used voluntarily; the Georgia Accessibility Code, Ga. Comp. R. & Regs. 120-3-20, does not reach detached single-family dwellings) and short of a ramp under 2024 IRC (GA 2026) R311.8. At 0'-8" the porch is also far below the 30-in height at which 2024 IRC (GA 2026) R312.1.1 would require a guard, so the porch stays open to the street rather than being fenced by a code-driven railing. **Every cottage has a zero-step entry at the front porch and at the garage-to-house door**, and Plan B adds a third at the recessed rear porch.

Materials. Walls are fiber-cement — 7-1/4-in lap at a 6-in exposure, or vertical panel with 12-in-o.c. battens — over a **masonry water table 2'-6" (30 in) high**, adhered ledge stone or modular brick by scheme, capped with sloped cast stone. The porch piers are the same masonry as the water table, so the base of every house reads as one continuous plinth. Roofs are 30-year architectural asphalt shingles with a ridge vent, 5-in K-style aluminium gutters and round downspouts. Trim is 5/4 painted fiber-cement or cellular PVC: 4-in flat window casings, corner boards and a frieze. Windows are white vinyl single-hung units with a flat sill, 2-over-2 simulated divided lites on Scheme 1 and 1-over-1 with no grilles on Schemes 2 and 3. The garage door is a carriage-style insulated sectional, 16'-0" × 7'-0", with a single top row of lites. Full specifications are in docs/12-outline-specifications.md; the schedule keyed to it is §4 below.

Rhythm along the lane. The two plans alternate lot by lot (A-B-A-B) on both sides of the lane — **21 Plan A and 20 Plan B** (data/layout.json metrics.plan_mix) — and the three colour schemes rotate on a three-lot cycle over the top of that alternation. Because 2 and 3 have no common factor, the combined pattern repeats only every **six** lots and produces six visually distinct front elevations (§4.2). At a 50'-0" lot width that means a person walking the lane passes 300 ft of frontage before seeing the same house twice — the opposite of the repetition that the 2025 filing's neighbours objected to.

What the community is not. It is not a gated development (voluntary condition 6). It has no on-lane parking, no individual curbside mailboxes, no overhead utility poles or wires inside the site, and no cul-de-sac bulb — turnarounds are hammerheads, which Table 4.2 prefers over the cul-de-sac it says is "not permitted except in the most unusual circumstances."

4. Colour and material schedule

4.1 The reconciled schedule

Item (11) requires "the color and materials of all structures and roofing." The table below is the single reconciled schedule for the development. Each row names the CSI section in docs/12-outline-specifications.md that specifies the product, and gives, for each of the three approved schemes, the material, the colour and the **hex value actually drawn** on Sheets A-2.1, A-2.2 and A-2.3 by tools/elevations.py (SCHEMES). Hex values are illustrative placeholders for a manufacturer's standard colour, to be replaced by the manufacturer's name and number when the Owner and Architect select from dropdowns (docs/12 §09 91 13 1.04).

Element	CSI section (docs/12)	Scheme 1 — "Warm White"	Scheme 2 — "Sage"	Scheme 3 — "Clay"
Walls (field)	07 46 46 Fiber-Cement Siding	Fiber-cement vertical panel with 12-in-o.c. battens (board-and-batten), warm white — #F1EDE3	Fiber-cement lap, 7-1/4-in plank at 6-in exposure , sage green — #98A189	Fiber-cement lap, 6-in exposure , clay / beige — #D7C8AD
Trim, corner boards, frieze, fascia	06 20 00 Finish Carpentry; 07 46 46; 09 91 13	5/4 painted trim, warm white — #FFFFFF	5/4 painted trim, soft white — #F7F5EF	5/4 painted trim, cream — #F5EEDC
Water table (30 in) and porch piers	04 40 00 Stone Assemblies (schemes 1, 3); 04 20 00 Unit Masonry (scheme 2)	Adhered ledge stone , gray-tan "Appalachian" blend, dry-stack — #ABA495	Modular brick veneer , ASTM C216 Grade SW Type FBS, red-brown blend, running bond, tooled concave joints — #8C5A4A	Adhered ledge stone , buff / tan blend — #C4B594
Water-table and pier cap	04 40 00 §2.02 (ASTM C1364 cast stone, 2-1/2 in, sloped with drip); 04 20 00 §2.04 (rowlock alternate)	Cast stone, buff or gray	Brick rowlock or cast stone	Cast stone, buff
Roofing	07 31 00 Shingles — 30-year laminated architectural asphalt, Class A, ASTM D3462, algae-resistant, ridge vent	Charcoal — #4A4E52	Weathered wood — #6B6255	Driftwood / brown — #7A6E60
Front entry door	08 14 00 / 08 16 13 — insulated fiberglass, 3'-0" × 6'-8", glazed upper panel, ≤ 1/2-in bevelled sill	Deep green — #2E4A38	Oxblood (natural stain alternate) — #6E2B2B	Navy — #23364F
Garage door	08 36 13 Sectional Doors — carriage-style insulated steel, 16'-0" × 7'-0", R-12 min., top row of lites	Painted to match trim , warm white — #F4F1E9	Painted to match siding , sage — #98A189	Painted to match trim , cream — #F5EEDC
Windows (frame and sash)	08 53 13 Vinyl Windows — uPVC single-hung, low-E argon IGU, 4-in flat casing, sloped sill	White , 2-over-2 SDL — #FFFFFF	White , 1-over-1, no grilles — #FFFFFF	White , 1-over-1, no grilles — #FFFFFF
Porch posts and brackets	06 20 00 §2.02 — 8×8 nominal Western Red Cedar on standoff bases; 4×6 / 4×8 cedar brackets	Cedar, natural semi-transparent stain — #A98C5F	Cedar, natural stain — #A98C5F	Cedar, natural stain — #A98C5F
Porch ceiling	06 20 00 / 07 46 46 — 1/4-in fiber-cement beadboard, flat at 9'-0"	Pale sky #DCE5E8	Warm white	Cream
Gutters and downspouts	07 71 00 Roof Specialties — 5-in K-style aluminium, round downspouts	Match trim, warm white	Match trim, soft white	Match trim, cream

Distribution of materials, not just colour. Scheme 1 is the board-and-batten scheme and Schemes 2 and 3 are lap-siding schemes; Scheme 2 is the only brick scheme. The three schemes therefore differ in **texture and base material**, not merely in paint colour, which is what makes the six-lot rhythm read from the lane rather than from the paint chip.

Roofing across structures. The roofing product is identical on every dwelling, on the clubhouse and on the mail kiosk; only the colour changes with the scheme (note printed on Sheet A-2.3). The clubhouse, the mail kiosk and the monument sign **are drawn**

in **Scheme 1 "Warm White"** on Sheet A-3.0 (tools/amenity.py SCHEME, taken from tools/elevations.py SCHEMES['1']) with the Scheme 1 deep-charcoal door of docs/12 §09 91 13), so the amenity block reads as one building group at the entrance. The intent this section previously recorded as undrawn is now on the sheet.

4.2 How the three schemes are distributed

Voluntary condition 8 offers "three approved color schemes." Sheet A-2.3 carries the distribution rule: **no scheme repeats on adjacent lots, no scheme faces itself across the lane, and no scheme is used on more than 40 % of the 41 lots.** The rule is administered by the homeowners association under the recorded covenants and is proposed as a stated element of condition 8.

The rule had to be re-cut when the count fell to 41, and this is why. Lots are numbered 1–14 up the south-west side and 15–41 up the north-east side (data/layout.json). The single-sequence rule this section previously stated — $\text{scheme} = ((\text{lot number} - 1) \bmod 3) + 1$ across both sides, with one hand exception at old lot 16 — no longer works: the two sides are displaced by different amounts because the north-east side runs past three open-space breaks that the south-west side does not, so the across-lane pairs are (1,15) ... (10,24) and then **(11,29), (12,30), (13,31), (14,32)**. Under the single sequence the first ten pairs are clear and **all four of the last pairs collide**. Rotating the north-east side two steps removes every collision with no exception at all:

South-west side, lots 1–14: $\text{scheme} = ((n - 1) \bmod 3) + 1$ North-east side, lots 15–41: $\text{scheme} = ((n + 1) \bmod 3) + 1$ — the same three-lot cycle, offset by two

Checked against the lot polygons in data/layout.json:

- **No two abutting lots on the same side of the lane receive the same scheme** — consecutive numbers on a side always differ by one step of the cycle. Zero repeats on either side.

- **No cottage faces its own scheme across the lane.** Zero collisions across all fourteen facing pairs, and no exception is needed — an improvement on the 43-lot rule, which needed one.

- Resulting counts: **Scheme 1 on 14 lots, Scheme 2 on 14, Scheme 3 on 13.** The largest is 14 of 41 =

34.1 %, against the 40 % cap ($0.40 \times 41 = 16.4$, i.e. 16 lots). At 43 lots the same rule gave 14 / 15 / 14 and 34.9 %, so the margin against the cap has widened slightly.

- Crossed with the A-B-A-B plan alternation, the six plan-and-scheme combinations occur **6 to 8 times each**

(A-1 on 8 lots, A-2 on 7, A-3 on 6, B-1 on 6, B-2 on 7, B-3 on 7) and the streetscape pattern repeats only every six lots (300 ft of frontage).

- **Stated plainly, because a reviewer will notice it:** every across-lane pair is the *same* plan (the facing lot numbers differ by 14 or 18, both even, so the A-B alternation puts the same plan opposite itself). The colour offset is therefore the only thing distinguishing a facing pair, which is precisely what the two-step rotation is for.

MUST BUILD before filing: a colour-key plan — the master plan tinted by scheme, one colour per lot — belongs on Sheet A-2.3. data/layout.json carries no scheme field on the lot records today, so the key must be generated (the rule above is deterministic and can be written straight into tools/siteplan.py), not drawn by hand.

4.3 Reconciliation — where the specification and the drawn palette differ

docs/12-outline-specifications.md and the palette drawn by tools/elevations.py were written independently and do not agree everywhere. The table in §4.1 resolves each difference; the resolutions and the reasons are recorded here so the outline specification can be conformed rather than left in conflict. **The drawn palette governs**, because item (11) requires the *drawings* to carry the colour and because voluntary condition 8 binds the applicant to "elevations substantially as shown."

#	Element	docs/12 says	The drawings show	Resolution
1	Front door	§08 14 00 2.04 and §09 91 13 2.04: scheme 1 deep charcoal #3B3F44, scheme 2 near-black #2B2B2B, scheme 3 deep green #2F4F3E	Scheme 1 deep green #2E4A38, scheme 2 oxblood #6E2B2B, scheme 3 navy #23364F	Drawings govern. Conform docs/12 §08 14 00 2.04 and §09 91 13 2.04. Rendering R-01, already generated and in renderings/, carries the deep-green Scheme 1 door
2	Roof colour, schemes 2 and 3	§07 31 00 2.04: scheme 1 charcoal, scheme 2 weathered wood, scheme 3 driftwood/brown — agrees with the drawings	Same	No change to docs/12. But data/plans.json materials_by_scheme has schemes 2 and 3 reversed (it gives scheme 2 "charcoal" and scheme 3 "weathered wood"). Conform tools/floorplans.py materials_by_scheme
3	Window frame colour, scheme 3	§08 53 13 2.04 offers "bronze/black laminate (scheme 3)"	White on all three schemes	White on all three. One frame colour across the community simplifies the HOA's replacement stock; conform docs/12 §08 53 13 2.04

#	Element	docs/12 says	The drawings show	Resolution
4	Porch posts, scheme 2	\$06 20 00 2.04: cedar natural stain on schemes 1 and 3, "painted trim color on scheme 2 as selected"	Natural-stain cedar on all three	Natural stain on all three. The cedar post and bracket are the character element the three schemes share; conform docs/12 \$06 20 00 2.04
5	Field and trim hex values	\$09 91 13 2.04: scheme 1 field #F3EFE6 / trim #FAF8F3; scheme 2 field #8E9C86 / trim #F6F3EC; scheme 3 field #CDB89A / trim #F3EEE2	#F1EDE3 / #FFFFFF; #98A189 / #F7F5EF; #D7C8AD / #F5EEDC	Differences are within one drawdown step and are immaterial at hearing. Both files state the hex values are placeholders. Conform at colour selection, once, from the manufacturer's drawdowns
6	Batten spacing	\$07 46 46 2.02: battens at 12 in o.c., "16 in o.c. at the Architect's option"	12 in o.c.	12 in o.c. , as drawn and as the renderings were generated

5. Height

5.1 The numbers, and how each is derived

Every ridge height below is computed, not asserted. The formula used by both tools/floorplans.py and tools/elevations.py is:

ridge above finished floor = plate + heel + (span ÷ 2) × pitch, and ridge above finished grade = that + the finished-floor height above grade.

Inputs, from data/plans.json roof and tools/elevations.py:

Input	Value	Source
Wall plate	9'-0"	plans.json roof.plate_ft = 9.0; docs/12 \$06 10 00 1.01
Truss heel, as drawn	0'-6"	plans.json roof.heel_ft = 0.5
Eave height above finished floor	9'-6" (9'-0" + 0'-6")	derived
Finished floor above finished grade at the front porch	0'-8"	tools/elevations.py FF = 0.667
Main and living-wing pitch	8:12	plans.json roof.elements
Garage pitch	6:12	plans.json roof.elements (revised 2026-09-03 — \$5.2)
Voluntary maximum ridge	24'-0" above grade	data/voluntary-conditions.md condition 3
District maximum height	40'-0"	Lilburn Zoning Ordinance 2023-603 Table 4.1, R-2, "Maximum height (feet) — 40"

Plan A "The Springbrook"

Roof element	Span	Pitch	Rise	Ridge above finished floor	Ridge above finished grade
Main gable (rear block), ridge parallel to the lane	25'-0"	8:12	8'-4"	17'-10"	18'-6"
Front-wing (living) gable, front-facing, carried over the porch	17'-0"	8:12	5'-8"	15'-2"	15'-10"
Garage gable, front-facing	21'-0"	6:12	5'-3"	14'-9"	15'-5"
Governing ridge				17'-10"	18'-6"

Plan B "The Laurel"

Roof element	Span	Pitch	Rise	Ridge above finished floor	Ridge above finished grade
Main gable (rear block), ridge parallel to the lane	28'-6"	8:12	9'-6"	19'-0"	19'-8"
Front-wing (living) gable, front-facing, carried over the porch	17'-0"	8:12	5'-8"	15'-2"	15'-10"
Garage gable, front-facing	21'-0"	6:12	5'-3"	14'-9"	15'-5"
Governing ridge				19'-0"	19'-8"

The Sheet A-3.0 structures (tools/amenity.py, same formula)

Structure	Span	Pitch	Plate + heel	Ridge above finished floor	Ridge above finished grade
Clubhouse — main gable, ridge parallel to the lane	40'-0"	6:12	10'-0" + 0'-10" = 10'-10"	20'-10"	21'-6"

Structure	Span	Pitch	Plate + heel	Ridge above finished floor	Ridge above finished grade
Mail-kiosk shelter — hip	18'-0" (16'-0" + 2 × 1'-0" overhang)	4:12	—	—	11'-7"
Monument entry sign — masonry monument including cast-stone cap	—	—	—	—	3'-9"

Against the two limits. The tallest thing in the development is the **clubhouse ridge at 21'-6" above finished grade** (Sheet A-3.0) — the tallest *dwelling* ridge is Plan B's at **19'-8" above finished grade**. Both are under the 24'-0" voluntary maximum of condition 3 — the clubhouse by 2'-6", Plan B by 4'-4" — and both are under the 40'-0" maximum height of Ordinance 2023-603 Table 4.1 for the R-2 district by 18'-6" and 20'-4" respectively. All three appear consistent with both limits with substantial margin. **VERIFY:** Ordinance 2023-603 does not define, in the excerpts retrieved (data/ordinance-excerpts.md), how the 40'-0" is measured — from average finished grade, from the lowest adjacent grade, to the ridge or to the mean roof height. This document reports the ridge above finished floor **and** above finished grade so that the answer is available under any of those readings; the measurement datum should be confirmed at the pre-application conference.

5.2 What was revised on 2026-09-03 (Rev B), and why

Both plans were revised on 2026-09-03. The revision is recorded here because the elevations, the renderings and the outline specification all depend on it, and because several older numbers in the package (including FACTS.md §4) are now superseded.

- The front porch is now roofed by carrying the front-wing gable forward, not by a separate 4:12 shed.** The 2026-08-28 program assumed a shed roof over the porch. It cannot be built: a full-width shed cannot tie under a gable-end rake. At 4:12 across a 6'-0" porch the shed's high side lands **2'-0" above the plate**, and the 8:12 rake of the wing above it is *below* that height for the outer **3'-0" at each end** of the 17'-0" wall — the shed would have to cut through the gable it is leaning on. Carrying the gable forward 6'-0" solves it, and costs nothing: the porch keeps its full programmed **17'-0" × 6'-0" = 102 SF**, keeps a flat 9'-0" ceiling, and **adds no height** (the wing's own ridge, 15'-2", is unchanged). The gable end above the porch is carried on a header spanning between the outer posts. (tools/elevations.py, *FRONT PORCH note*.)
- Window sills were raised to 2'-8" (32 in) above finished floor.** The masonry water table is 2'-6" (30 in) high, with its cast-stone or rowlock cap set so that the **top of cap lands at 30 in** above finished floor (docs/12 §04 20 00 3.02). A sill at the earlier height fell below the cap, which would have driven the window sill, its casing and its sill flashing into the masonry. At **2'-8"** the sill clears the top of the cap by **0'-2"**, which is room for the Z-flashing and the 1/4-in clearance that fiber-cement requires above horizontal flashing (docs/12 §07 46 46 2.03). The raised sill also stays far below the **44-in maximum** sill height for an emergency escape and rescue opening under **2024 IRC (GA 2026) R310.2.2**: at 32 in there is 12 in of margin.
- The garage gable was lowered from 8:12 to 6:12.** At 8:12 the 21'-0"-wide garage gable reached **16'-6"** above the floor, standing **1'-4" above** the 15'-2" ridge of the house's living-wing gable — the garage would have been the dominant mass in the front elevation, which is precisely what Ordinance 2023-603 Table 4.2 tells a designer to avoid ("subordinate rather than dominant when viewed from the city street"). At **6:12** the garage ridge is **14'-9"**, **0'-5" below** the living-wing gable. The 5'-0" plan recess of Table 4.2 is now matched by a subordinate silhouette. Neither plan's governing ridge changes, because the main gable governs in both.
- Finished floor was set at 0'-8" above finished grade** instead of the 1'-6" a slab house usually carries, so that the 4'-0" entry walk can rise from the lane to a flush landing at **1:23.5** and remain a zero-step entry rather than becoming a ramp (§3, Grade and entry). The lower floor also keeps the porch below the 30-in guard threshold of 2024 IRC (GA 2026) R312.1.1.
- Plan B was re-proportioned from 40'-0" wide to 38'-0" wide.** A 50'-0" lot less two 5'-0" side yards (Table 4.1) leaves 40'-0" of buildable width — and the **roof** has to fit in it, not just the walls. At an 8-in side overhang a 40'-0" body measures **41'-4" roof to roof** and does not fit; Ordinance 2023-603 contains no provision permitting a projection into a required yard (**VERIFY** at pre-application). At 38'-0" the roof measures **39'-4"**, leaving **0'-4" of clearance to each side-yard line**. Depth was increased to recover floor area. Plan A was already 38'-0" wide.

Consequently superseded: the "Plan A 38'-0" × 38'-0", ~1,444 SF / Plan B 40'-0" × 40'-0", ~1,600 SF" and "8:12 main gable, 4:12 porch" of FACTS.md §4; the "40'-0" × 57'-6", 1,595 SF, ridge 19'-0", 114-SF porch, 96-SF rear porch" of audit-2026-09-03/docs-consistency.md §4.4; and the Plan B dimension block of renderings/PROMPTS.md / prompts.json (generated 13:47 on 2026-09-03, before the 14:16 regeneration of data/plans.json).

Current authoritative areas (data/plans.json areas, computed from the wall-face polygons):

	Plan A "The Springbrook"	Plan B "The Laurel"
Body (bounding box of conditioned + garage, outside face)	38'-0" × 51'-10"	38'-0" × 57'-6"
Roof to roof across the front	39'-4"	39'-4"

	Plan A "The Springbrook"	Plan B "The Laurel"
Conditioned area	1,406 SF	1,492 SF
Garage, gross / clear	458 SF / 20'-4" × 21'-2" = 430 SF	504 SF / 20'-4" × 23'-4" = 474 SF
Covered front porch	102 SF (17'-0" × 6'-0")	102 SF (17'-0" × 6'-0")
Rear	Uncovered patio 72 SF (12'-0" × 6'-0") , its edge 20'-6" from the rear lot line — 0'-6" outside the buffer easement	Covered rear porch 84 SF (14'-0" × 6'-0"), recessed under the main roof, its edge 20'-10" from the rear lot line
Total under roof	1,966 SF	2,182 SF
Building coverage on a 5,000-SF lot	39.3 %	43.6 %

Both plans exceed the R-2 minimum heated floor area for a cottage home of **1,000 SF**, and both exceed even the **1,400 SF** required of "all other dwelling types," under Ordinance 2023-603 Table 4.1 — which appears consistent with that table.

The plans did not change when the lot count did. The 2026-09-03 site-plan correction removed two lots (one inside a stream buffer once all three digitised reaches were screened, one to enlarge the basins for the real 7.54 disturbed acres); it did not alter either house. What it changed here is the *mix*: 21 Plan A and 20 Plan B instead of 22 and 21.

5.3 Geometry items — status at 2026-09-03

Eight inconsistencies between files were found on 2026-09-03. **Four are now closed.** None of them changes the answer to the 24'-0" or 40'-0" limits.

#	Item	Status
G-1	data/plans.json roof.elements[0].span_ft for Plan B still carries 29'-6" , the rear-block span of the superseded 58'-6" body, and the file therefore still prints max_ridge_ft = 19.33 ft (19'-4" above the floor, 20'-0" above grade). On the current 57'-6" body the rear block measures 28'-6" and the ridge is 19'-0" / 19'-8" , which is what tools/elevations.py computes and what Sheet A-2.2 draws	OPEN — a 0'-4" disagreement between data/plans.json and the issued sheet. Conform tools/floorplans.py PLAN_B['roof']['elements'] main-gable span 29.5 → 28.5 and regenerate. The sheet governs and this document uses 19'-0" / 19'-8" , which is also what voluntary condition 3 states. Note that docs/10 §1 item 14 has this backwards — it says the sheets draw 19'-4"; they do not
G-2	tools/elevations.py MASSING['B'] carried the 58'-6" rectangles and check_massing() failed	CLOSED — check_massing() and check_width() now pass for both plans; A-2.1 and A-2.2 were regenerated 2026-09-03
G-3	Truss heel drawn at 0'-6" ; docs/12 §06 10 00 2.03 specifies raised-heel trusses ≥ 12 in at exterior walls, to carry full-depth R-38 over the top plate	OPEN. Conforming raises every eave and ridge by 0'-6": Plan A to 18'-4" AFF / 19'-0" above grade, Plan B to 19'-6" AFF / 20'-2" . Still 3'-10" under the 24'-0" condition. Decide once — 12-in heel and redraw, or amend docs/12 §06 10 00 2.03 to a 6-in heel and re-check the ceiling R-value path
G-4	Plan A's rear patio edge sat 19'-6" from the rear lot line, 0'-6" inside the 20'-0" buffer easement	CLOSED — the patio was drawn at 12'-0" × 6'-0" = 72 SF , its edge 20'-6" from the rear lot line, 0'-6" clear of the easement (data/plans.json lot_siting.patio_edge_from_rear_line_ft = 20.5). It is 12 SF smaller than the 84-SF patio the program brief called for; that is the price of staying out of the easement
G-5	The 12-in rear eave on Plan B reaches 19'-10" from the rear lot line, 0'-2" inside the buffer easement; the 12-in porch-roof overhang on both plans reaches 14'-8" from the front lot line, 0'-4" inside the 15'-0" front setback	OPEN. Ordinance 2023-603 has no projections-into-yards provision either way. VERIFY at pre-application. If staff require the roof outside the line, hold Plan B's body at 57'-0" and use an 8-in rear eave
G-6	data/plans.json Plan A note 2 still reads "4:12 porch shed" and note 5 still describes NFPA 13D sprinklers as "mitigation for the single access road, IFC 2024 (GA) App. D107.1"; Plan B note 5 still reads "at 43 units"	OPEN. All three are superseded: the porch is under the wing gable (\$5.2); at 41 units Georgia's D107.1 trigger of <i>more than 120</i> dwelling units is not engaged, so sprinklers are a voluntary offer (voluntary condition 5; Ga. Comp. R. & Regs. 120-3-3-.04). Conform Plan A's notes to Plan B's, and conform Plan B's unit count, in tools/floorplans.py
G-7	tools/elevations.py CAP_RIDGE comment cites the 24'-0" ridge cap as "voluntary condition 4"	OPEN — it is condition 3 ; condition 4 is the buffer condition. Correct the comment
G-8	renderings/PROMPTS.md and prompts.json carried the superseded Plan B block	CLOSED — regenerated 2026-09-03 at 15:21. The locked design basis they now carry reads 38'-0" × 57'-6", 1,492 SF, ridge 19'-0" AFF / 19'-8" above grade, 41 lots , open space 141,089 SF = 33.8 %

A ninth item, found while conforming this document: drawings/amenity-sheet.svg (Sheet A-3.0) carries a clubhouse note reading "**the 43 dwellings** are sprinklered under NFPA 13D". Correct tools/amenity.py and regenerate — a superseded unit count printed on a filed sheet is exactly the kind of discrepancy the 2025 filing was tabled over.

6. Sign schedule

6.1 The one sign proposed — a ground-mounted monument entry sign

Item	Proposed	Source / basis
Number	One, for the whole development	Voluntary condition 14
Type	Ground-mounted monument sign — a low masonry wall with pin-mounted dimensional letters. Not a pole sign, not internally illuminated, not changeable-copy, not electronic	docs/12 §10 14 00 2.02–2.03
Location	Arcado Road frontage, in the 10'-0" landscape strip, at local coordinates u –9.7 to –1.7 / v –171.9 to –167.9 — about 18 ft north-east of the entrance drive centreline (v = –190), inside the front amenity tract and 19.0 ft from the Arcado Road right-of-way , outside it	data/layout.json amenity.entry_sign; tools/amenity.py; voluntary condition 14
Face area — as drawn on A-3.0	30.0 SF , against the voluntary limit of 32 SF. The 8'-0" × 4'-0" rectangle in data/layout.json is the bounding footprint of the monument in plan , not the face: the monument is an 8'-0"-long × 1'-4"-thick masonry wall with a 1'-4" wing / planter return at each end, 4'-0" deep overall. The 30.0 SF is the whole structure face (8'-0" × 3'-9"), the most conservative of the three measurement methods in §6.3; the cast-stone copy panel inside it is 6'-0" × 1'-9" = 10.5 SF . Both faces carry copy; the area above is one face	tools/amenity.py (SG_LEN, SG_H, SG_PANEL); Sheet A-3.0 notes
Overall height — as drawn on A-3.0	3'-9" above finished grade, cap included , against the voluntary limit of 6'-0" — 2'-3" of margin	tools/amenity.py SG_H; Sheet A-3.0
Structure	Reinforced CMU core on a 3,000-psi concrete footing 12 in below grade (frost), sized for wind. A Georgia PE designs the footing if the sign exceeds 6 ft or 32 SF — it is designed not to	docs/12 §10 14 00 1.05, 2.02
Materials and colours	Base and body : adhered ledge stone (04 40 00) in the Scheme 1 gray-tan blend, matching the cottage water tables — stone is the default at the entry; brick (04 20 00) if the Owner selects the Scheme 2 palette for the amenity block. Cap : cast stone, ASTM C1364, 2-1/2 in, sloped with a drip, buff or gray. Copy panel : cast stone or 15-lb HDU, painted to match the trim warm white. Letters : 1/2-in cast-aluminium or 1/4-in flat-cut aluminium, 8–10-in cap height , pin-mounted on 1/2-in standoffs, sat in black or dark bronze	docs/12 §10 14 00 2.02, 2.04; §4.1 above
Copy	"Cottages at Arcado Springs". No tenant panel, no leasing copy, no phone number, no changeable copy	docs/12 §10 14 00 1.01
Illumination	External only — two ground-mounted, fully shielded LED floods at ≤ 3000 K (2700 K preferred), aimed at the face only, ≤ 0.1 fc spill at the property line, on a photocell and timer. No internal illumination, no exposed lamps, no halo	docs/12 §10 14 00 2.03; voluntary condition 11 (full-cutoff, ≤ 3000 K)
Sight distance — computed and drawn	Located wholly outside the 390-ft departure sight triangle (35 mph, Gwinnett County UDO §900-40 Table 900.2, AASHTO Case B1), struck from a driver eye 14.5 ft behind the near edge of the travelled way on the drive centreline. The sign stands 20'-6" behind that point and its nearest corner is 20.1 ft clear of the nearer sight line; no part of the sign or its bed lies within the triangle . Bed planting held below 2'-6". A field sight-distance survey and the Gwinnett DOT driveway permit govern — VERIFY	Sheet A-3.0 (tools/amenity.py SIGHT_CLEAR, SIGN_BEHIND, SIGN_IN_TRI = False); docs/12 §10 14 00 1.03, 2.03; Checklist §6.j
Landscaping	Planted bed at the base with an irrigation stub, kept below 2'-6" within the sight triangle	docs/12 §10 14 00 2.05; §32 93 00
Maintenance	Owned and maintained by the mandatory homeowners association	Voluntary condition 10
Permitting	Permitted separately . The plan set carries the Checklist §4.q note verbatim: " <i>All signs shall be permitted separately.</i> " A sign easement may be required	Checklist §4.q; voluntary condition 14

Both cautions this section carried on 2026-09-03 are answered by the sheet as drawn:

- **The area is safe under every measurement method.** The sign was drawn to **30.0 SF measured the most conservative way** — the whole structure face, base and cap included — so it survives whichever of the three methods in §6.3 the ordinance turns out to use. The copy panel alone is 10.5 SF. It remains **VERIFY** until the governing article is identified, but the number no longer sits exactly on the limit.
- **The plan rectangle is understood.** The 8'-0" × 4'-0" rectangle in data/layout.json is the bounding footprint, and Sheet A-3.0's plan resolves it into a 1'-4"-thick wall with 1'-4" wing returns in a landscaped bed. That resolved footprint should be carried onto **C-2.3** when the entry enlargement is drawn.

6.2 No wall signs are proposed

No wall signs of any kind are proposed anywhere in the development — not on any of the 41 dwellings, not on the clubhouse, not on the mail-kiosk shelter, and not on any accessory structure, fence or wall. There is no wall sign to locate and no wall-sign area to state, which disposes of the fourth requirement of item (11).

This statement is printed as a general note **on each elevation sheet** (A-2.1, A-2.2 and A-3.0) and on the material and colour board (A-2.3), in this form:

WALL SIGNS: none are proposed on any dwelling, on the clubhouse or on any accessory structure. One ground-mounted monument entry sign not exceeding 32 SF in face area and 6'-0" in height is proposed at the Arcade Road entrance — see sheet A-3.0 for its elevation, dimensions, materials, colours and sight-triangle clearance.

It is also carried as **voluntary condition 8**, which now ends "...three approved color schemes; **no wall signs on any dwelling.**"

Two things that are not signs, and are proposed:

1. **Premises identification.** Address numerals on each dwelling, and a separate address-range sign at the entrance, 4-in minimum height in a contrasting colour, per the Gwinnett County Fire Marshal (docs/12 §10 14 00 2.05). The Site Development Plan Review Checklist §4.r notes that "one street name may serve to assign all house numbers." House numbers are premises identification required for emergency response, not advertising signage. **VERIFY** whether the ordinance's sign article excludes address numerals, as sign codes normally do.
2. **Traffic-control and regulatory markers** inside the private lane — stop sign at the Arcade Road entrance, "NO PARKING — FIRE LANE" signs to IFC 2024 (GA) Appendix D103.6 if the Fire Marshal requires them, and the accessible-space sign at the van-accessible stall in the amenity bay. These are regulatory devices, not on-premises advertising.

6.3 The ordinance question that must be asked at pre-application

data/ordinance-excerpts.md — the working extract of Lilburn Zoning Ordinance 2023-603 — covers §§308–319, §325, §§401–402, Tables 4.1 and 4.2, §602, §603, §§705–706, §734, Article 8 and §§1003–1005. **It contains no sign regulations.** The only occurrence of "sign" in a regulatory sense is §1003-6.2, the *public-hearing notice* sign the Director posts on the property 15 to 45 days before the hearing — which has nothing to do with a subdivision entrance sign. docs/12 §10 14 00 1.03 flags the same gap.

The applicant therefore cannot cite a section for the 32-SF area and 6'-0" height it has offered. Those figures are the applicant's own voluntary limits (condition 14), not a recitation of the code. This must be put to the Planning Director at the pre-application conference as a numbered question:

PRE-APPLICATION QUESTION (signs). Which article of Ordinance 2023-603 (or of the Lilburn Code of Ordinances) governs a residential subdivision entrance sign, and what does it set for (a) maximum sign area and **the method of measuring it** — copy panel, panel including border, or the entire monument face including base and cap; (b) maximum height above grade; (c) minimum setback from the right-of-way and from a side property line; (d) permitted illumination; (e) the number of entrance signs permitted per development; and (f) whether a sign easement is required (Checklist §4.q)? Are address numerals and traffic-control devices excluded from the definition of "sign"?

Until that is answered, every sign figure in this package is stated as a **voluntary limit the applicant offers**, not as a statement that a code requirement is met, and the sign is drawn to be defensible on either reading. **VERIFY.**

7. Rendering index

7.1 What the renderings are, and what they are not

Item (11) says "Visual imagery **may** be used." The renderings are the optional half of the requirement; the **scaled elevations are the submittal**, and the perspectives illustrate them.

Every image in renderings/ is an **illustrative AI-generated perspective prepared by the owner-applicant from the scaled elevations**. No image is a photograph, none depicts an existing building, none depicts a real neighbouring house or a recognisable person, and **none is offered as a representation of what will be built to the inch**. Where an image and a drawing disagree, **the scaled drawing governs** — that is stated on the sheet, in the caption under every image, and here.

The method is deliberate and is worth stating to the Commission: each perspective was generated against a **reference elevation exported from the same geometry file that generates the scaled drawings** (renderings/reference/ref-plan-*.png, written by tools/elevations.py), and every prompt states the real dimensions in architectural notation, so a returned image can be **measured against the plan set and rejected**. That is why voluntary condition 8 — "elevations substantially as shown" — can be offered at all: the images cannot show something the plan set does not permit without the discrepancy being visible.

7.2 Caption

Each image is captioned, burned into the sheet or set immediately beneath the image, in this form (plan name and scheme varying):

Illustrative concept rendering — AI-generated by the owner-applicant from the scaled elevations. Not a photograph; not an existing building. Plan A "The Springbrook", Scheme 1 "Warm White". Colours and materials per

docs/12-outline-specifications.md. **See Sheets A-2.1 / A-2.2 / A-3.0 for scaled elevations, which govern. DRAFT — to be superseded by sealed drawings by a Georgia-registered architect.**

(Sheet numbers in the caption are those of the settled register in tools/transmittal.py SHEETS: A-2.1 = Plan A elevations, A-2.2 = Plan B elevations, A-3.0 = clubhouse, mail kiosk and entry sign.)

7.3 The index

File names are those in renderings/prompts.json, generated by tools/prompts.py and re-generated on 2026-09-03 against the 41-lot layout. The eight images marked **core** are the item-(11) set — each side of each structure visible from a street, plus the sign, plus the colour and materials board. The remaining four answer specific objections raised against the 2025 filing on this property. **All twelve files are present in renderings/ as of 2026-09-03**, and each is listed below with the file name on disk.

Ref	File	What it shows	Item-(11) role	Aspect	Status (2026-09-03)
R-01	R-01_p lan-a- front- scheme 1.jpg	Plan A "The Springbrook" front elevation from the lane , Scheme 1 Warm White, on a 50'-0" × 100'-0" lot with the 20'-0" × 26'-8" driveway	core — the street-visible front of the more common dwelling; shows one story, the 5'-0" garage recess (Table 4.2), the colours and materials	3:2	Generated
R-02	R-02_p lan-b- front- scheme 2.jpg	Plan B "The Laurel" front elevation from the lane , Scheme 2 Sage lap over brick	core — the second dwelling type, the second scheme, the only brick base	3:2	Generated (2026-09-03 14:26, after G-2 and G-8 closed)
R-03	R-03_p lan-b- rear-g arden- scheme 3.jpg	Plan B rear / garden view , Scheme 3 Clay, the 14'-0" × 6'-0" covered rear porch recessed under the main roof, the rear yard running into the 20-ft undisturbed buffer	core — the rear elevation, which on this site faces an occupied R-1 back yard on every lot	3:2	Generated (2026-09-03 14:22, after G-2 and G-8 closed)
R-04	R-04_l ane-st reetsc ape-nw .jpg	Lane streetscape looking north-west: 22'-0" pavement, a 5'-0" sidewalk (on the north-east side for the lane's full length, and on the south-west side as well from u = 530 ft), the 50-ft lot rhythm with alternating Plan A / Plan B and rotating colour schemes	core — "proper perspective" for the street-visible fronts collectively; the answer to the "single-family character" objection	16:9	Generated — the prompt describes "the sidewalk on one side", which is true only of the front 530 ft; acceptable for a view down that reach, but say so if the image is presented as typical
R-05	R-05_h ammerh ead-po cket-g reen.j pg	A hammerhead (T) turnaround, two 20'-0" × 60'-0" legs, with the 50'-0" × 100'-0" pocket greens either side	supporting — shows no cul-de-sac bulb (Table 4.2) and the fire-apparatus turnaround	16:9	Generated
R-06	R-06_e ntranc e-arca do-mon ument. jpg	The Arcado Road entrance with the monument sign : 24'-0" drive, 25-ft north-east and 15-ft south-west curb returns, the sign, the 10'-0" landscape strip, the 5'-0" frontage sidewalk, the village green beyond	core — the sign is a "structure" and item (11) requires its location and size to be shown	16:9	Generated — re-check against Sheet A-3.0, which draws the sign at 8'-0" × 3'-9" (30.0 SF) and 3'-9" high , lower than the "not exceeding 6'-0"" the prompt described
R-07	R-07_c lubhou se-vil lage-g reen.j pg	The clubhouse and village green : the 60'-0" × 40'-0" one-story 2,400-SF clubhouse across the 14,354-SF green, with the 16'-0" × 10'-0" mail kiosk and its 4 short-term spaces in frame	core — clubhouse and kiosk are street-visible structures needing colour and material imagery	3:2	Generated — re-check against Sheet A-3.0, which fixes the clubhouse ridge at 21'-6" above grade, a 6:12 roof and a 400-SF covered porch
R-08	R-08_p ickleb all-co urts.j pg	The two 20'-0" × 44'-0" courts on 30'-0" × 60'-0" fenced pads, 10-ft black chain link, no light poles	supporting — the amenity at its real size, honouring voluntary condition 11 (no court lighting)	3:2	Generated
R-09	R-09_a erial- obliqu e-nw.j pg	Aerial oblique of the whole strip from over Arcado Rd along the N 28°43' W axis: one entrance in the south-west third, 41 one-story roofs in two rows (27 north-east / 14 south-west), one lane, 3 hammerheads, 3 pocket greens, 2 dry basins, the creek woods, the 20-ft treed buffer all round	core — "proper perspective" at site scale; shows the true 236–246 ft × ~1,750 ft proportion and that nothing touches the neighbours' lines	16:9	Generated (2026-09-03 15:24, against drawings/mcp-sheet.png)

Ref	File	What it shows	Item-(11) role	Aspect	Status (2026-09-03)
R-10	R-10_b uffer- from-n eighbo ur.jpg	Eye-level view from an adjoining back yard , across the 20'-0" undisturbed buffer, to the rear of a cottage beyond the rear lot line	supporting — the exhibit that answers the "looming"/character objection	3:2	Generated — recheck the stated rear-wall setback (Plan A 26'-6", Plan B 20'-10" from the rear lot line) and ridge height against §5.1
R-11	R-11_c reek-w oods-d ry-bas in.jpg	The preserved creek-woods tract at the stream head with its 50-ft undisturbed buffer, and Pond 2 as a grassed dry basin	supporting — answers the stormwater / erosion objection and the Jackson Creek 303(d) water-quality point	16:9	Generated
R-12	R-12_m ateria ls-col our-bo ard.jp g	Flat-lay materials and colour board : three columns (Schemes 1 / 2 / 3), each with siding, trim, shingle, masonry base, cast-stone cap, cedar post, door and window colour	core — item (11)'s literal requirement, "the colour and materials of all structures and roofing," in one filable exhibit; labels typeset in post, never asked of the image model	4:3	Generated — must be checked against the reconciled schedule in §4.1 (door colours, scheme 2/3 roof colours)

Index sheet — TO BUILD. A one-page contact index, R-00_index.jpg, listing the twelve images and their subjects, is to be placed at the front of the exhibit set, which is bound **behind** the scaled elevation sheets — so that a reader reaches the drawings first and the pictures second. **It has not been laid out; renderings/ holds R-01 through R-12 and no R-00.**

Reference elevations. renderings/reference/ holds the twelve title-block-free coloured elevations exported by tools/elevations.py (ref-plan-a-front-scheme1/2/3, ref-plan-a-rear/right/left-scheme2, and the same six for Plan B). These are working files for image generation and are **not** part of the submittal.

7.4 Acceptance rule

An image goes into the package only after it is checked against its fidelity list in renderings/PROMPTS.md. If it fails, it is **re-generated** — the prompt's dimensions are never edited to match the image. **All twelve images now exist**, and the three that were outstanding on 2026-09-03 (R-02, R-03 and R-09) were generated after G-2 and G-8 closed, so R-02 and R-03 illustrate the 57'-6" Plan B drawn on Sheet A-2.2, and R-09 shows 41 roofs. **Two acceptance checks remain open:** R-06 and R-07 were generated before Sheet A-3.0 fixed the sign at 3'-9" / 30.0 SF and the clubhouse at a 6:12 roof with a 400-SF covered porch, and must be re-checked against that sheet and re-generated if they fail.

8. Supersession, seals and status

These are DRAFT illustrative drawings prepared by the owner-applicant. They were produced with AI drafting tools from a dimensioned geometry model, they are drawn to scale, and they are internally consistent with the floor plans and the site plan in this package. **They are not sealed, and they are not construction documents.**

- **They are to be superseded, in their entirety, by drawings prepared and sealed by a Georgia-registered architect before any building permit is issued** for any dwelling, the clubhouse, the mail kiosk or the monument sign. docs/10-submittal-checklist-and-roadmap.md carries the engagement and the budget for that work.
- Every sheet carries, in its title block: *"ILLUSTRATIVE — NOT FOR CONSTRUCTION · DRAFT, to be superseded by sealed drawings by a Georgia-registered architect,"* the AI-analysis disclaimer, and the preparer's name.
- Structural elements shown or implied — trusses, headers, porch beams and posts, the sign footing, the masonry veneer support and ties — are **presumptive** until designed by a Georgia Professional Engineer. Truss design drawings sealed by a Georgia PE are required (docs/12 §06 10 00 1.04).
- The site geometry these elevations sit on — lot lines, setbacks, the buffer easement, the sight triangles — is **DRAFT** until the boundary and topographic survey is sealed by a Georgia Registered Land Surveyor and the civil sheets are sealed by a Georgia PE.
- Nothing in this document is an opinion that a code or ordinance requirement is met. Every regulatory statement is "appears consistent with," and the interpretations this package rests on — chiefly the §313(1) reading that lets the 20-ft buffer coincide with the rear yard inside the lot — are offered as interpretations to be confirmed by the Planning Director, not as settled law.
- What the applicant asks the Commission and Council to bind is **voluntary condition 8**: one story; the materials and the three schemes scheduled in §4; front-loaded garages recessed at least 5'-0"; covered front porches at least 6'-0" deep; zero-step entries; elevations substantially as shown; and **no wall signs on any dwelling**. Together with condition 3 (one story, ridge not exceeding 24'-0" above finished grade — the plans are drawn at 18'-6" and 19'-8", the clubhouse at 21'-6") and condition 14 (one monument sign not exceeding 32 SF and 6'-0" — drawn at 30.0 SF and 3'-9"), those conditions are the enforceable content of this document; the drawings and images illustrate them. **Condition 8's sheet citations were conformed to the**

register on 2026-09-03 (§1.1).

9. Open items — what must be closed before this document is filed

The 2026-09-03 site-plan correction, the issue of Sheet A-3.0 and the conforming of the voluntary conditions closed six of the twelve items this section carried. The eleven that remain:

#	Item	Owner	Section
1	Re-number two generated title blocks — amenity-sheet.svg prints "A-3" and cross-refers to "Sheet C-1"; existing-conditions.svg titles itself C-0 and cross-refers to "C-1, MASTER CONCEPT PLAN". Correct tools/amenity.py and tools/existing_conditions.py and regenerate	Drawings / tools	§1.1
2	Correct the "43 dwellings" note on Sheet A-3.0 (tools/amenity.py clubhouse sprinkler note) to 41	Drawings / tools	§5.3
3	Draw the entry enlargement C-2.3 and carry onto it the resolved sign footprint (a 1'-4"-thick wall with 1'-4" wing returns, not the 8'-0" × 4'-0" bounding rectangle) and the sight triangle A-3.0 already computes	Civil	§2.4, §6.1
4	Generate the colour-key plan on A-2.3 from the deterministic rule in §4.2 (SW lots $((n-1) \bmod 3)+1$, NE lots $((n+1) \bmod 3)+1$); add a scheme field to the lot records in data/layout.json	Site plan	§4.2
5	Conform docs/12 on the six reconciliation points — door colours, window frame colour, porch-post finish, batten spacing, hex values; and conform tools/floorplans.py materials_by_scheme, whose scheme 2 and 3 roof colours are reversed	Specifications	§4.3
6	Close geometry items G-1, G-3, G-5, G-6 and G-7 ; G-2, G-4 and G-8 are closed	Drawings / tools	§5.3
7	Re-check R-06 and R-07 against Sheet A-3.0 — both were generated before the sheet fixed the sign at 3'-9" / 30.0 SF and the clubhouse at 6:12 with a 400-SF covered porch — and lay out the R-00 contact index , which does not exist	Renderings	§7.3, §7.4
8	Ask the sign question at the pre-application conference and record the answer. The sign is now drawn at 30.0 SF measured the most conservative way, so it is defensible on any of the three methods, but the governing article is still unidentified	Owner	§6.3
9	Confirm the height-measurement datum for the 40'-0" maximum of Table 4.1	Owner / Planning Director	§5.1
10	Architect's review and seal of A-1.1, A-1.2, A-2.1, A-2.2, A-2.3, A-3.0, A-4.0 and A-4.1. The scope is now review and seal, not origination	Architect	§8
11	Draw the pickleball fence section on C-8.0 — the only item-(11)-adjacent content not yet on a sheet	Civil	§2.3, §2.4

Closed since the earlier 2026-09-03 revision of this document: the sheet-numbering conflict, now settled in tools/transmittal.py SHEETS and carried into voluntary condition 8 (§1.1); the clubhouse, mail kiosk and monument sign, all now drawn on A-3.0 (§2.3, §2.4); the Plan B massing failure G-2 and the Plan A rear-patio buffer encroachment G-4 (§5.3); the stale rendering prompts G-8 and the three outstanding perspectives R-02, R-03 and R-09 (§7.3).

Disclaimer: This is an AI-generated analysis for preliminary planning purposes. All findings must be verified by a licensed professional before use in design, permitting, or regulatory submissions.