Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 236 (2024) 386–393

Procedia Computer Science

www.elsevier.com/locate/procedia

International Symposium on Green Technologies and Applications (ISGTA'2023)

Harnessing Deep Learning Techniques for Enhanced Detection and Classification of Cracks in Pavement Imagery

Knnou omar[a], El Arbi ABDELLAOUI ALAOUI[b,*], Hanae Errousso[c,d], Youssef Filali[e], Chaimae Chekira[f], Said Agoujil[g]

[a]*MMIS Team, MAIS Laboratory, Faculty of Sciences and Technics, Errachidia, University of Moulay Ismail, Morocco*
[b]*IEVIA team, IMAGE laboratory, Department of Sciences, ENS, Moulay Ismail University of Meknes, Morocco*
[c]*EIGSI, La Rochelle-Casablanca, 17041-20410, France-Morocco*
[d]*National and high school of electricity and mechanic, HASSAN II University, 8118, Casablanca, Morocco*
[e]*Faculty of Sciences Dhar-Mahraz, 30000, Fez, Morocco*
[f]*Computer Science and Interdisciplinary Physics Laboratory (LIPI), National School of Applied Sciences, Sidi Mohamed Ben Abdellah University, B.P. 5206 Route Bensouda, 30003, Fez, Morocco.*
[g]*MMIS Team, MAIS Laboratory,École Nationale de Commerce et de Gestion, Moulay Ismail University of Meknes, El Hajeb, Morocco*

Abstract

With the increased demand for infrastructure maintenance and the evolving capabilities of deep learning, there is a pressing need to apply advanced techniques for efficient and accurate detection of structural anomalies. This paper delves into the application of Convolutional Neural Networks (CNNs) and transfer learning to address the problem of pavement crack classification using images. Three distinctive models were explored: a 4-layer CNN, a 2-layer CNN, and a VGG-based transfer learning model. Through comprehensive experimentation, we demonstrate the efficacy of these models in accurately classifying Pavement cracks from a curated dataset. Our findings indicate that while each model possesses its unique strengths, the VGG-based transfer learning model exhibits superior performance in terms of precision and recall. This research not only contributes to the growing body of knowledge in infrastructure maintenance using deep learning but also provides practical insights for professionals aiming to employ automated systems for Pavement inspection.

© 2024 The Authors. Published by ELSEVIER B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the International Symposium on Green Technologies and Applications

Keywords: Deep Learning, Convolutional Neural Networks (CNNs), Transfer Learning, VGG Model, Pavement Crack Detection, Image Classification, Infrastructure Maintenance;

In the realm of civil engineering, the integrity of infrastructure is paramount, with Pavement being a fundamental material in various structures. As these structures age, the timely and accurate detection of cracks becomes crucial for ensuring safety and longevity [1]. However, traditional methods of crack detection, primarily manual inspections, are not only labor-intensive but also prone to human error. This highlights an urgent need for more efficient, reliable, and

* Corresponding author. Tel.: +0-000-000-0000 ; fax: +0-000-000-0000.
E-mail address: e.abdellaouialaoui@umi.ac.ma

1877-0509 © 2024 The Authors. Published by ELSEVIER B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the International Symposium on Green Technologies and Applications
10.1016/j.procs.2024.05.045

automated methods for structural health monitoring. Currently, the assessment of Pavement integrity largely relies on visual inspections and basic imaging techniques [3]. These methods, while foundational, have significant limitations. They are not only time-consuming and costly but also lack consistency and precision, especially in complex or inaccessible environments. Additionally, the subjective nature of manual inspections can lead to variability in assessments, posing a challenge for consistent structural health monitoring [2].

With the advent of deep learning, a subset of machine learning, there has been a paradigm shift in how data-intensive problems are approached. Deep learning, particularly through Convolutional Neural Networks (CNNs), has shown remarkable success in image recognition and analysis. This technology holds great promise for revolutionizing Pavement crack detection, offering a way to automate and enhance accuracy in identifying structural anomalies [5, 7].

This study aims to harness the power of deep learning to tackle the challenge of crack detection in Pavement structures. We explore and compare the efficacy of three deep learning models: a 4-layer CNN, a 2-layer CNN, and a VGG-based transfer learning model. Each model represents a unique approach within the field of deep learning, varying in complexity and learning methodology. The objective is to assess which model most effectively classifies and detects cracks in Pavement , potentially setting a new standard in automated structural health monitoring.

Our research contributes to the burgeoning field of applying advanced computational techniques in civil engineering. By comparing different deep learning models, we aim to provide insights into the most effective methods for Pavement crack detection, addressing a critical gap in current structural assessment practices. The paper is structured to first present the methodology, followed by a detailed analysis of the results, a discussion of the implications, and concluding with recommendations for future research. This study not only enhances the understanding of deep learning applications in infrastructure maintenance but also paves the way for more advanced, efficient, and safer structural monitoring practices.

This paper is organized into several key sections to present a comprehensive view of our study. Following this introduction, Section 2, 'Methodology,' details the techniques and processes we employed, including the specifics of data collection, preprocessing, and the deep learning models used. In Section 3, 'Experiments and Results,' we delve into the experimental setup and present the findings from our comparative analysis of the different models. This section is crucial as it provides empirical evidence of the models' performance in crack detection and classification. Finally, Section 4, 'Conclusion,' synthesizes our key findings, discusses their implications in the field of structural health monitoring, and offers insights for future research directions. This structure is designed to systematically guide the reader through our research process, from methodology to conclusions, ensuring a clear and cohesive understanding of our study.

1. Methodology

The methodology section outlines the systematic approach undertaken in this research, delineating both the dataset used and the deep learning models developed. The flowchart presented in the Figure 1 provides a visual representation of the research pipeline, from data acquisition to model evaluation. The ensuing subsections delve into a detailed description of the dataset, the architectures of the employed deep learning models [4], and the metrics used for evaluation.

1.1. Dataset Description

Our research employed a dataset specifically curated for the study of Pavement cracks. The dataset comprises two distinct classes of images:

- **Positive Class:** Images showcasing Pavement walls with visible cracks.
- **Negative Class**: Images of intact Pavement walls with no discernible cracks.

These classes are conveniently separated into two folders labeled "Positive" and "Negative" for ease of access and processing. In total, the dataset boasts 1024 images.




Fig. 1. Flowchart for this study

1.2. Model Development

For the Pavement crack detection task, we developed and evaluated three deep learning models. The primary motivation behind choosing diverse architectures was to assess the relative strengths and weaknesses of varying complexities and methodologies.

1.2.1. Model 1: CNN with 4 convolution layers

The CNN model comprises four primary convolutional layers, followed by max-pooling layers to reduce spatial dimensions and increase the receptive field. The convolutional layers are designed to capture hierarchical patterns in the data.

- **Layer 1:** Convolutional layer with 32 filters of size 3×3, followed by a 2×2 max-pooling layer.
- **Layer 2:** Convolutional layer with 64 filters of size 3×3, followed by a 2×2 max-pooling layer.
- **Layer 3:** Convolutional layer with 128 filters of size 3×3, followed by a 2×2 max-pooling layer.
- **Layer 4:** Convolutional layer with 256 filters of size 3×3, followed by a 2×2 max-pooling layer.

Each convolutional layer utilizes the ReLU (Rectified Linear Unit) activation function for introducing non-linearity. Following these layers, a flattening step and subsequent dense layers lead to the final classification output.


The convolution operation, pivotal to this architecture, for an input matrix I and a filter K is mathematically expressed as:

$$(I * K)(x, y) = \sum_{i=-\infty}^{\infty} \sum_{j=-\infty}^{\infty} I(i, j) \cdot K(x - i, y - j)$$

The ReLU activation function, utilized after each convolutional operation, is given by:

$$f(x) = \max(0, x)$$

Max-pooling operates on each feature map separately, down-sampling by considering the maximum value in each window for every shift.



1.3. Model 2- CNN with 2 Convolution layers

A simpler CNN with two layers, possibly faster but potentially less accurate than a more complex model.

1.3.1. First Convolutional Layer

Given an input image of size $W_1 \times H_1$, a filter size F_1, stride S_1, and padding P_1, the output dimensions for the convolutional operation are:

$$W_{out1} = \frac{W_1 - F_1 + 2P_1}{S_1} + 1$$
$$H_{out1} = \frac{H_1 - F_1 + 2P_1}{S_1} + 1$$

1.3.2. First Pooling Layer

Assuming a 2×2 pooling operation with a stride of 2, the output dimensions become:

$$W_{pool1} = \frac{W_{out1}}{2}$$
$$H_{pool1} = \frac{H_{out1}}{2}$$

1.3.3. Second Convolutional Layer

With the filter size F_2, stride S_2, and padding P_2, the output dimensions for the second convolutional operation are:

$$W_{out2} = \frac{W_{pool1} - F_2 + 2P_2}{S_2} + 1$$
$$H_{out2} = \frac{H_{pool1} - F_2 + 2P_2}{S_2} + 1$$

1.3.4. Second Pooling Layer

Again, assuming a 2×2 pooling operation with a stride of 2:

$$W_{pool2} = \frac{W_{out2}}{2}$$
$$H_{pool2} = \frac{H_{out2}}{2}$$

1.3.5. Flattening

The pooled feature maps are flattened into a single vector of length:

$$D_{flat} = W_{pool2} \times H_{pool2} \times C$$

Where C represents the number of channels or feature maps.

1.3.6. Activation Functions

ReLU is a common activation function applied after convolutional operations:

$$f(x) = \max(0, x)$$

For the output layer, in a binary classification problem:

$$f_j(z) = \frac{e^{z_j}}{\sum_{k=1}^{K} e^{z_k}}$$


Where j represents the jth node in the output layer, z is the input to the node, and K is the total number of classes.

1.3.7. Training

For training using the cross-entropy loss in a binary classification:

$$L = -\sum_{i=1}^{N} \sum_{j=1}^{K} y_{ij} \log(\hat{y}_{ij})$$

Where N is the number of training samples, K is the number of classes, y is the true label, and $\hat{y}$ is the predicted



label.

1.4. Model 3: VGG Transfer Learning

This model employs a pre-trained network (VGG) using transfer learning [8, 6], a technique that leverages knowledge gained from one task to improve performance in a similar one.

1.4.1. Convolutional Layer Operation:

Given an input tensor I of shape $H \times W \times C$ and a convolutional filter F of shape $k \times k \times C$, the convolution operation is:

$$O_{(i,j)} = \sum_{m=0}^{k-1} \sum_{n=0}^{k-1} \sum_{c=0}^{C-1} I_{(i+m,j+n,c)} \times F_{(m,n,c)} \tag{1}$$

Max-Pooling Layer Operation:

Given an input tensor I and pooling size $p \times p$, the max-pooling operation for location (i, j) is:

$$O_{(i,j)} = \max_{0 \le m,n < p} I_{(pi+m,pj+n)} \tag{2}$$

1.4.2. Flatten Operation:

This operation reshapes the tensor into a 1-dimensional tensor. If I has the shape $H \times W \times C$, then the flattened vector O will have the shape $H \times W \times C$.

1.4.3. Dense (Fully Connected) Layer Operation:

Given an input vector I of size N and a weight matrix W of size $M \times N$, the output O of size M is:

$$O = \sigma(W \times I + b) \tag{3}$$

Where σ is the activation function (ReLU for the dense layer and Sigmoid for the last layer).

1.4.4. Dropout Operation:

During training, dropout sets a random fraction α (e.g., 0.45) of the input tensor to zero. During inference, this operation is bypassed or the output is scaled.

2. Experiments and results

2.1. Metrics of Performance

1. **Accuracy**
   Accuracy is a general measure of how often the model makes the correct prediction. It's the ratio of the number of correct predictions to the total number of predictions.

$$\text{Accuracy} = \frac{\text{Number of Correct Predictions}}{\text{Total Number of Predictions}} = \frac{TP + TN}{TP + TN + FP + FN} \tag{4}$$

2. **Precision (Positive Predictive Value)**
   Precision is the ratio of correctly predicted positive observations to the total predicted positives. It gives you an idea of when the model predicts yes, how often it is correct.

$$\text{Precision} = \frac{TP}{TP + FP} \tag{5}$$

3. **Recall (Sensitivity, True Positive Rate)**
   Recall is the ratio of correctly predicted positive observations to all the observations in the actual class. It gives you an idea about when it's actually yes, how often does the model predict yes.

$$\text{Recall} = \frac{TP}{TP + FN} \tag{6}$$

4. **F1 Score (F1)**
   The F1 Score is the weighted average of Precision and Recall. Therefore, this score takes both false positives and false negatives into account. It is a good way to show that a classifier has a good value for both precision and recall.

$$\text{F1 Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} \tag{7}$$

2.2. Results

In the comparative analysis of the three models used for detecting and classifying Pavement cracks, Model 3 emerges as the clear leader. It boasts the highest accuracy at 85.0%, indicating its superior ability to correctly classify the largest proportion of total cases. Additionally, this model also excels in precision and recall, both at 85.0% and 86.0% respectively. The high precision rate signifies its effectiveness in minimizing false positives, while the exceptional recall rate indicates its proficiency in correctly identifying almost all actual positives. The F1-score of 85.0% further reinforces its balanced performance, demonstrating an optimal blend of precision and recall.

On the other hand, Models 1 and 2 exhibit comparatively lower efficacy. Model 1, with an accuracy of 74.0%, precision of 77.0%, and recall of 70.0%, performs moderately well but falls short of the standards set by Model 3. Its

Table 1. Comparative Analysis of Models

Metric	Model 1	Model 2	Model 3
Accuracy	74.0%	65.0%	85.0%
Precision	77.0%	67.0%	85.0%
Recall	70.0%	59.0%	86.0%
F1-Score	71.0%	57.0%	85.0%

F1-score of 71.0% reflects a decent but not outstanding balance between precision and recall. Model 2 lags behind, with the lowest accuracy (65.0%), precision (67.0%), and recall (59.0%) of the three. This model's F1-score of 57.0% suggests a significant gap in its ability to balance precision with recall, marking it as the least effective of the trio. The superior performance of Model 3 (VGG-based transfer learning model) exhibits superior performance, highlighting its potential for practical application in infrastructure maintenance.

3. Conclusion

Our study demonstrates the effectiveness of deep learning techniques in detecting and classifying Pavement cracks. Among the three models tested, the VGG-based transfer learning model notably outperformed the others in accuracy, precision, recall, and F1-score. This highlights the potential of advanced deep learning methods in enhancing infrastructure maintenance, particularly in early crack detection which is crucial for structural safety and longevity. The findings suggest that while simpler models are faster, they lack the accuracy and precision of more complex models like the VGG-based transfer learning approach. This research underscores the importance of selecting appropriate deep learning strategies for specific applications in structural health monitoring.

Looking forward, we recommend further exploration into integrating these models into real-time monitoring systems and expanding the dataset diversity for broader applicability. This study paves the way for more technologically advanced, efficient, and cost-effective methods in infrastructure maintenance, marking a significant step forward in the field of structural health monitoring.

References

[1] Sutanu Bhowmick, Satish Nagarajaiah, and Ashok Veeraraghavan. Vision and deep learning-based algorithms to detect and quantify cracks on concrete surfaces from uav videos. *Sensors*, 20(21):6299, 2020.

[2] Xiaolong Chen, Jian Li, Shuowen Huang, Hao Cui, Peirong Liu, and Quan Sun. An automatic concrete crack-detection method fusing point clouds and images based on improved otsu's algorithm. *Sensors*, 21(5):1581, 2021.

[3] Sattar Dorafshan, Robert J Thomas, and Marc Maguire. Comparison of deep convolutional neural networks and edge detectors for image-based crack detection in concrete. *Construction and Building Materials*, 186:1031–1045, 2018.

[4] Cao Vu Dung et al. Autonomous concrete crack detection using deep fully convolutional neural network. *Automation in Construction*, 99:52–58, 2019.

[5] Kasthurirangan Gopalakrishnan. Deep learning in data-driven pavement image analysis and automated distress detection: A review. *Data*, 3(3):28, 2018.

[6] Taranjit Kaur and Tapan Kumar Gandhi. Automated brain image classification based on vgg-16 and transfer learning. In *2019 International Conference on Information Technology (ICIT)*, pages 94–98. IEEE, 2019.

[7] Hoang Nhat-Duc, Quoc-Lam Nguyen, and Van-Duc Tran. Automatic recognition of asphalt pavement cracks using metaheuristic optimized edge detection algorithms and convolution neural network. *Automation in Construction*, 94:203–213, 2018.

[8] Srikanth Tammina. Transfer learning using vgg-16 with deep convolutional neural network for classifying images. *International Journal of Scientific and Research Publications (IJSRP)*, 9(10):143–150, 2019.