












## SYMBOLS

The symbols used throughout this manual show specific service procedures. If supplementary information is required pertaining to these symbols, it would be explained specifically in the text without the use of the symbols.

	Replace the part(s) with new one(s) before assembly.
	Use the recommend engine oil, unless otherwise specified.
	Use molybdenum oil solution (mixture of the engine oil and molybdenum grease in a ratio of 1:1).
	Use multi-purpose grease (lithium based multi-purpose grease NLGI #2 or equivalent).
	Use molybdenum disulfide grease (containing more than 3% molybdenum disulfide, NLGI #2 or equivalent). <b>Example:</b> <ul style="list-style-type: none"> <li>• Molykote® BR-2 plus manufactured by Dow Corning U.S.A.</li> </ul>
	Use molybdenum disulfide paste (containing more than 40% molybdenum disulfide, NLGI #2 or equivalent). <b>Example:</b> <ul style="list-style-type: none"> <li>• Molykote® G-n Paste manufactured by Dow Corning U.S.A.</li> <li>• Pro Honda M-77 Assembly Paste (Moly) (U.S.A. only)</li> <li>• Rocol ASP manufactured by Rocol Limited, U.K.</li> <li>• Moly Paste 500 manufactured by Sumico Lubricant, Japan</li> </ul>
	Use silicone grease.
	Apply a locking agent. Use a medium strength locking agent unless otherwise specified.
	Apply sealant.
	Use DOT 4 brake fluid. Use the recommended brake fluid unless otherwise specified.

	
	Use fork or suspension fluid.