

JavaScript For Cats

An introduction for new programmers

So easy your human companion could do it too!

JavaScript is a programming language or, in other words, a means by which a computer is instructed to do things. Just the same as one controls humans with hisses and meows, one controls computers with statements written in a programming language. All web browsers understand JavaScript and you can take advantage of that to make web pages do crazy things!



JavaScript started as a programming language to make internet pages more interactive. Nowadays JavaScript runs in more places than just in web browsers -- it runs on web servers, phones and **even robots!** This page will teach you some JavaScript basics so that you can get up and running in no time*!


** actual time: more than none. probably an hour or two. Also since you are a cat you are less likely to run and more likely to lay around in the sun*

Table of contents

- The console
- Strings
- Values and variables
- Using functions
- Built in JS functions
- Download new JS functions
- Writing new functions
- Loops
- Arrays
- Recommended reading

Don't be a scaredy cat

You will always land on your feet -- even when programming! Unlike **pawing over a glass of water** on your laptop, *nothing* in these tutorials will damage your computer in any way, even if you mistype a command or click the wrong button. Like cats, computer programmers make mistakes all the time: misspelling things, forgetting quotes or brackets, and being forgetful of how basic functions (and yarn) work. Programmers care more about making it work *eventually* rather than trying to make it work the very first time. The best way to learn is by making mistakes!




So don't be a scaredy cat! The absolute worst thing that will happen is that you might have to refresh this page in your web browser if you get stuck. Don't worry though, this will happen very rarely — and we're talkin' 13-toed cat rare.

The basics

There is JavaScript running on this page right now! Let's play around with it a little. For the sake of simplicity I'll assume you are using Google Chrome to read this page (if you aren't it's probably easier on both of us if you follow along with Chrome).

First, right click anywhere on the screen and hit **Inspect Element**, then click on the **Console** tab. You should see a thingy that looks like this:



This is a console, otherwise known as a "command line" or "terminal". Basically it's a way to type one thing at a time into a computer and immediately get the computer's answer back. They are super useful as a learning tool (I still use the console nearly every day I'm coding).


The console does some pretty cool stuff. Here I have started to type something and the console is helping me out by giving me a list of all the possible things I could continue to type! Another thing you could do is type `1 + 1` into the console and then hit the `Enter` key and watch what happens.

Using the console is a very important part of learning JavaScript. If you don't know if something

works or what the command is for something, go to the console and figure it out! Here's an example:

Strings

Since I am a cat I want to replace every instance of the word `dog` on the internet with `those blasted dogs`. First go into your console and type in a few sentences that contain the word `dog` at least once. In JavaScript a bunch of letters, numbers, words or anything else is known as a **String** (as in a *string* of characters). Strings have to begin AND end with a quotation mark. Single `'` or double `"` is fine, just make sure you use the same at the beginning as you do at the end.



See the nasty error message? Don't worry - you didn't break any laws. `SyntaxError ILLEGAL` is just the way it sounds when robots tell you that your program has a problem. The first two sentences had matching quotation marks at the beginning and end, but when I mixed single and double quotation marks it freaked out on me.

Ok, to fix up one of these sentences (by replacing `dog` with our enhanced version) we have to first save the original sentence so that we can call it up later when we do our replacing magic. Notice how the string gets repeated in red when we type it into the console? This is because we haven't told it to save the sentence anywhere so it just gives it right back (or it gives us an Error back if we messed something up).

Values and variables

Values are the simplest components in JavaScript. `1` is a value, `true` is a value, `"hello"` is a value, `function() {}` is a value, the list goes on! There are a handful of different **types** of values in JavaScript but we don't need to go over them all right away -- you will learn them naturally the more you code!

To store values we use things called **variables**. The word 'variable' means 'can change' and is used because variables can store many different types of values and can change their value many times. They are pretty much like mailboxes. We put something in a variable, like our sentence, and then give the variable an address that we can use to look up the sentence later. In real life mailboxes have to have PO Box numbers but in JavaScript you usually just use lowercase letters or numbers without any spaces.

The screenshot shows the Google Chrome Developer Tools console. At the top, there are tabs for Elements, Resources, Network, Sources, Timeline, and Profiles. Below the tabs, the search bar contains "Search Console". The main area of the console shows the following JavaScript code:

```
> var dogSentence = "dogs are the bane of my existence"
undefined
> dogSentence
"dogs are the bane of my existence"
> |
```

At the bottom of the console, there are buttons for Back, Forward, Stop, Refresh, and a dropdown menu labeled "<top frame>". To the right of the dropdown are buttons for All, Errors, Warnings, and Logs, with "Logs" being the active tab. On the far right, there is a gear icon.

`var` is shorthand for variable and the `=` means *store the thing on the right hand side in the thing on the left hand side*. Also as you can see, now that we are storing our sentence in a variable the console doesn't just return our sentence right away, but instead gives us `undefined` which means *there was nothing to return*.

If you simply type a variable name into the console it will print out the value stored in that variable. A note about variables is that by default they go away when you switch to a different page. If I were to hit the Refresh button in Chrome, for example, my `dogSentence` variable would get wiped and it would be like it never existed. But don't worry about this too much for now -- you can just hit the up or down arrows on your keyboard while in the console to go through everything you've entered in recently.

Functions

Now that we have our sentence stored in a variable lets give that variable to something that will replace words! We call things that perform actions like this **functions** because, well, they serve a specific *function* (AKA purpose or action) for us. Calling them "actions" sounded weird I guess so they went with the word "function" instead.

JavaScript has a function called `replace` that does exactly what we want! Functions take in any number of values (zero, one or many) and return either nothing (`undefined`) or exactly one value (functions can't return two or more values at a time -- only a single value). The `replace` function is available to use on any strings and takes in two values: the characters to take out and the characters to swap in. It gets confusing to describe these things so here is a visual example:

The screenshot shows the Chrome Developer Tools interface with the 'Console' tab selected. The console window displays the following JavaScript code and its execution:

```
> var dogSentence = 'dogs are the bane of my existence'
undefined
> dogSentence.replace('dogs', 'those blasted dogs')
"those blasted dogs are the bane of my existence"
> dogSentence
"dogs are the bane of my existence"
>
```

The 'Elements', 'Resources', 'Network', 'Sources', 'Timeline', 'Profiles', and 'Audits' tabs are visible at the top. Below the console, there are buttons for 'All', 'Errors', 'Warnings', and 'Logs'. A search bar labeled 'Search Console' is also present.


Notice how the value of `dogSentence` is the same even after we run `replace` on it? This is because `replace` (and most JavaScript functions for that matter) takes the variable or value that we give it and returns a **new value** instead of modifying the thing we passed in. Since we didn't store the new variable (there is no `=` on the left side of the `replace` function) it just printed out the return value in our console.

The "standard library"


You might be wondering what other functions are available in JavaScript. The answer: A TON. There are lots **built in, standard libraries** that you can learn about at MDN (A site run by Mozilla that has lotsa nifty information about web technologies). For example [here is the MDN page on JavaScript's Math object](#).

Third-party JavaScript

There is also a lot of JavaScript code available that is **not built in**. JavaScript from third parties is usually referred to as a "library" or "plugin". One of my favorites is called **Underscore.js**. Let's go and grab it and load it into our page! First go to the Underscore site, <http://underscorejs.org/>, click on the download link (I usually use development versions because they are easier to read but both will give you the same basic functionality), and then copy all the code onto your clipboard (you can use Select All from the Edit menu to select everything).



Then paste it into your console and hit enter. Now your browser has a new variable in it: . Underscore gives you a ton of helpful functions to play with. We'll learn more about how to use them later.




Making new functions

You aren't limited to using other peoples functions -- you can also write them yourself. It's pretty easy! Lets make a function called `makeMoreExciting` that adds a bunch of exclamation points to the end of a string.

```
function makeMoreExciting(string) {
    return string + '!!!!'
}
```


In my head I read it out loud like this: "theres a function called 'make more exciting' that takes in a string and returns a new copy of that string that has a bunch of exclamation points at the end". Here is how we would write this in the console manually if we weren't using a function:



The expression `string + '!!!!'` returns a new string and our variable called `string` stays the same as before (since we never updated it to anything else with `=`).

Lets use our function instead of doing it manually. First, paste the function into the console and then

call the function by passing in a string:




The screenshot shows the Chrome Developer Tools console window. At the top, there are tabs for Elements, Resources, Network, Sources, Timeline, Profiles, and Audits. Below the tabs, the console output is displayed:

```
> function makeMoreExciting(string) {
    return string + '!!!!'
}
undefined
> makeMoreExciting('lounging')
"lounging!!!!"
>
```

At the bottom of the console window, there are buttons for Search, Refresh, and a dropdown menu labeled <top frame>. To the right of the dropdown are buttons for All, Errors, Warnings, and Logs. On the far right, there is a gear icon.

You could also call the same function by passing in a variable that points to a string (in the above example we just typed the string straight in there as a value instead of saving it to a variable first):



The screenshot shows the Chrome Developer Tools console window. The interface is identical to the previous one, with tabs for Elements, Resources, Network, Sources, Timeline, Profiles, and Audits. The console output shows:

```
> var sentence = "time for a nap"
undefined
> makeMoreExciting(sentence)
"time for a nap!!!!"
> sentence
"time for a nap"
>
```


The bottom of the window includes buttons for Search, Refresh, and a dropdown for <top frame>. To the right are buttons for All, Errors, Warnings, and Logs, and a gear icon.

The line `makeMoreExciting(sentence)` is equivalent to saying `sentence + '!!!!'`. What if we wanted to **modify in-place** (aka update) the value of sentence? Simply save the return value of the function back into our `sentence` variable:

```
var sentence = "time for a nap"
sentence = makeMoreExciting(sentence)
```

Now `sentence` will have the exclamation marks in it! Note that you only have to use `var` when you are **initializing** a variable -- the first time you ever use it. After that you shouldn't use `var` unless you want to re-initialize (reset/clear/empty) the variable.

What would happen if we took out the `return` statement in our function?




Why is `sentence` empty? Because functions return `undefined` by default! You can choose to return a value by `return`ing something. Functions should take in a value and, if they change the value or create a new value that is supposed to be used later, `return` a value (fun fact: a fancy term for this style is *functional programming*). Here is another function that doesn't return anything but instead uses a different method to show us the output:

```
function yellIt(string) {
  string = string.toUpperCase()
  string = makeMoreExciting(string)
  console.log(string)
}
```

This function, `yellIt`, uses our previous function `makeMoreExciting` as well as the built-in String method `toUpperCase`. Methods are just a name for a function when it belongs to something -- in this case `toUpperCase` is a function that belongs to `String` so we can refer to it as either a method *or* a function. `makeMoreExciting` on the other hand doesn't belong to anyone so it would be technically incorrect to refer to it as a method (confusing, I know).

The last line of the function is another built-in that simply takes in any values that you give it and prints them out into the console.



So is there something wrong with the above `yellIt` function? It depends! Here are the two major types of functions:

- functions that modify or create values and return them
- functions take in values and perform some action that cannot be returned

`console.log` is an example of the second type of function: it prints things out to your console -- an action that you can see with your eyes but that cannot be represented as a JavaScript value. My own rule of thumb is to try to keep the two types of functions separate from each other, so here's how I would rewrite the `yellIt` function:

```
function yellIt(string) {  
  string = string.toUpperCase()  
  return makeMoreExciting(string)  
}  
  
console.log(yellIt("i fear no human"))
```

This way `yellIt` becomes more **generic**, meaning it only does one or two simple little things and doesn't know anything about printing itself to a console -- that part can always be programmed later, outside the function definition.

Loops

Now that we have some basic skills under our belt (*Author note: do cats even wear belts?*) we can start being lazy. What?! Yes, that's right: programming is about being lazy. Larry Wall, inventor of the Perl programming language, called laziness the **most important virtue** of a good programmer. If computers didn't exist you would have to do all sorts of tedious tasks by hand, but if you learn to program you can lay in the sun all day while a computer somewhere runs your programs for you. It is a glorious lifestyle filled with relaxation!


Loops are one of the most important ways to harness the power of a computer. Remember `Underscore.js` from earlier? Make sure you have it loaded in the page (remember: you can just hit the up arrow on your keyboard a few times and then hit `Enter` to load it in again if you need to) and try copy/pasting this into your console:

```
function logANumber(someNumber) {  
  console.log(someNumber)
```

```
}
```

```
_times(10, logANumber)
```

This code uses the **times** method of Underscore which takes in 1 number and 1 function and then starts from 0 and for 10 steps counts up by 1, calling the function with the number each step of the way.



If we were to manually write out what **times** is doing in the above code it would look like this:

```
logANumber(0)
logANumber(1)
logANumber(2)
logANumber(3)
logANumber(4)
logANumber(5)
logANumber(6)
logANumber(7)
logANumber(8)
logANumber(9)
```

But cats refuse to do unnecessary manual work like this so we must always ask ourselves, "*am I doing this in the laziest way possible?*".

So why is this called looping? Think of it like this: If we were to write out a list of 10 numbers (from 0 to 9) using a JavaScript Array it would look like this:

```
var zeroThroughTen = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

What **times** really does is visit each number and repeat a task: in the example above the task was to call the **logANumber** function with the current number. Repeating tasks in this way is referred to as *looping over* the Array.

Arrays

I've mentioned these a few times but let's spend a minute learning about them. Imagine you need to keep track of all your buddies. Well, an Array will do just fine. Think of an Array like a sorted list that you can keep *tons* of stuff in.

This is how you make one:


```
var myCatFriends = ["tommy", "tabby", "ceiling"]
```

Sweet! Now you have a list of your cat buddies.

Elements (that is what you call a single item in an array) that are stored within arrays start at 0 and count up from there. So `myCatFriends[0]` returns `tommy` and `myCatFriends[1]` returns `tabby` ... etc etc.


To get buddies out of your brand new Array you can just access an element directly like so:

```
console.log(myCatFriends[0])
```



If you made a brand new cat friend at the hippest cat club the other night and you want to add them to your list it is super simple: `myCatFriends.push("super hip cat")`.

To check that the new cat made it into your array you can use `.length`:



Notice how `push` returned the length? Handy! Also take note that arrays will always **preserve**

ordering which means they will remember the order in which you added or defined things. Not everything in JavaScript preserves ordering so remember this special property of Arrays!

That is the end for now, but here's what I'm working on:

- More crazy looping!
- Objects and JSON!
- Grabbing stuff from other pages on the internet and displaying it
- How to use Github to find and share code
- Node.js and server side catgramming

Got another topic you wanna see covered? Open an issue for it [on github](#).

I'd recommend coming back again tomorrow and going through the entire thing again from the beginning! It might take a few times through before you get everything (programming is hard). Just try to avoid reading this page in any rooms that contain shiny objects... they can be incredibly distracting.

Recommended reading

JavaScript For Cats skips over lots of details that aren't important for getting started (cats are not known for their attention spans), but if you feel like you need to dive in deeper then check these out:


- Eloquent Javascript is a free book that teaches you JavaScript! It's pretty good! Especially the chapter on values, variables, and control flow
- Mozilla's JavaScript Guide also has a pretty sweet intro chapter called [values, variables and literals](#)
- Felix's Node.js Style Guide was written about programming JavaScript on the server-side using Node.js but there are lots of tips in here that are useful for anyone programming with JavaScript.

JSForCats.com is a labor of love and work in progress by @maxogden. If you would like to contribute and make this tutorial better there is a Github repo right over here. Bonus: Here is a PDF version of JSForCats.



Satisfied customers

Here are some of our early students (who went on to found the successful company **RealtimeCats®** which offers "Software as a Service" integrated cloud solutions for high resolution feline imagery in faster than real time)



JavaScript For Cats

An introduction for new programmers

So easy your human
companion could do it
for you!

JavaScript is a programming
language that allows you to
instruct the which a computer
is instructed to do things. Just
like you are one controls
household with remote and
switches, one controls
computers with statements.
Written in a programming
language called JavaScript.



SAMSUNG

