## Systemd Tools

Maksim 'max\_posedon' Melnikau

Linux Mobile hobbyist World of Tanks developer

June 23, 2012

### systemctl status

```
Loaded: loaded (/usr/lib64/systemd/system/NetworkManage:
   Active: active (running) since Fri, 27 Apr 2012 21:12:48
Main PID: 1307 (NetworkManager)
   CGroup: name=systemd:/system/NetworkManager.service
              1307 /usr/sbin/NetworkManager --no-daemon
           | 13523 /sbin/dhclient -d -4 -sf /usr/libexec/nm
           | 18796 /usr/libexec/nm-openvpn-service
           | 18798 /usr/sbin/openvpn --remote vpn.wargaming
<info> (tun0): writing resolv.conf to /sbin/resolvconf
<info> Clearing nscd hosts cache.
<info> VPN connection 'WG openvpn' (IP Config Get) complete
<info> Policy set 'posedon' (wlan0) as default for IPv4 row
<info> VPN plugin state changed: started (4)
Initialization Sequence Completed
```

4 D > 4 B > 4 E > 4 E > E 990

# systemctl status NetworkManager.service -o cat -n 6

NetworkManager.service - Network Manager

## systemd-nspawn

```
# systemd-nspawn -D /media/gentoo-mobile
Spawning namespace container on /media/gentoo-mobile \
(console is /dev/pts/6).
root@gentoo-mobile ~ # ps -Af
PID USER TIME COMMAND
    1 root    0:00 -bash
    2 root    0:00 ps -Af
```

## systemd-cat

```
# systemd-cat seq 1 5
# systemd-journalctl -n 5
Apr 29 23:43:43 m_melnikau-vaio[19403]: 1
Apr 29 23:43:43 m_melnikau-vaio[19403]: 2
Apr 29 23:43:43 m_melnikau-vaio[19403]: 3
Apr 29 23:43:43 m_melnikau-vaio[19403]: 4
Apr 29 23:43:43 m_melnikau-vaio[19403]: 5
```

# systemd-cgtop

| Path                               | Tasks | %CPU |
|------------------------------------|-------|------|
| /                                  | 477   | 27.0 |
| /system                            | 1     | 26.5 |
| /system/kdm@.service               | _     | 25.2 |
| /system/rabbitmq-server.service    | 44    | 0.7  |
| /system/dbus.service               | 12    | 0.3  |
| /system/NetworkManager.service     | 4     | 0.2  |
| /system/mysqld.service             | 16    | 0.1  |
| /system/avahi-daemon.service       | 2     | 0.0  |
| /system/console-kit-daemon.service | 65    | _    |
| /system/rtkit-daemon.service       | 3     | _    |
| /system/systemd-journald.service   | 1     | _    |
| /system/systemd-logind.service     | 1     | _    |
| /system/udev.service               | 3     | _    |

## systemd-tmpfiles

#### x11.conf

```
# Make sure these are created by default
# so that nobody else can
d /tmp/.X11-unix 1777 root root 10d
d /tmp/.ICE-unix 1777 root root 10d
d /tmp/.XIM-unix 1777 root root 10d
d /tmp/.font-unix 1777 root root 10d
d /tmp/.Test-unix 1777 root root 10d
# Unlink the X11 lock files
r /tmp/.X\[0-9\]*-lock
```

## systemd-analyze

```
# systemd-analyze blame
  1256ms udev-trigger.service
   554ms NetworkManager.service
   248ms avahi-daemon.service
   196ms systemd-logind.service
   170ms media.mount
   169ms systemd-vconsole-setup.service
   155ms dev-mqueue.mount
   141ms sys-kernel-debug.mount
   124ms sys-kernel-config.mount
   121ms console-kit-log-system-start.service
   119ms remount-rootfs.service
   110ms sys-fs-fuse-connections.mount
   106ms systemd-sysctl.service
   106ms dbus.service
```

## systemd-journalctl

```
# systemd-journalctl -o verbose _PID=11937
Sun, 29 Apr 2012 10:39:29 +0300 [s=bacf660eec8340c99fcc4e5
 _TRANSPORT=syslog
PRIORITY=4
 SYSLOG_FACILITY=1
 SYSLOG_IDENTIFIER=org.kde.powerdevil.backlighthelper
MESSAGE=QDBusConnection: system D-Bus connection created
 PID=11937
 UID=0
 GID=0
 _COMM=backlighthelper
 _EXE=/usr/lib64/kde4/libexec/backlighthelper
 _CMDLINE=/usr/lib64/kde4/libexec/backlighthelper
 _SYSTEMD_CGROUP=/system/dbus.service
 _SYSTEMD_UNIT=dbus.service
 _SOURCE_REALTIME_TIMESTAMP=1335685169367215
 _BOOT_ID=083530b34e7547e48fcfe7be0726fa3f
                                     <ロ > ← □ > ← □ > ← □ > ← □ = ・ の へ ○
```

. . .

- ► Maksim 'max\_posedon' Melnikau maxposedon@gmail.com
- http://www.freedesktop.org/wiki/Software/systemd