

● Review

ULTRASOUND CONTRAST AGENT MODELING: A REVIEW

MICHEL VERSLUIS,^{*} ELEANOR STRIDE,[†] GUILLAUME LAJOINIE,^{*} BENJAMIN DOLLET,[‡] and TIM SEGERS^{*}

^{*} Physics of Fluids Group, MESA+ Institute for Nanotechnology, Technical Medical (TechMed) Center, University of Twente, Enschede, the Netherlands; [†] Department of Engineering Science, Institute of Biomedical Engineering, University of Oxford, Oxford, UK; and [‡] Centre National de la Recherche Scientifique (CNRS), Laboratoire Interdisciplinaire de Physique (LIPhy), Université Grenoble Alpes, Grenoble, France

(Received 22 January 2020; revised 11 April 2020; in final form 14 April 2020)

Abstract—Ultrasound is extensively used in medical imaging, being safe and inexpensive and operating in real time. Its scope of applications has been widely broadened by the use of ultrasound contrast agents (UCAs) in the form of microscopic bubbles coated by a biocompatible shell. Their increased use has motivated a large amount of research to understand and characterize their physical properties as well as their interaction with the ultrasound field and their surrounding environment. Here we review the theoretical models that have been proposed to study and predict the behavior of UCAs. We begin with a brief introduction on the development of UCAs. We then present the basics of free-gas-bubble dynamics upon which UCA modeling is based. We review extensively the linear and non-linear models for shell elasticity and viscosity and present models for non-spherical and asymmetric bubble oscillations, especially in the presence of surrounding walls or tissue. Then, higher-order effects such as microstreaming, shedding and acoustic radiation forces are considered. We conclude this review with promising directions for the modeling and development of novel agents. (E-mail: m.versluis@utwente.nl) © 2020 The Author(s). Published by Elsevier Inc. on behalf of World Federation for Ultrasound in Medicine & Biology. This is an open access article under the CC BY license. (<http://creativecommons.org/licenses/by/4.0/>).

Key Words: Ultrasound contrast agents, Microbubble dynamics, Modeling.

INTRODUCTION

While in the 17th century Robert Hooke had already predicted that we would be able to image the human body with sound (Tyndall 1875), it was not until the 1940s that the first ultrasound scan of soft tissue was realized (Howry 1952). Today, ultrasound is one of the most widely used medical imaging techniques because of its safety and relatively low expense compared with magnetic resonance imaging and X-ray computed tomography. As with the other modalities, ultrasound allows for functional imaging, including Doppler (Evans et al. 1989; Christopher et al. 1996), vector flow imaging (Jensen et al. 2016) and neuroimaging (Deffieux et al. 2018). Moreover, ultrasound machines are small and portable and can be used at the bedside. Finally, ultrasound provides real-time imaging, offering typically 50 frames per second for conventional line-by-line scanning and up to 10,000 frames/s for ultrafast plane wave imaging (Tanter and Fink 2014).

The best-known application of medical ultrasound is fetal scanning. The amniotic fluid around the fetus contains very few scatterers in comparison to the fetal tissue, and as a result the image of the fetus stands out clearly against a black background. Such high contrast can also be found in echocardiography, where the blood in the left ventricular cavity is a poor ultrasound scatterer as compared with the cardiac muscle tissue. This high contrast then aids in the delineation of the endocardial border and the diagnosis of regional wall motion abnormalities (Mulvagh et al. 2008; Senior et al. 2009). However, the poor backscatter from the blood pool is problematic for perfusion imaging and blood flow quantification.

Ultrasound contrast agents (UCAs) can dramatically boost the native contrast of the blood pool. A UCA consists of a suspension of stabilized gas microbubbles (Quaia 2005) that is injected intravenously. As the microbubbles are smaller than red blood cells, they can traverse even the smallest capillaries. Despite their diminutive size, their scattering cross section can be up to nine orders of magnitude larger than that of red blood cells, and this highly efficient scattering enables the quantification of the perfusion

Address correspondence to: Michel Versluis, Physics of Fluids Group, MESA+ Institute for Nanotechnology, Technical Medical (TechMed) Center, University of Twente, P.O. Box 217, Enschede 7500 AE, the Netherlands. E-mail: m.versluis@utwente.nl

of the myocardium and other organs, including liver, brain and kidney.

The potential of microbubbles as UCAs was in fact discovered by accident in 1968, during an intravenous injection of a saline solution while performing a cardiac ultrasound examination (Gramiak and Shah 1968). The microbubbles that were formed in solution by hand agitation were found to scatter the administered ultrasound highly efficiently. Given the poor stability of the air-filled bubbles in the electrolyte solution, considerable effort was put into finding more stable alternatives. This led to the first class of agents—including Quantison (Frinking and de Jong 1998), Albunex (Feinstein et al. 1984) and Optison (Skyba et al. 1996; Cohen et al. 1998)—containing coated microbubbles that were formed by sonication of human serum albumin. With their relatively rigid shells and corresponding decreased scattering response, a second generation of UCAs was developed that was inspired by the more flexible nature of lipid cell membranes. These novel agents—including SonoVue (Schneider 1999), Definity (Unger et al. 1994) and Sonazoid (Sontum 2008)—are composed of a suspension of purified phospholipid-mixture—encapsulated gas microbubbles, with diameters ranging from 1 to 10 μm , that are filled with a high-molecular-weight gas, typically perfluorocarbons or sulfur hexafluoride. Examples of UCA microbubbles are given in Figure 1a–d.

The coating of the microbubbles decreases (or potentially eliminates) the interfacial tension, which stabilizes the bubble against Laplace pressure—driven dissolution (Epstein and Plesset 1950). The stability of the microbubbles is further enhanced by both the low solubility of the gas and the resistive barrier that the encapsulation forms against gas diffusion through the monolayer membrane (Borden and Longo 2002). Long-chain polyethylene glycol spacers are added to provide stealth capability against detection by the body's immune system and therefore improve the circulation lifetime *in vivo* (Klibanov 2006). Furthermore, they prevent bubble coalescence through repulsive intermolecular forces (Segers et al. 2017; Borden and Song 2018). Cumulatively, this leads to an overall bubble lifetime of 5–10 mins after intravenous injection (Kaul 2000; Lindner 2019). Perfluorocarbon gas-filled microbubbles can be stable in suspension for several days to a few weeks when kept in a vial under a protective gas headspace. Freeze-dried bubbles can be stored for several years (European Medicines Agency 2015).

The physical mechanism by which microbubbles enhance image contrast is twofold. First, acoustic waves are scattered by the bubbles owing to the large difference in acoustic impedance between the gas core and the surrounding liquid. Second, and more important, the large compressibility of the gas core leads to volumetric oscillations in response to ultrasound pressure waves. Thus, the

oscillating bubble acts as a source of sound with an effective scattering cross section up to several orders of magnitude larger than that of a rigid sphere of the same size and acoustic impedance (Hilgenfeldt et al. 1998). Furthermore, when the bubbles are driven at resonance, their oscillations can be highly non-linear and therefore they can produce scattered ultrasound fields containing a range of frequencies, including whole and fractional harmonics of the driving frequency. In addition, and particularly at lower driving pressures (<100 kPa), further non-linearities are induced by the non-linear viscoelastic properties of the stabilizing shell. To date, contrast-specific imaging modes use the non-linear echoes to detect the contrast agent response while suppressing the linear tissue echoes (Hope Simpson et al. 1999; Frinking et al. 2000; Rafter et al. 2004; Eckersley et al. 2005; Averkiou et al. 2008). By fortunate coincidence, the range of microbubble sizes appropriate for clinical use corresponds to resonance frequencies on the order of 1–10 MHz, the typical frequency range used in diagnostic ultrasound. It is this combination of scattering efficiency and non-linearity that makes microbubbles such excellent UCAs.

While the use of coated bubbles as a perfusion contrast agent is clinically established, the interest in oscillating bubbles as a theranostic agent is also rapidly increasing for the following reasons. First, transfer of momentum to the surrounding fluid by the non-linearly oscillating bubble can set up a steady flow, or microstreaming, that can both affect the transport of therapeutic material and impose shear stresses on biological membranes, thereby altering their permeability and thus mediating therapeutic effects (Ward et al. 2000; Marmottant and Hilgenfeldt 2003; Pereno et al. 2018). Second, absorption of the acoustic emissions from the bubbles can produce localized heating of the surroundings (Prosperetti 1977b; Coussios and Roy 2008) that can directly produce bio-effects or be used, *e.g.* to release drugs from thermally sensitive carriers. Heating is increased compared with direct ultrasound exposure on account of the higher-frequency components in the bubble emissions that are more readily absorbed by tissue (Hilgenfeldt et al. 2000). Third, the increased temperature and pressure in the core of the bubble during compression can stimulate sonochemistry (Suslick and Flannigan 2008), leading to the production of chemical species including oxygen radicals, although this effect is reduced for the polyatomic gases typically used in contrast agents. Finally, there may be complex interactions between oscillating bubbles and biological structures that promote therapeutic effects. These include microjetting and radiation force phenomena.

In the mid-1990s, a new field emerged that focused on the complex interaction between coated microbubbles and ultrasound. Advances were made through experimental




Fig. 1. Ultrasound contrast-agent microbubbles. (a) Lipid-coated microbubbles as seen in bright-field microscopy (reprinted with permission from Segers *et al.* 2016b. Copyright 2016 American Chemical Society); (b) perfluoropropane bubbles with a protein shell (Optison), seen here against a background of red blood cells (reproduced from Wilson and Burns 2010); (c) lipid-coated microbubbles of perfluoropropane gas (Definity) as seen in dark-field microscopy (reproduced from Wilson and Burns 2010); (d) scanning electron micrograph of a Quantison microsphere, fractured owing to vacuum (reproduced with permission from Frinking and de Jong 1998); (e) vapor bubble release from a laser-heated single oil-filled microcapsule captured under ultrahigh-speed imaging (reproduced with permission from Lajoinie *et al.* 2014); (f) scanning electron micrograph of monodisperse microcapsules (image courtesy of Nanomi, Oldenzaal, the Netherlands); (g) monodisperse microbubbles with a radius of $2.7\ \mu\text{m}$ produced in a flow-focusing device (reprinted with permission from Segers *et al.* 2016b. Copyright 2016 American Chemical Society); (h) numerical simulation of the buckling instability of the elastic shell of a polymeric hard-shelled microcapsule (reproduced with permission from Marmottant *et al.* 2011); (i) buckling instability upon dissolution for two different surfactants (Survanta and dipalmitoylphosphatidylcholine (DPPC)) (reprinted with permission from Thomas and Borden 2017. Copyright 2017 American Chemical Society); (j) buckling observed during compression of a lipid-coated microbubble (reproduced with permission from Sijl *et al.* 2011).

observations, first using acoustic spectroscopy (de Jong *et al.* 1992) and later using ultra high-speed imaging (Morgan *et al.* 2000; Chin *et al.* 2003). Along with the experimental work, great progress has been made in model development. The majority of the available coated-bubble models have in common a starting point of a Rayleigh Plesset–type equation (Lauterborn 1976; Matula 1999). The field of UCA modeling has greatly benefited from the field of sonoluminescence, where the dynamics of free gas bubbles in an unbounded fluid have been fully described (Brenner *et al.* 2002; Lohse 2018). The effect of the viscoelastic shell on bubble dynamics is evident from

acoustical and optical characterization. The pressure contributions resulting from the viscoelastic shell are incorporated into the Rayleigh–Plesset (RP) equation as additional interfacial pressure terms (de Jong *et al.* 1994; Church 1995; Hoff *et al.* 2000). The shell elasticity increases the stiffness of the system, and an increase in the resonance frequency is expected. Similarly, the shell viscosity leads to energy dissipation which results in increased damping and hence a small reduction in resonance frequency and decreased amplitude of oscillation.

The non-linear properties of the bubble shell are especially important at small oscillation amplitudes. The

densely packed lipid monolayer may buckle during compression, while the bubble coating may rupture upon expansion, forming lipid domains on the otherwise free interface and thereby exposing the gas directly to the surrounding liquid. Such changes in the interfacial properties of the coating lead to surprising contrast response characteristics, including thresholding behavior (Emmer et al. 2007), compression-only behavior (de Jong et al. 2007; Sijl et al. 2011) and subharmonics (Sijl et al. 2010). In addition, gas loss through diffusion, or acoustic deflation, upon ultrasound driving may lead to a higher concentration of lipids at the bubble interface, changing its dynamics. Alternatively, the bubble may expel excess lipids (Luan et al. 2014), leading to higher surface tension and promoting gas loss (Viti et al. 2012). Altogether, the interfacial rheology is an important factor in fully describing the origin and details of the non-linear echoes generated by bubbles. Ultimate control over the shell properties and its physical behavior is elementary for the design of optimized agents for contrast imaging, displaying improved backscatter, less attenuation and superior non-linear properties. Such agents can then also act as vector flow tracers for echo particle image velocimetry (Leow et al. 2015; Poelma 2016; Engelhard et al. 2018) and enable non-invasive pressure measurements (Shi et al. 1999; Frinking et al. 2010).

In addition to the dramatic effect of the stabilizing shell, bubble dynamics are highly dependent on the biological environment and the presence of neighboring bubbles. A compliant blood vessel wall will reflect part of the pressure field emitted by the bubble in a non-trivial way, resulting in a complex interaction with the bubbles (Garbin et al. 2007; Doinikov et al. 2009b; Hay et al. 2012; Helfield et al. 2014). Similarly, the sound field generated by neighboring bubbles interacts with that of the bubble, thereby altering its dynamics and inducing acoustic radiation forces (Bjerknes 1906; Crum 1975). These effects are considered higher-order effects and are discussed in more detail later under Modeling higher-order effects, as well as in the companion review on therapeutic applications of microbubbles (Kooiman et al. 2020).

This article reviews the modeling efforts that have been undertaken, starting with bubble fundamentals, bubble shell models and secondary higher-order effects, and finishing with new directions that are explored for improved models to describe bubble dynamics in tissues and those of novel agents such as bubble clusters and bubbles for multimodality imaging. One or more of our cited studies used human subjects, and these were, to the best of our knowledge, granted protocol approval by an ethics committee or institutional review board. Where animals were studied the research protocol was, again to the best of our knowledge, approved by a local institutional care and animal use committee.

Modeling free-bubble dynamics

The free-gas-bubble model. Numerous mathematical formulations have been developed to describe bubble dynamics. Historically these have been motivated primarily by the hydrodynamic effects of bubbles in turbomachinery. The first published use of the term *cavitation* dates to Thornycroft and Barnaby (1895) and is attributed to the engineer and naval architect Robert Froude. That bubbles might be generated by the motion of a water turbine had in fact been proposed over a century earlier by Euler (1756), but it was not until the late 19th century that the relationship between liquid pressure, bubble formation and, importantly, physical effects on the surroundings became the focus of intense research.

Besant (1859) and subsequently Lamb (1879) and Rayleigh (1917) considered an empty spherical cavity in a large volume of inviscid fluid. In this case the bubble undergoes a single, very rapid, collapse, driven by the inertia of the surrounding fluid and generating a shock wave as a result of the high pressure developed at the site of the bubble. Blake (1949), Noltingk and Neppiras (1950) and Neppiras and Noltingk (1951) subsequently considered the more commonly encountered case of a bubble partially or completely filled with gas. In this case the pressure inside the bubble increases as it is compressed, producing a *cushioning* effect. Finally, an additional term was included to account for viscous dissipation in the surrounding fluid. According to Young (1989) this was originally given by Taylor and Davies (1963), although it is generally attributed to Poritsky (1951). The result was the Rayleigh-Plesset or Rayleigh–Plesset–Noltingk–Neppiras–Poritsky equation (Lauterborn 1976):

$$\rho_L \left(R\ddot{R} + \frac{3}{2}\dot{R}^2 \right) = P_B - P_\infty. \quad (1)$$

This is a pressure balance between the inertial term on the left-hand side, originating from the inertia of the liquid associated with the bubble motion, and the pressure difference on the right-hand side arising from the difference in work done at the bubble wall and done remotely from the bubble (Leighton 2011). Table 1 summarizes all symbols used in this review. In this equation, R is the time-dependent bubble radius (see Fig. 2, left), with initial value R_0 ; $\dot{R}$ and $\ddot{R}$ are the velocity and acceleration, respectively, of the bubble wall; ρ_L is the density of the surrounding fluid; P_B is the pressure in the liquid at the bubble wall; and P_∞ is the pressure in the liquid far away from the bubble, defined as the sum of the hydrostatic pressure P_0 and the time-varying driving pressure $P_A(t)$ in the liquid.

When the gas in the bubble is an ideal gas, from the pressure balance at the bubble interface P_B can be

Table 1. List of symbols

Symbol	Meaning
A	Bubble surface area
A_0	Bubble surface area at rest
a_n	Amplitude of surface mode number n
α	Total attenuation
c_L	Speed of sound in the liquid
d	Acoustic path length
dA	Bubble surface-area dilatation
δ_{BL}	Boundary-layer thickness
δ_{tot}	Total damping
δ_{rad}	Radiative damping
δ_{vis}	Liquid viscous damping
δ_{shell}	Shell viscous damping
δ_{th}	Thermal damping
e	Bubble location in the tube
ϵ	Small oscillation amplitude (dimensionless)
ϕ	Azimuthal angle of the spherical harmonics
η	Backscatter coefficient
f	Ultrasound frequency
f_T	Transmit frequency
f_{res}	Resonance frequency
f_0	Bubble eigenfrequency
κ	Polytropic exponent
κ_s	Shell viscosity
l	One-dimensional bubble length
l_0	One-dimensional bubble length at rest
L	One-dimensional tube length
ℓ	Typical streaming length scale
μ_L	Liquid viscosity
n	Spherical harmonic mode number
$n(R)$	Bubble concentration of bubbles with radius R
P_0	Hydrostatic pressure
P_∞	Pressure in the liquid far from the bubble
P_A	Driving pressure
P_B	Pressure in the liquid at the bubble wall
p_v	Vapor pressure
P_s	Scattered pressure
P_T	Transmit pressure
P_{vis}	Viscous pressure term
P_{elas}	Elastic pressure term
R	Bubble radius
$\dot{R}$	Bubble wall velocity
$\ddot{R}$	Bubble wall acceleration
R_0	Bubble radius at rest
R_b	Bubble buckling radius
R_r	Bubble rupture radius
R_{tube}	Tube radius
ρ_L	Liquid density
σ	Surface tension
$\sigma(R)$	Size-dependent surface tension
$\sigma(R_0)$	Surface tension at rest
σ_s	Scattering cross section
t	Time
θ	Polar angle of the spherical harmonics
τ_{xz}	Shear stress along the wall
U	Oscillatory flow velocity
u_s	Streaming velocity
V	Bubble volume
ω	Angular ultrasound frequency
ω_0	Angular bubble eigenfrequency
ω_{0n}	Angular bubble eigenfrequency of surface mode n
Ω_s	Linearized scattering cross section
x	Coordinate along the wall
χ	Shell elasticity
Y_n	Spherical harmonic of mode number n
z	Coordinate away from the wall




Fig. 2. Schematic view of a free gas bubble (*left*) and a lipid-coated microbubble (*right*). To the right, the coating is indicated by the primary phospholipids and lipids with polyethylene glycol added (not drawn to scale). R_0 = bubble size; P_B = liquid pressure at the bubble wall; P_∞ = liquid pressure far away from the bubble; μ_L = liquid viscosity; ρ_L = liquid density; c_L = speed of sound in the liquid; σ = surface tension of water; κ_s = shell viscosity; χ = shell elasticity; $\sigma(R)$ = size-dependent effective surface tension of the coated bubble.

expressed as

$$P_B = \left(P_0 + \frac{2\sigma}{R_0} - p_v(R_0) \right) \left(\frac{R_0}{R} \right)^{3\kappa} - \frac{2\sigma}{R} - \frac{4\mu_L \dot{R}}{R} + p_v, \quad (2)$$

following the ideal gas law, with σ the surface tension at the gas–liquid interface, κ the polytropic constant and μ_L the viscosity of the surrounding liquid. The vapor pressure p_v inside the bubble is typically neglected in the modeling of the dynamics of micrometer-sized bubbles because the vapor pressure of water at atmospheric conditions (2.3 kPa) is low as compared with the hydrostatic and interfacial pressure terms.

There are a number of assumptions implicit in the derivation of eqns (1) and (2): the bubble is assumed to remain spherical at all times, with no heat or mass transfer across the bubble wall during oscillation. The surrounding fluid is assumed to be infinite, incompressible and Newtonian. The gas inside the bubble is assumed to behave ideally. The wavelength of the incident ultrasound field is assumed to be sufficiently large that the bubble experiences a spatially uniform pressure. The effects of gravity and buoyancy are ignored.

Acoustic reradiation. At small amplitudes of oscillation the assumption of an incompressible fluid is justified. However, with increasing driving pressure it becomes necessary to modify eqn (1) to correct for the

effects of liquid compressibility and energy dissipation associated with generating acoustic emissions. This may become significant for situations in which the velocity of the bubble wall is comparable with the speed of sound in the surrounding liquid ($|\dot{R}|/c_L \sim 1$). Based on the work of Herring (1941), Trilling (1952) rederived eqn (1) to take into account the energy stored in the liquid during bubble oscillation and the damping effect produced by the re-radiation of sound waves. This treatment assumes that the sound velocity c_L in the surrounding liquid is constant and is therefore limited in terms of the maximum amplitude of oscillation for which it is valid. Gilmore (1952) improved upon this assumption by employing the Kirkwood–Bethe hypothesis (Bethe 1935; Kirkwood 1938), which states that the wave velocity is equal to the sum of the velocity of the liquid and the local speed of sound at the bubble wall.

In 1980, building upon the earlier models, Keller and Miksis (1980) published a more complete treatment for large-amplitude bubble oscillations, which included surface tension and liquid viscosity, both of which were neglected in earlier work:

$$\left(1 - \frac{\dot{R}}{c_L}\right) R\ddot{R} + \frac{3}{2} \left(1 - \frac{\dot{R}}{3c_L}\right) \dot{R}^2 = \frac{1}{\rho_L} \left(1 + \frac{\dot{R}}{c_L} + \frac{R}{c_L} \frac{d}{dt}\right) (P_B - P_\infty), \quad (3)$$

with P_B and P_∞ as defined before. This expression was subsequently refined by Prosperetti et al. (1988), who removed the assumption of ideal gas behavior and coupled the equation of motion for the bubble to the equations of mass and energy conservation. Note that eqn (3) is no longer valid when $|\dot{R}|/c_L \sim 1$. Therefore, a popular form in the context of sonoluminescence and UCA modeling is given by (Löfstedt et al. 1995; Barber et al. 1997; Brenner et al. 2002; Marmottant et al. 2005; Paul et al. 2010):

$$\rho_L \left(R\ddot{R} + \frac{3}{2} \dot{R}^2 \right) = \left(P_0 + \frac{2\sigma}{R_0} \right) \left(\frac{R_0}{R} \right)^{3\kappa} \left(1 - \frac{3\kappa \dot{R}}{c_L} \right) - \frac{2\sigma}{R} - \frac{4\mu_L \dot{R}}{R} - P_0 - P_A(t). \quad (4)$$

For an exhaustive review of the derivation of the different RP-type equations, see Brenner et al. (2002).

Modeling coated-bubble dynamics

Adding the interfacial pressure terms. The gas core of UCA microbubbles is typically coated with a layer of proteins, polymers or phospholipids (Stride and Saffari 2003; Faez et al. 2013). The first class of agents comprised microbubbles with a rigid shell, often referred to as *hard-*

shelled agents, which motivated the initial approach to modeling their response to ultrasound. This work was started by de Jong and Hoff, who proposed a model describing the behavior of microbubbles of Albunex contrast agent, where the shell was considered to be perfectly elastic (*i.e.*, obeying Hooke's law with no additional damping [de Jong et al. 1992]). The resulting stiffness pressure term was added in an ad hoc way to the RP equation to describe the bubble dynamics. They later added a semi-empirical shell dissipation term to fit the experimental observations (de Jong and Hoff 1993). Church (1995) and Hoff et al. (2000) then followed a similar approach using a more thorough derivation to account for the viscoelastic shell of Albunex. They considered the shell material to be incompressible, but the shear viscosity of the shell was directly included in the derivation of the modified RP equation. Several other models were developed based on linear elasticity (some of them are compared by Sarkar et al. 2005), presenting similar results. Non-linear elasticity considerations were added by Allen and Rashid (2004), who considered a non-linear Hooke's law, or neo-Hookean model, for the shell. However, all these models missed the most important aspects of the behavior of the rigid shells, namely (non-spherical) buckling upon compression and rupture upon large expansion. These aspects were investigated and implemented in a model by Marmottant et al. (2011). Despite its simple approach, this model captures many features observed in experiments (Lensen et al. 2011). The model shows, in particular, that these bubbles mostly behave as a free gas bubble after rupture of the shell, as demonstrated before by Postema et al. (2005a) and Bouakaz et al. (2005). A more extensive review of the hard-shelled models is given by Doinikov and Bouakaz (2011).

To date, the majority of the clinically approved UCAs and research-grade UCAs consist of microbubbles coated with a phospholipid monolayer. In the following, we therefore focus on the modeling of non-linear lipid-coated microbubble dynamics—*e.g.*, the observed driving-pressure-dependent resonance behavior (Chen et al. 2002; Emmer et al. 2009; Segers et al. 2016a) and asymmetric oscillation amplitudes—with more pronounced compression than expansion, termed *compression-only* behavior (de Jong et al. 2007; Sijl et al. 2011). Figure 2 (right) gives a schematic of the coated bubble. The viscoelastic lipid coating changes the pressure jump condition across the bubble interface that is used in the RP equation, eqns (1) and (3). The seminal articles by de Jong et al. (1992, 1994) and Church (1995) include the presence of a shell through the addition of two independent pressure terms on the right-hand side of eqn (4), one accounting for the elasticity P_{elas} of the shell and one accounting for the viscous dissipation P_{vis} in the shell. These terms can be derived for a shell of finite

thickness (Church 1995; Hoff *et al.* 2000) and for an infinitesimally thin surface layer using material constitutive laws (de Jong *et al.* 1992; de Jong and Hoff 1993; de Jong *et al.* 1994; Chatterjee and Sarkar 2003; Marmottant *et al.* 2005; Sarkar *et al.* 2005; Tsigliffis and Pelekasis 2008; Doinikov *et al.* 2009a). The physical principles of the available models for soft-shelled models have been exhaustively reviewed by Doinikov and Bouakaz (2011). For a more extensive review, see Faez *et al.* (2013).

The viscous pressure term P_{vis} is added to account for viscous energy dissipation in the microbubble shell resulting from the work done to change the distance between the lipid molecules during an acoustic cycle. The most common form of P_{vis} is derived from Newton's linear viscous law for an infinitesimally thin shell (de Jong *et al.* 1994; Church 1995; Morgan *et al.* 2000; Chatterjee and Sarkar 2003; Marmottant *et al.* 2005; Sarkar *et al.* 2005):

$$P_{\text{vis}} = 4\kappa_s \frac{\dot{R}}{R^2}, \quad (5)$$

with κ_s the surface dilatational viscosity of the lipid monolayer shell. Typically, it is assumed that κ_s does not depend on the bubble surface area, surface dilatation, or surface dilatation rate. The validity of eqn (5) will be discussed in the final paragraph of this section.

The elastic pressure term P_{elas} accounts for the pressure increase inside the bubble owing to the stiffness of the shell. Shell elasticity χ can be described to result from interfacial tension gradients $d\sigma$ induced by (acoustically-driven) bubble surface-area variations dA (Glazman 1983; Mohwald 1995; Marmottant *et al.* 2005; Sarkar *et al.* 2005):

$$\chi = A \frac{d\sigma}{dA}. \quad (6)$$

Assuming a constant and surface-area-independent shell elasticity, eqn (6) can be integrated to find the effective interfacial tension: $\sigma(R) = \chi(R^2/R_0^2 - 1)$, with R_0 the equilibrium bubble radius. With the effective interfacial tension, the elastic pressure term reads

$$P_{\text{elas}} = \frac{2\sigma(R)}{R} = \frac{2\chi}{R} \left(\frac{R^2}{R_0^2} - 1 \right). \quad (7)$$

Equation (7) is the most common form of the elastic pressure term (de Jong *et al.* 1994; Church 1995; Chatterjee and Sarkar 2003; Marmottant *et al.* 2005; Sarkar *et al.* 2005; Tsigliffis and Pelekasis 2008). The full equation—including the shell pressure terms and eqns (5) and (7)—then reads:

$$\begin{aligned} & \rho_L \left(R\ddot{R} + \frac{3}{2}\dot{R}^2 \right) \\ &= \left(P_0 + \frac{2\sigma(R_0)}{R_0} \right) \left(\frac{R_0}{R} \right)^{3\kappa} \left(1 - \frac{3\kappa\dot{R}}{c_L} \right) - P_0 \\ & \quad - P_A(t) - \frac{4\mu_L\dot{R}}{R} - \frac{2\chi}{R} \left(\frac{R^2}{R_0^2} - 1 \right) - \frac{4\kappa_s\dot{R}}{R^2}, \end{aligned} \quad (8)$$

where $\sigma(R_0)$ represents the surface tension of the bubble at rest.

With a complete description of the radial oscillations of coated bubbles, we can now calculate the echo produced by UCA microbubbles. The sound emitted by an oscillating microbubble has two contributions. The first is a passive contribution that simply results from the mismatch in acoustic impedance between the gas core and the surrounding medium. The second one is the active part and results from the volumetric oscillations $V(t)$ of the bubble. Micrometer-sized bubbles driven near resonance (see also the next section) have a size that is typically three orders of magnitude smaller than the incident wavelength. It has been shown that in this case the passive contribution is negligible with respect to the active part (Hilgenfeldt *et al.* 1998). From mass and momentum conservation it follows that the active scattered pressure wave P_s at a distance r from the bubble center equals (Vokurka 1985):

$$P_s = \frac{\rho_L}{4\pi r} \ddot{V} = \frac{\rho_L}{r} \left(R^2\ddot{R} + 2R\dot{R}^2 \right). \quad (9)$$

Thus, the scattered pressure $P_s(t)$ can be directly calculated by inserting into eqn (9) the solution of the RP equation, $R(t)$, and its derivatives.

The numerical solution $R(t)$ of the ordinary differential equation (ODE) given by eqn (8) is displayed in Figure 3 (left) for a bubble with radius 2.0 μm . Three driving pressures were used here—5, 50 and 500 kPa—corresponding to bubble oscillation behavior in the linear, non-linear and inertial-collapse regimes, respectively. The scattered pressure $P_s(t)$ was calculated by inserting $R(t)$ and its derivatives $\dot{R}$ and $\ddot{R}$ directly into eqn (9) (see Fig. 3, middle). Figure 3 (right) gives the spectral content of the scattered pressure. It nicely shows the different regimes of bubble oscillation behavior: in the linear regime, the response of the bubble is at the fundamental frequency of 2.0 MHz; for a driving pressure of 50 kPa the response is non-linear, with buildup of second harmonic and superharmonic components and some small amount of broadband emission; and for the highest-pressure regime, despite some harmonic content, the response is primarily broadband owing to the impulsive collapses of the bubble.




Fig. 3. (Left) Radius-time $R(t)$ curves of a bubble with a radius $R_0 = 2.0 \mu\text{m}$ at three different driving pressures: $P_A = 5, 50$ and 500 kPa . The parameters for this system are as follows: ambient pressure $P_0 = 100 \text{ kPa}$; surface tension $\sigma = 72 \text{ mN/m}$; polytropic exponent $\kappa = 1.07$; speed of sound $c_L = 1500 \text{ m/s}$; liquid density $\rho_L = 1000 \text{ kg/m}^3$; liquid viscosity $\mu_L = 2.0 \text{ mPa s}$ (to account for thermal damping); shell elasticity $\chi = 1.0 \text{ N/m}$; shell viscosity $\kappa_s = 1.0 \times 10^{-8} \text{ kg/s}$; and initial surface tension $\sigma(R_0) = 20 \text{ mN/m}$. Ultrasound consisted of a Gaussian-tapered narrowband driving pulse with 16 cycles at a driving frequency of 2.0 MHz . (Middle) Scattered pressure $P_s(t)$ at a distance of $r = 2.54 \text{ cm}$ at the three driving pressures. (Right) Spectral content of the scattered pressures.

Figure 4a shows the maximum bubble response, expressed as the normalized difference of maximum and minimum bubble amplitude, as a function of the bubble radius for a driving frequency of 1.0 MHz and a driving pressure of 75 kPa . Bubble shell and liquid properties are the same as in Figure 3. The resonance behavior is clearly visible, with bubbles with a radius of $3.2 \mu\text{m}$ displaying maximum oscillation amplitudes. Figure 4B shows the fundamental and second harmonic components of the scattered response of the bubbles driven in Figure 4a. It shows first of all that next to the resonance behavior, bubbles of a larger size also contribute to the scattering at the fundamental driving frequency. More importantly, it shows that the non-linear generation of the second harmonic is limited to the resonant bubbles.

Linear bubble-shell modeling: Resonance frequency and damping. The role of the shell in the microbubble dynamics becomes clear through linearization of the RP equation (eqn [8]), by assuming sinusoidal

acoustic driving and small amplitudes of oscillation with respect to the equilibrium radius (*i.e.*, $R = R_0(1 + \varepsilon(t))$, with $\varepsilon(t) \ll 1$), and by neglecting higher-order terms to yield the classic equation of a driven harmonic oscillator:

$$\ddot{\varepsilon} + \delta_{\text{tot}}\omega_0\dot{\varepsilon} + \omega_0^2\varepsilon = \frac{P_A}{\rho R_0} \sin\omega t, \quad (10)$$

with $\dot{\varepsilon}$ and $\ddot{\varepsilon}$ the first- and second-order derivatives of ε with respect to time, δ_{tot} the total damping of the system, ω the angular ultrasound frequency and ω_0 the angular eigenfrequency of the oscillator:

$$\omega_0 = 2\pi f_0 = \frac{1}{R_0} \sqrt{\frac{1}{\rho_L} \left(3\kappa P_0 + (3\kappa - 1) \frac{2\sigma(R_0)}{R_0} + \frac{4\chi}{R_0} \right)}. \quad (11)$$

In these equations, $\sigma(R_0)$ represents the surface tension of the bubble at rest. Equation (11) shows that the eigenfrequency of a bubble is inversely proportional to the




Fig. 4. (a) Maximum bubble response, expressed as the normalized amplitude (*i.e.*, difference of maximum and minimum bubble amplitudes normalized by $2R_0$) as a function of the bubble radius for a driving frequency of 1.0 MHz and a driving pressure of 75 kPa. Other parameters the same as in Figure 3. (b) The fundamental and second harmonic components of the scattered response of the bubble driven in (a) at a distance $r = 2.54$ cm. (c) The total damping δ_{tot} of an uncoated bubble in water as a function of bubble size with damping contributions from sound reradiation δ_{rad} , viscous damping δ_{vis} owing to liquid viscosity and thermal damping δ_{th} . (d) The total damping of a coated bubble ($\chi = 0.5$ N/m) over the size range relevant for ultrasound contrast agents. The shell damping δ_{shell} was calculated using a fixed shell viscosity $\kappa_s = 1.0 \times 10^{-8}$ kg/s. Note that the total damping of a coated bubble is dominated by shell damping for bubbles in the diameter range 2–3 μm .

microbubble size and that the stiffness χ of the coating increases the eigenfrequency of the coated bubble compared with the free gas bubble.

The total damping δ_{tot} is a summation of the damping contributions that arise from reradiation of sound, viscous dissipation in the surrounding liquid and shell viscous dissipation: $\delta_{\text{tot}} = \delta_{\text{rad}} + \delta_{\text{vis}} + \delta_{\text{shell}}$. The linearization of eqn (8) results in the following expressions for the damping terms at $\omega = \omega_0$:

$$\begin{aligned}\delta_{\text{rad}} &= \frac{3\kappa P_0}{\rho_L \omega_0 c_L R_0}, \\ \delta_{\text{vis}} &= \frac{4\mu_L}{\rho_L \omega_0 R_0^2}, \\ \delta_{\text{shell}} &= \frac{4\kappa_s}{\rho_L \omega_0 R_0^3}.\end{aligned}\quad (12)$$

This expression for radiation damping is in approximate agreement with the exact form $\delta_{\text{rad}} = \omega R_0 / c_L$ (Leighton 1994). A microbubble also experiences thermal damping δ_{th} owing to heat diffusion (Prosperetti 1976; Leighton 1994). For micrometer-sized bubbles it is of the same order as the viscous damping for a bubble in water (Devin 1959), and therefore typically the viscosity of the medium is increased phenomenologically by a factor of 2 to account for thermal damping (van der Meer *et al.* 2007; Sijl *et al.* 2010; Segers *et al.* 2016a). The damping constants for an uncoated bubble are

plotted in Figure 4c. Figure 4d shows the damping constants for a coated bubble ($\chi = 0.5$ N/m). Shell damping was calculated using a fixed shell viscosity $\kappa_s = 1.0 \times 10^{-8}$ kg/s. Note that the damping for a coated bubble is dominated by the shell viscous damping, as it contributes approximately 75% of the total damping for bubbles in the relevant size range of 2–3 μm . The total damping δ_{tot} of the system results in a slightly reduced microbubble resonance frequency f_{res} as compared with its eigenfrequency f_0 : $f_{\text{res}} = f_0 \sqrt{1 - \delta_{\text{tot}}^2/2}$. For a typical total damping of 0.25, however, the decrease in resonance frequency is less than 2%. On the other hand, eqn (11) demonstrates that the microbubble shell stiffness can dramatically increase the resonance frequency. Figure 5 compares the resonance curve of a free gas bubble ($R_0 = 2.5$ μm) with that of lipid-coated bubbles of the same sizes, with respective shell stiffness of 1.0 and 2.5 N/m and shell viscosities of $\kappa_s = 6 \times 10^{-9}$ and 12×10^{-9} kg/s. Note that the linearization performed here provides insightful information only for coated microbubbles driven at very low pressure amplitudes (<5 kPa).

Non-linear bubble-shell modeling: Buckling and rupture. For elevated acoustic pressures we will need to describe the non-linear dynamics of the coated bubble,




Fig. 5. Amplitude of oscillation normalized to that of the uncoated bubble ($R_0 = 2.5 \mu\text{m}$). The resonance curves shift toward higher frequencies with increasing shell stiffness χ and broaden with increasing shell damping κ_s . The other parameters are as follows: driving pressure $P_A = 1 \text{ kPa}$; ambient pressure $P_0 = 100 \text{ kPa}$; surface tension of water $\sigma = 72 \text{ mN/m}$; polytropic exponent $\kappa = 1.07$; liquid density $\rho_L = 1000 \text{ kg/m}^3$; speed of sound in the liquid $c_L = 1500 \text{ m/s}$; liquid viscosity $\mu_L = 2 \text{ mPa s}$ (to also account for thermal damping); and $\sigma(R_0) = 20 \text{ mN/m}$.

which is then modeled by solving the full RP equation including the shell pressure terms (eqn [8]). The RP equation is non-linear owing to the intrinsic non-linearities in the ODE. However, the shell pressure terms are linear (*i.e.*, the surface tension is linearly dependent on the microbubble surface area) and can adopt negative values or values exceeding the surface tension of the surrounding medium (see the black dotted line in Fig. 6a), and the shell stiffness χ is constant throughout and independent of the surface dilatation (see Fig. 6b). Therefore, eqn 8 does not predict the experimentally observed non-linear microbubble dynamics such as compression-only behavior (de Jong et al. 2007) and the resonance-frequency shift with increasing acoustic pressure amplitudes for lipid-coated bubbles (Overvelde et al. 2010).

The breakthrough in modeling non-linear bubble dynamics came from Marmottant et al. (2005). Inspired by Langmuir-trough surface pressure-area isotherms of lipid monolayers (Fig. 6c), they limited the surface tension to zero for a compression below a certain buckling radius R_b and to the surface tension of the surrounding medium for an expansion above a so-called rupture radius R_r :

$$\sigma(R) = \begin{cases} 0 & \text{if } R \leq R_b \\ \chi \left(\frac{R^2}{R_b^2} - 1 \right) & \text{if } R_b \leq R \leq R_r \\ \sigma_{\text{water}} & \text{if } R \geq R_r. \end{cases} \quad (13)$$

The main idea is that during the compression phase, the lipid monolayer cannot withstand compression beyond the buckling radius, at which the shell buckles, resulting in a tensionless shell ($\chi = A d\sigma/dA = 0$); see

Figure 1j, where buckling is captured by ultrahigh-speed imaging. During the expansion phase, the average area per lipid molecule increases, either owing to shell rupture (*e.g.*, along lipid domains [Borden et al. 2006]) or owing to a more uniform increase in the area per lipid molecule, resulting in an increase of the effective surface tension until the surface tension σ_{water} of the surrounding medium is reached, again leading to a tensionless state ($\chi = A d\sigma/dA = 0$). In the elastic phase, the surface tension was assumed to increase monotonically with surface area, as in eqn (7). The solid black line in Figure 6a shows the surface-tension curve used in the Marmottant model. Note that purely elastic (linear) oscillations are limited to small amplitudes of oscillation around the initial bubble surface area with radius R_0 . Figure 6b shows the corresponding elasticity χ as a function of the surface area.

When the bubble is driven slightly outside the elastic regime, there are three possible oscillation scenarios, depending on the initial surface tension $\sigma(R_0)$ of the bubble. At $\sigma(R_0) < \sigma_{\text{water}}/2$, the bubble can reach the buckling state during compression while it remains in the elastic state during expansion. During the buckling phase, the shell stiffness vanishes and the bubble therefore experiences less resistance against compression than against expansion. This asymmetry in shell stiffness over an oscillation period induces compression-only behavior, as shown in Figure 6d. Similarly, at $\sigma(R_0) > \sigma_{\text{water}}/2$, the bubble experiences less resistance upon expansion than during compression once it is driven beyond the rupture radius. This drives the asymmetric expansion-only behavior (Fig. 6d). At $\sigma(R_0) = \sigma_{\text{water}}/2$, the bubble oscillations are symmetric.

The non-linear interfacial tension and corresponding shell stiffness have another implication for a coated bubble driven outside its elastic regime, namely a downshift of its resonance frequency. The downshift results from the effective averaging of the shell stiffness over elastic and non-elastic regimes. When the acoustic pressure is increased, the effective shell stiffness decreases. At high driving pressures, the contribution of shell stiffness becomes negligible and the resonance frequency approaches that of an uncoated bubble. This sudden increase in microbubble response above an acoustic pressure threshold has also been named *thresholding* behavior (Emmer et al. 2007). A detailed explanation of thresholding behavior is given by Overvelde et al. (2010).

Next to compression-only and driving-pressure-dependent resonance behavior, the Marmottant model has also proven successful in modeling the generation of subharmonics (Frinking et al. 2010; Sijl et al. 2010). It has been shown that subharmonics are induced by rapid change in shell stiffness with a small change in surface




Fig. 6. (a) Ad hoc surface-tension curves implemented in Rayleigh–Plesset–type equations to account for shell elasticity (reproduced from Segers *et al.* 2018a by permission of The Royal Society of Chemistry); (b) shell stiffness ($\chi = A d\sigma / dA$) curves corresponding to the surface-tension curves plotted in (a) (reproduced from Segers *et al.* 2018a by permission of The Royal Society of Chemistry); (c) surface tension as a function of area per lipid molecule measured at slow dilatational rates in a Langmuir trough for disaturated phosphatidylcholine (DSPC) (solid line) and dipalmitoylphosphatidylglycerol (DPPG) (dotted line; reproduced with permission from Marmottant *et al.* 2005); (d) “compression-only” (red curve) and “expansion-only” (black curve) behavior modeled by limiting the surface tension between zero and that of the surrounding medium (solid curves in a); (e) measured surface-tension curve compared with Marmottant’s ad hoc implementation (reproduced from Segers *et al.* 2018a by permission of The Royal Society of Chemistry); (f) measured non-linear dilatational elasticity as a function of surface area (reproduced from Segers *et al.* 2018a by permission of The Royal Society of Chemistry).

area (Sijl *et al.* 2010, 2011). Thus, the second-order derivative of the interfacial tension curve with respect to the bubble surface area is the driving factor behind the generation of subharmonics. However, Marmottant *et al.* (2005) implemented the dilatational interfacial tension and corresponding shell stiffness in a rather unphysical way, as they are discontinuous at the buckling and rupture radii (Fig. 6a, 6b). Therefore, the numerical

solutions of eqns (8) and (13) are sensitive to the integration time step of the ODE solver, as this sets $d^2\sigma/dA^2$. To circumvent this problem, Sijl *et al.* (2010) proposed extending the Marmottant model with two crossover functions for the transition from the regions with zero elasticity to the one with finite elasticity (see the blue curves in Fig. 6a, 6b). With the aim of getting closer to a more physicochemical surface-area–dependent surface

tension (*i.e.*, with decreasing elasticity for increasing area per lipid molecule) Paul et al. (2010) tested a quadratic elasticity model and an exponential elasticity model (see Fig. 6a, 6b). They once again pointed out the importance of a surface-area–dependent elasticity for non-linear bubble dynamics.

It has now become clear that the actual shape of the surface-tension curve and the initial surface tension are important for the correct prediction of non-linear radial bubble dynamics. In the modeling efforts, ad hoc assumptions have been made regarding the rheological properties of the microbubble shell, as measurement of the actual $\sigma(R)$ dependence of a lipid-coated microbubble interface is difficult at megahertz frequencies (Marmottant et al. 2005; Stride 2008). The difficulty lies in the extremely short timescales and small length scales of ultrasound-driven microbubble oscillations, which render useless the relatively slow measurements obtained by Langmuir trough (Lozano and Longo 2009) or bubble tensiometer (Lee et al. 2001). Furthermore, UCA bubbles are at least one order of magnitude smaller than the minimum cap radius in a bubble tensiometer (Alvarez et al. 2010), and the curvature of a monomolecular film may play a role in its viscoelastic properties (Kotula and Anna 2016). Recently, the dilatational shell elasticity curve of lipid-coated bubbles has been measured experimentally by controlling the surface area of monodisperse bubbles through the ambient pressure and measuring the resonance behavior from acoustic attenuation measurements (Segers et al. 2018a). The measured $\chi(A/A_0)$ curve, Figure 6f, has been integrated to find the $\sigma(A/A_0)$ curve, Figure 6e. The measured dilatational interfacial tension curve shows remarkable agreement with the initial assumptions of (Marmottant 2005), explaining the effectiveness of their model in the prediction of non-linear bubble dynamics. It has also been shown that the $\chi(A/A_0)$ curve is independent of the total bubble surface area for a given lipid composition (Segers et al. 2018a); in other words, it is independent of the bubble size. However, it is also shown that the shell stiffness is not constant in the elastic regime (see Fig. 6f), which may result in a change in acoustic properties of a dilute bubble suspension over time through gas loss.

Modeling shell viscosity

In contrast to the bubble-size–independent shell stiffness, the reported shell viscosity values are strongly dependent on the equilibrium bubble size. Shell viscosity κ_s has been extensively characterized through a direct fit of eqn (8) to experimental $R(t)$ curves, through optical light scattering (Tu et al. 2009) and through acoustic and high-speed imaging characterization (Morgan et al. 2000; van der Meer et al. 2007; Overvelde et al. 2010; Segers et al. 2018a). The data show an exponential

increase of κ_s with bubble size, which indicates an incomplete implementation of shell viscous dissipation in eqn (5). Shell viscosity has been shown to decrease with dilatation rate (van der Meer et al. 2007), which indicates shear-thinning behavior. Based on those experimental data, Doinikov et al. (2009a) included shear-thinning behavior in the RP equation in an empirical way. Furthermore, Segers et al. (2018a) have measured a dependence of κ_s on the bubble surface area (lipid-packing density), indicating that not only the dilatation rate is important but also surface dilatation itself. The future challenge is to clarify this matter, including the role of different shell components on the acoustic bubble response. Attempts have been made to model shell parameters based on molecular interactions (Stride 2008; Borden 2019). This route can be further explored, for example using molecular-dynamics simulations (Boek et al. 2005; van Opheusden and Molenaar 2011). Control over the bubble-size distribution has now been achieved (Fig. 1g; Segers et al. 2016b, 2017, 2019). Together with monodispersity, control over the acoustic response of coated bubbles would be highly valuable, as this would allow the tailoring of microbubble design for specific clinical applications, *e.g.* non-invasive blood-pressure measurements, and therapeutic applications [Miller et al. 2018], including sonothrombolysis and drug and gene delivery using bubbles and ultrasound.

Scattering and attenuation

Scattering leads to a loss of energy of the insonifying acoustic wave. The acoustic energy that is lost by the scattering of a single bubble, assuming that the scattering is purely spherical, can be expressed as the ratio of the scattered power to the incident acoustic intensity, also known as the scattering cross section σ_s :

$$\sigma_s = 4\pi r^2 \frac{|P_s(r)|^2}{|P_T|^2}, \quad (14)$$

with r the distance from the bubble where the pressure is measured, $|P_s(r)|$ the amplitude of the scattered pressure and $|P_T|$ the pressure amplitude of the incident acoustic wave (Hilgenfeldt et al. 1998). This expression also holds at the bubble wall, at $r = R_0$. The frequency-dependent scattering cross section can be calculated by using the power spectrum of $P_s(r)$ in eqn (14) instead of the total scattered power. Note that through P_s , the scattering cross section is now a function of the shell parameters and depends on the frequency and the pressure amplitude of the acoustic wave.

For small-amplitude bubble oscillations driven in the linear regime at low acoustic pressure amplitudes, the linearized scattering cross section Ω_s can be expressed as follows (de Jong et al. 1992; Leighton

1994):

$$\Omega_s = \frac{4\pi R_0^2}{\left((\omega_0/\omega)^2 - 1\right)^2 + \delta_{\text{tot}}^2}. \quad (15)$$

Equation (15) shows that for a bubble driven at resonance ($\omega = \omega_0$) and with a total damping of 0.25 (which is typical for UCA bubbles), the scattering cross section is two orders of magnitude larger than its geometric cross-sectional area.

In addition to scattering, energy of the insonifying ultrasound wave is dissipated through viscous damping, thermal damping and shell damping. The *total* energy loss of the acoustic wave owing to the scattering and damping can therefore be expressed as the ratio of the total energy loss per bubble to the intensity of the acoustic wave: the extinction cross section σ_e . It is found by multiplying the scattering cross section σ_s and the ratio of the total damping δ_{tot} to the radiation damping δ_{rad} (Medwin 1977).

The total amount of scattered and absorbed energy of an acoustic wave propagating through a dilute cloud of homogeneously distributed bubbles at concentration $n(R)$ of bubbles with radius R can now be obtained by summation over the scattering and extinction cross sections of all the individual bubbles present in the acoustic beam (de Jong *et al.* 1992; Raymond *et al.* 2014). This linearized approach only holds if the pressure wave scattered by a neighboring bubble at a distance d is much smaller than the average insonifying pressure field: $|P_s(d)|/|P_T| \ll 1$. At a bubble concentration n , the average distance between bubbles is $d = n^{-1/3}$, which, using eqn (14), results in the condition $n(R)^{2/3}\Omega_s \ll 1$ (Commander and Prosperetti 1989; Goertz *et al.* 2007). The total attenuation α of an ultrasound wave traveling through a bubble suspension is a result of the total energy dissipation resulting from the presence of bubbles. For linear bubble oscillations, it is given by

$$\alpha = -\frac{10}{\ln(10)} \sum_R \frac{\delta_{\text{tot}}}{\delta_{\text{rad}}} n(R) \Omega_s d, \quad (16)$$

with d the acoustic path length over which the sound wave interacts with the bubbles. Similarly, again for linear bubble oscillations, the backscatter coefficient η can be calculated as follows (Marsh *et al.* 1999; Gorce *et al.* 2000):

$$\eta = -\frac{1}{4\pi} \sum_R n(R) \Omega_s. \quad (17)$$

As discussed before, when the acoustic pressure is increased, the effective shell stiffness decreases. At high driving pressures, the contribution of shell stiffness then becomes negligible and the resonance frequency

approaches that of an uncoated bubble. The decrease of the resonance frequency with increasing acoustic pressure is shown in Figure 7a for measured attenuation spectra of a monodisperse microbubble suspension (Segers *et al.* 2016a). The shift in resonance frequency can be extremely useful in contrast imaging schemes such as power modulation (Eckersley *et al.* 2005). The transmit frequency can be chosen such that it coincides with the microbubble resonance frequency at the higher acoustic pressures, generating a strong echo only when the transmit power exceeds the threshold for the resonance-frequency downshift.

For non-linearly oscillating bubbles, attenuation can be modeled by solving the full non-linear RP equation to obtain the radius time curves of all bubbles in the size distribution. Then the scattered pressure can be calculated, using eqn (9), and subsequently the scattering cross section σ_s . Attenuation is then calculated through integration over the size distribution (Hilgenfeldt *et al.* 2000; Segers *et al.* 2016a). Note that for contrast bubbles, P_s is dependent not only on the ultrasound frequency but also on the acoustic driving pressure. As a consequence, the acoustic bubble response will depend not only on the local pressure at the bubble position in the transmit beam (typically extracted from hydrophone measurements in a calibration tank) but also on the attenuation experienced by the transmit beam on its path to the bubble, which will lower the local acoustic driving pressure. Thus, to accurately model attenuation of a sample of contrast bubbles, the full two-way coupled interaction of the non-linearly oscillating bubbles with the complete ultrasound field must be taken into account (*e.g.*, through forward integration) (Segers *et al.* 2018b). For acoustic characterization of UCAs, the effect of a non-uniform acoustic driving pressure can be minimized by using a narrow bubble sample holder such that it forms a sheet of bubbles in the acoustic characterization beam rather than a 3-D volume (Segers *et al.* 2018b).




Fig. 7. (a) Attenuation of a monodisperse bubble sample (monodispersity achieved by acoustic sorting) measured at pressures ranging from 5 to 75 kPa (Segers and Versluis 2014); (b) modeled attenuation (reproduced with permission from Segers *et al.* 2016a).

BUBBLE NON-SPHERICITY AND ASYMMETRY

While spherical-bubble models provide a basic fundamental understanding of bubble behavior and the influence of the physical parameters of the surrounding environment, the assumption of spherical symmetry is often challenged. Then, modeling the bubble behavior requires the inclusion of the effects of surface instabilities and neighboring membranes or walls. This breaking of symmetry deeply affects the fundamental behavior of a bubble, namely its resonance frequency and quality factor, and enables, or amplifies, higher-order phenomena such as streaming.

Two main mechanisms can destabilize the spherical shape of a bubble during ultrasound-induced oscillations in the free field: Rayleigh–Taylor–type instability and parametric instability. Rayleigh–Taylor instability can occur at the point of maximum bubble compression while the bubble wall is experiencing maximum acceleration. It can only dominate after repeated, strong collapse events of the bubble or during the after-bounces that follow violent bubble collapse occurring at a low

driving frequency (e.g., in sonoluminescence) (Hilgenfeldt et al. 1996). In such a configuration, shape destabilization results in pinch-off, jetting or bubble breakup, and the bubble fate becomes unpredictable. Parametric instabilities, on the other hand, arise during long driving pulses. They grow from an infinitesimally small perturbation on the bubble interface and develop with certain mode preferences depending on the bubble size and driving frequency. Such instabilities are often observed for UCAs (see a typical example in Fig. 8a; Raymond et al. 2016), especially when using long driving pulses (e.g., for therapeutic applications).

Non-spherical oscillations: Modeling

One of the first models for spherical instability was developed by Plesset (1954). In essence, the derivation considers a nearly spherical bubble, with a distortion of small amplitude from the spherical shape that can be written in the form of spherical harmonics:

$$R(t, \theta, \phi) = R(t) + a_n(t)Y_n(\theta, \phi), \quad (18)$$




Fig. 8. (a) Evolution of the buildup of surface mode vibrations for echogenic liposomes. Asymmetric patterns indicative of surface mode oscillations are first visible, after several cycles of acoustic excitation (copyright Institute of Physics and Engineering in Medicine. Reproduced by permission of IOP Publishing from Raymond et al. 2016. All rights reserved). (b) Surface mode vibrations for BR-14 (Bracco Research) contrast agent. (Top) Applied acoustic pressure; (middle) radius-time curve; (bottom) evolution of mode 2, which saturates after about 4 cycles. Note the period-doubling behavior of the surface mode vibration (reproduced with permission from Dollet et al. 2008). (c) Top-view and side-view ultrahigh-speed imaging of ultrasound-driven contrast microbubbles (reproduced with permission from Vos et al. 2011). (d) Shift in the resonance frequency of a cylindrical bubble of length l as a function of initial length l_0 and axial location e within an open-ended tube of length L and radius R_{tube} (adapted from Oguz and Prosperetti 1998). In the top panel, $L/R_{\text{tube}} = 10$ and $e/L = 0.5$; in the bottom panel, $L/R_{\text{tube}} = 10$ and $e/L = 0.17$.

with Y_n the spherical harmonic mode of order n and a_n its amplitude; $R(t)$ is assumed to obey the spherical RP equation (eqn [1]). Using an analogous derivation of the RP equation, and following a first-order Taylor expansion, we find

$$\ddot{a}_n + \frac{3\dot{R}}{R}\dot{a}_n - \left((n-1)\frac{\ddot{R}}{R} - \frac{(n-1)(n+1)(n+2)\sigma}{\rho_L R^3} \right) a_n = 0. \quad (19)$$

As before, the overdots represent the time derivatives. This equation is a Hill equation, or a generalized Mathieu equation. The eigenfrequency of the mode directly follows from the small oscillation limit:

$$\omega_{0n} = \frac{(n-1)(n+1)(n+2)\sigma}{\rho_L R_0^3}. \quad (20)$$

In this potential flow approach, the velocity field is described by the gradient of the velocity potential $\nabla\phi$, which is a function of space and time. This description, however, does not include any form of damping or viscosity, which results in parametric mode behavior with a threshold of $\dot{R} = 0$. This model was later picked up by [Ceschia and Nabergoj \(1978\)](#) and [Nabergoj and Francescutto \(1979\)](#), who applied a similar principle by using a Lagrangian approach to find the equation of motion of the bubble from the RP equation and the governing equation of the modes. They assumed purely sinusoidal bubble oscillations; the vorticity is neglected and the viscosity is introduced solely by assuming a vanishing tangential stress. Note that this last assumption is debatable for coated microbubbles, owing to the presence of the shell. This derivation, using a known solution for the resulting Mathieu equation, provides a first estimate of the threshold for the growth of each parametric mode (*i.e.*, the pressure leading to bubble instability). Despite these simplifications, the results have demonstrated good agreement with experimental observations ([Fig. 8b](#); [Dollet et al. 2008](#); [Versluis et al. 2010](#)).

Around the same time, [Prosperetti \(1977b\)](#) provided a more rigorous theoretical framework to study surface oscillations of a bubble. Vorticity was accounted for by writing the curl as the sum of a poloidal and a toroidal component. Application to a non-driven bubble provides the same mode frequency and decay rate as given by [Nabergoj and Francescutto \(1979\)](#). Based on the reference work of Prosperetti, subsequent studies ([Hilgenfeldt et al. 1996](#); [Wu and Roberts 1999](#)) have lifted some assumptions on the vorticity and instead limited the range of the curl to a small boundary layer whose

thickness δ_{BL} depends on the bubble size and the mode number:

$$\delta_{BL} = \min\left(\sqrt{\frac{\mu_L}{\rho_L \omega}}, \frac{R_0}{2n}\right). \quad (21)$$

Including this short-range vorticity modifies the second term of [eqn \(19\)](#), where $3\dot{R}/R$ must be replaced by the damping term $B_n(t)$ given by [eqn \(13\)](#) of [Hilgenfeldt et al. \(1996\)](#).

Two major research directions evolved from this founding work. First, the coupling between bubble motion and surface modes is of particular importance for local drug delivery that involves bubble translation and bubble oscillations. This problem has been mainly investigated in an axisymmetric geometry with viscous effects ([Benjamin and Ellis 1990](#); [Shaw 2009](#)) or without ([Shaw 2006](#)), demonstrating that shape oscillations can result in self-propulsion and bubble translation. This phenomenon is distinct from radiation forces. Some attention has also been given to the coupling between the surface modes themselves ([Mei and Zhou 1991](#); [Feng and Leal 1993](#); [Mao et al. 1995](#); [Harkin et al. 2013](#)).

The second direction consists in modeling the impact of the shell on the existence of surface modes. A few recent studies have investigated the effect of an elastic shell on the parametric oscillations of a coated bubble ([Liu et al. 2012](#); [Liu and Wang 2016](#); [Liu et al. 2018](#)). These articles consider linear elasticity theory for the shell, with or without the effect of viscosity, and have determined a correction for the eigenfrequency of the surface modes to account for the presence of the elastic shell. However, polymer-coated ultrasound contrast microbubbles typically fail to display such extreme elastic behavior owing to the buckling or breakup of the fairly rigid shell ([Fig. 1h](#); [Marmottant et al. 2011](#)). The influence of a non-linear phospholipid shell, which constitutes the vast majority of contrast microbubble shells, remains mostly unexplored.

Bubbles near a wall

The presence of a boundary near the oscillating bubbles is difficult to avoid, both *in vitro* and *in vivo*, and is known to influence the response of the microbubble in a non-trivial way, affecting its oscillation amplitude and non-linear response and shifting its resonance frequency. When the bubble is targeted, and therefore adherent to the wall, bubble–wall interactions are inevitable and typically desirable. It is therefore of utmost importance to fundamentally understand the effect of a neighboring wall on the bubble response. *In vivo*, it is key to enabling many novel applications that require a very fine control of bubble dynamics. *In vitro*, it is

essential to extract meaningful and precise mechanical parameters describing the bubble and its shell as well as its interaction with the boundary.

Physically, the presence of a wall has two distinct effects whose magnitudes depend on its mechanical properties: (i) the bubble interacts with its own acoustic reflection returning from the interface, often described as the *image bubble*, and (ii) the flow around the bubble deviates from the spherical flow derived from the RP equation, owing to the presence of the wall.

The simplest treatment of the boundary was proposed by Lamb (1932) and consists in adding a pressure term to the RP equation representing the pressure reflected at the interface. Since the bubble is considered to be small compared with the acoustic wavelength, phase lag is disregarded. The reflection decreases the resonance frequency by a factor of $\sqrt{2/3}$. Much later, Doinikov et al. (2011) investigated the problem from a potential flow perspective. They considered a thin flexible wall and added bubble translation as a result of radiation forces. In this picture, the resonance frequency decreases for a rigid wall and increases for an elastic wall, compared with the free-bubble case. This model was later confirmed experimentally by the same group (Doinikov and Bouakaz, 2015). This result is well aligned with that of Oguz and Prosperetti (1990), who used perturbation theory to derive a model describing the extreme case of a bubble oscillating near a free surface. That work shows that, near a free surface, the resonance frequency should increase by about 40%.

With respect to microbubble oscillations near a wall, of special interest are the non-linear echoes of the microbubbles. These non-linearities are essential for harmonic imaging, including pulse inversion and amplitude modulation, designed to boost the contrast-to-tissue ratio. Suslov et al. (2012) have shown that the dominant harmonic frequencies that are emitted depend on the bubble-to-wall distance. They also suggest an increased chance of period-doubling behavior for bubbles in contact with the wall. The most important effect of a boundary on the bubble behavior, however, lies in the loss of spherical symmetry of the bubble oscillations. Such non-spherical oscillations are systematically observed experimentally (e.g., Fig. 8c), but they are generally overlooked in the modeling work. Recently, Lajoinie et al. (2018) proposed a model for bubbles adherent to or in contact with a boundary, based on a segmentation of the bubble along the inclination angle and with the bubble dynamics solved on a per-segment basis. Despite its extreme simplicity, this model recovers the non-spherical shapes observed experimentally and quantifies the effect of the boundary on the bubble oscillation amplitude and subsequently on streaming (discussed later

under “Modeling of higher-order effects”). Much work, however, remains to be done to achieve a rigorous description of non-spherical bubble oscillations near a boundary, especially in relation to resonance shift, and of non-linear emissions.

Bubbles in a tube

As blood-pool agents, contrast microbubbles circulate within the confines of the blood vessel network (*i.e.*, within tubes of various sizes lined with compliant walls). The simplified 1-D case of a bubble of length l oscillating without surface tension or friction in the center of a rigid tube of length L yields (Sun et al. 2009):

$$\rho_L \ddot{l}(L-l) = P_0 \left(\frac{l_0}{l} \right)^\kappa - P(L). \quad (22)$$

After linearization around $l = l_0(1 + \varepsilon)$ for small amplitude $\varepsilon \ll 1$,

$$[\rho_L l_0(L-l_0)]\ddot{\varepsilon} + \kappa P_0 \varepsilon = -P_A, \quad (23)$$

with eigenfrequency

$$\omega_0 = \sqrt{\frac{\kappa P_0}{\rho_L l_0(L-l_0)}}. \quad (24)$$

Owing to the incompressibility of the liquid, it is clear that significant pulsations are only possible if the tube has an open end. Oguz and Prosperetti (1998) proposed a more complete incompressible disk bubble model that includes the effects of surface tension, the position e of the bubble along the tube axis, and tube radius R_{tube} (Fig. 8d). This model also provides a first-order estimate for the thermal and viscous damping experienced by such a bubble.

In the same paper, Oguz and Prosperetti (1998) also proposed a model for small bubbles obtained by projecting the velocity potential in the liquid on to the Legendre polynomial base. According to this model, a bubble 10 times smaller than the tube is still strongly affected by the geometry, even when the tube in question is short. Going further, Leighton (2011) has shown, by changing the inertial term in the RP equation, that a long rigid tube 1000 times larger than the bubble can have a significant effect on its behavior.

Let us now consider a bubble trapped in a long tube, replicating a vessel, with a diameter of the same order as the bubble size. If we assume that the compressibility of the surrounding medium does not allow for large-amplitude oscillations (e.g., in water), significant bubble motion can only arise from large compliance of the vessel wall, which allows for bubble motion in three

dimensions. The compliance of a blood vessel and its response to stress are complex to model in themselves (Misra and Singh 1983; Humphrey and Na 2002), in particular since blood vessels behave in a non-linear fashion. Qin and Ferrara (2006) have proposed a model that describes the axisymmetric bubble oscillations in a non-linear compliant vessel by adding a pressure jump across the vessel-wall location. There, the properties of the blood vessel are fitted to stress measurements on frog mesenteric capillaries. An important conclusion of this model is that, on the one hand, the bubble behavior is modified by the presence of the wall, and on the other hand, the stress experienced by the vessel wall is far greater if a bubble is present within the system during insonation. This model was later amended by Qin and Ferrara (2007) and numerically solved to include the effect of soft tissue around the vessel, providing an extensive study of the impact of wall compliance and its geometric parameters. This line of modeling is of major importance for applications such as the controlled opening of the blood–brain barrier. Owing to the complexity of such modeling, most investigations are performed numerically, but new biomedical applications of bubbles that require more precision and control would also benefit from simplified analytical models.

Bubble jetting

When a bubble undergoes collapse in an asymmetric environment, it forms a jet. The asymmetry can result from the presence of a nearby soft (or gaseous) interface (Krishnan *et al.* 2017), a rigid boundary, other bubbles in the vicinity (Han *et al.* 2015; Kwan *et al.* 2016) or even a non-linear acoustic wave (Ohl and Ikink 2003). Jet formation can have severe consequences; the high jet velocity is crucial in bubble-induced erosion and in bubble cleaning applications (Fernandez Rivas *et al.* 2012; Verhaagen and Fernandez Rivas 2016). Jetting can lead to the breakup of bubbles into numerous daughter bubbles, the destruction of the agent, or the deposition of the shell material onto the rigid boundary (Roovers *et al.* 2019). Jetting becomes more prominent as bubble size increases (owing to reduced stabilization by surface tension), as frequency decreases and as pressure increases (owing to increased inertia).

In terms of fluid dynamics, bubble jetting can be described using fairly strong assumptions: the flow is considered inviscid and irrotational, leading to a potential flow description. This approach was first presented by Plesset and Chapman (1971), who predicted jet velocities on the order of 100 m/s. The shapes that were computed based on this approach were later experimentally verified by Lauterborn and Bolle 1975 (Fig. 9a) with remarkable agreement. Going beyond this initial




Fig. 9. Bubble jetting. (a) Calculated shape of a jetting bubble (reproduced with permission from Lauterborn and Bolle 1975); (b) jetting observed for a microbubble and a schematic representation of jet formation (reproduced with permission from Postema *et al.* 2005b); (c) jetting observed for a 3.0 μm lipid-coated bubble (reproduced with permission from Lajoinie *et al.* 2018); (d) SonoVue ultrasound contrast microbubbles driven at 200 kHz jetting in a capillary, with ultrasound beam (red dashed line; reproduced with permission from Cleve *et al.* 2019).

description, Blake *et al.* (1997) implemented the presence of the boundary using a Green's function for the velocity potential to account for the source (the bubble) and its image. This Green's function enforces a no-flow condition across the boundary.

To better account for the large jet velocities involved and the presence of an acoustic wave, Wang and Blake (2010) extended these formulations to slightly compressible fluids, demonstrating a measurable effect of compressibility on bubble jetting and in particular on the orientation of the jet as compared with the propagation direction of the ultrasound wave. Next to bubble size, ultrasound frequency and pressure, jetting is also very sensitive to the initial distance between the bubble and the rigid boundary (Fig. 9b–d) (Prentice *et al.* 2005; Wang *et al.* 2015). In particular, the problem was treated by Brujan (2017) using weakly compressible theory, showing that jet velocity rapidly increases as the initial bubble–boundary distance increases, while the total amount of kinetic energy in the jet overall decreases.

Biological tissues present a wide range of mechanical properties but are nearly all flexible in the sense that they can be deformed during bubble oscillations. This is true for cell membranes as well as for blood-vessel walls. It is therefore of prime importance to describe the effect of soft surfaces on jetting, which is expected to be a major cause of damage *in vivo*. It has been shown that the jet direction can be reversed when the substrate

material becomes very soft, namely when it becomes easier to pull the elastic material than to overcome the water inertia (Gibson and Blake 1982; Brujan et al. 2001; Li et al. 2018). There have, however, been only a few studies on the transition regimes and on its effect in biological tissues (Chen et al. 2011).

Modeling bubbles in tissue and soft matter

Given the complex nature of biological tissues and the interest in novel extravasating agents and bubble precursors, it is important to study the behavior of bubbles in viscoelastic materials. In particular, the bubble resonance frequency is known to change significantly with the elastic modulus of the enclosing medium. A number of mechanical models have been developed—initially based on Kelvin–Voigt models (Macosko 1994) and later on Maxwell models, both linear (Allen and Roy 2000a) and non-linear (Allen and Roy 2000b; Naude and Mendez 2008)—demonstrating the change in resonance frequency as a result of the elastic modulus of the bubble surroundings. De Corato et al. (2019) investigated the dynamics of large bubbles ($>50\ \mu\text{m}$) immersed in a yield-stress fluid using theory and numerical simulations. They quantified the viscoelastic and viscoplastic response of the material using the model developed by Saramito (2009). In another notable example, Yang and Church (2005) investigated the increased threshold for subharmonic emissions in these materials. Linear and non-linear viscoelastic models are more extensively reviewed by Dollet et al. (2019).

MODELING HIGHER-ORDER EFFECTS

Streaming and shedding

Acoustic streaming is a phenomenon whereby an oscillating flow generates a non-linear, second-order steady flow (Fig. 10a, 10b). In particular, it occurs in the presence of walls, along which viscous effects are localized in a boundary layer of typical thickness $\delta_{\text{BL}} = \sqrt{\mu_{\text{L}}/\rho_{\text{L}}\omega}$, with ω the angular frequency. Rayleigh (1884) was the first to describe acoustic streaming theoretically. He showed that an oscillatory flow of velocity $U(x)\cos\omega t$ along a wall (x being a coordinate along the wall) causes a steady-state streaming flow of velocity u_s such that $u_s(x) = -(3/4)U(x)U'(x)/\omega$ along the wall (e.g., Lighthill 1978); to be rigorous, this applies only if the streaming Reynolds number $u_s\rho_{\text{L}}\ell/\mu_{\text{L}}$ is much lower than 1 (ℓ being the typical scale over which streaming takes place).

Acoustic streaming can be generated by an oscillating bubble close to a wall (Marmottant and Hilgenfeldt 2003) (Fig. 10c). It is thought to be a key transport mechanism for drug release from drug-loaded UCAs (Luan et al. 2014), and one of the main mechanisms of

sonoporation through the induced shear stress on a cell layer. To theoretically assess the latter effect in the specific context of UCAs, Doinikov and Bouakaz (2010) computed the shear stress associated with streaming. Generally speaking, it is of order $\tau_{xz} \approx \mu_{\text{L}}u_s/\delta_{\text{BL}}$, z being the coordinate away from the wall. Hence, $\tau_{xz} \approx \sqrt{\rho_{\text{L}}\mu_{\text{L}}/\omega} U(x)U'(x)$. Doinikov and Bouakaz (2010) also computed the velocity U related to a micro-bubble located at a distance d from the wall and undergoing volumetric oscillations of radius $R(t)$ forced by an acoustic field, using a modified RP equation with the model by de Jong et al. (1994) for the shell term, and obtained the corresponding shear stress. They showed that it displays a maximum at a finite radial distance along the wall, and estimated its potential implications for sonoporation.

Chomas et al. (2001) presented one of the first systematic studies of UCA destruction under insonation. The most violent destruction mechanism is fragmentation into smaller bubbles at high amplitude, but at lower amplitude they evidenced a progressive deflation of the UCA, which they argue is owing to acoustically driven diffusion. Actually, when lipid monolayers get sufficiently compressed, they can shed some material in the surrounding liquid. This mechanism has been recognized as important in the context of the slow dissolution of lipid-coated bubbles (Borden and Longo 2002) (Fig. 1i) and has been proposed as key for the understanding of UCA deflation under prolonged insonation. Using fluorescence imaging, Borden et al. (2005) evidenced ultrasound-induced shedding and quantified the time evolution of bubble deflation toward an equilibrium (around $2\ \mu\text{m}$ in radius) (Fig. 10f). They showed different mechanisms of shedding, depending on lipid composition, from submicrometer particle expulsion to budding, then to buildup and expulsion of larger lipid aggregates as the shell becomes more cohesive. Similar observations have been made by Kooiman et al. (2017) using ultrahigh-speed imaging. Kwan and Borden (2012) argue that the microscopic mechanisms initiating shedding are the local collapse of the lipid monolayer and the subsequent aggregation of new folds. Guidi et al. (2010) subjected UCAs to repeated low-amplitude ultrasonic pulses at a frequency of 2 MHz, and consistently observed deflation for bubbles with an initial radius below $3\ \mu\text{m}$ toward a stable radius of $1.4\ \mu\text{m}$, but no deflation for larger bubbles.

The time evolution of the deflation process is qualitatively similar to the one reported by Borden et al. (2005), with the fastest deflation rate near resonance, where UCAs are more prone to dissolve or shed their coating owing to large volumetric oscillations. Viti et al. (2012) focused on megahertz bubble oscillations using ultrahigh-speed imaging while the bubbles underwent




Fig. 10. (a) Microstreaming field as a result of an oscillating SonoVue microbubble (reproduced with permission from [Pereno et al. 2018](#)). (b) Lipid shedding and transport as a result of acoustic streaming (reproduced with permission from [Versluis 2013](#)). (c) Simulation of the acoustic streaming generated by an oscillating bubble of radius a (the half-circle) in contact with a plane wall located at $z=0$. Only half of the space is sketched, owing to axisymmetry about the $x=0$ axis. The solid curves are the streamlines, and the direction of velocity is indicated with the arrows; in particular, the streaming flow goes away from the wall above the bubble (reproduced with permission from [Marmottant et al. 2006](#)). (d) Lipid shedding from a targeted bubble and transport by acoustic streaming. (Top) Schematics of the shedding process of the released material (red) with the calculated streamlines (solid black lines); (bottom) experimental recording of the release of the fluorescent material from a targeted oscillating microbubble driven at a pressure of 331 kPa, showing transport over a distance several times larger than the bubble size (reproduced with permission from [Lajoinie et al. 2018](#)). (E) Streak imaging of two ultrasound contrast agents of equilibrium radius $2.1 \mu\text{m}$ (top) and $2.0 \mu\text{m}$ (bottom), showing the displacement in the direction of propagation of the acoustic wave. The acoustic forcing represents 20 cycles at amplitude 380 kPa and frequency 2.25 MHz. These snapshots are overlaid with simulated curves of the time evolution of the bubble radius (reproduced with permission from [Dayton et al. 2002](#)). (F) Evolution of the radius of a lipid-coated microbubble subjected to repeated acoustic pulses (frequency 2.25 MHz, peak negative pressure 400 kPa, pulse repetition frequency 0.5 Hz; data kindly provided by Mark Borden).

(slower) deflation. They showed that deflation occurs in discrete steps, and that the radius time oscillations usually evolve from being rather symmetric just after a deflation event to compression-only behavior after some

time in a non-deflating state, thereby suggesting that the lipid shell reforms after each shedding event.

The idea that a sufficiently compressed lipid monolayer collapses and expels excess lipids is the basis of

the surfactant-shedding model of O'Brien et al. (2011), based on phenomenological dependences of molecular diffusivity and surface viscosity on surface concentration of lipids. This model reproduced the deflation results of Borden et al. (2005). To clarify lipid shedding dynamics under insonation, Luan et al. (2014) used high-speed fluorescence imaging at 150,000 frames/s. They showed that shedding may occur already within a few ultrasound pulses, in contrast to the picture of a (relatively slow) build up of expelled material. Lajoinie et al. (2018) refined this setup by coupling it with ultrahigh-speed imaging. They showed that non-spherical oscillations of a lipid-coated bubble in contact with a wall lead to local oversaturation and shedding, and that the subsequent transport of the shed lipid is mediated by acoustic streaming (Fig. 10d).

Radiation forces

Any body of volume V in a space-dependent pressure field p experiences a force equal to $-V \nabla p$, provided that the size of the body is much smaller than the acoustic wavelength. If the body is a bubble in an acoustic field, this can lead to a strong time-averaged force, owing to the large gas compressibility. This force is termed *acoustic radiation force* or, in the bubble context, *Bjerknes force* (Bjerknes 1906; Crum 1975; Leighton 1994). Two radiation forces are usually distinguished: primary forces, when the bubble responds directly to the external applied pressure field (typically from a transducer), and secondary forces, when a given bubble reacts to the pressure field re-emitted by a second neighboring bubble or, in the case of a neighboring wall, by the image bubble. These forces are maximal at the resonance frequency of the bubble. For traveling waves, the primary radiation force always acts in the direction of ultrasound wave propagation.

Dayton et al. (2002) characterized the influence of primary radiation forces on UCAs. They showed that a bubble with a radius of $1.5 \mu\text{m}$ can be displaced by as much as $5 \mu\text{m}$ by a 20-cycle pulse with a frequency of 2.25 MHz at an amplitude of 180 kPa (Fig. 10E). However, assessing radiation forces quantitatively turns out to be difficult because the force balance involves hydrodynamic forces, including added mass, drag and history force. Dayton et al. (1999), Zhao et al. (2004), Rychak et al. (2005), Lum et al. (2006) and Frinking et al. (2012) have all used primary radiation forces as a strategy to achieve targeted drug delivery.

Segers and Versluis (2014) proposed a novel use of primary radiation forces: using the dependency of this force on bubble resonance, they were able to deflect and isolate resonant bubbles from the main flow of a polydisperse suspension of microbubbles and collect them using a dedicated microfluidic device. A simple force-balance

model for the acoustic sorting showed very good agreement with the experiment. Thus, they were able to narrow down the size distribution and thereby to improve the sensitivity of these UCAs by more than 10 dB (Segers et al. 2018b).

Secondary radiation forces lead to attraction of bubbles of similar size and repulsion of bubbles of different size if the driving frequency is in between the two resonance frequencies (Leighton 1994). The effect of secondary radiation forces on UCAs has been studied by Garbin et al. (2011) and Kokhuis et al. (2013) for targeted microbubbles. They confirmed that UCAs of similar sizes attract. For bubbles isolated from a neighboring wall using optical tweezers, it has been shown that using the same kind of force balance as Dayton et al. (2002), one must include nontrivial added mass and history forces stemming from delayed viscous effects caused by the back-and-forth motion of the bubble in the vorticity generated in its own wake (Garbin et al. 2009).

MODELS FOR NOVEL AGENTS

The creation of new classes of microbubble agents also triggers the need for novel models. First, bubbles can be loaded with functional nanoparticles as a method to enhance drug delivery. Such self-assembled systems include: microbubbles that are conjugated with liposomes (Kheirloom et al. 2007; Lentacker et al. 2010; Luan et al. 2012; Peyman et al. 2012; Yan et al. 2013), echogenic liposomes (Paul et al. 2012; Raymond et al. 2015), colloids (Poulichet and Garbin 2015; Huerre et al. 2018) and polymeric nanoparticles (Borden and Rege 2012; Burke et al. 2012; Mørch et al. 2015; Z. Chen et al. 2019; Jamburidze et al. 2019) (Fig. 11a, 11b). Encapsulation of plasmonic, photoacoustic or magnetic nanoparticles allows for multimodality contrast imaging, with the aim of combining imaging techniques and thereby compensating for the inherent weaknesses of one modality by exploiting the strengths of another. Similarly, bubbles can be added to other constructs to add or enhance a specific functionality. For example, acoustic cluster therapy (Healey et al. 2016) utilizes an agent comprised of clusters of microdroplets conjugated with Sonazoid bubbles, where the microbubbles lower the activation threshold for the formation of gas bubbles, or emboli, from the microdroplets upon ultrasound exposure. This confines systemically administered chemotherapy drugs within the tumor to enable diffusion. To overcome the high washout rates of cardiac stem cells, Naaijken et al. (2013) decorated adipose-derived stem cells with functionalized microbubbles (Fig. 11c), effectively creating echogenic complexes, dubbed StemBells, that are then susceptible to acoustic radiation force. The behavior of these complexes has been modeled by




Fig. 11. Modeling novel agents. (a) Liposome-loaded microbubble. Overlay: bubble—bright field; lipids—red DiI fluorescence; liposomes—green fluorescence (reproduced with permission from Luan *et al.* 2012). (b) Nanoparticle-coated microbubble (reproduced with permission from Sulheim *et al.* 2019). (c) A StemBell: stem cells decorated with targeted microbubbles for localized stem cell delivery using ultrasound radiation force (reproduced with permission from Woudstra *et al.* 2018). (d) Collection of microbubbles formed from vaporized perfluorocarbon nanodroplets (reproduced with permission from Williams *et al.* 2013). (e) Nanocups (reproduced with permission from Kwan *et al.* 2015). (f) Gas vesicles (reproduced with permission from Lakshmanan *et al.* 2017).

Kokhuis *et al.* (2017) based on a modified RP equation, showing both theoretically and experimentally how radiation forces can be used to push the StemBells out of the mainstream flow and toward the vessel wall. This approach leads to a significant increase in stem cell delivery (Kokhuis *et al.* 2015; Woudstra *et al.* 2016) to the damaged area of the heart. Finally, nano-sized agents, including nanobubbles, nanodroplets and gas vesicles, are a class of their own. Models describing the behavior of these novel contrast agents are thus needed to understand and further exploit their linear and non-linear contrast features. A more extensive discussion on these novel agents is provided in another review of this issue on future directions (Stride *et al.* 2020).

Modeling bubbles for multimodality imaging

Since microbubbles are unparalleled contrast agents for ultrasound imaging and display remarkable (non-linear) properties, there is great interest in driving them with other sources than ultrasound (Owen *et al.* 2018). In particular, researchers have combined microbubbles with plasmonic nanoparticles (Wilson *et al.* 2012), magnetic nanoparticles (Stride *et al.* 2009; Vlaskou *et al.* 2010) or an additional liquid or polymeric layer that contains a dye (Lajoinie *et al.* 2014, 2017a; Visscher *et al.* 2019) (Fig. 1e, 1f). These constructs are light-sensitive so that they can generate contrast in both ultrasound and photoacoustic imaging. Heat transfer in an acoustically driven bubble was investigated decades ago, in particular by Prosperetti

(1977a), which led to the well-known thermal damping in the modified RP equation (discussed earlier in this article). The thermal exchanges in a bubble driven into oscillations using light are, however, different from the classical picture, and one can no longer assume polytropic behavior of the gas. Heat diffusion must be resolved in space and time, together with the momentum, to describe the bubble oscillations. Initial models have been proposed for bubbles coated with a dye-doped oil layer (Lajoinie *et al.* 2017b) that qualitatively explain the experimental observations. Further modeling is required to accurately describe and understand both linear and non-linear bubble oscillations for these systems. In particular, this modeling must include the partial pressures of the surrounding liquid for multilayered bubbles and a more detailed description of the optical and mechanical properties of the bubble shells once they are coated with plasmonic nanoparticles.

Modeling bubbles formed from droplet vaporization

A sufficiently intense burst of ultrasound can vaporize otherwise inert droplets, forming echogenic microbubbles, a process termed acoustic droplet vaporization (ADV) (Kripfgans *et al.* 2000; Rapoport *et al.* 2007; Williams *et al.* 2013; Sheeran *et al.* 2014) (Fig. 11d). The freshly formed bubbles are stabilized over timescales of seconds to minutes by the same coating material initially used to encapsulate their liquid precursors (Reznik *et al.* 2013). There is great interest in the use of these agents

for both diagnosis and therapy, for example, as boosters for high-intensity focused ultrasound therapy (Zhang and Porter 2010; Phillips et al. 2013), embolotherapy (Zhang et al. 2010), dissolved oxygen scavengers (Radhakrishnan et al. 2016) and vehicles for drug delivery (Rapoport 2012).

Having a diameter in the micrometre range is a disadvantage for a number of applications because the bubbles are confined to the blood vasculature and cannot easily extravasate into the interstitium. Liquid perfluorocarbon nanodroplets, however, have been studied as novel extravascular contrast agents for ultrasound. With a typical size of a few hundred nanometers, these droplets have the ability to extravasate selectively into porous tumor tissue—presumably through the enhanced permeability and retention effect (Maeda et al. 2000)—where they can then be vaporized for imaging or drug delivery purposes.

The mechanisms underlying droplet nucleation have received considerable interest (Kripfgans et al. 2000; Sheeran et al. 2011; Shpak et al. 2014). This paragraph now focuses on bubble stabilization upon vaporization for the purpose of generating stable contrast on clinically relevant timescales (hundreds of milliseconds). Reznik et al. (2013) studied the pathways after initial vaporization, demonstrating the complex interaction of the vapor bubble with its surrounding, including coalescence, gas diffusion and rectified heat transfer (Shpak et al. 2013a; Doinikov et al. 2014). Shpak et al. (2013b) simulated the role of gas in ultrasonically driven vapor-bubble growth and underlined the fundamental role of gas diffusion during acoustic forcing. They showed that an amount of air as low as 10% of the saturation concentration in the perfluorocarbon is enough to allow the bubble to survive the first collapse. Mercado-Shekhara et al. (2019) exploited this rapid diffusion property for an ultrasound-mediated gas-scavenging technology for dissolved oxygen. There, the oxygen transfer is driven by the gas concentration gradients resulting from droplet vaporization. Outside the context of ADV, Sarkar et al. (2009), Kwan and Borden (2010) and Segers et al. (2016b) have also modeled the important effects of gas exchange for bubble stability, including the effects of lipid formulation (Széjjártó et al. 2012; Garg et al. 2013; van Rooij et al. 2015).

Modeling nanobubbles and nanovesicles

In recent years, nanobubbles have attracted considerable attention. Their existence, however, seems to be paradoxical. A simple classical estimate based on the Laplace pressure inside such bubbles suggests that they should dissolve in microseconds. However, once stabilized by surface heterogeneities, pinning of the three-phase contact line can occur and these

surface nanobubbles can be stable for days as the gas influx from the gas-oversaturated aqueous surrounding and the outflux owing to Laplace pressure balance (Lohse and Zhang 2015). One such system developed in the context of cavitation therapy is a novel ultrasound-responsive single-cavity polymeric nanoparticle, or *nanocup* (Fig. 11e), capable of trapping and stabilizing gas against dissolution in the bloodstream (Kwan et al. 2015). Ultrahigh-speed imaging of the nucleated bubble shows an initial growth phase followed by detachment from the nanocup and subsequent inertial collapse, confirming the underpinning hypothesis. These experiments were quantitatively predicted using a modified RP model (Kwan et al. 2016). Direct observation of bubble nucleation from nanopits (Borkent et al. 2009), which typically reside in mesoporous silica nanoparticle agents, is out of reach owing to the small spatial and temporal scales involved. Thus, for now we must rely on indirect measurements by scanning the vast parameter space of ambient pressure, surfactant concentration, wetting properties and gas saturation, going hand in hand with theory and numerical simulations, including finite-difference simulations and molecular-dynamics simulations.

Finally, naturally occurring nano-sized gas-filled vesicles can be bioengineered to form "à la carte" biomolecules to non-invasively image and control biological functions using ultrasound (Lakshmanan et al. 2017). These gas vesicles (Fig. 11f) form a unique class of protein nanostructures that are detectable at subnanomolar concentrations and whose physical properties allow them to serve as highly sensitive imaging agents for ultrasound (Shapiro et al. 2014). Such gas vesicles also produce a non-linear response, enabling contrast imaging with these agents using amplitude modulation (Maresca et al. 2017). While direct observation of their shell dynamics under ultrasound exposure is so far out of reach, a finite-element model can be used to predict shell buckling behavior for these vesicles, leading to non-linear ultrasound backscatter at both their fundamental and second harmonic frequencies of 10–20 MHz when exposed to ultrasound above a threshold pressure of 300 kPa.

Conflict of interest disclosure—The authors declare no competing interests.

REFERENCES

- Allen JS, Rashid MM. Dynamics of a hyperelastic gas-filled spherical shell in a viscous fluid. *J Appl Mech* 2004;71:195–200.
- Allen JS, Roy RA. Dynamics of gas bubbles in viscoelastic fluids. I. Linear viscoelasticity. *J Acoust Soc Am* 2000;107:3167–3178.
- Allen JS, Roy RA. Dynamics of gas bubbles in viscoelastic fluids. II. Nonlinear viscoelasticity. *J Acoust Soc Am* 2000;108:1640–1650.

- Alvarez NJ, Walker LM, Anna SL. A microtensiometer to probe the effect of radius of curvature on surfactant transport to a spherical interface. *Langmuir* 2010;26:13310–13319.
- Averkiou MA, Mannaris C, Bruce M, Powers J. Nonlinear pulsing schemes for the detection of ultrasound contrast agents. *J Acoust Soc Am* 2008;123:3110.
- Barber BP, Hiller RA, Löfstedt R, Putterman SJ, Weninger KR. Defining the unknowns of sonoluminescence. *Phys Rep* 1997;281:65–143.
- Benjamin TB, Ellis AT. Self-propulsion of asymmetrically vibrating bubbles. *J Fluid Mech* 1990;212:65–80.
- Besant WH. A treatise on hydrostatics and hydrodynamics. Cambridge, UK: Deighton, Bell, and Co.; 1859.
- Bethe HA. Statistical theory of superlattices. *Proc R Soc Lond A Math Phys Sci* 1935;150:552–575.
- Bjerknes VFK. Fields of force: Supplementary lectures, applications to meteorology. New York: Columbia University Press; 1906.
- Blake FG. Onset of cavitation in liquids. Technical Memo No. 12. Cambridge, MA: Acoustics Research Laboratory, Harvard University; 1949.
- Blake JR, Tomita Y, Tong RP. The art, craft and science of modelling jet impact in a collapsing cavitation bubble. *Appl Sci Res* 1997;58:77–90.
- Boek ES, Padding JT, den Otter WK, Briels WJ. Mechanical properties of surfactant bilayer membranes from atomistic and coarse-grained molecular dynamics simulations. *J Phys Chem B* 2005;109:19851–19858.
- Borden MA. Intermolecular forces model for lipid microbubble shells. *Langmuir* 2019;35:10042–10051.
- Borden MA, Kruse DE, Caskey CF, Zhao S, Dayton PA, Ferrara KW. Influence of lipid shell physicochemical properties on ultrasound-induced microbubble destruction. *IEEE Trans Ultrason Ferroelectr Freq Control* 2005;52:1992–2002.
- Borden MA, Longo ML. Dissolution behavior of lipid monolayer-coated, air-filled microbubbles: Effect of lipid hydrophobic chain length. *Langmuir* 2002;18:9225–9233.
- Borden MA, Martinez GV, Ricker J, Tsvetkova N, Longo M, Gillies RJ, Dayton PA, Ferrara KW. Lateral phase separation in lipid-coated microbubbles. *Langmuir* 2006;22:4291–4297.
- Borden M, Rege K. Theranostic biocolloids: Soft matter colloids for imaging and therapy. *Theranostics* 2012;2:1115–1116.
- Borden MA, Song KH. Reverse engineering the ultrasound contrast agent. *Adv Colloid Interface Sci* 2018;262:39–49.
- Borkent BM, Gekle S, Prosperetti A, Lohse D. Nucleation threshold and deactivation mechanisms of nanoscopic cavitation nuclei. *Phys Fluids* 2009;21:102003.
- Bouakaz A, Versluis M, de Jong N. High-speed optical observations of contrast agent destruction. *Ultrasound Med Biol* 2005;31:391–399.
- Brenner MP, Hilgenfeldt S, Lohse D. Single-bubble sonoluminescence. *Rev Mod Phys* 2002;74:425–484.
- Brujan E-A. Jets from pulsed-ultrasound-induced cavitation bubbles near a rigid boundary. *J Phys D Appl Phys* 2017;50:215302.
- Brujan EA, Nahen K, Schmidt P, Vogel A. Dynamics of laser-induced cavitation bubbles near elastic boundaries: Influence of the elastic modulus. *J Fluid Mech* 2001;433:283–314.
- Burke CW, Suk JS, Kim AJ, Hsiang YHJ, Klibanov AL, Hanes J, Price RJ. Markedly enhanced skeletal muscle transfection achieved by the ultrasound-targeted delivery of non-viral gene nanocarriers with microbubbles. *J Control Release* 2012;162:414–421.
- Ceschia M, Nabergoj R. On the motion of a nearly spherical bubble in a viscous liquid. *Phys Fluids* 1978;21:140–142.
- Chatterjee D, Sarkar K. A Newtonian rheological model for the interface of microbubble contrast agents. *Ultrasound Med Biol* 2003;29:1749–1757.
- Chen H, Kreider W, Brayman AA, Bailey MR, Matula TJ. Blood vessel deformations on microsecond time scales by ultrasonic cavitation. *Phys Rev Lett* 2011;106:034301.
- Chen Q, Zagzebski J, Wilson T, Stiles T. Pressure-dependent attenuation in ultrasound contrast agents. *Ultrasound Med Biol* 2002;28:1041–1051.
- Chen Z, Pulsipher KW, Chattaraj R, Hammer DA, Sehgal CM, Lee D. Engineering the echogenic properties of microfluidic microbubbles using mixtures of recombinant protein and amphiphilic copolymers. *Langmuir* 2019;35:10079–10086.
- Chin CT, Lancée C, Borsboom J, Mastik F, Frijlink ME, de Jong N, Versluis M, Lohse D. Brandaris 128: A digital 25 million frames per second camera with 128 highly sensitive frames. *Rev Sci Instrum* 2003;74:5026–5034.
- Chomas JE, Dayton P, Allen J, Morgan K, Ferrara KW. Mechanisms of contrast agent destruction. *IEEE Trans Ultrason Ferroelectr Freq Control* 2001;48:232–248.
- Christopher DA, Burns PN, Armstrong J, Foster FS. A high-frequency continuous-wave Doppler ultrasound system for the detection of blood flow in the microcirculation. *Ultrasound Med Biol* 1996;22:1191–1203.
- Church CC. The effect of an elastic solid surface layer on the radial pulsation of gas bubbles. *J Acoust Soc Am* 1995;97:1510–1521.
- Cleve S, Inserra C, Prentice P. Contrast agent microbubble jetting during initial interaction with 200-kHz focused ultrasound. *Ultrasound Med Biol* 2019;45:3075–3080.
- Cohen JL, Cheirif J, Segar DS, Gillam LD, Gottdiener JS, Hausnerova E, Bruns DE. Improved left ventricular endocardial border delineation and opacification with OPTISON (FS069), a new echocardiographic contrast agent: Results of a phase III multicenter trial. *J Am Coll Cardiol* 1998;32:746–752.
- Commander KW, Prosperetti A. Linear pressure waves in bubbly liquids: Comparison between theory and experiment. *J Acoust Soc Am* 1989;85:732–746.
- Coussios CC, Roy RA. Applications of acoustics and cavitation to non-invasive therapy and drug delivery. *Annu Rev Fluid Mech* 2008;40:395–420.
- Crum LA. Bjerknes forces on bubbles in a stationary sound field. *J Acoust Soc Am* 1975;57:1363–1370.
- Dayton PA, Allen JS, Ferrara KW. The magnitude of radiation force on ultrasound contrast agents. *J Acoust Soc Am* 2002;112:2183–2192.
- Dayton P, Klibanov A, Brandenburger G, Ferrara K. Acoustic radiation force in vivo: A mechanism to assist targeting of microbubbles. *Ultrasound Med Biol* 1999;25:1195–1201.
- De Corato M, Saint-Michel B, Makrigiorgos G, Dimakopoulos Y, Tsamopoulos J, Garbin V. Oscillations of small bubbles and medium yielding in elastoviscoplastic fluids. *Phys Rev Fluids* 2019;4:073301.
- de Jong N, Cornet R, Lancée CT. Higher harmonics of vibrating gas-filled microspheres, part one: Simulations. *Ultrasonics* 1994;32:447–453.
- de Jong N, Emmer M, Chin CT, Bouakaz A, Mastik F, Lohse D, Versluis M. “Compression-only” behavior of phospholipid-coated contrast bubbles. *Ultrasound Med Biol* 2007;33:653–656.
- de Jong N, Hoff L. Ultrasound scattering properties of Alunex microspheres. *Ultrasonics* 1993;31:175–181.
- de Jong N, Hoff L, Skotland T, Bom N. Absorption and scatter of encapsulated gas filled microspheres: Theoretical considerations and some measurements. *Ultrasonics* 1992;30:95–103.
- Deffieux T, Demene C, Pernot M, Tanter M. Functional ultrasound neuroimaging: A review of the preclinical and clinical state of the art. *Curr Opin Neurobiol* 2018;50:128–135.
- Devin C, Jr. Survey of thermal, radiation, and viscous damping of pulsating air bubbles in water. *J Acoust Soc Am* 1959;31:1654–1667.
- Doinikov AA, Aired L, Bouakaz A. Acoustic scattering from a contrast agent microbubble near an elastic wall of finite thickness. *Phys Med Biol* 2011;56:6951–6968.
- Doinikov AA, Bouakaz A. Theoretical investigation of shear stress generated by a contrast microbubble on the cell membrane as a mechanism for sonoporation. *J Acoust Soc Am* 2010;128:11–19.
- Doinikov AA, Bouakaz A. Review of shell models for contrast agent microbubbles. *IEEE Trans Ultrason Ferroelectr Freq Control* 2011;58:981–993.
- Doinikov AA, Bouakaz A. Interaction of an ultrasound-activated contrast microbubble with a wall at arbitrary separation distances. *Phys Med Biol* 2015;60:7909–7926.

- Doinikov AA, Haac JF, Dayton PA. Modeling of nonlinear viscous stress in encapsulating shells of lipid-coated contrast agent microbubbles. *Ultrasonics* 2009;49:269–275.
- Doinikov AA, Sheeran PS, Bouakaz A, Dayton PA. Vaporization dynamics of volatile perfluorocarbon droplets: A theoretical model and in vitro validation. *Med Phys* 2014;41:102901.
- Doinikov AA, Zhao S, Dayton PA. Modeling of the acoustic response from contrast agent microbubbles near a rigid wall. *Ultrasonics* 2009;49:195–201.
- Dollet B, Marmottant P, Garbin V. Bubble dynamics in soft and biological matter. *Annu Rev Fluid Mech* 2019;51:331–355.
- Dollet B, van der Meer SM, Garbin V, de Jong N, Lohse D, Versluis M. Nonspherical oscillations of ultrasound contrast agent microbubbles. *Ultrasound Med Biol* 2008;34:1465–1473.
- Eckersley RJ, Chin CT, Burns PN. Optimising phase and amplitude modulation schemes for imaging microbubble contrast agents at low acoustic power. *Ultrasound Med Biol* 2005;31:213–219.
- Emmer M, van Wamel A, Goertz DE, de Jong N. The onset of microbubble vibration. *Ultrasound Med Biol* 2007;33:941–949.
- Emmer M, Vos HJ, Goertz DE, van Wamel A, Versluis M, de Jong N. Pressure-dependent attenuation and scattering of phospholipid-coated microbubbles at low acoustic pressures. *Ultrasound Med Biol* 2009;35:102–111.
- Engelhard S, Voorneveld J, Vos HJ, Westenberg JJM, Gijzen FJH, Taimr P, Versluis M, de Jong N, Bosch JG, Reijnen MMPJ, Groot Jebbink E. High-frame-rate contrast-enhanced US particle image velocimetry in the abdominal aorta: First human results. *Radiology* 2018;289:119–125.
- Epstein PS, Plesset MS. On the stability of gas bubbles in liquid-gas solutions. *J Chem Phys* 1950;18:1505–1509.
- Euler L. Théorie plus complète des machines qui sont mises en mouvement par la réaction de l'eau. *Mem Acad Sci Ber* 1756;10:227–295.
- European Medicines Agency. SonoVue: EPAR—Product information. Available at: https://www.ema.europa.eu/en/documents/product-information/sonovue-epar-product-information_en.pdf. Accessed January 22, 2020.
- Evans D, McDicken WN, Skidmore R, Woodcock JP. Doppler ultrasound: Physics, instrumentation, and clinical applications. Chichester, UK: John Wiley & Sons; 1989.
- Faez T, Emmer M, Kooiman K, Versluis M, van der Steen AFW, de Jong N. 20 years of ultrasound contrast agent modeling. *IEEE Trans Ultrason Ferroelectr Freq Control* 2013;60:7–20.
- Feinstein SB, Ten Cate FJ, Zwehl W, Ong K, Maurer G, Tei C, Shah PM, Meerbaum S, Corday E. Two-dimensional contrast echocardiography. I: In vitro development and quantitative analysis of echo contrast agents. *J Am Coll Cardiol* 1984;3:14–20.
- Feng ZC, Leal LG. On energy transfer in resonant bubble oscillations. *Phys Fluids A Fluid Dyn* 1993;5:826–836.
- Fernandez Rivas D, Verhaagen B, Seddon JRT, Zijlstra AG, Jiang LM, van der Sluis LWM, Versluis M, Lohse D, Gardeniers HJGE. Localized removal of layers of metal, polymer, or biomaterial by ultrasound cavitation bubbles. *Biomicrofluidics* 2012;6:034114.
- Frinking PJA, Bouakaz A, Kirkhorn J, Ten Cate FJ, de Jong N. Ultrasound contrast imaging: Current and new potential methods. *Ultrasound Med Biol* 2000;26:965–975.
- Frinking PJA, de Jong N. Acoustic modeling of shell-encapsulated gas bubbles. *Ultrasound Med Biol* 1998;24:523–533.
- Frinking PJA, Gaud E, Brochot J, Arditi M. Subharmonic scattering of phospholipid-shell microbubbles at low acoustic pressure amplitudes. *IEEE Trans Ultrason Ferroelectr Freq Control* 2010;57:1762–1771.
- Frinking PJA, Tardy I, Théraulaz M, Arditi M, Powers J, Pochon S, Tranquart F. Effects of acoustic radiation force on the binding efficiency of BR55, a VEGFR2-specific ultrasound contrast agent. *Ultrasound Med Biol* 2012;38:1460–1469.
- Garbin V, Cojoc D, Ferrari E, Di Fabrizio E, Overvelde MLJ, van der Meer SM, de Jong N, Lohse D, Versluis M. Changes in microbubble dynamics near a boundary revealed by combined optical micromanipulation and high-speed imaging. *Appl Phys Lett* 2007;90:114103.
- Garbin V, Dollet B, Overvelde M, Cojoc D, Di Fabrizio E, van Wijnngaarden L, Prosperetti A, de Jong N, Lohse D, Versluis M. History force on coated microbubbles propelled by ultrasound. *Phys Fluids* 2009;21:092003.
- Garbin V, Overvelde M, Dollet B, de Jong N, Lohse D, Versluis M. Unbinding of targeted ultrasound contrast agent microbubbles by secondary acoustic forces. *Phys Med Biol* 2011;56:6161–6178.
- Garg S, Thomas AA, Borden MA. The effect of lipid monolayer in-plane rigidity on in vivo microbubble circulation persistence. *Biomaterials* 2013;34:6862–6870.
- Gibson DC, Blake JR. The growth and collapse of bubbles near deformable surfaces. *Appl Sci Res* 1982;38:215–224.
- Gilmore FR. The growth or collapse of a spherical bubble in a viscous compressible liquid. *Hydrodynamics Laboratory Report No. 26-4*. Pasadena, CA: California Institute of Technology, 1952.
- Glazman RE. Effects of adsorbed films on gas bubble radial oscillations. *J Acoust Soc Am* 1983;74:980–986.
- Goertz DE, de Jong N, van der Steen AFW. Attenuation and size distribution measurements of Definity and manipulated Definity populations. *Ultrasound Med Biol* 2007;33:1376–1388.
- Gorce JM, Arditi M, Schneider M. Influence of bubble size distribution on the echogenicity of ultrasound contrast agents: A study of SonoVue. *Invest Radiol* 2000;35:661–671.
- Gramiak R, Shah PM. Echocardiography of the aortic root. *Invest Radiol* 1968;3:356–366.
- Guidi F, Vos HJ, Mori R, de Jong N, Tortoli P. Microbubble characterization through acoustically induced deflation. *IEEE Trans Ultrason Ferroelectr Freq Control* 2010;57:193–202.
- Han B, Köhler K, Jungnickel K, Mettin R, Lauterborn W, Vogel A. Dynamics of laser-induced bubble pairs. *J Fluid Mech* 2015;771:706–742.
- Harkin AA, Kaper TJ, Nadim A. Energy transfer between the shape and volume modes of a nonspherical gas bubble. *Phys Fluids* 2013;25:062101.
- Hay TA, Ilinskii YA, Zabolotskaya EA, Hamilton MF. Model for bubble pulsation in liquid between parallel viscoelastic layers. *J Acoust Soc Am* 2012;132:124–137.
- Healey AJ, Sontum PC, Kvåle S, Eriksen M, Bendiksen R, Tørnæs A, Østensen J. Acoustic cluster therapy: In vitro and ex vivo measurement of activated bubble size distribution and temporal dynamics. *Ultrasound Med Biol* 2016;42:1145–1166.
- Helfield BL, Leung BYC, Goertz DE. The effect of boundary proximity on the response of individual ultrasound contrast agent microbubbles. *Phys Med Biol* 2014;59:1721–1746.
- Herring C. Theory of the pulsations of the gas bubble produced by an underwater explosion. Washington, DC: Columbia University, Division of National Defense Research; 1941.
- Hilgenfeldt S, Lohse D, Brenner MP. Phase diagrams for sonoluminescent bubbles. *Phys Fluids* 1996;8:2808–2826.
- Hilgenfeldt S, Lohse D, Zomack M. Response of bubbles to diagnostic ultrasound: A unifying theoretical approach. *Eur Phys J B* 1998;4:247–255.
- Hilgenfeldt S, Lohse D, Zomack M. Sound scattering and localized heat deposition of pulse-driven microbubbles. *J Acoust Soc Am* 2000;107:3530–3539.
- Hoff L, Sontum PC, Hovem JM. Oscillations of polymeric microbubbles: Effect of the encapsulating shell. *J Acoust Soc Am* 2000;107:2272–2280.
- Hope Simpson D, Chin CT, Burns PN. Pulse inversion Doppler: A new method for detecting nonlinear echoes from microbubble contrast agents. *IEEE Trans Ultrason Ferroelectr Freq Control* 1999;46:372–382.
- Howry DH. The ultrasonic visualization of soft tissue structures and disease processes. *J Lab Clin Med* 1952;40:812–813.
- Huerre A, De Corato M, Garbin V. Dynamic capillary assembly of colloids at interfaces with 10,000g accelerations. *Nat Commun* 2018;9:3620.
- Humphrey JD, Na S. Elastodynamics and arterial wall stress. *Ann Biomed Eng* 2002;30:509–523.

- Jamburidze A, Huerre A, Baresch D, Poulichet V, De Corato M, Garbin V. Nanoparticle-coated microbubbles for combined ultrasound imaging and drug delivery. *Langmuir* 2019;35:10087–10096.
- Jensen JA, Nikolov SI, Yu ACH, Garcia D. Ultrasound vector flow imaging—part I: Sequential systems. *IEEE Trans Ultrason Ferroelectr Freq. Control* 2016;63:1704–1721.
- Kaul S. Current status of contrast echocardiography. *ACC Curr J Rev* 2000;9:73–75.
- Keller JB, Miksis M. Bubble oscillations of large amplitude. *J Acoust Soc Am* 1980;68:628–633.
- Kheirrolomoom A, Dayton PA, Lum AFH, Little E, Paoli EE, Zheng H, Ferrara KW. Acoustically-active microbubbles conjugated to liposomes: Characterization of a proposed drug delivery vehicle. *J Control Release* 2007;118:275–284.
- Kirkwood JG. Order and disorder in binary solid solutions. *J Chem Phys* 1938;6:70–75.
- Klibanov AL. Microbubble contrast agents: Targeted ultrasound imaging and ultrasound-assisted drug-delivery applications. *Invest Radiol* 2006;41:354–362.
- Kokhuis TJA, Garbin V, Kooiman K, Naaijken BA, Juffermans LJM, Kamp O, van der Steen AFW, Versluis M, de Jong N. Secondary Bjerknes forces deform targeted microbubbles. *Ultrasound Med Biol* 2013;39:490–506.
- Kokhuis TJA, Naaijken BA, Juffermans LJM, Kamp O, van der Steen AFW, Versluis M, de Jong N. On the dynamics of StemBells: Microbubble-conjugated stem cells for ultrasound-controlled delivery. *Appl Phys Lett* 2017;111 023701.
- Kokhuis TJA, Skachkov I, Naaijken BA, Juffermans LJM, Kamp O, Kooiman K, van der Steen AFW, Versluis M, de Jong N. Intravital microscopy of localized stem cell delivery using microbubbles and acoustic radiation force. *Biotechnol Bioeng* 2015;112:220–227.
- Kooiman K, Roovers S, Langeveld SAG, Kleven RT, Dewitte H, O'Reilly MA, Escoffier J-M, Bouakaz A, Verweij MD, Hynynen K, Lentacker I, Stride E, Holland CK. Ultrasound-responsive cavitation nuclei for therapy and drug delivery. *Ultrasound Med Biol* 2020;46:1296–1325.
- Kooiman K, van Rooij T, Qin B, Mastik F, Vos HJ, Versluis M, Klibanov AL, de Jong N, Villanueva FS, Chen X. Focal areas of increased lipid concentration on the coating of microbubbles during short tone-burst ultrasound insonification. *PLoS One* 2017;12 e0180747.
- Kotula AP, Anna SL. Insoluble layer deposition and dilatational rheology at a microscale spherical cap interface. *Soft Matter* 2016;12:7038–7055.
- Kripfgans OD, Fowlkes JB, Miller DL, Eldevik OP, Carson PL. Acoustic droplet vaporization for therapeutic and diagnostic applications. *Ultrasound Med Biol* 2000;26:1177–1189.
- Krishnan S, Hopfinger EJ, Puthenveetil BA. On the scaling of jetting from bubble collapse at a liquid surface. *J Fluid Mech* 2017;822:791–812.
- Kwan JJ, Borden MA. Microbubble dissolution in a multigas environment. *Langmuir* 2010;26:6542–6548.
- Kwan JJ, Borden MM. Lipid monolayer collapse and microbubble stability. *Adv Colloid Interface Sci* 2012;183–184:82–99.
- Kwan JJ, Lajoinie G, de Jong N, Stride E, Versluis M, Coussios CC. Ultrahigh-speed dynamics of micrometer-scale inertial cavitation from nanoparticles. *Phys Rev Appl* 2016;6 044004.
- Kwan JJ, Myers R, Coviello CM, Graham SM, Shah AR, Stride E, Carlisle RC, Coussios CC. Ultrasound-propelled nanocups for drug delivery. *Small* 2015;11:5305–5314.
- Lajoinie G, Gelderblom E, Chlon C, Böhmer M, Steenbergen W, de Jong N, Manohar S, Versluis M. Ultrafast vaporization dynamics of laser-activated polymeric microcapsules. *Nat Commun* 2014;5:3671.
- Lajoinie G, Linnartz E, Kruizinga P, de Jong N, Stride E, van Soest G, Versluis M. Laser-driven resonance of dye-doped oil-coated microbubbles: A theoretical and numerical study. *J Acoust Soc Am* 2017;141:2727–2745.
- Lajoinie G, Lee JY, Owen J, Kruizinga P, de Jong N, van Soest G, Stride E, Versluis M. Laser-driven resonance of dye-doped oil-coated microbubbles: Experimental study. *J Acoust Soc Am* 2017;141:4832–4846.
- Lajoinie G, Luan Y, Gelderblom E, Dollet B, Mastik F, Dewitte H, Lentacker I, de Jong N, Versluis M. Non-spherical oscillations drive the ultrasound-mediated release from targeted microbubbles. *Commun Phys* 2018;1:22.
- Lakshmanan A, Lu GJ, Farhadi A, Nety SP, Kunth M, Lee-Gosselin A, Maresca D, Bourdeau RW, Yin M, Yan J, Witte C, Malounda D, Foster FS, Schröder L, Shapiro MG. Preparation of biogenic gas vesicle nanostructures for use as contrast agents for ultrasound and MRI. *Nat Protoc* 2017;12:2050–2080.
- Lamb H. A treatise on the mathematical theory of the motion of fluids. Cambridge, UK: The University Press; 1879.
- Lamb H. Hydrodynamics. 6th ed. Cambridge, UK: The University Press; 1932.
- Lauterborn W. Numerical investigation of nonlinear oscillations of gas bubbles in liquids. *J Acoust Soc Am* 1976;59:283–293.
- Lauterborn W, Bolle H. Experimental investigations of cavitation-bubble collapse in the neighbourhood of a solid boundary. *J Fluid Mech* 1975;72:391–399.
- Lee S, Kim DH, Needham D. Equilibrium and dynamic interfacial tension measurements at microscopic interfaces using a micropipet technique. 2: Dynamics of phospholipid monolayer formation and equilibrium tensions at the water-air interface. *Langmuir* 2001;17:5544–5550.
- Leighton TG. The acoustic bubble. London: Academic Press; 1994.
- Leighton TG. The inertial terms in equations of motion for bubbles in tubular vessels or between plates. *J Acoust Soc Am* 2011;130:3333–3338.
- Lensen D, Gelderblom EC, Vriezema DM, Marmottant P, Verdonchot N, Versluis M, de Jong N, van Hest JCM. Biodegradable polymeric microcapsules for selective ultrasound-triggered drug release. *Soft Matter* 2011;7:5417–5422.
- Lentacker I, Geers B, Demeester J, De Smedt SC, Sanders NN. Design and evaluation of doxorubicin-containing microbubbles for ultrasound-triggered doxorubicin delivery: Cytotoxicity and mechanisms involved. *Mol Ther* 2010;18:101–108.
- Leow CH, Bazigou E, Eckersley RJ, Yu ACH, Weinberg PD, Tang M-X. Flow velocity mapping using contrast enhanced high-frame-rate plane wave ultrasound and image tracking: Methods and initial in vitro and in vivo evaluation. *Ultrasound Med Biol* 2015;41:2913–2925.
- Li S, Zhang AM, Han R. Letter: Counter-jet formation of an expanding bubble near a curved elastic boundary. *Phys Fluids* 2018;30 121703.
- Lighthill J. Acoustic streaming. *J Sound Vib* 1978;61:391–418.
- Lindner JR. Principles of contrast echocardiography. In: Solomon SD, Wu JC, Gillam LD, (eds). *Essential echocardiography*. Philadelphia: Elsevier; 2019. p. 27–33.
- Liu Y, Calvisi ML, Wang Q. Shape oscillation and stability of an encapsulated microbubble translating in an acoustic wave. *J Acoust Soc Am* 2018;144:2189–2200.
- Liu Y, Sugiyama K, Takagi S, Matsumoto Y. Surface instability of an encapsulated bubble induced by an ultrasonic pressure wave. *J Fluid Mech* 2012;691:315–340.
- Liu Y, Wang Q. Stability and natural frequency of nonspherical mode of an encapsulated microbubble in a viscous liquid. *Phys Fluids* 2016;28 062102.
- Löfstedt R, Weninger K, Putterman S, Barber BP. Sonoluminescing bubbles and mass diffusion. *Phys Rev E* 1995;51:4400–4410.
- Lohse D. Bubble puzzles: From fundamentals to applications. *Phys Rev Fluids* 2018;3 110504.
- Lohse D, Zhang X. Surface nanobubbles and nanodroplets. *Rev Mod Phys* 2015;87:981–1036.
- Lozano MM, Longo ML. Complex formation and other phase transformations mapped in saturated phosphatidylcholine/DSPE-PEG2000 monolayers. *Soft Matter* 2009;5:1822–1834.
- Luan Y, Faez T, Gelderblom E, Skachkov I, Geers B, Lentacker I, van der Steen T, Versluis M, de Jong N. Acoustical properties of individual liposome-loaded microbubbles. *Ultrasound Med Biol* 2012;38:2174–2185.

- Luan Y, Lajoinie G, Gelderblom E, Skachkov I, van der Steen AFW, Vos HJ, Versluis M, de Jong N. Lipid shedding from single oscillating microbubbles. *Ultrasound Med Biol* 2014;40:1834–1846.
- Lum AFH, Borden MA, Dayton PA, Kruse DE, Simon SI, Ferrara KW. Ultrasound radiation force enables targeted deposition of model drug carriers loaded on microbubbles. *J Control Release* 2006;111:128–134.
- Macosko CW. *Rheology: Principles, measurements, and applications*. Weinheim, Germany: VCH; 1994.
- Maeda H, Wu J, Sawa T, Matsumura Y, Hori K. Tumor vascular permeability and the EPR effect in macromolecular therapeutics: A review. *J Control Release* 2000;65:271–284.
- Mao Y, Crum LA, Roy RA. Nonlinear coupling between the surface and volume modes of an oscillating bubble. *J Acoust Soc Am* 1995;98:2764–2771.
- Maresca D, Lakshmanan A, Lee-Gosselin A, Melis JM, Ni Y-L, Bourdeau RW, Kochmann DM, Shapiro MG. Nonlinear ultrasound imaging of nanoscale acoustic biomolecules. *Appl Phys Lett* 2017;110 073704.
- Marmottant P, Bouakaz A, de Jong N, Quilliet C. Buckling resistance of solid shell bubbles under ultrasound. *J Acoust Soc Am* 2011;129:1231–1239.
- Marmottant P, Hilgenfeldt S. Controlled vesicle deformation and lysis by single oscillating bubbles. *Nature* 2003;423:153–156.
- Marmottant P, van der Meer S, Emmer M, Versluis M, de Jong N, Hilgenfeldt S, Lohse D. A model for large amplitude oscillations of coated bubbles accounting for buckling and rupture. *J Acoust Soc Am* 2005;118:3499–3505.
- Marmottant P, Versluis M, de Jong N, Hilgenfeldt S, Lohse D. High-speed imaging of an ultrasound-driven bubble in contact with a wall: “Narcissus” effect and resolved acoustic streaming. *Exp Fluids* 2006;41:147–153.
- Marsh JN, Hughes MS, Brandenburger GH, Miller JG. Broadband measurement of the scattering-to-attenuation ratio for Albunex at 37°C. *Ultrasound Med Biol* 1999;25:1321–1324.
- Matula TJ. Inertial cavitation and single-bubble sonoluminescence. *Philos Trans A Math Phys Eng Sci* 1999;357:225–249.
- Medwin H. Counting bubbles acoustically: A review. *Ultrasonics* 1977;15:7–13.
- Mei CC, Zhou X. Parametric resonance of a spherical bubble. *J Fluid Mech* 1991;229:29–50.
- Mercado-Shekar KP, Su H, Kalaikadal DS, Lorenz JN, Manglik RM, Holland CK, Redington AN, Haworth KJ. Acoustic droplet vaporization-mediated dissolved oxygen scavenging in blood-mimicking fluids, plasma, and blood. *Ultrason Sonochem* 2019;56:114–124.
- Miller DL, Lu X, Dou C, Fabiilli ML, Church CC. The dependence of glomerular capillary hemorrhage induced by contrast enhanced diagnostic ultrasound on microbubble diameter. *Ultrasound Med Biol* 2018;44:613–621.
- Misra JC, Singh SI. A large deformation analysis for aortic walls under a physiological loading. *Int J Eng Sci* 1983;21:1193–1202.
- Mohwald H. *Handbook of biological physics*. Amsterdam: Elsevier Science; 1995.
- Mørch Y, Hansen R, Berg S, Aslund AKO, Glomm WR, Eggen S, Schmid R, Johnsen H, Kubowicz S, Snipstad S, Sulheim E, Hak S, Singh G, McDonagh BH, Blom H, de Lange Davies C, Stenstad PM. Nanoparticle-stabilized microbubbles for multimodal imaging and drug delivery. *Contrast Media Mol Imaging* 2015;10:356–366.
- Morgan K, Allen J, Dayton P, Chomas J, Klibanov A, Ferrara K. Experimental and theoretical evaluation of microbubble behavior: Effect of transmitted phase and bubble size. *IEEE Trans Ultrason Ferroelectr Freq Control* 2000;47:1494–1509.
- Mulvagh SL, Rakowski H, Vannan MA, Abdelmoneim SS, Becher H, Bierig SM, Burns PN, Castello R, Coon PD, Hagen ME, Jollis JG, Kimball TR, Kitzman DW, Kronzon I, Labovitz AJ, Lang RM, Mathew J, Moir WS, Naguch SF, Pearlman AS, Perez JE, Porter TR, Rosenbloom J, Strachan GM, Thanigaraj S, Wei K, Woo A, Yu EH, Zoghbi WA. American Society of Echocardiography consensus statement on the clinical applications of ultrasonic contrast agents in echocardiography. *J Am Soc Echocardiogr* 2008;21:1179–1201.
- Naaijkens B, Bogaards SJP, Krijnen PAJ, Kamp O, Musters RJP, Kokhuis TJA, de Jong N, Niessen NWM, Van Dijk A, Juffermans LJM. Directing stem cells to the infarcted heart using targeted microbubbles: Development of a new molecular therapeutic technique. *Eur Heart J* 2013;34:P1451.
- Nabergoj R, Francescutto A. On thresholds for surface waves on resonant bubbles. *J Phys Colloques* 1979;40 C8-306–C8-309.
- Naude J, Mendez F. Periodic and chaotic acoustic oscillations of a bubble gas immersed in an upper convective Maxwell fluid. *J Nonnewton Fluid Mech* 2008;155:30–38.
- Neppiras EA, Noltingk BE. Cavitation produced by ultrasonics - theoretical conditions for the onset of cavitation. *Proc Phys Soc B* 1951;64:1032–1038.
- Noltingk BE, Neppiras EA. Cavitation produced by ultrasonics. *Proc Phys Soc B* 1950;63:674–685.
- O’Brien J, Ovenden N, Stride E. Accounting for the stability of microbubbles to multi-pulse excitation using a lipid-shedding model. *J Acoust Soc Am* 2011;130:180–185.
- Oguz HN, Prosperetti A. Bubble oscillations in the vicinity of a nearly plane free surface. *J Acoust Soc Am* 1990;87:2085–2092.
- Oguz HN, Prosperetti A. The natural frequency of oscillation of gas bubbles in tubes. *J Acoust Soc Am* 1998;103:3301–3308.
- Ohl CD, Ikink R. Shock-wave-induced jetting of micron-size bubbles. *Phys Rev Lett* 2003;90 214502.
- Overvelde M, Garbin V, Sijl J, Dollet B, de Jong N, Lohse D, Versluis M. Nonlinear shell behavior of phospholipid-coated microbubbles. *Ultrasound Med Biol* 2010;36:2080–2092.
- Owen J, Crake C, Lee JY, Carugo D, Beguin E, Khrapitchev AA, Browning RJ, Sibson N, Stride E. A versatile method for the preparation of particle-loaded microbubbles for multimodality imaging and targeted drug delivery. *Drug Deliv Transl Res* 2018;8:342–356.
- Paul S, Katiyar A, Sarkar K. Material characterization of the encapsulation of an ultrasound contrast microbubble and its subharmonic response: Strain-softening interfacial elasticity model. *J Acoust Soc Am* 2010;127:3846–3857.
- Paul S, Russakow D, Nahire R, Nandy T, Ambre AH, Katti K, Mallik S, Sarkar K. In vitro measurement of attenuation and nonlinear scattering from echogenic liposomes. *Ultrasonics* 2012;52:962–969.
- Pereno V, Aron M, Vince O, Mannaris C, Seth A, de Saint Victor M, Lajoinie G, Versluis M, Coussios C, Carugo D, Stride E. Layered acoustofluidic resonators for the simultaneous optical and acoustic characterisation of cavitation dynamics, microstreaming, and biological effects. *Biomicrofluidics* 2018;12 034109.
- Peyman SA, Abou-Saleh RH, McLaughlan JR, Ingram N, Johnson BRG, Critchley K, Freear S, Evans JA, Markham AF, Coletta PL, Evans SD. Expanding 3D geometry for enhanced on-chip microbubble production and single step formation of liposome modified microbubbles. *Lab Chip* 2012;12:4544–4552.
- Phillips LC, Puett C, Sheeran PS, Dayton PA, Wilson Miller G, Matsunaga TO. Phase-shift perfluorocarbon agents enhance high intensity focused ultrasound thermal delivery with reduced near-field heating. *J Acoust Soc Am* 2013;134:1473–1482.
- Plesset MS. On the stability of fluid flows with spherical symmetry. *J Appl Phys* 1954;25:96–98.
- Plesset MS, Chapman RB. Collapse of an initially spherical vapour cavity in the neighbourhood of a solid boundary. *J Fluid Mech* 1971;47:283–290.
- Poelma C. Ultrasound imaging velocimetry: A review. *Exp Fluids* 2016;58:3.
- Poritsky H. The collapse or growth of a spherical bubble or cavity in a viscous fluid. *J Appl Mech* 1951;18:332–333.
- Postema M, Bouakaz A, Versluis M, de Jong N. Ultrasound-induced gas release from contrast agent microbubbles. *IEEE Trans Ultrason Ferroelectr Freq Control* 2005;52:1035–1041.
- Postema M, van Wamel A, ten Cate FJ, de Jong N. High-speed photography during ultrasound illustrates potential therapeutic applications of microbubbles. *Med Phys* 2005;32:3707–3711.

- Poulichet V, Garbin V. Ultrafast desorption of colloidal particles from fluid interfaces. *Proc Natl Acad Sci U S A* 2015;112:5932–5937.
- Prentice P, Cuschieri A, Dholakia K, Prausnitz M, Campbell P. Membrane disruption by optically controlled microbubble cavitation. *Nat Phys* 2005;1:107–110.
- Prosperetti A. Thermal effects and damping mechanisms in the forced radial oscillations of gas bubbles in liquids. *J Acoust Soc Am* 1976;61:17–27.
- Prosperetti A. Current topics in the dynamics of gas and vapor bubbles. *Meccanica* 1977;12:214–235.
- Prosperetti A. Thermal effects and damping mechanisms in the forced radial oscillations of gas bubbles in liquids. *J Acoust Soc Am* 1977;61:17–27.
- Prosperetti A, Crum LA, Commander KW. Nonlinear bubble dynamics. *J Acoust Soc Am* 1988;83:502–514.
- Qin S, Ferrara KW. Acoustic response of compliant microvessels containing ultrasound contrast agents. *Phys Med Biol* 2006;51:5065–5088.
- Qin S, Ferrara KW. The natural frequency of nonlinear oscillation of ultrasound contrast agents in microvessels. *Ultrasound Med Biol* 2007;33:1140–1148.
- Quiaia E, (ed). Contrast media in ultrasonography. Berlin: Springer; 2005.
- Radhakrishnan K, Holland CK, Haworth KJ. Scavenging dissolved oxygen via acoustic droplet vaporization. *Ultrason Sonochem* 2016;31:394–403.
- Rafter P, Phillips P, Vannan MA. Imaging technologies and techniques. *Cardiol Clin* 2004;22:181–197.
- Rapoport N. Phase-shift, stimuli-responsive perfluorocarbon nanodroplets for drug delivery to cancer. *Wiley Interdiscip Rev Nanomed Nanobiotechnol* 2012;4:492–510.
- Rapoport NY, Gao Z, Kennedy A. Multifunctional nanoparticles for combining ultrasonic tumor imaging and targeted chemotherapy. *J Natl Cancer Inst* 2007;99:1095–1106.
- Rayleigh L. On the circulation of air observed in Kundt's tubes, and on some allied acoustical problems. *Philos Trans R Soc Lond* 1884;175:1–21.
- Rayleigh L. On the pressure developed in a liquid during the collapse of a spherical cavity. *Philos Mag* 1917;34:94–98.
- Raymond JL, Haworth KJ, Bader KB, Radhakrishnan K, Griffin JK, Huang SL, McPherson DD, Holland CK. Broadband attenuation measurements of phospholipid-shelled ultrasound contrast agents. *Ultrasound Med Biol* 2014;40:410–421.
- Raymond JL, Luan Y, Peng T, Huang SL, McPherson DD, Versluis M, de Jong N, Holland CK. Loss of gas from echogenic liposomes exposed to pulsed ultrasound. *Phys Med Biol* 2016;61:8321–8339.
- Raymond JL, Luan Y, van Rooij T, Kooiman K, Huang SL, McPherson DD, Versluis M, de Jong N, Holland CK. Impulse response method for characterization of echogenic liposomes. *J Acoust Soc Am* 2015;137:1693–1703.
- Reznik N, Shpak O, Gelderblom EC, Williams R, de Jong N, Versluis M, Burns PN. The efficiency and stability of bubble formation by acoustic vaporization of submicron perfluorocarbon droplets. *Ultrasonics* 2013;53:1368–1376.
- Roovers S, Lajoinie G, Cock ID, Brans T, Dewitte H, Braeckmans K, Versluis M, Smedt SCD, Lentacker I. Sonoprinting of nanoparticle-loaded microbubbles: Unraveling the multi-timescale mechanism. *Biomaterials* 2019;217:119250.
- Rychak JJ, Klibanov AL, Hossack JA. Acoustic radiation force enhances targeted delivery of ultrasound contrast microbubbles: In vitro verification. *IEEE Trans Ultrason Ferroelectr Freq Control* 2005;52:421–433.
- Saramito P. A new elastoviscoplastic model based on the Herschel–Bulkley viscoplastic model. *J Nonnewton Fluid Mech* 2009;158:154–161.
- Sarkar K, Katiyar A, Jain P. Growth and dissolution of an encapsulated contrast microbubble: Effects of encapsulation permeability. *Ultrasound Med Biol* 2009;35:1385–1396.
- Sarkar K, Shi WT, Chatterjee D, Forsberg F. Characterization of ultrasound contrast microbubbles using in vitro experiments and viscous and viscoelastic interface models for encapsulation. *J Acoust Soc Am* 2005;118:539–550.
- Schneider M. Characteristics of SonoVue. *Echocardiography* 1999;16:743–746.
- Segers T, de Jong N, Versluis M. Uniform scattering and attenuation of acoustically sorted ultrasound contrast agents: Modeling and experiments. *J Acoust Soc Am* 2016;140:2506–2517.
- Segers T, de Rond L, de Jong N, Borden M, Versluis M. Stability of monodisperse phospholipid-coated microbubbles formed by flow-focusing at high production rates. *Langmuir* 2016;32:3937–3944.
- Segers T, Gaud E, Versluis M, Frinking P. High-precision acoustic measurements of the nonlinear dilatational elasticity of phospholipid coated monodisperse microbubbles. *Soft Matter* 2018;14:9550.
- Segers T, Kruijzinga P, Kok M, Lajoinie G, de Jong N, Versluis M. Monodisperse versus polydisperse ultrasound contrast agents: Nonlinear response, sensitivity, and deep tissue imaging potential. *Ultrasound Med Biol* 2018;44:1482–1492.
- Segers T, Lassus A, Bussat P, Gaud E, Frinking P. Improved coalescence stability of monodisperse phospholipid-coated microbubbles formed by flow-focusing at elevated temperatures. *Lab Chip* 2019;19:158–167.
- Segers T, Lohse D, Versluis M, Frinking P. Universal equations for the coalescence probability and long-term size stability of phospholipid-coated monodisperse microbubbles formed by flow-focusing. *Langmuir* 2017;33:10329–10339.
- Segers T, Versluis M. Acoustic bubble sorting for ultrasound contrast agent enrichment. *Lab Chip* 2014;14:1705–1714.
- Senior R, Becher H, Monaghan M, Agati L, Zamorano J, Vanoverschelde JL, Nihoyannopoulos P. Contrast echocardiography: Evidence-based recommendations by European Association of Echocardiography. *Eur J Echocardiogr* 2009;10:194–212.
- Shapiro MG, Goodwill PW, Neogy A, Yin M, Foster FS, Schaffer DV, Conolly SM. Biogenic gas nanostructures as ultrasonic molecular reporters. *Nat Nanotechnol* 2014;9:311–316.
- Shaw SJ. Translation and oscillation of a bubble under axisymmetric deformation. *Phys Fluids* 2006;18:072104.
- Shaw SJ. The stability of a bubble in a weakly viscous liquid subject to an acoustic traveling wave. *Phys Fluids* 2009;21:022104.
- Sheeran P, Luo S, Dayton PA, Matsunaga T. Formulation and acoustic studies of new phase-shift agent for diagnostic and therapeutic ultrasound. *Langmuir* 2011;27:10412–10420.
- Sheeran PS, Matsunaga TO, Dayton PA. Phase change events of volatile liquid perfluorocarbon contrast agents produce unique acoustic signatures. *Phys Med Biol* 2014;59:379–401.
- Shi WT, Forsberg F, Raichlen JS, Needleman L, Goldberg BB. Pressure dependence of subharmonic signals from contrast microbubbles. *Ultrasound Med Biol* 1999;25:275–283.
- Shpak O, Kokhuis T, Luan Y, Lohse D, de Jong N, Fowlkes JB, Fabiilli ML, Versluis M. Ultrafast dynamics of the acoustic vaporization of phase-change microdroplets. *J Acoust Soc Am* 2013;134:1610–1621.
- Shpak O, Stricker L, Versluis M, Lohse D. The role of gas in ultrasonically driven vapor bubble growth. *Phys Med Biol* 2013;58:2523–2535.
- Shpak O, Verweij M, Vos HJ, de Jong N, Lohse D, Versluis M. Acoustic droplet vaporization is initiated by superharmonic focusing. *Proc Natl Acad Sci U S A* 2014;111:1697–1702.
- Sijl J, Dollet B, Overvelde M, Garbin V, Rozendal T, de Jong N, Lohse D, Versluis M. Subharmonic behavior of phospholipid-coated ultrasound contrast agent microbubbles. *J Acoust Soc Am* 2010;128:3239–3252.
- Sijl J, Overvelde M, Dollet B, Garbin V, de Jong N, Lohse D, Versluis M. “Compression-only” behavior: A second-order nonlinear response of ultrasound contrast agent microbubbles. *J Acoust Soc Am* 2011;129:1729–1739.
- Skyba DM, Camarano G, Goodman NC, Price RJ, Skalak TC, Kaul S. Hemodynamic characteristics, myocardial kinetics and microvascular rheology of FS-069, a second-generation echocardiographic

- contrast agent capable of producing myocardial opacification from a venous injection. *J Am Coll Cardiol* 1996;28:1292–1300.
- Sontum PC. Physicochemical characteristics of Sonazoid, a new contrast agent for ultrasound imaging. *Ultrasound Med Biol* 2008;34:824–833.
- Stride E. The influence of surface adsorption on microbubble dynamics. *Philos Trans R Soc A* 2008;366:2103–2115.
- Stride E, Porter C, Prieto AG, Pankhurst Q. Enhancement of microbubble mediated gene delivery by simultaneous exposure to ultrasonic and magnetic fields. *Ultrasound Med Biol* 2009;35:861–868.
- Stride E, Saffari N. Microbubble ultrasound contrast agents: A review. *Proc Inst Mech Eng H* 2003;217:429–476.
- Stride E, Segers T, Lajoinie G, Cherkaoui S, Bettinger T, Versluis M, Borden M. Microbubble agents: New directions. *Ultrasound Med Biol* 2020;46:1326–1343.
- Sulheim E, Mørch Y, Snipstad S, Borgos SE, Miletic H, Bjerkvig R, de Lange Davies C, Aslund AK. Therapeutic effect of cabazitaxel and blood-brain barrier opening in a patient-derived glioblastoma model. *Nanotheranostics* 2019;3:103–112.
- Sun C, Can E, Dijkink R, Lohse D, Prosperetti A. Growth and collapse of a vapour bubble in a microtube: The role of thermal effects. *J Fluid Mech* 2009;632:5–16.
- Suslick KS, Flannigan DJ. Inside a collapsing bubble: Sonoluminescence and the conditions during cavitation. *Annu Rev Phys Chem* 2008;59:659–683.
- Suslov SA, Ooi A, Manasseh R. Nonlinear dynamic behavior of microscopic bubbles near a rigid wall. *Phys Rev E* 2012;85 066309.
- Szűjártó C, Rossi S, Waton G, Krafft MP. Effects of perfluorocarbon gases on the size and stability characteristics of phospholipid-coated microbubbles: Osmotic effect versus interfacial film stabilization. *Langmuir* 2012;28:1182–1189.
- Tanter M, Fink M. Ultrafast imaging in biomedical ultrasound. *IEEE Trans Ultrason Ferroelectr Freq Control* 2014;61:102–118.
- Taylor GI, Davies RM. The motion and shape of the hollow produced by an explosion in a liquid. In: Batchelor GK, (ed). *The scientific papers of Sir Geoffrey Ingram Taylor*, vol. III: Aerodynamics and the mechanics of projectiles and explosions. London: Cambridge University Press; 1963. p. 337–353.
- Thomas A, Borden M. Hydrostatic pressurization of lung surfactant microbubbles: Observation of a strain-rate dependent elasticity. *Langmuir* 2017;33:13699–13707.
- Thornycroft JJ, Barnaby SW. Torpedo-boat destroyers. *Minutes Proc Inst Civ Eng* 1895;122:51–69.
- Trilling L. The collapse and rebound of a gas bubble. *J Appl Phys* 1952;23:14–17.
- Tsiglilis K, Pelekasis NA. Nonlinear radial oscillations of encapsulated microbubbles subject to ultrasound: The effect of membrane constitutive law. *J Acoust Soc Am* 2008;123:4059–4070.
- Tu J, Guan J, Qiu Y, Matula TJ. Estimating the shell parameters of SonoVue microbubbles using light scattering. *J Acoust Soc Am* 2009;126:2954–2962.
- Tyndall J. *Sound: 8 lectures*. London: Longmans, Green, and Co.; 1875.
- Unger E, Shen D, Fritz T, Kulik B, Lund P, Wu GL, Yellowhair D, Ramaswami R, Matsunaga T. Gas-filled lipid bilayers as ultrasound contrast agents. *Invest Radiol* 1994;29:S134–S136.
- van der Meer S, Dollet B, Voormolen M, Chin CT, Bouakaz A, de Jong N, Versluis M, Lohse D. Microbubble spectroscopy of ultrasound contrast agents. *J Acoust Soc Am* 2007;121:648–656.
- van Opheusden JHJ, Molenaar J. Lipid aggregate formation at an oscillating bubble surface: A simulation study. *Phys Rev E* 2011;83 051606.
- van Rooij T, Luan Y, Renaud G, van der Steen A, Versluis M, de Jong N, Kooiman K. Non-linear response and viscoelastic properties of lipid-coated microbubbles: DSPC versus DPPC. *Ultrasound Med Biol* 2015;41:1432–1445.
- Verhaagen B, Fernandez Rivas D. Measuring cavitation and its cleaning effect. *Ultrason Sonochem* 2016;29:619–628.
- Versluis M. High-speed imaging in fluids. *Exp Fluids* 2013;54:1458.
- Versluis M, Goertz DE, Palanchon P, Heitman IL, van der Meer SM, Dollet B, de Jong N, Lohse D. Microbubble shape oscillations excited through ultrasonic parametric driving. *Phys Rev E* 2010;82 026321.
- Visscher M, Lajoinie G, Blazejewski E, Veldhuis G, Versluis M. Laser-activated microparticles for multimodal imaging: Ultrasound and photoacoustics. *Phys Med Biol* 2019;64 034001.
- Viti J, Mori R, Guidi F, Versluis M, de Jong N, Tortoli P. Nonlinear oscillations of deflating bubbles. *IEEE Trans Ultrason Ferroelectr Freq Control* 2012;59:2818–2824.
- Vlaskou D, Mykhaylyk O, Kraetz F, Hellwig N, Renner R, Schillinger U, Gleich B, Heidsieck A, Schmitz G, Hensel K, Plank C. Magnetic and acoustically active lipospheres for magnetically targeted nucleic acid delivery. *Adv Funct Mater* 2010;20:3881–3894.
- Vokurka K. On Rayleigh's model of a freely oscillating bubble. 1: Basic relations. *Czech J Phys* 1985;35:28–40.
- Vos HJ, Dollet B, Versluis M, de Jong N. Nonspherical shape oscillations of coated microbubbles in contact with a wall. *Ultrasound Med Biol* 2011;37:935–948.
- Wang QX, Blake JR. Non-spherical bubble dynamics in a compressible liquid. Part 1: travelling acoustic wave. *J Fluid Mech* 2010;659:191–224.
- Wang Q, Liu W, Zhang AM, Sui Y. Bubble dynamics in a compressible liquid in contact with a rigid boundary. *Interface Focus* 2015;5 20150048.
- Ward M, Wu J, Chiu JF. Experimental study of the effects of Optison concentration on sonoporation in vitro. *Ultrasound Med Biol* 2000;26:1169–1175.
- Williams R, Wright C, Cherin E, Reznik N, Lee M, Gorelikov I, Foster FS, Matsuura N, Burns PN. Characterization of submicron phase-change perfluorocarbon droplets for extravascular ultrasound imaging of cancer. *Ultrasound Med Biol* 2013;39:475–489.
- Wilson K, Homan K, Emelianov S. Biomedical photoacoustics beyond thermal expansion using triggered nanodroplet vaporization for contrast-enhanced imaging. *Nat Commun* 2012;3:618.
- Wilson SR, Burns PN. Microbubble-enhanced US in body imaging: What role?. *Radiology* 2010;257:24–39.
- Woudstra L, Krijnen P, Bogaards S, Meinster E, Emmens R, Kokhuis T, Bollen I, Baltzer H, Baart S, Parbhudayal R, Helder M, van Hinsbergh V, Musters R, de Jong N, Kamp O, Niessen H, van Dijk A, Juffermans L. Development of a new therapeutic technique to direct stem cells to the infarcted heart using targeted microbubbles: StemBells. *Stem Cell Res* 2016;17:6–15.
- Woudstra L, Meinster E, Van Haren L, Kay AM, Koopman M, Belien JAM, Morrison MC, van Rossum AC, Helder MN, Juffermans LJM, Niessen HWM, Krijnen PAJ. StemBell therapy stabilizes atherosclerotic plaques after myocardial infarction. *Cytherapy* 2018;20:1143–1154.
- Wu CC, Roberts PH. Bubble shape instability and sonoluminescence. *Phys Lett A* 1999;250:131–136.
- Yan F, Li L, Deng Z, Jin Q, Chen J, Yang W, Yeh CK, Wu J, Shandas R, Liu X, Zheng H. Paclitaxel-liposome microbubble complexes as ultrasound-triggered therapeutic drug delivery carriers. *J Control Release* 2013;166:246–255.
- Yang X, Church CC. A model for the dynamics of gas bubbles in soft tissue. *J Acoust Soc Am* 2005;118:3595–3606.
- Young F. *Cavitation*. London: McGraw-Hill; 1989.
- Zhang M, Fabiilli M, Haworth K, Fowlkes JB, Kripfgans O, Roberts W, Ives K, Carson P. Initial investigation of acoustic droplet vaporization for occlusion in canine kidney. *Ultrasound Med Biol* 2010;36:1691–1703.
- Zhang P, Porter T. An in vitro study of a phase-shift nanoemulsion: A potential nucleation agent for bubble-enhanced HIFU tumor ablation. *Ultrasound Med Biol* 2010;36:1856–1866.
- Zhao S, Borden M, Bloch SH, Kruse D, Ferrara KW, Dayton PA. Radiation-force assisted targeting facilitates ultrasonic molecular imaging. *Phys Fluids* 2004;3:135–148.