

tbl.typ: a **tbl**-like preprocessor for Typst and **tablex**

Version **TK**

Max Rees

2023

Contents

Introduction	2
Region options	3
Format specifications	4
Data	5
Examples	5
References	10

Introduction

Typst [1] is “a new markup-based typesetting system that is powerful and easy to learn.” While Typst provides a built-in `table()` function, it does not currently support more advanced features such as row spans and column spans, fine-grain control of borders, or complex cell alignments. Pg Biel’s `tablex` project [2] provides many of these features. However, it remains the case that writing a table using either `table()` or `tablex()` can require rather verbose syntax.

The `tbl.typ` project is an effort to allow the expression of rich tables in Typst using a more terse syntax. This syntax comes from a UNIX heritage: the `tbl` preprocessor which designed for use with the traditional TROFF typesetting system [3] [4] [5]. Important differences between the syntax of traditional `tbl` and `tbl.typ` are noted in Section **TK**.

After importing the library using `#import "tbl.typ"`, the basic format of a table when using `tbl.typ` is the following:

```
```tbl
Format specifications .
Data
```
```

The two main components of this syntax are:

- *Format specifications*. This describes the layout of the table in terms of the number and style of columns for each row.

The last line of the format specifications must end in a period (`.`). This is the separator between the two sections.

- *Data*. This is the content that will fill each cell of the table. Generally every line of input in this section corresponds to a row in the table, though there are exceptions noted later. Cells are separated by the `tab` option which defaults to a TAB character.

Region options

In addition to the overall [table syntax](#) itself, you may specify *region options* that control the parsing and styling of the table as a whole using a “show-everything” rule prior to the tables you would like to control. For example:

```
#show: tbl.template.with(
  allbox: true,
  tab: "|",
)
```

The following options are recognized:

auto-lines Like [box](#), but also draw a line between every cell if `true`. This is the same option from [tablex](#).

Aliases: `allbox`

Default: `false`

box If `true`, draw a line around the entire table.

Aliases: `frame`

Default: `false`

breakable If `true`, the table can span multiple pages if necessary.

Aliases: `nokeep`

Default: `false`

decimalpoint The string used to separate the integral part of a number from the fractional part.

Default: `"."`

doublebox Like [box](#), but also draw a second line around the entire table if `true`.

Aliases: `doubleframe`

Default: `false`

font The font for the table. Can be overridden later by the format specifications.

Default: `"Times"`

| | |
|----------------------|---|
| header-rows | <p>The number of rows at the beginning of the table to consider part of the “header” for the purposes of <code>repeat-header</code>. This option is also controlled by <code>.TH</code> rows in the table data.</p> <p><i>Default:</i> <code>1</code></p> |
| macros | <p>A dictionary of (name, function) pairs that can be used with column modifier <code>m</code>.</p> <p><i>Default:</i> <code>(:)</code></p> |
| repeat-header | <p>If <code>breakable</code> is <code>true</code> and this option is <code>true</code>, then the table header controlled by <code>header-rows</code> will be re-displayed on each subsequent page. This option is also controlled by <code>.TH</code> rows in the table data.</p> <p><i>Default:</i> <code>false</code></p> |
| stroke | <p>How to draw all lines in the table.</p> <p><i>Aliases:</i> <code>linesize</code></p> <p><i>Default:</i> <code>1pt</code></p> |
| tab | <p>The string delimiter that separates different cells within a given row of the table data.</p> <p><i>Default:</i> <code>"\t"</code> (a TAB character)</p> |
| tbl-align | <p>How to align the table as a whole.</p> <p><i>Default:</i> <code>left</code></p> |

Format specifications

The format specifications section controls the layout and style of cells within rows and columns of the table.

Each comma or new line of format specification begins a new *row definition*. Within each row definition, encountering a *column classifier* character denotes a new column in the table. The classifier may be followed by any number of *column modifiers*, some of which may have required arguments enclosed in parentheses.

The following column classifiers are recognized. They may be given as either capital or lowercase.

| | |
|-------------------------|--|
| L | Left align. |
| R | Right align. |
| C | Center align. |
| N | Numerically align. |
| S | This cell is column-spanned by the previous cell to the left in the current row.

<i>The corresponding table data entries should be empty.</i> |
| ^ (caret) | This cell is row-spanned by the corresponding cell in the previous row above.

<i>The corresponding table data entries should be empty.</i> |
| _ (underscore) | This cell contains a vertically-centered horizontal rule.

<i>The corresponding table data entries should be empty.</i>
<i>Aliases: -</i> |
| = (equals sign) | Same as _ , but draw a double horizontal rule instead.

<i>The corresponding table data entries should be empty.</i> |
| (vertical bar) | This classifier does not actually begin a new column, but rather indicates the location of a vertical line.

If placed at the beginning of a row definition, the line is drawn to the left of the first cell in that row. Otherwise, it is drawn to the right of the current cell in that row. |

Data

Examples

Example 1: adapted from [4]

```

tbl
lz s | rt
lt| cb| ^
^ | rz s.
left||r
l|center|
|right

```

| | | |
|------|--------|-------|
| left | | r |
| l | center | |
| | | right |

Example 2: adapted from [5, p. 41]

```

tbl
c c c
l l ne .
Fact|Location|Statistic
Largest state|Alaska|591,004 sq. mi.
Smallest state|Rhode Island|1,212 sq. mi.
Longest river|Mississippi-Missouri|3,710 mi.
Highest mountain|Mount McKinley, AK|20,320 ft.
Lowest point|Death Valley, CA|-- 282 ft.

```

| Fact | Location | Statistic |
|------------------|----------------------|-----------------|
| Largest state | Alaska | 591,004 sq. mi. |
| Smallest state | Rhode Island | 1,212 sq. mi. |
| Longest river | Mississippi-Missouri | 3,710 mi. |
| Highest mountain | Mount McKinley, AK | 20,320 ft. |
| Lowest point | Death Valley, CA | – 282 ft. |

Example 3: adapted from [4]

```

tbl
r| l
r n.
software|version
—
AFL|2.39b
Mutt|1.8.0
Ruby|1.8.7.374
TeX Live|2015

```

| software | version |
|----------|-----------|
| AFL | 2.39b |
| Mutt | 1.8.0 |
| Ruby | 1.8.7.374 |
| TeX Live | 2015 |

Example 4: adapted from [5, p. 43]

```

tbl
cf(Courier New) s s s
c | cs s
c | cs s
c |c|c|c
c |c|c|c
l |n |ne |ne.
Composition of Foods
-
Food|Percent by Weight
\^|_
\^|Protein|Fat|Carbo-
\^|\^|\^|hydrate
-
Apples|.4|.5|13.0
Halibut|18.4|5.2|...
Lima beans|7.5|.8|22.0
Milk|3.3|4.0|5.0
Mushrooms|3.5|.4|6.0
Rye bread|9.0|.6|52.7
tbl

```

| Composition of Foods | | | |
|----------------------|-------------------|-----|-------------------|
| Food | Percent by Weight | | |
| | Protein | Fat | Carbo-
hydrate |
| Apples | .4 | .5 | 13.0 |
| Halibut | 18.4 | 5.2 | ... |
| Lima beans | 7.5 | .8 | 22.0 |
| Milk | 3.3 | 4.0 | 5.0 |
| Mushrooms | 3.5 | .4 | 6.0 |
| Rye bread | 9.0 | .6 | 52.7 |

Example 5: adapted from [5, p. 42]

```

tbl
c s s
c | c | c
l | l | ne .
Major New York Bridges
-
Bridge|Designer|Length
-
Brooklyn|J . A . Roebling|1595
Manhattan|G . Lindenthal|1470
Williamsburg|L . L . Buck|1600
-
Queensborough|Palmer &|1182
|Hornbostel
-
||1380
Triborough|O . H . Ammann|_
||383
-
Bronx Whitestone|O . H . Ammann|2300
Throgs Neck|O . H . Ammann|1800
-
George Washington|O . H . Ammann|3500
tbl

```

| Major New York Bridges | | |
|------------------------|------------------------|--------|
| Bridge | Designer | Length |
| Brooklyn | J . A . Roebling | 1595 |
| Manhattan | G . Lindenthal | 1470 |
| Williamsburg | L . L . Buck | 1600 |
| Queensborough | Palmer &
Hornbostel | 1182 |
| Triborough | O . H . Ammann | 1380 |
| | | 383 |
| Bronx Whitestone | O . H . Ammann | 2300 |
| Throgs Neck | O . H . Ammann | 1800 |
| George Washington | O . H . Ammann | 3500 |

Example 6: adapted from [4]

```

```tbl
rb c lb
r ci l.
r|center|l
ri|ce|le
right|c|left
```

```

| | | |
|-------|--------|------|
| r | center | l |
| ri | ce | le |
| right | c | left |

Example 7: adapted from [3]

```

```tbl
Cf(BI) Cf(BI) Cf(B), C C Cu.
n|n*#sym.times;*n|difference
1|1
2|4|3
3|9|5
4|16|7
5|25|9
6|36|11
```

```

| <i>n</i> | <i>n</i> × <i>n</i> | difference |
|----------|---------------------|------------|
| 1 | 1 | 3 |
| 2 | 4 | 5 |
| 3 | 9 | 7 |
| 4 | 16 | 9 |
| 5 | 25 | 11 |
| 6 | 36 | |

Example 8: adapted from [5, p. 42]

```

```tbl
c c
np(-2) | n | .
|Stack
|_
1|46
|_
2|23
|_
3|15
|_
4|6.5
|_
5|2.1
|_
```

```

| | Stack |
|---|-------|
| 1 | 46 |
| 2 | 23 |
| 3 | 15 |
| 4 | 6.5 |
| 5 | 2.1 |

Example 9: adapted from [5, p. 37]

```

```tbl
n.
13
4.2
26.4.12
26.4. 12
26.4 .12
abc
abc\&
43\&3.22
749.12
```

```

| | |
|----------|----------|
| n. | 13 |
| 13 | 4.2 |
| 4.2 | 26.4.12 |
| 26.4.12 | 26.4. 12 |
| 26.4 .12 | 26.4 .12 |
| abc | abc |
| abc\& | abc |
| 43\&3.22 | 433.22 |
| 749.12 | 749.12 |

Example 10: adapted from [5, p. 41]

```

``tbl
c s s
c c c
n n ne .
AT&T Common Stock
Year|Price|Dividend
1984|15-20|\$1.20
5|19-25|1.20
6|21-28|1.20
7|20-36|1.20
8|24-30|1.20
9|29-37|.30\*
``

```

| AT&T Common Stock | | |
|-------------------|-------|----------|
| Year | Price | Dividend |
| 1984 | 15-20 | \$1.20 |
| 5 | 19-25 | 1.20 |
| 6 | 21-28 | 1.20 |
| 7 | 20-36 | 1.20 |
| 8 | 24-30 | 1.20 |
| 9 | 29-37 | .30* |

Example 11

```

``tbl
cb cb
c c.
Grade|Points
A|510
B|450
C|390
D|330
``

```

| Grade | Points |
|-------|--------|
| A | 510 |
| B | 450 |
| C | 390 |
| D | 330 |

Example 12: adapted from [5, p. 44]

```

``tbl
cf(I) s s
c cw(1in) cw(1in)
ltp(9) ltp(9) ltp(9).
New York Area Rocks
Era|Formation|Age (years)
Precambrian|Reading Prong|>1 billion
Paleozoic|Manhattan Prong|400 million
Mesozoic|T{
#set text(hyphenate: true, overhang: true)
Newark Basin, incl.
Stockton, Lockatong, and Brunswick
formations; also Watchungs
and Palisades.
T}|200 million
Cenozoic|Coastal Plain|T{
#set text(hyphenate: true, overhang: true)
#set par(justify: true)
On Long Island 30,000 years;
Cretaceous sediments redeposited
by recent glaciation.
T}
``

```

| <i>New York Area Rocks</i> | | |
|----------------------------|--|---|
| Era | Formation | Age (years) |
| Precambrian | Reading Prong | >1 billion |
| Paleozoic | Manhattan Prong | 400 million |
| Mesozoic | Newark Basin,
incl. Stockton,
Lockatong, and
Brunswick forma-
tions; also
Watchungs and
Palisades. | 200 million |
| Cenozoic | Coastal Plain | On Long Island
30,000 years; Cre-
taceous sediments
redeposited by re-
cent glaciation. |

Example 13: adapted from [4]

```

``tbl
le le7| lw(10).
The fourth line|_|line 1
of this column|=|line 2
determines|\_|line 3
the column width.|T{
This text is too wide to fit into a column of width 17.
T}|line 4
T{
No break here.
T}||line 5
``

```

| | | |
|-------------------|--|--------|
| The fourth line | | line 1 |
| of this column | | line 2 |
| determines | | line 3 |
| the column width. | This text is too wide to fit into a
column of width 17. | line 4 |
| No break here. | | line 5 |

Example 14: adapted from [5, p. 45]

```

``tbl
cb s s s s
cp(-2) s s s s
c | c | c | c | c
c | c | c | c | c
r2 | n2 | n2 | n2e | nbe.
Readability of Text
Line Width and Leading for 10-Point Type
-
Line : Set : 1-Point : 2-Point : 4-Point
Width : Solid : Leading : Leading : Leading
-
9 Pica : 93 : --6.0 : --5.3 : --7.1
14 Pica : 450 : --0.6 : --0.3 : --1.7
19 Pica : 5 : --5.1 : 0.0 : --2.0
31 Pica : 3 : --3.8 : --2.4 : --3.6
43 Pica : 5.1 : --90000.000 : --5.9 : --8.8
``

```

| Readability of Text | | | | |
|--|-----------|-----------------|-----------------|-----------------|
| Line Width and Leading for 10-Point Type | | | | |
| Line Width | Set Solid | 1-Point Leading | 2-Point Leading | 4-Point Leading |
| 9 Pica | 93 | -6.0 | -5.3 | -7.1 |
| 14 Pica | 450 | -0.6 | -0.3 | -1.7 |
| 19 Pica | 5 | -5.1 | 0.0 | -2.0 |
| 31 Pica | 3 | -3.8 | -2.4 | -3.6 |
| 43 Pica | 5.1 | -90000.000 | -5.9 | -8.8 |

References

- [1] <https://typst.app/>
- [2] Pg Biel, “Typst-tablex.” <https://github.com/PgBiel/typst-tablex>
- [3] <https://man7.org/linux/man-pages/man1/tbl.1.html>

- [4] <https://man.openbsd.org/tbl.7>
- [5] L. L. Cherry, and M. E. Lesk, “Tbl – a program to format tables,” in *Unix Res. System*, A. G. Hume, and M. D. McIlroy, Eds., vol. 2, 10th ed., Murray Hill, New Jersey 07974: Holt Rinehart & Winston, pp. 35–51. [Online]. Available: <https://9p.io/10thEdMan/tbl.pdf>