```
Macro
         pg_edit.the V0.1 (THE)
            Pablo Garcia-Abia (Pablo.Garcia.Abia@cern.ch)
  Author:
  Date:
            27/09/1999
  Syntax:
            pg_edit
  Description:
     Macro to be assigned to a key (mouse or keyboard). When
     issued, the string under the cursor (delimited by the
     characters of 'delim') is taken as a filename and the file, if
     exists, is edited. Otherwise, no action is taken.
     This macro works in any file, not only in a directory list
     (like the command 'sos edit' does).
     For example, I have defined:
          'define 2LB IN FILEAREA cursor MOUSE#macro pg_edit'
          'define C-X
                                macro pg_edit'
 * Bugs, comments and/or questions to Pablo.Garcia.Abia@cern.ch
/**** Modify this list by hand to match your needs ****/
 delim = " ,;:'`[]{}()<>|!@%^&?*+="
 delim = delim||'"'
                               /* add " to the list */
'EXTRACT /LINE/CURSOR'
 If cursor.3 <= 0 Then Return
  'LOCATE : 'cursor.3
  'EXTRACT /CURLINE'
  'LOCATE :'line.1
/* Make sure cursor is not on one of the delimiters */
 Do d=1 To length(delim)
    char = substr(delim,d,1)
    If substr(curline.3,cursor.4,1) == char Then Return
 End
/* Search for the beginning of the string */
 Do i=cursor.4-1 To 1 By -1
    ifo = 0
```

1 of 2 26/10/2024, 19:07

Return

```
Do d=1 To length(delim)
        char = substr(delim,d,1)
        If substr(curline.3,i,1) == char Then Do
          Leave
        End
     End
     If ifo == 1 Then Leave
  End
/* Search for the end of the string */
  Do j=cursor.4+1 To length(curline.3)
     ifo = 0
     Do d=1 To length(delim)
        char = substr(delim,d,1)
        If substr(curline.3,j,1) == char Then Do
          ifo=1
          Leave
        End
     End
     If ifo == 1 Then Leave
  End
/* Edit the file if exists */
  file = substr(curline.3,i+1,j-i-1)
  If length(file) > 0 Then Do
    If state(file) > 0 Then EMSG "File '"file"' does not exist."
    Else 'XEDIT' file
  End
```

26/10/2024, 19:07