
Max Haviv

Assignment 1 Image Resolution

Initial Image

```
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.image as mpimg

img = mpimg.imread('rose.jpg')
plt.imshow(img, cmap='gray')
plt.show()
```



Down Sample Function

```
In [187... def down_sample(input_dimensions, output_dimensions, img):
    factor = int(input_dimensions / output_dimensions)
    down_sampled_img = np.zeros((output_dimensions, output_dimensions))

# loop through the dimensions of the output to fill in the new image
for row in range(output_dimensions):
    for col in range(output_dimensions):
        # select a pixel from the original image to set into the downscaled image
        # this pixel is the row and col multiplied by the factor that the image is being d
        selected_pixel= img[factor * row][factor * col]
        down_sampled_img[row,col] = selected_pixel

return down_sampled_img
```

Up Sample Function

```
In [188...

def up_sample(input_dimensions, output_dimensions, img):
    factor = int(output_dimensions / input_dimensions)
    up_sample_img = np.zeros((output_dimensions, output_dimensions))


# loop through the input image
for row in range(input_dimensions):
    for col in range(input_dimensions):
        selected_pixel = img[row][col]
        # spread the slected pixel through the rows and columns
        up_sample_img[row * factor:(row + 1) * factor,col * factor:(col + 1) * factor] = s
    return up_sample_img
```

512 Down and Up Sample

```
In [210... img_512 = down_sample(1024, 512, img)
    img_512_upsample = up_sample(512, 1024, img_512)
    fig, ax = plt.subplots(1,2, figsize=(15,10))
    ax[0].imshow(img_512, cmap='gray', aspect='equal', extent=[0, img_512.shape[1], img_512.ax[0].set_title(f"Down Sample to 512x512")
    ax[0].axis('on')

ax[1].imshow(img_512_upsample, cmap='gray', aspect='equal', extent=[0, img_512_upsample.ax[1].set_title(f"Up Sample to 1024x1024")
    ax[1].axis('on')


plt.autoscale(False)
    plt.tight_layout()
    plt.show()
```



```
In [253... img1 = img img2 = img_512
```

```
img3 = img_512_upsample
# Get image dimensions
img1_height, img1_width = img1.shape[:2]
img2_height, img2_width = img2.shape[:2]
img3_height, img3_width = img3.shape[:2]
spacing = 300
fig, ax = plt.subplots(figsize=(20,10))
ax.imshow(img1, cmap='gray', extent=(0, img1_width, 0, img1_height))
plt.text(img1_width / 2, img1_height + 10, 'Original Image', ha='center', fontsize=12)
ax.imshow(img2, cmap='gray', extent=(img1_width + spacing, img1_width + img2_width + spa
plt.text(img1_width + img2_width / 2 + spacing, max(img1_height, img2_height) + 10, '512
ax.imshow(img3, cmap='gray', extent=(img1_width + img2_width + 2 * spacing, img1_width +
plt.text(img1_width + img2_width + img3_width / 2 + 2 * spacing, max(img1_height, img3_h
# Adjust the axes limits to fit all three images and titles with spacing
ax.set_xlim(0, img1_width + img2_width + img3_width + 2 * spacing)
ax.set_ylim(0, max(img1_height, img2_height, img3_height) + 30)
ax.axis('off')
plt.show()
```










256 Down and Up Sample

```
img_256 = down_sample(1024, 256, img)
img_256_upsample = up_sample(256, 1024, img_256)
fig, ax = plt.subplots(1,2, figsize=(15,10))
ax[0].imshow(img_256, cmap='gray', aspect='equal', extent=[0, img_256.shape[1], img_256.ax[0].set_title(f"Down Sample to 256x256")
ax[0].axis('on')


ax[1].imshow(img_256_upsample, cmap='gray', aspect='equal', extent=[0, img_256_upsample.ax[1].set_title(f"Up Sample to 1024x1024")
ax[1].axis('on')

plt.autoscale(False)
plt.tight_layout()
plt.show()
```



```
In [254...
         img1 = img
         img2 = img_256
         img3 = img_256_upsample
         # Get image dimensions
         img1_height, img1_width = img1.shape[:2]
         img2_height, img2_width = img2.shape[:2]
         img3_height, img3_width = img3.shape[:2]
         spacing = 300
         fig, ax = plt.subplots(figsize=(20,10))
         ax.imshow(img1, cmap='gray', extent=(0, img1_width, 0, img1_height))
         plt.text(img1_width / 2, img1_height + 10, 'Original Image', ha='center', fontsize=12)
         ax.imshow(img2, cmap='gray', extent=(img1_width + spacing, img1_width + img2_width + spa
         plt.text(img1_width + img2_width / 2 + spacing, max(img1_height, img2_height) + 10, '256
         ax.imshow(img3, cmap='gray', extent=(img1_width + img2_width + 2 * spacing, img1_width +
         plt.text(img1_width + img2_width + img3_width / 2 + 2 * spacing, max(img1_height, img3_h
         # Adjust the axes limits to fit all three images and titles with spacing
         ax.set_xlim(0, img1_width + img2_width + img3_width + 2 * spacing)
         ax.set_ylim(0, max(img1_height, img2_height, img3_height) + 30)
         ax.axis('off')
         plt.show()
```









128 Down and Up Sample


```
img_128 = down_sample(1024, 128, img)
img_128_upsample = up_sample(128, 1024, img_128)

fig, ax = plt.subplots(1,2, figsize=(15,10))

ax[0].imshow(img_128, cmap='gray', aspect='equal', extent=[0, img_128.shape[1], img_128.
ax[0].set_title(f"Down Sample to 128x128")
ax[0].axis('on')

ax[1].imshow(img_128_upsample, cmap='gray', aspect='equal', extent=[0, img_128_upsample.
ax[1].set_title(f"Up_Sample to 1024x1024")
ax[1].axis('on')


plt.autoscale(False)
plt.tight_layout()
plt.show()
```



```
In [255... img1 = img
    img2 = img_128
```

```
img3 = img_128_upsample
# Get image dimensions
img1_height, img1_width = img1.shape[:2]
img2_height, img2_width = img2.shape[:2]
img3_height, img3_width = img3.shape[:2]
spacing = 300
fig, ax = plt.subplots(figsize=(20,10))
ax.imshow(img1, cmap='gray', extent=(0, img1_width, 0, img1_height))
plt.text(img1_width / 2, img1_height + 10, 'Original Image', ha='center', fontsize=12)
ax.imshow(img2, cmap='gray', extent=(img1_width + spacing, img1_width + img2_width + spa
plt.text(img1_width + img2_width / 2 + spacing, max(img1_height, img2_height) + 10, '128
ax.imshow(img3, cmap='gray', extent=(img1_width + img2_width + 2 * spacing, img1_width +
plt.text(img1_width + img2_width + img3_width / 2 + 2 * spacing, max(img1_height, img3_h
# Adjust the axes limits to fit all three images and titles with spacing
ax.set_xlim(0, img1_width + img2_width + img3_width + 2 * spacing)
ax.set_ylim(0, max(img1_height, img2_height, img3_height) + 30)
ax.axis('off')
plt.show()
```









Change the gray level of an 8-bit gray level image


define funtion

```
In [256... def change_gray_level(bit):
    new_img = np.zeros((1024,1024))

for row in range(1024):
    for col in range(1024):
        pixel = img[row,col]
        # create a mask for bits that we want to discard
        mask = 256 - (2 ** (8-bit))
        # bitwise operation clears the lower bits
        bitwise_pixel = pixel & mask
        # shift the bits from their original 8 bits to the bits provided
        final_pixel = bitwise_pixel >> (8 - bit)
```

```
In [257... img_128_gray = change_gray_level(7)
    img_64_gray = change_gray_level(6)
    img_32_gray = change_gray_level(5)


In [258... plt.imshow(img_128_gray, cmap='gray')
    plt.title("128 gray level")
    plt.show()
```




new_img[row, col] = final_pixel

return new_img


```
In [259... plt.imshow(img_64_gray, cmap='gray')
    plt.title("64 gray level")
    plt.show()
```



```
In [260... plt.imshow(img_32_gray, cmap='gray')
    plt.title("32 gray level")
    plt.show()
```



```
In [262... plt.imshow(change_gray_level(3), cmap='gray')
    plt.title("8 gray level for fun")
    plt.show()
```



In [261... plt.imshow(change_gray_level(2), cmap='gray')
 plt.title("4 gray level for fun")
 plt.show()

