

How can I make CMake use Mingw-w64 gcc/g++? [duplicate]

Asked 8 years, 2 months ago Modified 7 years, 7 months ago Viewed 69k times



19



This question already has answers here:

[Running CMake on Windows](#) (4 answers)

Closed 7 years ago.

I am on Windwos trying to get Mingw-w64 to work with CMake since my MSVC is somehow not working at all (using Windows10 64bit.

Basically I add the arguments `-DCMAKE_CXX_COMPILER="C:/MinGW-w64/mingw64/bin/g++.exe" -DCMAKE_C_COMPILER="C:/MinGW-w64/mingw64/bin/gcc.exe"` to my call to CMake which sets the corresponding compiler.

However I get these errors:



```
-- The C compiler identification is unknown
-- The CXX compiler identification is unknown
-- Check for working C compiler: C:/MinGW-w64/mingw64/bin/gcc.exe
-- Check for working C compiler: C:/MinGW-w64/mingw64/bin/gcc.exe -- broken
CMake Error at C:/Program Files/CMake/share/cmake-
3.12/Modules/CMakeTestCCompiler.cmake:52 (message):
  The C compiler

    "C:/MinGW-w64/mingw64/bin/gcc.exe"

  is not able to compile a simple test program.
```

How could I get this to work?

c++

gcc

cmake

g++

mingw-w64

Share Improve this question Follow

asked Jul 25, 2018 at 0:09



Leslie

363

1

4

16

Can you launch `"C:/MinGW-w64/mingw64/bin/gcc.exe"` (e.g. from `cmd`)? You might also want to try the *Win* path style: `"C:\MinGW-w64\mingw64\bin\gcc.exe"` (if that doesn't work either you could try doubling the `"**\**s)` – [CristiFati](#) Jul 27, 2018 at 20:51

1 Answer

Sorted by: Highest score (default) ▾



The simplest way to generate makefiles for MinGW (and MinGW-w64) is to use the appropriate CMake generator. Just call cmake with

42



-G "MinGW Makefiles"

Copy



no need to set DCMMAKE_CXX_COMPILER and DCMMAKE_C_COMPILER by hand.



For this to work, CMake must find your compilers. So this path must be added to the windows PATH variable, as CristiFati pointed out:

Copy

C:/MinGW-w64/mingw64/bin

To check if the PATH is correct, fire up a Windows command prompt and run

Copy

where gcc

The output should be (at least) the path you just added to the Windows PATH variable.

Share Improve this answer Follow

answered Feb 26, 2019 at 20:02



[duddel](#)

831 10 15

4 Comments ^

Add a comment



[sancelot](#) Over a year ago

You hadditionally have to specify CMAKE_MAKE_PROGRAM to mingw32-make

▲ 2

Reply



[Patafikss](#) Over a year ago

we specifically want to use mingw64, isn't that contradictory to set the make programe to mingw32? am I missing something?

▲ 1

Reply



[Catradora](#) Over a year ago

@Patafikss somewhat confusingly, mingw64 is invoked by calling mingw32. mingw32 is used to compile both 32-bit and 64-bit binaries.

▲ 5 Reply ...



AndreGraveler Over a year ago

@sancelot you can make a batch program called make.bat that refer to mingw32-make.exe. Place this batch program in the MinGW bin folder. See [Calling an executable by a different name](#)

▲ 1 Reply ...

Start asking to get answers

Find the answer to your question by asking.

[Ask question](#)

Explore related questions

[c++](#) [gcc](#) [cmake](#) [g++](#) [mingw-w64](#)

See similar questions with these tags.