

Uri



Added in [API level 1](#) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

[Kotlin](/reference/kotlin/android/net/Uri) | **Java**

```
public abstract class Uri
extends Object (/reference/java/lang/Object) implements Comparable
(/reference/java/lang/Comparable)<Uri (/reference/android/net/Uri)>, Parcelable
(/reference/android/os/Parcelable)
```

[java.lang.Object](/reference/java/lang/Object) (</reference/java/lang/Object>)
↳ [android.net.Uri](#)

Immutable URI reference. A URI reference includes a URI and a fragment, the component of the URI following a '#'. Builds and parses URI references which conform to [RFC 2396](#) (<http://www.faqs.org/rfcs/rfc2396.html>).

In the interest of performance, this class performs little to no validation. Behavior is undefined for invalid input. This class is very forgiving--in the face of invalid input, it will return garbage rather than throw an exception unless otherwise specified.

Summary

Nested classes

class

[Uri.Builder](/reference/android/net/Uri.Builder) (</reference/android/net/Uri.Builder>)

Helper class for building or manipulating URI references.

Inherited constants

From interface [android.os.Parcelable](#) (/reference/android/os/Parcelable)

int

CONTENTS_FILE_DESCRIPTOR

(/reference/android/os/Parcelable#CONTENTS_FILE_DESCRIPTOR)

Descriptor bit used with [describeContents\(\)](#)

(/reference/android/os/Parcelable#describeContents()): indicates that the Parcelable object's flattened representation includes a file descriptor.

int

PARCELABLE_WRITE_RETURN_VALUE

(/reference/android/os/Parcelable#PARCELABLE_WRITE_RETURN_VALUE)

Flag for use with [writeToParcel\(Parcel, int\)](#)

(/reference/android/os/Parcelable#writeToParcel(android.os.Parcel, %20int))

: the object being written is a return value, that is the result of a function such as "[Parcelable someFunction\(\)](#)", "[void someFunction\(out Parcelable\)](#)", or "[void someFunction\(inout Parcelable\)](#)".

Fields

**public static final
Creator**

(/reference/android/os/Parcelable.Creator)

<Uri (/reference/android/net/Uri)

>

CREATOR (/reference/android/net/Uri#CREATOR)

Reads Uris from Parcels.

public static final Uri
(/reference/android/net/Uri)

EMPTY (/reference/android/net/Uri#EMPTY)

The empty URI, equivalent to "".

Public methods

abstract Uri.Builder[\(/reference/android/net/Uri.Builder\)](/reference/android/net/Uri.Builder)**buildUpon** [\(/reference/android/net/Uri#buildUpon\(\)\)](/reference/android/net/Uri#buildUpon()) ()

Constructs a new builder, copying the attributes from this Uri.

int**compareTo** [\(/reference/android/net/Uri#compareTo\(android.net.Uri\) \)](/reference/android/net/Uri#compareTo(android.net.Uri))
 [\(Uri](/reference/android/net/Uri) [\(/reference/android/net/Uri\)](/reference/android/net/Uri) **other**)

Compares the string representation of this Uri with that of another.

static String [\(/reference/java/lang/String\)](/reference/java/lang/String)**decode** [\(/reference/android/net/Uri#decode\(java.lang.String\) \)](/reference/android/net/Uri#decode(java.lang.String)) ([String](/reference/java/lang/String) **s**)

Decodes '%'-escaped octets in the given string using the UTF-8 scheme.

static String [\(/reference/java/lang/String\)](/reference/java/lang/String)**encode**[\(/reference/android/net/Uri#encode\(java.lang.String, %20java.lang.String\) \)](/reference/android/net/Uri#encode(java.lang.String,%20java.lang.String))
 [\(String](/reference/java/lang/String) [\(/reference/java/lang/String\)](/reference/java/lang/String) **s**, [String](/reference/java/lang/String) **allow**)

Encodes characters in the given string as '%'-escaped octets using the UTF-8 scheme.

static String [\(/reference/java/lang/String\)](/reference/java/lang/String)**encode** [\(/reference/android/net/Uri#encode\(java.lang.String\) \)](/reference/android/net/Uri#encode(java.lang.String)) ([String](/reference/java/lang/String) **s**)

Encodes characters in the given string as '%'-escaped octets using the UTF-8 scheme.

boolean**equals** [\(/reference/android/net/Uri#equals\(java.lang.Object\) \)](/reference/android/net/Uri#equals(java.lang.Object)) ([Object](/reference/java/lang/Object) **o**)

Compares this Uri to another object for equality.

static Uri [\(/reference/android/net/Uri\)](/reference/android/net/Uri)**fromFile** [\(/reference/android/net/Uri#fromFile\(java.io.File\) \)](/reference/android/net/Uri#fromFile(java.io.File)) ([File](/reference/java/io/File) **file**)

Creates a Uri from a file.

static Uri**fromParts**

(/reference/android/net/Uri)	(/reference/android/net/Uri#fromParts(java.lang.String,%20java.lang.String,%20java.lang.String)) (String (/reference/java/lang/String) scheme, String (/reference/java/lang/String) ssp, String (/reference/java/lang/String) fragment) Creates an opaque Uri from the given components.
abstract String (/reference/java/lang/String)	getAuthority (/reference/android/net/Uri#getAuthority())() Gets the decoded authority part of this URI.
boolean	getBooleanQueryParameter (/reference/android/net/Uri#getBooleanQueryParameter(java.lang.String,%20boolean)) (String (/reference/java/lang/String) key, boolean default Value) Searches the query string for the first value with the given key and interprets it as a boolean value.
abstract String (/reference/java/lang/String)	getEncodedAuthority (/reference/android/net/Uri#getEncodedAuthority())() Gets the encoded authority part of this URI.
abstract String (/reference/java/lang/String)	getEncodedFragment (/reference/android/net/Uri#getEncodedFragment())() Gets the encoded fragment part of this URI, everything after the '#'.
abstract String (/reference/java/lang/String)	getEncodedPath (/reference/android/net/Uri#getEncodedPath())() Gets the encoded path.
abstract String (/reference/java/lang/String)	getEncodedQuery (/reference/android/net/Uri#getEncodedQuery())() Gets the encoded query component from this URI.
abstract String (/reference/java/lang/String)	getEncodedSchemeSpecificPart (/reference/android/net/Uri#getEncodedSchemeSpecificPart())() Gets the scheme-specific part of this URI, i.e. everything between the

scheme separator ':' and the fragment separator '#'.

abstract String

(/reference/java/lang/String)

getEncodedUserInfo

(/reference/android/net/Uri#getEncodedUserInfo())()

Gets the encoded user information from the authority.

abstract String

(/reference/java/lang/String)

getFragment (/reference/android/net/Uri#getFragment())()

Gets the decoded fragment part of this URI, everything after the '#'.

abstract String

(/reference/java/lang/String)

getHost (/reference/android/net/Uri#getHost())()

Gets the encoded host from the authority for this URI.

abstract String

(/reference/java/lang/String)

getLastPathSegment

(/reference/android/net/Uri#getLastPathSegment())()

Gets the decoded last segment in the path.

abstract String

(/reference/java/lang/String)

getPath (/reference/android/net/Uri#getPath())()

Gets the decoded path.

abstract List

(/reference/java/util/List)

<String

(/reference/java/lang/String)>

getPathSegments (/reference/android/net/Uri#getPathSegments())()

Gets the decoded path segments.

abstract int

getPort (/reference/android/net/Uri#getPort())()

Gets the port from the authority for this URI.

abstract String

(/reference/java/lang/String)

getQuery (/reference/android/net/Uri#getQuery())()

Gets the decoded query component from this URI.

String

(/reference/java/lang/String)

getQueryParameter

(/reference/android/net/Uri#getQueryParameter(java.lang.String))
(String (/reference/java/lang/String) key)

Searches the query string for the first value with the given key.

Set (/reference/java/util/Set)
<String
(/reference/java/lang/String)>

getQueryParameterNames
(/reference/android/net/Uri#getQueryParameterNames())()

Returns a set of the unique names of all query parameters.

List (/reference/java/util/List)
<String
(/reference/java/lang/String)>

getQueryParameters
(/reference/android/net/Uri#getQueryParameters(java.lang.String))
(**String** (/reference/java/lang/String) **key**)

Searches the query string for parameter values with the given key.

abstract String
(/reference/java/lang/String)

getScheme (/reference/android/net/Uri#getScheme())()

Gets the scheme of this URI.

abstract String
(/reference/java/lang/String)

getSchemeSpecificPart
(/reference/android/net/Uri#getSchemeSpecificPart())()

Gets the scheme-specific part of this URI, i.e. everything between the scheme separator ':' and the fragment separator '#'.

abstract String
(/reference/java/lang/String)

getUserInfo (/reference/android/net/Uri#getUserInfo())()

Gets the decoded user information from the authority.

int

hashCode (/reference/android/net/Uri#hashCode())()

Hashes the encoded string representation of this Uri consistently with **equals(Object)**
(/reference/android/net/Uri#equals(java.lang.Object)).

boolean

isAbsolute (/reference/android/net/Uri#isAbsolute())()

Returns true if this URI is absolute, i.e. if it contains an explicit scheme.

abstract boolean

isHierarchical (/reference/android/net/Uri#isHierarchical())()

Returns true if this URI is hierarchical like "http://google.com".

boolean**isOpaque** (/reference/android/net/Uri#isOpaque()) ()

Returns true if this URI is opaque like "mailto:nobody@google.com".

abstract boolean**isRelative** (/reference/android/net/Uri#isRelative()) ()

Returns true if this URI is relative, i.e. if it doesn't contain an explicit scheme.

Uri (/reference/android/net/Uri)**normalizeScheme** (/reference/android/net/Uri#normalizeScheme()) ()

Return an equivalent URI with a lowercase scheme component.

static Uri

(/reference/android/net/Uri)

parse (/reference/android/net/Uri#parse(java.lang.String)) (**String**
(/reference/java/lang/String) **uriString**)

Creates a Uri which parses the given encoded URI string.

abstract String

(/reference/java/lang/String)

toString (/reference/android/net/Uri#toString()) ()

Returns the encoded string representation of this URI.

static Uri

(/reference/android/net/Uri)

withAppendedPath(/reference/android/net/Uri#withAppendedPath(android.net.Uri,
%20java.lang.String))(**Uri** (/reference/android/net/Uri) **baseUri**, **String**
(/reference/java/lang/String) **pathSegment**)

Creates a new Uri by appending an already-encoded path segment to a base Uri.

static void**writeToParcel**(/reference/android/net/Uri#writeToParcel(android.os.Parcel,
%20android.net.Uri))(**Parcel** (/reference/android/os/Parcel) **out**, **Uri**
(/reference/android/net/Uri) **uri**)

Writes a Uri to a Parcel.

Inherited methods

From class [java.lang.Object](/reference/java/lang/Object) (/reference/java/lang/Object)

Object (/reference/java/lang/Object)

clone (/reference/java/lang/Object#clone()) ()

Creates and returns a copy of this object.

boolean

equals

(/reference/java/lang/Object#equals(java.lang.Object))
(**Object** (/reference/java/lang/Object) **obj**)

Indicates whether some other object is "equal to" this one.

void

finalize (/reference/java/lang/Object#finalize()) ()

Called by the garbage collector on an object when garbage collection determines that there are no more references to the object.

final Class (/reference/java/lang/Class)<?>

getClass (/reference/java/lang/Object#getClass()) ()

Returns the runtime class of this **Object**.

int

hashCode (/reference/java/lang/Object#hashCode()) ()

Returns a hash code value for the object.

final void

notify (/reference/java/lang/Object#notify()) ()

Wakes up a single thread that is waiting on this object's monitor.

final void

notifyAll (/reference/java/lang/Object#notifyAll()) ()

Wakes up all threads that are waiting on this object's monitor.

String (/reference/java/lang/String)**toString** (/reference/java/lang/Object#toString())()

Returns a string representation of the object.

final void**wait** (/reference/java/lang/Object#wait(long,%20int))
(**long timeoutMillis**, **int nanos**)Causes the current thread to wait until it is awakened, typically by being *notified* or *interrupted*, or until a certain amount of real time has elapsed.**final void****wait** (/reference/java/lang/Object#wait(long))(**long timeoutMillis**)Causes the current thread to wait until it is awakened, typically by being *notified* or *interrupted*, or until a certain amount of real time has elapsed.**final void****wait** (/reference/java/lang/Object#wait())()Causes the current thread to wait until it is awakened, typically by being *notified* or *interrupted*.From interface **java.lang.Comparable** (/reference/java/lang/Comparable)**abstract int****compareTo** (/reference/java/lang/Comparable#compareTo(T))(**Uri**
(/reference/android/net/Uri) **o**)

Compares this object with the specified object for order.

From interface [android.os.Parcelable](/reference/android/os/Parcelable) (/reference/android/os/Parcelable)

abstract int

describeContents

(/reference/android/os/Parcelable#describeContents())()

Describe the kinds of special objects contained in this Parcelable instance's marshaled representation.

abstract void

writeToParcel

(/reference/android/os/Parcelable#writeToParcel(android.os.Parcel, %20int))

([Parcelable](/reference/android/os/Parcelable) (/reference/android/os/Parcelable) **dest**, **int flags**)

Flatten this object in to a Parcel.

Fields

CREATOR

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static final Creator (/reference/android/os/Parcelable.Creator)<Uri (/reference/android/n
```

Reads Uris from Parcels.

EMPTY

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static final Uri (/reference/android/net/Uri) EMPTY
```

The empty URI, equivalent to "".

Public methods

buildUpon

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract Uri.Builder buildUpon ()
```

Constructs a new builder, copying the attributes from this Uri.

Returns

[Uri.Builder](/reference/android/net/Uri.Builder)

(/reference/android/net/
[Uri.Builder](/reference/android/net/Uri.Builder))

compareTo

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public int compareTo (Uri other)
```

Compares the string representation of this Uri with that of another.

Parameters

other

[Uri](/reference/android/net/Uri)

Returns

`int`

decode

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static String (/reference/java/lang/String) decode (String (/reference/java/lang/String) s)
```

Decodes '%'-escaped octets in the given string using the UTF-8 scheme. Replaces invalid octets with the unicode replacement character ("  FFFD").

Parameters

`s` `String`: encoded string to decode

Returns

`String` (/reference/java/lang/String) the given string with escaped octets decoded, or null if s is null

encode

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static String (/reference/java/lang/String) encode (String (/reference/java/lang/String) s,
String (/reference/java/lang/String) allow)
```

Encodes characters in the given string as '%'-escaped octets using the UTF-8 scheme. Leaves letters ("A-Z", "a-z"), numbers ("0-9"), and unreserved characters ("_!~'()*") intact. Encodes all other characters with the exception of those specified in the allow argument.

Parameters

<code>s</code>	String : string to encode
<code>allow</code>	String : set of additional characters to allow in the encoded form, null if no characters should be skipped

Returns

String (/reference/java/lang/String)	an encoded version of s suitable for use as a URI component, or null if s is null
--	---

encode

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static String encode (String s)
```

Encodes characters in the given string as '%'-escaped octets using the UTF-8 scheme. Leaves letters ("A-Z", "a-z"), numbers ("0-9"), and unreserved characters ("_!~'()*") intact. Encodes all other characters.

Parameters

s**String**: string to encode

Returns

String[\(/reference/java/lang/String\)](/reference/java/lang/String)an encoded version of s suitable for use as a URI component, or null if s is null

equals

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public boolean equals (Object o)
```

Compares this Uri to another object for equality. Returns true if the encoded string representations of this Uri and the given Uri are equal. Case counts. Paths are not normalized. If one Uri specifies a default port explicitly and the other leaves it implicit, they will not be considered equal.

Parameters

o**Object**: This value may be **null**.

Returns

boolean**true** if this object is the same as the obj argument; **false** otherwise.

fromFile

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static Uri fromFile (File file)
```

Creates a Uri from a file. The URI has the form "file:///". Encodes path characters with the exception of '/'.

Example: "file:///tmp/android.txt"

Parameters

file

File

Returns

[Uri](/reference/android/net/Uri) a Uri for the given file

Throws

[NullPointerException](/reference/java/lang/NullPointerException) if file is null
([NullPointerException](/reference/java/lang/NullPointerException))

fromParts

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static Uri fromParts (String s
```

```
String (/reference/java/lang/String) ssp,  
String (/reference/java/lang/String) fragment)
```

Creates an opaque Uri from the given components. Encodes the ssp which means this method cannot be used to create hierarchical URIs.

Parameters

<code>scheme</code>	<code>String</code> : of the URI
<code>ssp</code>	<code>String</code> : scheme-specific-part, everything between the scheme separator (':') and the fragment separator ('#'), which will get encoded
<code>fragment</code>	<code>String</code> : fragment, everything after the '#', null if undefined, will get encoded

Returns

`Uri` (/reference/android/net/Uri) Uri composed of the given scheme, ssp, and fragment

Throws

`NullPointerException` (/reference/java/lang/NullPointerException) if scheme or ssp is null

See also:

[if you don't want the ssp and fragment to be encoded](#)

(/reference/android/net/Uri.Builder)

getAuthority

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getAuthority ()
```

Gets the decoded authority part of this URI. For server addresses, the authority is structured as follows: [userinfo '@'] host [':' port]

Examples: "google.com", "bob@google.com:80"

Returns

[String](#) (/reference/java/lang/String) the authority for this URI or null if not present

getBooleanQueryParameter

Added in [API level 11](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public boolean getBooleanQueryParameter (String (/reference/java/lang/String) key,  
                                         boolean defaultValue)
```

Searches the query string for the first value with the given key and interprets it as a boolean value. "false" and "0" are interpreted as [false](#), everything else is interpreted as [true](#).

Parameters

key**String**: which will be decoded

defaultValue**boolean**: the default value to return if there is no query parameter for key

Returns

boolean

the boolean interpretation of the query parameter key

getEncodedAuthority

 Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedAuthority ()
```

Gets the encoded authority part of this URI. For server addresses, the authority is structured as follows: [userinfo '@'] host [':' port]

Examples: "google.com", "bob@google.com:80"

Returns

String[\(/reference/java/lang/String\)](#)

the authority for this URI or null if not present

getEncodedFragment

 Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedFragment ()
```

Gets the encoded fragment part of this URI, everything after the '#'.

Returns

String (/reference/java/lang/String)	the encoded fragment or null if there isn't one
---	---

getEncodedPath Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedPath ()
```

Gets the encoded path.

Returns

String (/reference/java/lang/String)	the encoded path, or null if this is not a hierarchical URI (like "mailto:nobody@google.com") or the URI is invalid
---	---

getEncodedQuery Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedQuery ()
```

Gets the encoded query component from this URI. The query comes after the query separator ('?') and before the fragment separator ('#'). This method would return "q=android" for "http://www.google.com/search?q=android".

Returns

String (/reference/java/lang/String) the encoded query or null if there isn't one

getEncodedSchemeSpecificPart

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedSchemeSpecificPart ()
```

Gets the scheme-specific part of this URI, i.e. everything between the scheme separator ':' and the fragment separator '#'. If this is a relative URI, this method returns the entire URI. Leaves escaped octets intact.

Example: "///www.google.com/search?q=android"

Returns

String (/reference/java/lang/String) the encoded scheme-specific-part

getEncodedUserInfo

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getEncodedUserInfo ()
```

Gets the encoded user information from the authority. For example, if the authority is "nobody@google.com", this method will return "nobody".

Returns

String (/reference/java/lang/String)	the user info for this URI or null if not present
---	---

getFragment Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getFragment ()
```

Gets the decoded fragment part of this URI, everything after the '#'.

Returns

String (/reference/java/lang/String)	the decoded fragment or null if there isn't one
---	---

getHost Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getHost ()
```

Gets the encoded host from the authority for this URI. For example, if the authority is "bob@google.com", this method will return "google.com".

Returns

String (/reference/java/lang/String) the host for this URI or null if not present

getLastPathSegment Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getLastPathSegment ()
```

Gets the decoded last segment in the path.

Returns

String (/reference/java/lang/String) the decoded last segment or null if the path is empty

getPath Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getPath ()
```

Gets the decoded path.

Returns

String (/reference/java/lang/String)	the decoded path, or null if this is not a hierarchical URI (like "mailto:nobody@google.com") or the URI is invalid
--	---

getPathSegments Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract List (/reference/java/util/List)<String (/reference/java/lang/String)> getPathSegr
```

Gets the decoded path segments.

Returns

List (/reference/java/util/List) < String (/reference/java/lang/String)>	decoded path segments, each without a leading or trailing '/'
--	---

getPort Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract int getPort ()
```

Gets the port from the authority for this URI. For example, if the authority is "google.com:80", this method will return 80.

Returns

`int` the port for this URI or -1 if invalid or not present

getQuery

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getQuery ()
```

Gets the decoded query component from this URI. The query comes after the query separator ('?') and before the fragment separator ('#'). This method would return "q=android" for "http://www.google.com/search?q=android".

Returns

`String` the decoded query or null if there isn't one
(/reference/java/lang/String)

getQueryParameter

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public String (/reference/java/lang/String) getQueryParameter (String (/reference/java/lang/Stri
```

Searches the query string for the first value with the given key.

Warning: Prior to Jelly Bean, this decoded the '+' character as '+' rather than ' '.

Parameters

key **String**: which will be encoded

Returns

String the decoded value or null if no parameter is found
(</reference/java/lang/String>)

Throws

NullPointerException if key is null
(</reference/java/lang/NullPointerException>)

UnsupportedOperationException if this isn't a hierarchical URI
(</reference/java/lang/UnsupportedOperationException>)

getQueryParameterNames Available in API level 11 (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public Set <String> getQueryParameterNames()
```

Returns a set of the unique names of all query parameters. Iterating over the set will return the names in order of their first occurrence.

Returns

[Set](/reference/java/util/Set) (</reference/java/util/Set>) a set of decoded names
[<String](/reference/java/lang/String)
 (</reference/java/lang/String>)>

Throws

[UnsupportedOperationException](#) if this isn't a hierarchical URI
[Exception](#)
 ([/reference/java/lang/](/reference/java/lang/UnsupportedOperationException)
[UnsupportedOperationException](#))

getQueryParameters Added in [API level 1](#) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public List (/reference/java/util/List)<<String (/reference/java/lang/String)> getQueryParameters (
```

Searches the query string for parameter values with the given key.

Parameters

[key](#) [String](#): which will be encoded

Returns

[List](/reference/java/util/List) (</reference/java/util/List>) a list of decoded values
[<String](/reference/java/lang/String)

(/reference/java/lang/String)>

Throws

NullPointerException if key is null
(/reference/java/lang/NullPointerException)

UnsupportedOperationException if this isn't a hierarchical URI
(/reference/java/lang/UnsupportedOperationException)

getScheme

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getScheme ()
```

Gets the scheme of this URI. Example: "http"

Returns

String the scheme or null if this is a relative URI
(/reference/java/lang/String)

getSchemeSpecificPart

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getSchemeSpecificPart ()
```

Gets the scheme-specific part of this URI, i.e. everything between the scheme separator ':' and the fragment separator '#'. If this is a relative URI, this method returns the entire URI. Decodes escaped octets.

Example: `"/www.google.com/search?q=android"`

Returns

<u>String</u> (/reference/java/lang/String)	the decoded scheme-specific-part
---	----------------------------------

getUserInfo

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract String (/reference/java/lang/String) getUserInfo ()
```

Gets the decoded user information from the authority. For example, if the authority is "nobody@google.com", this method will return "nobody".

Returns

<u>String</u> (/reference/java/lang/String)	the user info for this URI or null if not present
---	---

hashCode

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public int hashCode ()
```

Hashes the encoded string representation of this Uri consistently with `equals(Object)` ([/reference/android/net/Uri#equals\(java.lang.Object\)](/reference/android/net/Uri#equals(java.lang.Object))).

Returns

<code>int</code>	a hash code value for this object.
------------------	------------------------------------

isAbsolute

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public boolean isAbsolute ()
```

Returns true if this URI is absolute, i.e. if it contains an explicit scheme.

Returns

<code>boolean</code>	true if this URI is absolute, false if it's relative
----------------------	--

isHierarchical

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public abstract boolean isHierarchical ()
```

Returns true if this URI is hierarchical like "http://google.com". Absolute URIs are hierarchical if the scheme-specific part starts with a '/'. Relative URIs are always hierarchical.

Returns

`boolean`

isOpaque

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public boolean isOpaque ()
```

Returns true if this URI is opaque like "mailto:nobody@google.com". The scheme-specific part of an opaque URI cannot start with a '/'.

Returns

`boolean`

isRelative

Added in [API level 1](#) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public abstract boolean isRelative ()
```

Returns true if this URI is relative, i.e. if it doesn't contain an explicit scheme.

Returns

booleantrue if this URI is relative, false if it's absolute

normalizeScheme

Added in [API level 16](#) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public Uri (/reference/android/net/Uri) normalizeScheme ()
```

Return an equivalent URI with a lowercase scheme component. This aligns the Uri with Android best practices for intent filtering.

For example, "HTTP://www.android.com" becomes "http://www.android.com"

All URIs received from outside Android (such as user input, or external sources like Bluetooth, NFC, or the Internet) should be normalized before they are used to create an Intent.

This method does *not* validate bad URIs, or 'fix' poorly formatted URIs - so do not use it for input validation. A Uri will always be returned, even if the Uri is badly formatted to begin with and a scheme component cannot be found.

Returns

[Uri](#) (/reference/android/net/Uri) normalized Uri (never null)

See also:

[Intent.setData\(Uri\)](#) (/reference/android/content/Intent#setData(android.net.Uri))

`Intent.setDataAndNormalize(Uri)`

([/reference/android/content/Intent#setDataAndNormalize\(android.net.Uri\)](/reference/android/content/Intent#setDataAndNormalize(android.net.Uri)))

parse

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public static Uri (/reference/android/net/Uri) parse (String (/reference/java/lang/String) uriSt
```

Creates a Uri which parses the given encoded URI string.

Parameters

`uriString`

`String`: an RFC 2396-compliant, encoded URI

Returns

[Uri](/reference/android/net/Uri) (</reference/android/net/Uri>) Uri for this given uri string

Throws

[NullPointerException](/reference/java/lang/NullPointerException) (</reference/java/lang/NullPointerException>) if `uriString` is null

toString

Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)


```
public abstract String (/reference/java/lang/String) toString ()
```

Returns the encoded string representation of this URI. Example: "http://google.com/"

Returns

String (/reference/java/lang/String)	a string representation of the object.
--	--

withAppendedPath Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (/guide/topics/manifest/uses-sdk-element#ApiLevels)

```
public static Uri (/reference/android/net/Uri) withAppendedPath (Uri (/reference/android/net/U  
    String (/reference/java/lang/String) pathSegment)
```

Creates a new Uri by appending an already-encoded path segment to a base Uri.

Parameters

baseUri	Uri : Uri to append path segment to
----------------	--

pathSegment	String : encoded path segment to append
--------------------	--

Returns

Uri (</reference/android/net/Uri>) a new Uri based on baseUri with the given segment appended to the path

Throws

NullPointerException if baseUri is null
(</reference/java/lang/NullPointerException>)

writeToParcel Added in [API level 1](/guide/topics/manifest/uses-sdk-element#ApiLevels) (</guide/topics/manifest/uses-sdk-element#ApiLevels>)

```
public static void writeToParcel (Parcel out,  
                                Uri uri)
```

Writes a Uri to a Parcel.

Parameters

out **Parcel**: parcel to write to

uri **Uri**: to write, can be null

Content and code samples on this page are subject to the licenses described in the [Content License](/license) (</license>).
Java and OpenJDK are trademarks or registered trademarks of Oracle and/or its affiliates.

Last updated 2026-02-26 UTC.