

 DNS configuration (for scoped queries)    

  

- AI Mode
- All
- Videos
- Short videos
- Forums
- Shopping
- Images
- More ▾
- Tools ▾



DNS configuration (for scoped queries)



network interface (like a VPN tunnel `utun` or Wi-Fi `en0`) rather than being sent globally across all connections. macOS uses this to implement split-DNS, ensuring that traffic intended for internal corporate servers travels securely over your VPN, while regular internet traffic routes through your local Wi-Fi. [Super User](#) +2

If you view your system network configuration using `scutil --dns`, you will see a section labeled **"DNS configuration (for scoped queries)"**, which lists the search domains and nameservers restricted to individual network interfaces. [SparkLabs](#) +1

Why Git Fails with Scoped DNS

Git relies on standard system networking libraries, but connection problems happen when a Git command needs to resolve an internal repository address (e.g., `git.company.internal`).

- **The Problem:** Git uses underlying cURL and transport mechanisms. If a VPN changes your network routing or drops your connection momentarily, Git may fallback to an unscoped global resolver (like `8.8.8.8`) instead of using the scoped interface resolver.
- **The Result:** Git returns an error like `fatal: unable to access... Could not resolve host`. [GitHub](#) +1

How to Fix and Use it with Git

1. Force Git to Use a Specific Network Interface [🔗](#)

If you want Git to bypass the global DNS routing and explicitly use the network interface tied to your scoped DNS (such as your VPN), configure Git to bind to that interface's IP address. [🔗](#)

1. Find the local IP address of your VPN or target network interface by running:

```
bash
```

```
ifconfig
```

Use code with caution

