

 git command repack





AI Mode All Shopping Images Videos Forums Short videos More ▾ Tools ▾



git command repack



This command is **used to combine all objects that do not currently reside in a "pack", into a pack**. It can also be used to re-organize existing packs into a ...

SYNOPSIS

DESCRIPTION

OPTIONS



AI Overview



The **git repack** command combines loose, individual Git objects into a single compressed **packfile** (and its corresponding **.idx** index file) to optimize disk space and boost repository performance. It is typically executed automatically under the hood by high-level plumbing tools like **git gc**. Git +1

Why Use **git repack** ?

- **Reduces Disk Space:** It applies delta compression, storing similar objects as changes relative to one another.
- **Improves Performance:** Searching a single indexed packfile is much faster for Git than scanning thousands of loose files on your hard drive.
- **Network Efficiency:** Reduces the overhead on mirrors, backup engines, and remote pushes. Git +1

Common Commands & Examples

- **Standard Repack**

Combines loose objects into a new packfile without altering existing packs.

```
bash
```


```
git repack
```

Use code with caution.



- **Aggressive Full Repack**

Combines **all** objects (including previously packed ones) into a single pack, and completely removes the old, redundant files. This is the most common manual usage for repository cleanup.



```
git repack -a -d
```

Use code with caution.

- **Aggressive Full Repack (Including Unreachable Objects)**

Same as above, but leaves unreachable (dangling) objects as loose files instead of deleting them right away. This prevents accidental data loss if you are not backed up.

```
bash
```

```
git repack -A -d
```

Use code with caution.

Stack Overflow +4

Key Flags Explained

Flag	Name	Function
<code>-a</code>	Pack all	Packs all objects into a single pack file. Existing packs become redundant.
<code>-A</code>	Pack all (with loose)	Same as <code>-a</code> , but turns any unreachable objects from old packs back into loose objects.
<code>-d</code>	Delete redundant	Removes the old redundant packs after the new, more efficient pack is created.
<code>-f</code>	Force re-delta	Overrides existing delta compression and recomputes the object relationships from scratch.

`git repack` VS `git gc`

While `git repack` specifically handles the compression and grouping of repository



git command repack



Would you like to know how to use this command to **shrink a repository** that has accidentally tracked huge files, or are you troubleshooting a **specific performance issue**?

git gc --aggressive vs git repack

Feb 25, 2015 — The --aggressive flag does three things: * Uses "-f" to thro...

Stack Overflow

git-repack Documentation

* NAME. git-repack - Pack unpacked objects in a repository. * SYNOPSIS....

Git

Gi
De

Git
git



AI can make mistakes, so double-check responses

Ask anything



Stack Overflow

5 answers · 11 years ago

git gc --aggressive vs git repack

I want to reduce the size of a Git repository. I have discovered: git gc --aggressive. But some people discourage its use. Why? What's wrong with ...

How to use [git repack -a -d --depth=250 --window ...](#) 2 answers Feb 12, 2013

Is [repacking](#) a repository useful for large binaries? 4 answers Jun 23, 2018

[More results from stackoverflow.com](#)



Git

<https://git-scm.com/docs/git-repack>

Git - git-repack Documentation

This command is **used to combine all objects that do not currently reside in a "pack", into a pack**. It can also be used to re-organize existing packs into a ...



May 26, 2026 — This command is **used to combine all objects that do not currently reside in a "pack", into a pack**. It can also be used to re-organize existing packs into a ...



Git

<https://git-scm.com/docs/git-repack>

Git - git-repack Documentation

This command is **used to combine all objects that do not currently reside in a "pack", into a pack**. It can also be used to re-organize existing packs into a ...



Reddit · r/git

4 comments · 5 years ago

Is that reasonable that git repack give better result as more ...

Hi , I have git repo that used around 13MB of the disk without the git meta-data(what located under the .git) . It's consists of one file in size of ...

[How to repack files/folders back to ".pack" file ...](#) 4 answers Nov 5, 2022

[Is it safe to run `git gc` in a repository that is being ...](#) 12 answers Mar 14, 2017

[More results from www.reddit.com](#)



Atlassian Support

<https://support.atlassian.com/bitbucket-data-center/un...>

Understanding git repack and git prune options in Bitbucket ...

Jan 30, 2026 — **git repack** Rewrites Git objects into new packfiles to reduce redundancy. Consolidates loose objects and fragmented packs into fewer, optimized ...



graphapp.ai

<https://www.graphapp.ai/engineering-glossary/git-re...>

Git repack: Definition, Examples, and Applications | Graph AI

Git repack is a command that **optimizes Git repository storage** by consolidating loose objects into a more efficient pack file. This process reduces disk space ...



GitHub

<https://github.com/git/git/blob/master/repack>

git/repack.c at master

Git Source Code Mirror - This is a publish-only repository but pull requests can be turned into patches to the mailing list via GitGitGadget ...



Git command repack **github**

Git **gc --prune=now**

Git **gc --prune**

Git **gc vs git prune**

Git **gc** command

Gitlab git **gc**

1 2 3 4 5 6 7 8 9 10 [Next](#)

Results are personalized - [Try without personalization](#)

60605, Chicago, IL - [From your IP address](#) - [Update location](#)

[Help](#) [Send feedback](#) [Privacy](#) [Terms](#)