

The 2026 Annual Developer Survey is live— **take the Survey today!**.



Ask Different
Answers for your Apple questions

Broken DNS resolvers automatically included on scutil --dns

Asked 3 years, 5 months ago Modified 3 years, 5 months ago Viewed 2k times



What are the ways to persist DNS and SearchDomain settings? How to remove?

2

If I run `scutil --dns` it shows these two resolvers (and a few others for *.in-addr.arpa addresses)



```
resolver #1
  search domain[0] : 0.mydomain.com
  nameserver[0] : 10.10.50.53
  if_index : 15 (en0)
  flags : Request A records
  reach : 0x00000002 (Reachable)

resolver #2
  domain : 0.mydomain.com
  nameserver[0] : 10.10.10.53
  flags : Supplemental, Request A records
  reach : 0x00020002 (Reachable,Directly Reachable Address)
  order : 101600
...
```

Both resolvers include one of my domains, and #2 has the wrong nameserver IP.

I don't have a search domain configured on *Settings -> Network -> Detail -> DNS, and my local DHCP server does not provide a searchdomain.

If I remove the invalid resolver with:

```
# sudo scutil
# get State:/Network/Service/[redacted, random numbers and letters]/DNS
# d.show
<dictionary> {
  ServerAddresses : <array> {
    0 : 10.10.10.53
  }
  SupplementalMatchDomains : <array> {
    0 : 0.mydomain.com
  }
}
remove State:/Network/Service/a09acf02331d4926/DNS
quit
```

Then, `scutil --dns` shows the correct resolvers, without search domains.

```
resolver #1
  nameserver[0] : 10.10.50.53
  if_index : 15 (en0)
  flags : Request A records
  reach : 0x00000002 (Reachable)

resolver #2
  domain : local
  options : mdns
  timeout : 5
  --
```