

🔗 Search Assist

📄 ⬆ ⓘ ⚙

A **git repack** "invalid object" error usually means Git has missing or corrupt repository objects (for example, broken references to commits/trees/blobs). Run **git fsck** to list the problematic objects, then recover/restore the missing objects before trying to repack again. ➤ git-annex.branchable.com 🔴 git-scm.com

More ▾



Auto-generated based on listed sources. May contain inaccuracies.

Was this helpful? 👍 🗨

🔴 support.gitlab.com
<https://support.gitlab.com> › [hc](#) › [en-us](#) › [articles](#) › [20902108343068-How-To-Fix-Missing-or-Corru...](#) ...

How-To: Fix Missing or Corrupt Git Objects - GitLab, Inc.

Jul 1, 2025 · How-To: Fix Missing or Corrupt **Git Objects** Description In this knowledge base article we will cover troubleshooting and recovery techniques for **Git** repositories experiencing missing or corrupted **objects**, which are the fundamental data structures that **Git** uses to store commits, trees,...

🔴 [Stack Overflow](https://stackoverflow.com)
<https://stackoverflow.com> › [questions](#) › [4826639](#) › [repack-of-git-repository-fails](#) ...

Repack of Git repository fails - Stack Overflow

To handle this error I have tried to **repack** the original repository (according to this forum post). But instead of repacking the repository it describes how to use the "**git pack-objects**" command.

🔴 [Stack Overflow](https://stackoverflow.com)
<https://stackoverflow.com> › [questions](#) › [11834108](#) › [fatal-bad-object-xxx](#) ...

git - fatal: bad object xxx - Stack Overflow

bad **object** with some hexadecimal number tends to mean that a tag has an **invalid** reference number in it, but can also occur for a few other strange cases. For instance, if I do a: **\$ git tag foo \$ vi .git/refs/tags/foo** and change the last character (in this case from 6 to 5) and write that out: **\$ git log...**

I don't know the exact reason why that happens. For me, it's because I forgot to pull the entire...

BEST ANSWER

👍 33

I just ran into the same error (bad object [hash]) while attempting to merge from a branch my...

👍 28

[Edit 1, 19 Nov 2016] While this would sometimes indicate repository corruption, it...

👍 27

In my c... picking... bran... but I... ➤

🔴 [Git](https://git-scm.com)
<https://git-scm.com> › [docs](#) › [git-repack](#) ...

Git - git-repack Documentation

git repack ensures this by determining a "cut" of packfiles that need to be repacked into one in order to ensure a geometric progression. It picks the smallest set of packfiles such that as many of the larger packfiles (by count of **objects** contained in that pack) may be left intact.

🔴 [Git](https://git-scm.com)
<https://git-scm.com> › [docs](#) › [git-repack](#) › [2.8.6](#) ...

Git - git-repack Documentation

-F Pass the --no-reuse-object option to **git-pack-objects**, see **git-pack-objects** [1]. -q Pass the -q option to **git pack-objects**. See **git-pack-objects** [1]. -n Do not update the server information with **git update-server-info**. This option skips updating local catalog files needed to publish this repository (or a direct...

Repack of Git repository fails

🔴 [https://stackoverflow.com/...](https://stackoverflow.com/)

Your solution has got you a working copy locally and remotely, but will cause problems again when the remote **repository** decides to **repack** itself again. Fortunately, you can set config options that will reduce the amount of memory needed for repacking in both repositories -- these essentially make the command line

git

Ask Duck.ai



Was this helpful? 👍 🗨



DEV Community

<https://dev.to> › [alanwest](#) › [how-to-recover-from-a-corrupted-git-repository-22oc](#)



How to Recover from a Corrupted Git Repository

Mar 29, 2026 · Git stores everything as **objects** in `.git/objects/` — blobs (file contents), trees (directories), commits, and tags. Each **object** is named by its SHA-1 hash and compressed with zlib. Corruption usually happens when: Disk failure or power loss interrupts a write to `.git/objects/` A...



Atlassian Support

<https://support.atlassian.com> › [bitbucket-data-center](#) › [kb](#) › [git-operations-fail-due-to-git-pack-o...](#)



Git operations fail due to "git-pack-objects died with error"

Learn how to resolve **Git errors** like "git-pack-objects died with error" in Atlassian Bitbucket due to repository corruption.



Git Developer Pages

<https://git.github.io> › [htmldocs](#) › [howto](#) › [recover-corrupted-object-harder.html](#)



How to recover an object from scratch - GitHub Pages

6 days ago · And while it did report the error, I did get the right number of output bytes (i.e., it matched git's size header that we decoded above). But feeding the result back to "git hash-object" didn't produce the same sha1.

Searches related to **git repack error: invalid object**

[git repository failed to repack](#)

[gitlab repository errors](#)

[git repository not repacking](#)

[gitlab repository missing](#)

Was this helpful?

More Results



Get Our Windows Browser

Protect your data as you search, browse, and use AI.

Download