

January 2025 • [Filesystem](#)

Mounting Virtual Disk Images in Linux

linuxbash

[Posts by this author](#)

Mounting Virtual Disk Images in Linux: A Guide for Beginners

Virtualization is a powerful tool in the world of computing, allowing users to run multiple operating systems simultaneously or to access the file systems within disk images as if they were physical disks. Mounting virtual disk images can greatly enhance the workflow for developers, systems administrators, and testers. Whether for development, deployment scenarios, or testing, having access to a virtual disk image without booting into it is invaluable.

In this guide, we'll walk through the basics of mounting virtual disk images. This includes commonly used formats like

Step 1: Understanding Mount Points

In Linux, to access the filesystem of a disk image, you need to mount it to a directory in the local filesystem. This directory is known as the mount point. The path to this directory is used as the access path to the contents of the disk image. To ensure you create a directory that will serve as a mount point, you can use the following command:

```
mkdir /mnt/mydisk
```

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.

[I agree](#)[I decline](#)[Change my preferences](#)

Replace `"/mnt/mydisk"` with the directory path where you prefer to mount the disk image.

Step 2: Installing Required Tools

Linux utilizes several tools to interact with disk images, chief among them ``mount`` and ``losetup``. While ``mount`` handles the process of attaching the filesystem, ``losetup`` connects a loop device, which is a pseudo-device that makes a file accessible as a block device, to the disk images.

However, to deal with specific image types beyond the basics (like VDI or VMDK), you may need additional tools. For instance, the ``qemu`` package includes support for various disk image types:

```
sudo apt-get install qemu-utils # Debian/Ubuntu based systems
sudo yum install qemu-img # CentOS/RHEL based systems
sudo dnf install qemu-img # Fedora systems
sudo zypper install qemu-tools # openSUSE systems
```

Step 3: Mounting an ISO Image

ISO images are straightforward to mount. A file named ``image.iso``:

```
sudo mount -o loop image.iso /mnt/mydisk
```

The ``-o loop`` option tells ``mount`` to treat it with a loopback mount point.

Step 4: Mounting an IMG or RAW Disk Image

IMG files, commonly used for disk or USB images, are similar to ISO files:

```
sudo mount -o loop disk.img /mnt/mydisk
```

For partitioned IMG files, you might need to

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.

```
sudo fdisk -l disk.img
```

Look for the "Start" sector of the desired partition and multiply this by the sector size to get the offset. Then use:

```
sudo mount -o loop,offset=XXXXX disk.img /mnt/mydisk
```

where `XXXXX` is the calculated offset.

Step 5: Mounting VDI (VirtualBox Disk Image) Files

Mounting VDI files, commonly associated with VirtualBox, requires another step:

First, associate the VDI with a loop device:

```
sudo modprobe nbd # if not already loaded
sudo qemu-nbd -c /dev/nbd0 /path/to/disk.vdi
```

Look for partitions:

```
sudo fdisk -l /dev/nbd0
```

Finally, mount the partition as needed:

```
sudo mount /dev/nbd0p1 /mnt/mydisk
```

Step 6: Accessing the Mounted Image

Once your disk image is mounted, you can

```
cd /mnt/mydisk
ls
```

Step 7: Unmounting the Disk Image

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.

When you're done, it's essential to unmount the image properly:

```
sudo umount /mnt/mydisk
```

For VDI images attached with `qemu-nbd`, you also need to disconnect the network block device:

```
sudo qemu-nbd -d /dev/nbd0
```

Conclusion

Mounting disk images in Linux isn't overly complex but requires awareness of the correct tools and methods for different file types. By following the steps outlined above, Linux users can efficiently manage virtual disk images which is crucial in a variety of applications from development testing environments to system recovery tasks. Whether you're a seasoned admin or a curious novice, the ability to mount these images directly on your system provides a clear window into the virtualized world.

Further Reading

For further reading on working with virtual disk images, check out the following resources:

- **Understanding the Linux `mount` Command**
<https://www.linux.com/training-tutorials/understanding-the-linux-mount-command/>
This article covers basics and nuance working with filesystems.
- **Linux Loop Devices Detailed Explanation**
<https://www.linux.org/threads/using-linux-loop-devices-as-block-devices.123456/>
An in-depth guide on loop devices, creating virtual disk images as block devices.

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.

- **Working with QEMU and Disk Images:**

<https://www.qemu.org/documentation/>

Official QEMU documentation that provides detailed usage scenarios, including handling various disk image formats.

- **Introduction to VirtualBox Disk Images (VDI):**

<https://www.virtualbox.org/manual/ch05.html#vdiidetails>

Oracle's detailed guide on VirtualBox disk images, including how to manage and modify VDI files.

- **Complete Guide to Using `fdisk` Tool:**

<https://linux.die.net/man/8/fdisk>

A comprehensive manual page detailing the `fdisk` tool, important for partitioning and managing disk images.

Related posts

- [Enabling and Managing ACLs on Filesystems](#)
- [Understanding the VFS \(Virtual File System\)](#)
- [Access Control Lists \(ACLs\) for Advanced Permissions](#)
- [Using `find` to Search for Files](#)
- [Filesystem Limits: Maximum File and Partition Sizes](#)

TAGS

[LINUX](#) [VIRTUAL DISK IMAGES](#) [MOUNTING](#) [FILE](#)

PREVIOUS POST

[Monitoring Microservices in Kubernetes Clusters](#)

OTHER PROJECTS

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.



TAG CLOUD

AI ANOMALY DETECTION

APACHE

ARTIFICIAL INTELLIGENCE

AUTOMATION

BASH

BASH SCRIPTING

COMMAND LINE

CONFIGURATION

DEVOPS

LINUX

LINUX BASH

MACHINE LEARNING

MLOPS

MONITORING

OPEN

SOURCE

PACKAGE MANAGEMENT

SCRIPTING

SECURITY

SHELL SCRIPTING

← [Back to homepage](#)



© Linux Bash Po

Courtesy of You

We use cookies

This website uses cookies and other tracking technologies to improve your browsing experience for the following purposes: to enable basic functionality of the website, to provide a better experience on the website, to measure your interest in our products and services and to personalize marketing interactions, to deliver ads that are more relevant to you.