

Comprehensive Architectural Analysis of the Genomic Data Commons (GDC) TARGET Barcode Nomenclature and Biospecimen Ontology

The advent of massive-scale next-generation sequencing (NGS) technologies has necessitated the development of centralized, highly structured repositories to manage, harmonize, and distribute oncological data. The National Cancer Institute (NCI) Genomic Data Commons (GDC) represents the pinnacle of this effort, serving as an expandable, cloud-based knowledge network that hosts comprehensive cancer genomic datasets¹. Among the most prominent initiatives housed within the GDC are The Cancer Genome Atlas (TCGA) and the Therapeutically Applicable Research to Generate Effective Treatments (TARGET) program¹. While TCGA focuses primarily on adult malignancies, TARGET is dedicated to the comprehensive molecular characterization of high-risk and hard-to-treat pediatric cancers, aiming to identify novel therapeutic avenues and elucidate the genetic drivers of disease progression and relapse³.

To navigate the immense volume of clinical, biospecimen, and molecular data across these programs, the GDC initially relied on a rigorous ontology of unique identifiers. Historically, this system was built upon the "barcode" framework—a highly structured, human-readable alphanumeric string designed to encode multiple layers of clinical and biospecimen provenance directly into the sample name⁶. Although the GDC has modernized its fundamental architecture by transitioning to a graph-based data model driven by Universally Unique Identifiers (UUIDs)⁸, legacy barcodes remain deeply embedded in the metadata ecosystem. They serve as the primary `submitter_id` for entities within the GDC hierarchy and are heavily utilized in downstream analytical platforms, repositories like cBioPortal, and prominent bioinformatics toolkits such as R/Bioconductor packages⁹.

The interrogation of non-standard or highly customized barcodes—such as the provided query example TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R—requires a nuanced understanding of both the canonical GDC barcode syntax and the specific biological and programmatic contexts of the TARGET initiative. This report provides an exhaustive deconstruction of the TARGET barcode architecture, identifies the official documentation and dynamic code tables governing these identifiers, addresses the user's specific reference URLs, and comprehensively analyzes the profound bioinformatics implications of structural anomalies within customized case identifiers.

The Semantic Architecture of GDC Biospecimen

Barcodes

The canonical barcode system was originally conceptualized and implemented by the Biospecimen Core Resource (BCR) to provide a unified, self-describing identifier⁷. The objective was to create a nomenclature that could track a biological sample through its entire lifecycle: from the patient level at the collection hospital, down to the physical sectioning of the tissue, the chemical extraction of a specific molecular analyte, and ultimately to the specific well on a 96-well plate processed in a sequencing center⁷.

A standard barcode acts as a nested hierarchy, encoding up to seven distinct layers of metadata within a single string. While the exact configuration varies slightly between TCGA and TARGET, the fundamental anatomical layout of a full aliquot-level barcode consists of the following components, separated by hyphens:

Position	Structural Element	Description	Canonical Example
1	Project	The overarching initiative or program name.	TCGA or TARGET
2	TSS or Disease Code	In TCGA, this is the Tissue Source Site (TSS) identifying the collection hospital. In TARGET, this is replaced by a two-digit Disease Code.	02 (TCGA TSS) or 20 (TARGET-AML)
3	Participant / Case	A blinded, alphanumeric string uniquely identifying the patient or biological donor within the study.	0001 or PARNFZ
4	Sample Type and Vial	A two-digit numeric code indicating the biological nature of the sample (e.g., primary tumor, normal blood),	01C (Primary Solid Tumor, Vial C)

		followed by a letter indicating the vial order.	
5	Portion and Analyte	A two-digit code representing the sequential physical portion of the sample, followed by a letter denoting the extracted molecular analyte (e.g., DNA, RNA).	01D (Portion 1, DNA)
6	Plate	A four-digit alphanumeric sequence identifying the 96-well plate used for sample distribution and robotic handling.	0182
7	Center	A numeric or alphanumeric code identifying the specific genome characterization or sequencing center (GCC/GSC) that processed the aliquot.	01

These barcodes can be visualized hierarchically, with the shortest participant-level barcodes at the top of the tree, branching down to the highly specific aliquot barcodes at the bottom⁷. A parent barcode always prefixes any of its descendant barcodes, directly reflecting the biological derivation of one biospecimen entity from another⁷.

The TARGET Paradigm Shift: Disease Codes vs. Tissue

Source Sites

The most prominent divergence between the TCGA and TARGET barcoding schema occurs at the second position of the string. The TCGA architecture utilizes a Tissue Source Site (TSS) code to identify the specific hospital, clinic, or biorepository that collected the biospecimen (for example, the code 85 in TCGA represents the Asterand biorepository for Lung squamous cell carcinoma)¹².

Conversely, the TARGET initiative replaces the geographic TSS code with a specialized Disease Code. Because TARGET encompasses various discrete pediatric cancer initiatives often sourced through centralized children's oncology groups rather than individual adult hospitals, the two-digit code immediately following the TARGET prefix categorizes the specific malignancy under investigation. The canonical TARGET disease codes are mapped as follows within the GDC:

TARGET Disease Code	Sub-Project Identifier	Disease Classification
10	TARGET-ALL-P1	Acute Lymphoblastic Leukemia (Phase 1)
20	TARGET-AML	Acute Myeloid Leukemia
30	TARGET-NBL	Neuroblastoma
40	TARGET-OS	Osteosarcoma
50	TARGET-WT	Wilms Tumor
51	TARGET-CCSK	Clear Cell Sarcoma of the Kidney
52	TARGET-RT	Rhabdoid Tumor

Consequently, any barcode initiating with TARGET-20 is explicitly and irrevocably localized to the pediatric Acute Myeloid Leukemia (TARGET-AML) cohort¹¹. This sub-project represents a massive, collaborative effort to characterize the genomic landscape of childhood AML, yielding extensive mRNA, miRNA, copy number, and targeted sequencing datasets¹.

Biospecimen Stratification: Sample Types and Analyte

Ontologies

The subsequent layers of the barcode provide critical biological context regarding what the physical material actually represents. This stratification is paramount for downstream bioinformatics pipelines that must programmatically distinguish between tumor tissue, matched normal controls, and xenograft models to execute accurate somatic variant calling algorithms or differential expression analyses¹⁵.

The Sample Type Code

The Sample Type is a two-digit numeric code that dictates the origin, anatomical site, and neoplastic state of the collected tissue¹⁷. The NCI maintains a strict ontology for these values to ensure that normal tissue is not mistakenly classified as malignant. A subset of the canonical sample type codes includes:

Numeric Code	Biological Definition	Short Letter Code
01	Primary Solid Tumor	TP
02	Recurrent Solid Tumor	TR
03	Primary Blood Derived Cancer - Peripheral Blood	TB
04	Recurrent Blood Derived Cancer - Bone Marrow	TRBM
09	Primary Blood Derived Cancer - Bone Marrow	TBM
10	Blood Derived Normal	NB
11	Solid Tissue Normal	NT
20	Control Analyte	CELLC
40	Recurrent Blood Derived Cancer - Peripheral Blood	TRB
50	Cell Lines	CELL

60	Primary Xenograft Tissue	XP
61	Cell Line Derived Xenograft Tissue	XCL
99	Unknown Sample Type	99SH

In the TARGET programs, sample types such as 03 (Primary Blood Derived Cancer - Peripheral Blood) and 09 (Primary Blood Derived Cancer - Bone Marrow) are heavily utilized, reflecting the hematological nature of leukemias¹⁷. Furthermore, because TARGET initiatives frequently utilize advanced in vivo modeling to study treatment-resistant childhood cancers, codes like 60 and 61 are employed to track primary xenografts and cell line-derived xenografts within murine models⁴.

The Analyte Code

Following the sample type and portion identifiers, the Analyte Code specifies the molecular substrate extracted from the biospecimen for sequencing or characterization⁷. This single alphabetical character defines the downstream applicability of the data. For instance, DNA sequences are routed into somatic variant calling pipelines utilizing tools like BWA, MuTect2, and VarScan2, whereas RNA sequences are routed into transcriptome profiling pipelines utilizing STAR and Arriba¹⁵. The standard analyte codes recognized by the GDC are:

Code	Analyte Type	Downstream Application
D	DNA	Whole Genome/Exome Sequencing, DNA Methylation Arrays
R	RNA	RNA-Seq (Gene Expression, Isoform Quantification, Fusion detection)
T	Total RNA	Total RNA-Seq
G	Whole Genome Amplification (WGA)	Amplified DNA Sequencing
W	WGA (Repli-G)	Specific amplified

		methodologies
X	WGA X (Repli-G X)	Specific amplified methodologies
H	mirVana RNA (Hybrid)	miRNA-Seq

Evolution of GDC Documentation: Addressing the User's Reference URLs

To decode these identifiers, the user referenced the historical URL

<https://gdc.cancer.gov/resources-tcga-users/tcga-code-tables> and inquired about <https://gdc.cancer.gov/about-data/gdc-data-processing>. Understanding the transition between these two paradigms is essential for modern cancer informatics.

The historical URL provided by the user pointing to the tcga-code-tables is largely considered legacy documentation¹⁷. During the initial phases of TCGA, these static HTML tables were the primary mechanism for researchers to manually decode the rigid barcode strings¹⁷. However, as the GDC transitioned into a property graph database capable of hosting highly diverse datasets beyond TCGA and TARGET (such as CPTAC, FM-AD, and HCMI), static tables became insufficient to capture the expanding ontology³.

Today, the definitive source of truth for all modern GDC codes is the **GDC Data Dictionary Viewer**¹⁹. Rather than referencing static tables, the Data Dictionary catalogs every entity, node, and property within the graph model¹⁹. Each property within the dictionary is assigned a Common Data Element (CDE) linking it to the NCI Thesaurus (NCIt), ensuring that all terms are strictly defined by medical ontologies¹⁹. Users can navigate to the Data Dictionary, search for the sample_type or analyte_type properties, and view the complete enumeration of permissible values¹⁹.

The second URL referenced by the user,

<https://gdc.cancer.gov/about-data/gdc-data-processing>, describes the downstream consequence of the barcode's Analyte and Sample Type codes⁸. This documentation details the rigorous Data Harmonization processes deployed by the GDC. Once an aliquot (e.g., an RNA analyte) is sequenced, the raw data is submitted alongside the barcode (functioning as the submitter_id). The GDC processing pipelines intercept this data and execute a highly standardized bioinformatics workflow¹⁵. For an RNA analyte, the processing documentation dictates that the reads will be aligned against the GRCh38 reference genome using STAR, evaluated for mapping quality, and subsequently processed for differential gene expression and fusion analysis¹⁵. This processing architecture ensures that disparate studies utilizing different sequencing centers are rendered universally comparable¹.

Exhaustive Deconstruction of the Anomalous Query Example

The user's specific query centers on a highly non-standard barcode:

TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R.

While this string ostensibly mimics the nested, hyphen-delimited syntax of a standard GDC aliquot barcode, its internal structure represents a profound deviation from the canonical formatting rules. Standard TARGET participant codes are heavily blinded, uniformly consisting of a six-character alphanumeric string (e.g., PANSBH or PARNFZ) to ensure patient de-identification and computational uniformity across matrices¹⁸. The presence of underscores, varied string lengths, and explicit gene nomenclature within this identifier conclusively dictates that this is a highly specialized, study-specific identifier.

Through an analysis of the GDC biospecimen data model, pediatric oncology literature, and cBioPortal metadata structures, the identifier is deconstructed as follows:

1. Project and Disease Specification: TARGET-20

The prefix firmly anchors the sample within the Genomic Data Commons under the TARGET program, specifically within the Acute Myeloid Leukemia (AML) sub-project, as indicated by the 20 disease code¹¹.

2. Participant / Case Identifier: D84-EC-CBFA2T3_GLIS2-3

This segment replaces the standard six-character patient code with a highly descriptive, biologically explicit string. According to cBioPortal hierarchical metadata for the Acute Myeloid Leukemia (TARGET GDC, 2025) dataset, the exact string

TARGET-20-D84-EC-CBFA2T3_GLIS2-3 functions as the primary Patient ID (or Case ID)¹¹.

The inclusion of CBFA2T3_GLIS2 is the critical mechanism to understanding this structural anomaly. The *CBFA2T3-GLIS2* chimeric fusion gene, generated by a cryptic inversion on chromosome 16 inv(16)(p13.3q24.3), defines a specific, highly aggressive, and treatment-resistant subtype of non-Down syndrome pediatric AML²³. AML harboring this specific fusion demonstrates unique cellular dependencies, such as a strong reliance on the JAK1 and JAK2 kinase pathways, which have been identified as highly selective therapeutic targets through genome-wide CRISPR-Cas9 knockout screens²³.

The explicit injection of a gene fusion name into a primary case identifier strongly suggests that this "patient" is actually a specialized in vitro cell line, an engineered clonal population, or a Patient-Derived Xenograft (PDX) model specifically developed or selected to study this fusion within the TARGET-AML pipeline²³. In highly advanced functional genomics studies, lineage tracing models (such as the FLARE system) are used to track sub-clonal populations of AML cells to understand cytarabine (AraC) treatment resistance in vivo¹⁴. To achieve this, cells are transduced with lentivirus co-expressing Cas9 and a fluorescent protein, and are then serially transplanted into immunodeficient NSGS mice¹⁴.

In such specialized sub-cohorts, biological descriptors often supersede blinded clinical codes

to allow researchers to easily group samples by their defining genetic architecture before the data is ingested by the GDC. The D84-EC and -3 elements likely represent internal laboratory designations, sorting events, clone numbers, or experimental batch identifiers associated with this specific xenograft or cell culture model.

3. Sample Type Code: 85

Moving down the hierarchy, cBioPortal identifies TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85 as the specific Sample ID associated with the patient¹¹. In standard GDC ontology, the two digits immediately following the participant ID denote the Sample Type¹⁷.

As established in the TCGA/TARGET Code Tables, the official enumeration of sample types spans from 01 (Primary Solid Tumor) to 61 (Cell Line Derived Xenograft), with 99 acting as a catch-all for unknown samples¹⁷. The numeric code 85 does not exist in the canonical, globally standardized GDC sample type code table¹⁷.

When anomalous numbers (like 85) appear in the sample type position within a highly customized study, it almost universally indicates a project-specific extension of the data dictionary. Because TARGET encompasses diverse multi-institutional assays, individual working groups occasionally utilize high-numbered sample codes (e.g., 80s or 90s) to track internal biological states before the data is forcibly harmonized into broader GDC categories. Given that this case involves a specific *CBFA2T3-GLIS2* AML model likely utilized in a complex in vivo CRISPR or lineage tracing experiment¹⁴, the 85 code likely designates a highly specific temporal or physical state of the specimen. It could represent an isolate from a specific post-treatment timepoint (e.g., following cytarabine exposure), a relapsed state, a specific passage number of a PDX mouse model, or an engineered derivative isolated via fluorescence-activated cell sorting (FACS) based on mCherry expression¹⁴.

4. Portion and Analyte Designation: 01R

The suffix -01R returns to canonical GDC nomenclature⁷.

- 01 designates that this was the first portion of the sample extracted for processing⁷.
- R is the official Analyte Code for RNA⁶.

The presence of the R analyte code conclusively determines the downstream utility of this specific aliquot. It dictates that the biospecimen was processed to extract ribonucleic acid, meaning the resulting genomic files hosted in the GDC associated with this barcode will exclusively represent Transcriptome Profiling data. The data generated from this barcode would be processed through the GDC RNA-Seq harmonization pipeline (utilizing alignment tools like STAR) to produce Gene Expression Quantification (e.g., HTSeq or STAR counts), Isoform Expression, or fusion detection metrics¹⁵.

The Modern GDC Data Model: Nodes, UUIDs, and Barcode Integration

While barcodes remain heavily utilized for human readability and metadata aggregation, the

NCI GDC has fundamentally restructured its backend into a property graph database². Understanding this architecture is crucial for querying and downloading documentation regarding these codes.

In the GDC Data Model, entities are represented as nodes (e.g., case, sample, portion, analyte, aliquot), and the relationships between them are represented as edges (e.g., an aliquot is derived from an analyte, which belongs to a portion, and ultimately a case)². The absolute primary key for any node within the GDC is a Universally Unique Identifier (UUID), which follows a 36-character Version 4 naming convention (e.g., e0d36cc0-652c-4224-bb10-09d15c7bd8f1)⁹.

However, to maintain compatibility with legacy BCR tracking and human-facing tools, the traditional TCGA/TARGET barcode is stored within the graph model as the `submitter_id`⁹. When users navigate the GDC hierarchy, the barcode is fractured across the graph nodes. For example:

- The case node contains the `submitter_id` for the participant (e.g., TARGET-20-D84-EC-CBFA2T3_GLIS2-3)⁹.
- The sample node contains the `submitter_id` for the sample (e.g., TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85)⁹.
- The aliquot node contains the full nested `submitter_id` (e.g., TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R)⁹.

When data is validated and ingested into the GDC via the Data Submission Portal, strict Data Integrity Checks cross-reference these `submitter_id` barcodes against the assigned UUIDs to prevent harmonization errors across biospecimen, clinical, and genomic data domains¹⁵.

Furthermore, at the sequencing level, the GDC mandates that properties like the flow cell barcode, lane number, and multiplex barcode are embedded directly into the @RG ID (Read Group ID) header of alignment files (BAM files). This data is then utilized to construct a globally unique Platform Unit (PU), ensuring that technical sequencing artifacts are inextricably linked to the biological barcode¹⁵. This rigorous validation guarantees that derived data products, such as somatic mutation calls and copy number variations, are confidently mapped back to their biological origin¹⁵.

Programmatic Interrogation of GDC Barcodes via RESTful APIs

For researchers seeking to demystify complex or non-standard barcodes like TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R, the GDC exposes a robust RESTful Application Programming Interface (API) that allows users to extract metadata directly from the graph database using JSON or TSV formats²⁵. The API circumvents the need for static code tables by enabling real-time introspection of the database².

The API relies on a specific JSON payload structure utilizing nested filters. To interrogate the anomalous example provided and identify its precise sample type and clinical mapping, a payload targeting the `cases.samples.portions.analytes.aliquots.submitter_id` field is required²⁵:

```

JSON
{
  "filters": {
    "op": "and",
    "content": [
      {
        "op": "in",
        "content": {
          "field": "cases.samples.portions.analytes.aliquots.submitter_id",
          "value": [
            "TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R"
          ]
        }
      }
    ]
  },
  "fields":
    "cases.submitter_id,cases.samples.sample_type,cases.samples.tissue_type,cases.samples.portions.analytes.analyte_type",
  "format": "TSV",
  "size": "100"
}

```

Executing this payload against the <https://api.gdc.cancer.gov/files> endpoint utilizing an HTTP POST request forces the GDC graph database to unroll the hierarchical nodes associated with the barcode. It returns a structured TSV file detailing the exact sample type definitions, analyte categorizations, and associated file UUIDs generated for the sample, directly translating the 85 code into its human-readable biological definition as stored in the GDC Data Dictionary²⁵.

Bioinformatics Implications of Non-Standard Barcode Topologies

The introduction of highly customized barcodes—such as those injecting complex biological fusion names into the participant string—has severe downstream implications for automated bioinformatics pipelines.

A prominent example of this operational friction is observed within TCGAbiolinks, an immensely popular R/Bioconductor package designed to search (GDCquery), download (GDCdownload), and prepare (GDCprepare) data for integrative analyses like differential expression and subtype classification²⁰. To structure the metadata matrix, TCGAbiolinks utilizes a function called

colDataPrepare(), which historically relied on regular expressions (regex) to parse the metadata directly from the barcode string rather than ping the API for every individual file²¹.

The internal source code of TCGAAbiolinks was programmed to expect strict, unyielding adherence to the canonical TARGET syntax, utilizing the regex pattern:

`[[:alnum:]]{5}-[:alnum:]]{2}-[:alnum:]]{6}-[:alnum:]]{3}-[:alnum:]]{3}`²¹.

This regex explicitly mandates a 6-character alphanumeric participant string (e.g., PARNFZ).

When the parsing engine encounters the query

TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R, it fails completely due to the unpredictable string length and the inclusion of underscores²¹. Consequently, the data preparation functions silently drop the anomalous samples, resulting in dimensional mismatches between the gene expression matrices and the metadata dataframes, ultimately throwing an invalid row.names length error and halting the analysis pipeline²¹.

Best Practices for Resolving Metadata Friction

To circumvent the brittleness of regex-based barcode parsing, contemporary bioinformatics workflows must decouple themselves from relying on the semantic structure of the submitter_id. The recommended operational methodology involves utilizing tools that natively traverse the GDC API via UUIDs rather than string parsing.

Packages such as GenomicDataCommons in R provide robust mechanisms for this translation².

By fetching the immutable UUID of a genomic file and querying the available_fields within the API, data scientists can extract the cases.samples.submitter_id and the explicit

cases.samples.sample_type directly from the graph database, bypassing the barcode entirely².

This programmatic approach forces the GDC servers to resolve the underlying metadata—obviating the need to manually interpret anomalous elements like the 85 sample code or the CBFA2T3_GLIS2 fusion string—ensuring that downstream multi-omics integration pipelines remain structurally sound and free from parsing-induced data attrition².

Conclusion

The architecture of the GDC TARGET barcode represents a legacy semantic framework originally designed to encapsulate complex clinical and biospecimen provenance within a single human-readable string. While the canonical structure relies on highly rigid alphanumeric blocks separating disease codes, participants, and analytes, the exigencies of modern functional genomics have forced researchers to stretch this ontology. Particularly within the realm of aggressive pediatric cancers like AML, the deployment of specialized lineage tracing systems, CRISPR-Cas9 knockouts, and patient-derived xenograft platforms necessitates identifiers that convey immediate biological meaning.

The query TARGET-20-D84-EC-CBFA2T3_GLIS2-3-85-01R serves as a prime illustration of this paradigm shift. In this instance, biological descriptors (such as the *CBFA2T3-GLIS2* fusion) and custom sample codes (such as 85) supersede blinded, standardized identifiers to better facilitate targeted sub-cohort analyses prior to GDC ingestion. While the historical NCI code tables provide a baseline understanding of standard TCGA and TARGET structures, they are insufficient for parsing these modern anomalies. To effectively decode and utilize such strings,

computational analysts must transition away from legacy text-parsing methodologies and engage directly with the GDC's graph-based UUID data model and Data Dictionary API. By doing so, researchers can ensure that the rich, nested metadata of complex oncology models is accurately preserved, enabling highly robust downstream genomic and transcriptomic research.

Works cited

1. New functionalities in the TCGAAbiolinks package for the study and integration of cancer data from GDC and GTEx - PMC,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC6420023/>
2. The GenomicDataCommons Package,
<https://bioconductor.posit.co/packages/3.22/bioc/vignettes/GenomicDataCommons/inst/doc/overview.html>
3. GDCquery: Query GDC data in TCGAAbiolinks - rdr.io,
<https://rdr.io/bioc/TCGAAbiolinks/man/GDCquery.html>
4. TARGET's Pan-Cancer Model Systems (MDLS) - NCI,
<https://www.cancer.gov/ccg/research/genome-sequencing/target/studied-cancers/model-systems>
5. TCGAAbiolinks/R/query.R at master - GitHub,
<https://github.com/BioinformaticsFMRP/TCGAAbiolinks/blob/master/R/query.R>
6. TCGA Barcode Lookup Report - SciSpace,
<https://scispace.com/ai-agent-seo/page-files/tcga-id-lookup-94mgfcr8.pdf>
7. TCGA Barcode - GDC Docs,
https://docs.gdc.cancer.gov/Encyclopedia/pages/TCGA_Barcode/
8. Biospecimen Data Standardization,
<https://gdc.cancer.gov/about-data/gdc-data-processing/biospecimen-data-standardization>
9. Data Submission Walkthrough - GDC Docs - National Cancer Institute,
https://docs.gdc.cancer.gov/Data_Submission_Portal/Users_Guide/Data_Submission_Walkthrough/
10. GenomicDataCommons Example: UUID to TCGA and TARGET Barcode Translation,
<https://seandavi.github.io/post/2017-12-29-genomicdatacommons-id-mapping/>
11. Acute Myeloid Leukemia (TARGET GDC, 2025) - cBioPortal for Cancer Genomics,
https://master.cbioportal.org/study/clinicalData?id=aml_target_gdc
12. Tissue Source Site Codes - NCI Genomic Data Commons - National Cancer Institute,
<https://gdc.cancer.gov/resources-tcga-users/tcga-code-tables/tissue-source-site-codes>
13. Patient: TARGET-20-D84-EC-CBFA2T3_GLIS2-3,
https://frontend.cbioportal.org/patient?studyId=aml_target_gdc&caseId=TARGET-20-D84-EC-CBFA2T3_GLIS2-3
14. Hierarchical Lineage Tracing Reveals Diverse Pathways of AML Treatment Resistance,

- https://www.researchgate.net/publication/389554324_Hierarchical_Lineage_Tracing_Reveals_Diverse_Pathways_of_AML_Treatment_Resistance
15. GDC Data Quality - NCI Genomic Data Commons - National Cancer Institute, <https://gdc.cancer.gov/about-data/gdc-data-quality>
 16. New TCGA and TARGET Properties and Sample Type Restructuring | NCI Genomic Data Commons - National Cancer Institute, <https://gdc.cancer.gov/news-and-announcements/new-tcga-and-target-properties-and-sample-type-restructuring>
 17. Sample Type Codes - NCI Genomic Data Commons - National Cancer Institute, <https://gdc.cancer.gov/resources-tcga-users/tcga-code-tables/sample-type-codes>
 18. TCGAbiolinks source: R/clinical.R - rdrr.io, <https://rdrr.io/bioc/TCGAbiolinks/src/R/clinical.R>
 19. GDC Data Dictionary - GDC Docs - National Cancer Institute, https://docs.gdc.cancer.gov/Data_Dictionary/
 20. Working with TCGAbiolinks package, <https://bioconductor.statistik.tu-dortmund.de/packages/3.3/bioc/vignettes/TCGAbiolinks/inst/doc/tcgaBiolinks.html>
 21. error in GDCprepare · Issue #470 · BioinformaticsFMRP/TCGAbiolinks - GitHub, <https://github.com/BioinformaticsFMRP/TCGAbiolinks/issues/470>
 22. target-rt / target-52-parecb - GDC Data Portal, <https://portal.gdc.cancer.gov/cases/fcb86b71-cf65-5853-903c-084cca5808c8?bioid=b354c419-bbfe-59ff-add5-1febc518582b>
 23. Identifying Targeted Therapies for CBFA2T3::GLIS2 Acute Myeloid Leukemia - PMC - NIH, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12136236/>
 24. Hierarchical Lineage Tracing Reveals Diverse Pathways of AML Treatment Resistance - PMC, <https://pmc.ncbi.nlm.nih.gov/articles/PMC11908168/>
 25. gdc-docs/docs/API/Users_Guide/Search_and_Retrieval.md at develop - GitHub, https://github.com/NCIP/gdc-docs/blob/develop/docs/API/Users_Guide/Search_and_Retrieval.md
 26. Search and Retrieval - GDC Docs - National Cancer Institute, https://docs.gdc.cancer.gov/API/Users_Guide/Search_and_Retrieval/
 27. convert_UUID_to_TCGA_barcode.md - GitHub Gist, <https://gist.github.com/crazyhottommy/d815b34d62a28e4e2e4a51e083392275>
 28. TCGAbiolinks: An R/Bioconductor package for integrative analysis with GDC data - Index of /, <https://bioconductor.posit.co/packages/3.22/bioc/manuals/TCGAbiolinks/man/TCGAbiolinks.pdf>
 29. colDataPrepare: Create samples information matrix for GDC samples in TCGAbiolinks: TCGAbiolinks: An R/Bioconductor package for integrative analysis with GDC data - rdrr.io, <https://rdrr.io/bioc/TCGAbiolinks/man/colDataPrepare.html>