There were issues affecting this run of Lighthouse:

• There may be stored data affecting loading performance in this location: IndexedDB. Audit this page in an incognito window to prevent those resources from affecting your scores.



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so manual testing is also encouraged.

NAMES AND LABELS

A	Buttons do not have an accessible name	^
	Buttons do not have an accessible name	^


When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn how to make buttons more accessible</u>.

Failing Elements	
	button.sc-ec1e59c8-9.dleLod.sc-13c44f56-15.iXCaWY
	button.sc-ec1e59c8-9.dOnZWS.sc-9fa7cb36-8.UTIwY
	button.sc-ec1e59c8-9.dOnZWS.sc-9fa7cb36-8.UTIwY
	button.sc-ec1e59c8-9.dleLod.sc-9fa7cb36-8.sc-9fa7cb36-9.UTlwY.kTfldN

about:blank 1/12



Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <u>Learn how to make links accessible</u>.



These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.


CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. Learn how to provide sufficient color contrast.



about:blank 2/12



about:blank 3/12

Failing Elements
h4.sc-30f0cb72-4.jVWStu
a.sc-ec1e59c8-4.sc-ec1e59c8-5.sc-30f0cb72-13.jlqcEr.fruXwC.leVgeb
a.sc-ec1e59c8-4.sc-ec1e59c8-5.sc-30f0cb72-13.jlqcEr.fruXwC.leVgeb
p.sc-30f0cb72-12.bePRDG
hese are opportunities to improve the legibility of your content.
▲ Heading elements are not in a sequentially-descending order
Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <u>Learn more about heading order</u> .
Failing Elements
h4.sc-13c44f56-12.jBuxbc

These are opportunities to improve keyboard navigation in your application.

about:blank 4/12

ADDITIONAL ITEMS TO MANUALLY CHECK (10)	Hide
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn how to make custom controls focusable</u> .	
Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn how to decorate interactive elements with affordance hints</u> .	
The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more about logical tab ordering</u> .	
Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more about DOM and visual ordering</u> .	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn how to avoid focus traps</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn how to direct focus</u> <u>new content</u> .	s to
HTML5 landmark elements are used to improve navigation	^
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. <u>Learn more about landmark elements</u>.</nav></main>	
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content	<u>ıt</u> .
 Custom controls have associated labels 	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more about</u>	

about:blank 5/12

custom controls and labels.

 Custom controls have ARIA roles 	^
Custom interactive controls have appropriate ARIA roles. <u>Learn how to add roles to custom controls</u> .	
These items address areas which an automated testing tool cannot cover. Learn more in our guide on conductive accessibility review.	ucting an
PASSED AUDITS (21)	Hide
[aria-*] attributes match their roles	^
Each ARIA role supports a specific subset of aria—* attributes. Mismatching these invalidates the arattributes. Learn how to match ARIA attributes to their roles.	ia-*
[aria-hidden="true"] is not present on the document <body></body>	^
Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on s	the document
[role]s have all required [aria-*] attributes	^
Some ARIA roles have required attributes that describe the state of the element to screen readers. <u>Lea roles and required attributes</u> .	rn more about
[aria-*] attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn movalues for ARIA attributes</u> .	ore about valid
[aria-*] attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn modern ARIA attributes</u> .	ore about valid
Image elements have [alt] attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignor empty alt attribute. <u>Learn more about the alt attribute</u> .	ed with an
[user-scalable="no"] is not used in the <meta name="viewport"/> element and the [maximum-scale] at not less than 5.	tribute is
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly	see the

contents of a web page. <u>Learn more about the viewport meta tag</u>.

about:blank 6/12

ARIA attributes are used as specified for the element's role

Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes.

Elements use only permitted ARIA attributes

Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated

to users of assistive technologies. <u>Learn more about prohibited ARIA roles</u>.

[role] values are valid

ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more about valid ARIA roles</u>.

Document has a <title> element

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more about document titles</u>.

html element has a [lang] attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <u>Learn more about the lang attribute</u>.

<html> element has a valid value for its [lang] attribute

Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. <u>Learn how to use the language</u> attribute.

Form elements have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. <u>Learn more</u> about form element labels.

Lists contain only elements and script supporting elements (<script> and <template>).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more about proper list structure.

List items () are contained within , or <menu> parent elements

Screen readers require list items () to be contained within a parent , or <menu> to be announced properly. Learn more about proper list structure.

about:blank 7/12

No element has a [tabindex] value greater than 0	^
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more about the tabindex attribute</u> .	
Touch targets have sufficient size and spacing.	^
Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to active the targets. <u>Learn more about touch targets</u> .	/ate
Uses ARIA roles only on compatible elements	^
Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. <u>Learn more about ARIA roles</u> .	
Deprecated ARIA roles were not used	^
Deprecated ARIA roles may not be processed correctly by assistive technology. <u>Learn more about deprecated AFI roles</u> .	<u>≀IA</u>
Image elements do not have [alt] attributes that are redundant text.	^
Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be reatwice. Learn more about the alt attribute.	
NOT APPLICABLE (32)	Hide
O [accesskey] values are unique	^
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. <u>Learn more about access keys</u> .	
button, link, and menuitem elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn how to make command elements more accessible</u> .	
 Elements with role="dialog" or role="alertdialog" have accessible names. 	^
ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. <u>Learn how to make ARIA dialog elements more accessible</u> .	of

about:blank 8/12

O [aria-hidden="true"] elements do not contain focusable descendents	^
Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from be available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements available to users of assistive technologies like screen readers.	_
ARIA input fields have accessible names	^
When an input field doesn't have an accessible name, screen readers announce it with a generic name, making is unusable for users who rely on screen readers. <u>Learn more about input field labels</u> .	t
ARIA meter elements have accessible names	^
When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making unusable for users who rely on screen readers. <u>Learn how to name meter elements</u> .	ng it
ARIA progressbar elements have accessible names	^
When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name making it unusable for users who rely on screen readers. Learn how to label progressbar elements.	ie,
 Elements with an ARIA [role] that require children to contain a specific [role] have all required children. 	^
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn more about roles and required children elements</u> .	<u>l</u>
[role]s are contained by their required parent element	^
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element.	У
 Elements with the role=text attribute do not have focusable descendents. 	^
Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute.	
ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making i unusable for users who rely on screen readers. <u>Learn more about toggle fields</u> .	t
 ARIA tooltip elements have accessible names 	^
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, maki unusable for users who rely on screen readers. <u>Learn how to name tooltip elements</u> .	ing it

about:blank 9/12

When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more about labeling treeitem elements</u> .	
The page contains a heading, skip link, or landmark region	^
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more abouty</u> bypass blocks.	<u>ıt</u>
<dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</td><td>^</td></tr><tr><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Lea</u> how to structure definition lists correctly.</td><td><u>arn</u></td></tr><tr><td> Definition list items are wrapped in <dl> elements </td><td>^</td></tr><tr><td>Definition list items (<dt> and <dd>) must be wrapped in a parent <dl> element to ensure that screen readers can properly announce them. <u>Learn how to structure definition lists correctly</u>.</td><td>n</td></tr><tr><td>O ARIA IDs are unique</td><td>^</td></tr><tr><td>The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologic Learn how to fix duplicate ARIA IDs.</td><td>es.</td></tr><tr><td>No form fields have multiple labels</td><td>^</td></tr><tr><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn how to use form labels.</td><td>1</td></tr><tr><td><frame> or <iframe> elements have a title</td><td>^</td></tr><tr><td>Screen reader users rely on frame titles to describe the contents of frames. <u>Learn more about frame titles</u>.</td><td></td></tr><tr><td><html> element has an [xml:lang] attribute with the same base language as the [lang] attribute.</td><td>^</td></tr><tr><td>If the webpage does not specify a consistent language, then the screen reader might not announce the page's tex- correctly. <u>Learn more about the lang attribute</u>.</td><td>ίt</td></tr><tr><td> Input buttons have discernible text. </td><td>^</td></tr><tr><td>Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. <u>Learn more about input buttons</u>.</td><td></td></tr></tbody></table></script></dd></dt></dl>	

about:blank 10/12

<pre><input type="image"/> elements have [alt] text</pre>	^
When an image is being used as an <input/> button, providing alternative text can help screen reader users understand the purpose of the button. Learn about input image alt text.	
Links are distinguishable without relying on color.	^
Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. <u>Learn how to make links distinguishable</u> .	
The document does not use <meta http-equiv="refresh"/>	^
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. may create a frustrating or confusing experience. <u>Learn more about the refresh meta tag</u> .	This
O <object> elements have alternate text</object>	^
Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen reconvey meaning to users. Learn more about alt text for object elements.</object>	aders
O Select elements have associated label elements.	^
Form elements without effective labels can create frustrating experiences for screen reader users. <u>Learn more the select element</u> .	<u>about</u>
O Skip links are focusable.	^
Including a skip link can help users skip to the main content to save time. <u>Learn more about skip links</u> .	
 Tables have different content in the summary attribute and <caption>.</caption> 	^
The summary attribute should describe the table structure, while <caption> should have the onscreen title. Accurate table mark-up helps users of screen readers. Learn more about summary and caption.</caption>	
Cells in a element that use the [headers] attribute refer to table cells within the same table.	^
Screen readers have features to make navigating tables easier. Ensuring cells using the [headers] attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about headers attribute.	
elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.	^
Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some seculs may improve the experience for screen reader users. <u>Learn more about table headers</u> .	t of

about:blank 11/12

Generated by Lighthouse 12.8.2 | File an issue

with devtools

about:blank 12/12