



There were issues affecting this run of Lighthouse:

- The page may not be loading as expected because your test URL (<https://alfabank.ru/>) was redirected to [74](https://alfabank.ru/?oirutpspid=1761740837813_e20f4dd5359fd056c9751061451001c3_ag4ev19ajw1bi1js&oirutpspsc=1761740846986_9ac8f936c29361ee28c3a08bdb98b474_ux4GUPXCZyHjlxm8UvGZ0GxRbhYdju18ENO5Qbpt6IkZ&oirutpspjs=1761740846986_225fbb12_01350190_4d4e7feb24e63635d891ed3033be3b58_84RIKHicQ1%2B%2Bc1oW9zZCbCJh%2BrM1stBNjADIAuOmAytL3rYSczYMVSkcZUBgpQV4ttuTH365mveGKsIMZMEIdQR4wbw8sBZe4yZvSmqvCbJA1Z0ZelF0QYAkzAZuC5J%2FfnLbG8YbIY0tYMcktZjA3Dp65rMztx9S%2Bu3kUUO2%2FjoeuqL2M7JYkbRoBS2NIQxwBtri%2B35CXue3DgMYiO6HUgim3hp7HAPykhbee5vv98NJ0F3EVA1hnhahRKWZmKhJOasO%2Bx0e7f1B73eWiaUafWnh8h5EzlwrrKz8nTGn1vUUVqYTnXbFqQ4MvJz9vw7s3UPTpzVgsJfLi9k8Z6h%2BGQrain8sruhCJ7OUIANXJ4S1%2Bt9rGdkpm%2Bo8WHnDlpAt5Kc210SFVPr%2B6DjYG89ePe6Ht5bwcsBmlIBkkTr4yqsZwKMCeKC UH0guHf5Cqjy5CNSM6P%2F%2F7wsJTJq8V5T9FycmlISSRiLOeai4ffVuerk%2B4tKTDVKT F83ayJMEbDtw56K9%2FmAvlwHNChvRZouJY8wWcKkq4f0ju2pvz0nq9rRZEKMFgsODpzh5fDv4rsigN22SWZZHQIYD2skUj2571XqwpmDsZhDhm9vFnV4bGF%2FLkan%2BXR4bQMggl8xB619lyE1yrClmnAAx21WmGYOqa8wsSxmVjK76aFhSSbPLid0nZylenJSBskjo8IHfQz77N%2BC6ctIWGbQFy9UDwFBfCprby%2FZhZUsSsvf%2BoTwUBg%2Bq7RjQXNawWN8FCsfz2tMZhVcVjgHEowEXLQZFxJ%2Ba2VEWLWjoo6Hifz4zdfNMSokHgu9W62xjsh%2Fs4zSQZFjlarbQ3B4WQx%2Baz9XESSwraue7vcslaGcy0hMTjjXf2gaVIFatKuD9IKN6abRJvuH%2FMVdcB53J02JcEVA7vunnrWVLkV%2BX%2FfnKcv%2BvvLG7B4QATwv%2BuiEbpge%2By5OZzJip64aqezFgOD3DNoofmNft4ObRyfwkqxPUjnlUIBPMYqQEQz58%2B7S38mwrJ1vmtl3YVBIMTcmGgMM%2B%2BfQ0sW1rqyXi3B%2BZZEeYAtrPHI4eM1L%2F5bfWxIVVOyooO5dAwtlRb1qvDn2zCisKGPfVKq0WpE8IOJshMdhCE5YNvXAxIYACDIUUJWLOG8JBkXAVHewNeLvNKIGY4gd6tckkXRPgAXSv7x5fjMg7pjG7IEW3FnFJo7USCbEQZVpR7QJ7qso7WIPnEPTtn6gHxTkAda7iEtKqG1pp6NoXBqHVdOedMpnHfUx%2FAMB312PyGnOLTj3YsDKaedrFtPnvdmBHEtZAYaKUyKm6eyvMnV4xXu58Sa97my8nuD7vJ564JI73rtn9zZNHZDCnoAfQ0oFk%2BeJzl3GCFxviZ7BPY%2BzEVLdn%2BwNftwsLIBJmwXU1xqcPjuYypKvzGtkvWLPjJ3RMH57JKCQf6Y%2Bm5ZEzAZKlwPe8xiPLUeOG9WEbxJdWxHR58WLSwl3Hanm%2F7VkeEEFjzk3%2FRXarlzZCgaMPZuZU90La8Vgtt6QWWRWHonP1YETJDsZpeLjqWILMWDtCBiYEbuFW9UHPPV%2Fv7Z0rRwi9nLX1JZcECM7jMToiSk6QDGzycfiQ1WaXvlfB4CtauYcsR7bGBfw7z3rcHa5nlmOw0FMHQnWxKy%2FPyJ1Zfjr5PF4nZglI00pZhBbc6yGcW1aVEM%2FKStBICWT5NjPx7aom5PEei9y9FQVE2ZaJyDF6dzBNkZRXKMLdnJteU46N2tsMAT%2B7%2BPcyp2xhZtyf3oiVzFEUHknEg369OPfyMK1rZqUh3tsYIVJPjCnHiWt1GyVk%2BS4rGJotD7hBT7DI1bvvStNucz1AhAjuZ20ezrCFK0MSFGCDUJfY%2BaZImBcp4Xotx3MWwORWc%2BfBdVDISpfsjnt%2Byu9Yx8aHYasSodCR5QBprvYdRovDuOrQ0vaXgKZHVrKoIX7umxKvqfQZ39i6JOGtH%2FiS06UM%2B1bC3S0JbcsoX8FZxMJVcgFR. Try testing the second URL directly.</a></li></ul></div><div data-bbox=)

## Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

## NAMES AND LABELS


---

**▲ Buttons do not have an accessible name**

---



When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

**Failing Elements**

```
div.dNsLqP > div.gNsLqP > div.aUdnKq > button.bUdnKq  
<button class="bUdnKq dUdnKq" data-test-id="main-header-burger">
```

---

**▲ <frame> or <iframe> elements do not have a title**

---



Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

**Failing Elements**

body > iframe

```
<iframe src="https://sm.rtb.mts.ru/s?p=tL0GSZGkyHR7rU0%3D&random=0.6527115443744912"  
style="position: absolute; top: -2000px; left: 0px;">
```

---

**▲ Links do not have a discernible name**

---



Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

**Failing Elements**

div.kUI5hC > div.aUI5hC > div.kUI5hC > a.aXYDeT

```
<a class="aXYDeT gXYDeT cXYDeT bXYDeT" href="/feedback/support/reviews/" rel="noopener noreferrer">
```

div.kUI5hC > div.aUI5hC > div.kUI5hC > a.aXYDeT

```
<a class="aXYDeT mXYDeT cXYDeT bXYDeT" href="https://t.me/AlfaBank" rel="noopener noreferrer">
```

div.kUI5hC > div.aUI5hC > div.kUI5hC > a.aXYDeT

```
<a class="aXYDeT mXYDeT cXYDeT bXYDeT" href="https://vk.com/alfabank" rel="noopener noreferrer">
```

---

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

## ARIA

---

**▲** `[aria-hidden="true"]` elements contain focusable descendents ^

---

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how `aria-hidden` affects focusable elements](#).


**Failing Elements**

Войти в Альфа-Бизнес

```
<div aria-hidden="true" class="aZKuYI">
```


Войти в Альфа-Бизнес

```
<a class="button__component_1cfl7 button__ghost_1cfl7 button__size-64_1cfl7 button__..." data-widget-name="AnalyticsEventSender" data-widget-uid="0197fa1b-137d-7aab-92a8-f18669a225d2" href="/sme/rko/abm/app/">
```



Уже одобрили вам кредит Посмотрите одобренные условия

```
<div aria-hidden="true" class="aZKuYI">
```



Уже одобрили вам кредит Посмотрите одобренные условия

```
<a class="aXYDeT gXYDeT cXYDeT bXYDeT" href="https://alfabank.ru/get-money/credit/credit-cash/form-approve-retention/?a..." rel="noopener noreferrer">
```

Альфа-Бизнес Онлайн Мобильный банк, который работает на всех смартфонах. Он та...

```
<div aria-hidden="true" class="aZKuYI">
```

В Альфа-Бизнес Онлайн

```
<a class="button__component_1cfl7 button__primary_1cfl7 button__size-48_1cfl7 button..." href="/sme/rko/abm/app/" style="background: rgb(255, 255, 255);">
```

---

**▲** ARIA input fields do not have accessible names ^

---

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels](#).

**Failing Elements**

В отделениях

```
<div aria-expanded="false" aria-haspopup="listbox" role="combobox" class="select__component_184hn" tabindex="-1">
```

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.

## CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.



Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

## Failing Elements




Начать инвестировать

```
<span class="button__label_1cfl7 button__stretchText_1cfl7">
```




Начать инвестировать

```
<a class="button__component_1cfl7 button__primary_1cfl7 button__size-48_1cfl7  
button..." data-widget-name="AnalyticsEventSender" data-widget-uid="0199c3e8-8e1e-7ff9-  
8d58-48169d01877e" href="https://alfabank.ru/make-money/investments/promo/10000-za-5mes-oct/#Form-  
0...">
```




С бесплатным обслуживанием

```
<p class="aR70y1 bR70y1 xR70y1 TR70y1 cR70y1 nQWkTE CQWkTE RQWkTE _5QWkTE  
a1UcN1 h1U..." data-test-id="text">
```




Кредитная карта С бесплатным обслуживанием

```
<div class="c1UcN1 d1UcN1" style="background-color: rgb(243, 244, 245);">
```



Фамилия Имя Отчество

```
<span data-test-id="input-form-control-label" class="form-  
control__labelInner_16zaj">
```



Фамилия Имя Отчество Фамилия Имя Отчество

```
<div data-test-id="input-form-control-inner" class="form-control__inner_16zaj form-  
control__inner_paogy form-control__inner_15...">
```



Фамилия Имя Отчество Фамилия Имя Отчество Укажите точно как в паспорте Дата рож...


```
<div class="eBwr3K bBwr3K">
```



Заполните заявку на дебетовую карту Фамилия Имя Отчество Фамилия Имя Отчество ...


```
<div class="axpN2B hQWkTE aNQWkTE bxsrhW axsrhW" style="background-color: rgb(242, 243,  
245);">
```

## Failing Elements



Дата рождения

```
<span data-test-id="input-form-control-label" class="form-control__labelInner_16zaj">
```



Дата рождения Дата рождения

```
<div data-test-id="input-form-control-inner" class="form-control__inner_16zaj form-control__inner_paogy form-control__inner_15...">
```



Фамилия Имя Отчество Фамилия Имя Отчество Укажите точно как в паспорте Дата рож...

```
<div class="eBwr3K bBwr3K">
```




Заполните заявку на дебетовую карту Фамилия Имя Отчество Фамилия Имя Отчество ...

```
<div class="axpN2B hQWkTE aNQWkTE bxsrhW axsrhW" style="background-color: rgb(242, 243, 245);">
```



Мобильный телефон

```
<span data-test-id="phoneInput-form-control-label" class="form-control__labelInner_16zaj">
```



Мобильный телефон Мобильный телефон

```
<div data-test-id="phoneInput-form-control-inner" class="form-control__inner_16zaj form-control__inner_paogy form-control__inner_15...">
```




Фамилия Имя Отчество Фамилия Имя Отчество Укажите точно как в паспорте Дата рож...

```
<div class="eBwr3K bBwr3K">
```



Заполните заявку на дебетовую карту Фамилия Имя Отчество Фамилия Имя Отчество ...

```
<div class="axpN2B hQWkTE aNQWkTE bxsrhW axsrhW" style="background-color: rgb(242, 243, 245);">
```




Мы гарантируем безопасность и сохранность ваших данных

```
<p class="aR70y1 bR70y1 xR70y1 SR70y1 hR70y1 nQWkTE CQWkTE RQWkTE _5QWkTE" data-test-id="text">
```



Заполните заявку на дебетовую карту Фамилия Имя Отчество Фамилия Имя Отчество ...

```
<div class="axpN2B hQWkTE aNQWkTE bxsrhW axsrhW" style="background-color: rgb(242, 243, 245);">
```



Продолжить

```
<span class="button__label_1cfl7 button__stretchText_1cfl7">
```



Продолжить

Failing Elements



```
<button class="button__component_1cfl7 button__primary_1cfl7 button__size-48_1cfl7 button..." data-test-id="button" type="submit">
```

These are opportunities to improve the legibility of your content.

NAVIGATION


▲ Some elements have a `tabindex` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the `tabindex` attribute.](#)


Failing Elements



```
Накопления
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-1" role="button"
tabindex="1">
```




```
Кредиты
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-2" role="button"
tabindex="2">
```



```
Ипотека
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-3" role="button"
tabindex="3">
```



```
Инвестиции
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-4" role="button"
tabindex="4">
```



```
Alfa Only
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-5" role="button"
tabindex="5">
```




```
Мобильная связь
```

Failing Elements



```
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-6" role="button"
tabindex="6">
```




Самозанятость

```
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-7" role="button"
tabindex="7">
```




Семья и дети

```
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-8" role="button"
tabindex="8">
```



Альфа-Будущее

```
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-9" role="button"
tabindex="9">
```



Ещё

```
<div class="cUE1G6 AUE1G6" data-test-id="accordion-header-10" role="button"
tabindex="10">
```

МАЛОМУ БИЗНЕСУ

```
<div class="cUE1G6 AUE1G6 ajQWkTE aSQWkTE" data-test-id="accordion-header-1" role="button"
tabindex="1">
```

КРУПНОМУ БИЗНЕСУ

```
<div class="cUE1G6 AUE1G6 SQWkTE ajQWkTE" data-test-id="accordion-header-2" role="button" tabindex="2">
```

These are opportunities to improve keyboard navigation in your application.

BEST PRACTICES

▲ Touch targets do not have sufficient size or spacing. ^

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)

Failing Elements

Переключиться на слайд #2

## Failing Elements

```
<button aria-label="Переключиться на слайд #2" class="bNeTWy dNeTWy" data-test-id="dot-1">
```

Активный слайд #1

```
<button aria-label="Активный слайд #1" class="bNeTWy cNeTWy dNeTWy" data-test-id="dot-0">
```

Переключиться на слайд #3

```
<button aria-label="Переключиться на слайд #3" class="bNeTWy dNeTWy" data-test-id="dot-2">
```

Переключиться на слайд #3

```
<button aria-label="Переключиться на слайд #3" class="bNeTWy dNeTWy" data-test-id="dot-2">
```

Переключиться на слайд #2

```
<button aria-label="Переключиться на слайд #2" class="bNeTWy dNeTWy" data-test-id="dot-1">
```

Переключиться на слайд #4

```
<button aria-label="Переключиться на слайд #4" class="bNeTWy dNeTWy" data-test-id="dot-3">
```

Переключиться на слайд #4

```
<button aria-label="Переключиться на слайд #4" class="bNeTWy dNeTWy" data-test-id="dot-3">
```

Переключиться на слайд #3

```
<button aria-label="Переключиться на слайд #3" class="bNeTWy dNeTWy" data-test-id="dot-2">
```

Переключиться на слайд #5

```
<button aria-label="Переключиться на слайд #5" class="bNeTWy dNeTWy" data-test-id="dot-4">
```

Переключиться на слайд #5

```
<button aria-label="Переключиться на слайд #5" class="bNeTWy dNeTWy" data-test-id="dot-4">
```

Переключиться на слайд #4

```
<button aria-label="Переключиться на слайд #4" class="bNeTWy dNeTWy" data-test-id="dot-3">
```

Переключиться на слайд #6

```
<button aria-label="Переключиться на слайд #6" class="bNeTWy dNeTWy" data-test-id="dot-5">
```

Переключиться на слайд #6

```
<button aria-label="Переключиться на слайд #6" class="bNeTWy dNeTWy" data-test-id="dot-5">
```

Переключиться на слайд #5

```
<button aria-label="Переключиться на слайд #5" class="bNeTWy dNeTWy" data-test-id="dot-4">
```

Переключиться на слайд #7

```
<button aria-label="Переключиться на слайд #7" class="bNeTWy dNeTWy" data-test-id="dot-6">
```

Переключиться на слайд #7

```
<button aria-label="Переключиться на слайд #7" class="bNeTWy dNeTWy" data-test-id="dot-6">
```

Переключиться на слайд #6

```
<button aria-label="Переключиться на слайд #6" class="bNeTWy dNeTWy" data-test-id="dot-5">
```

Переключиться на слайд #8

```
<button aria-label="Переключиться на слайд #8" class="bNeTWy dNeTWy" data-test-id="dot-7">
```

Переключиться на слайд #8

```
<button aria-label="Переключиться на слайд #8" class="bNeTWy dNeTWy" data-test-id="dot-7">
```



## Failing Elements

Переключиться на слайд #7

```
<button aria-label="Переключиться на слайд #7" class="bNeTwy dNeTwy" data-test-id="dot-6">
```

Переключиться на слайд #9

```
<button aria-label="Переключиться на слайд #9" class="bNeTwy dNeTwy" data-test-id="dot-8">
```

Переключиться на слайд #9

```
<button aria-label="Переключиться на слайд #9" class="bNeTwy dNeTwy" data-test-id="dot-8">
```

Переключиться на слайд #8

```
<button aria-label="Переключиться на слайд #8" class="bNeTwy dNeTwy" data-test-id="dot-7">
```

Переключиться на слайд #10

```
<button aria-label="Переключиться на слайд #10" class="bNeTwy dNeTwy" data-test-id="dot-9">
```

Переключиться на слайд #10

```
<button aria-label="Переключиться на слайд #10" class="bNeTwy dNeTwy" data-test-id="dot-9">
```

Переключиться на слайд #9

```
<button aria-label="Переключиться на слайд #9" class="bNeTwy dNeTwy" data-test-id="dot-8">
```

Переключиться на слайд #11

```
<button aria-label="Переключиться на слайд #11" class="bNeTwy dNeTwy" data-test-id="dot-10">
```

Переключиться на слайд #11

```
<button aria-label="Переключиться на слайд #11" class="bNeTwy dNeTwy" data-test-id="dot-10">
```

Переключиться на слайд #10

```
<button aria-label="Переключиться на слайд #10" class="bNeTwy dNeTwy" data-test-id="dot-9">
```

These items highlight common accessibility best practices.

## AUDIO AND VIDEO

- `<video>` elements contain a `<track>` element with `[kind="captions"]`



When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#)

## Failing Elements



div#alfa > div > div.aPtNEv > video#myVideo

```
<video autoplay="" class="bPtNEv" data-test-id="video-background-video"
id="myVideo" loop="" playsinline="" poster="https://alfabank.servicecdn.ru/site-
upload/0e/8d/7110/Alfabank_Invest_Site..." style="height: 100%; top: 50%; left:
50%;" src="https://alfabank.servicecdn.ru/site-upload/08/fe/7110/1080p-10k.mp4">
```

These are opportunities to provide alternative content for audio and video. This may improve the experience for users with hearing or vision impairments.

## ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

- ☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#)

- ☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#)

- ☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#)

- ☐ Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#)

- ☐ User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#)

- ☐ The user's focus is directed to new content added to the page



If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#)

- ☐ HTML5 landmark elements are used to improve navigation



Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#)

- ☐ Offscreen content is hidden from assistive technology



Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content.](#)

- ☐ Custom controls have associated labels



Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels.](#)

---

○ Custom controls have ARIA roles ^

---

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#)

---

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (24)

Hide

---

`[aria-*)` attributes match their roles ^

---

Each ARIA role supports a specific subset of `aria-*)` attributes. Mismatching these invalidates the `aria-*)` attributes. [Learn how to match ARIA attributes to their roles.](#)

---

`[aria-hidden="true"]` is not present on the document `<body>` ^

---

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn how `aria-hidden` affects the document body.](#)

---

`[role]`s have all required `[aria-*)` attributes ^

---

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

---

Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children. ^

---

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#)

---

`[role]`s are contained by their required parent element ^

---

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#)

---

`[aria-*)` attributes have valid values ^

---

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

---

`[aria-*)` attributes are valid and not misspelled ^

---

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

---

Image elements have `[alt]` attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5.



Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

`button`, `link`, and `menuitem` elements have accessible names



When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#)

ARIA attributes are used as specified for the element's role



Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#)

Elements use only permitted ARIA attributes



Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#)

`[role]` values are valid



ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

`<html>` element has a `[lang]` attribute



If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

`<html>` element has a valid value for its `[lang]` attribute



Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the lang attribute.](#)

---

#### Form elements have associated labels

---

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#)

---

#### Links are distinguishable without relying on color.

---

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#)

---

#### Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table.

---

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#)

---

#### Heading elements appear in a sequentially-descending order

---

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

---

#### Uses ARIA roles only on compatible elements

---

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#)

---

#### Deprecated ARIA roles were not used

---

Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#)

---

#### Image elements do not have `[alt]` attributes that are redundant text.

---

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#)

---

#### Tables have different content in the summary attribute and `<caption>`.

---

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#)

---

## NOT APPLICABLE (24)

Hide

- ☐ [\[accesskey\]](#) values are unique



Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#)

- ☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names.



ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#)

- ☐ ARIA `meter` elements have accessible names



When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

- ☐ ARIA `progressbar` elements have accessible names



When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

- ☐ Elements with the `role=text` attribute do not have focusable descendents.



Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the role=text attribute.](#)

- ☐ ARIA toggle fields have accessible names



When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#)

- ☐ ARIA `tooltip` elements have accessible names



When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#)

- ☐ ARIA `treeitem` elements have accessible names



When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling treeitem elements.](#)

- ☐ The page contains a heading, skip link, or landmark region



Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#)

- `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#)

- Definition list items are wrapped in `<dl>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#)

- ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

- No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

- Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

- `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

- Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

- List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (<li>) to be contained within a parent <ul>, <ol> or <menu> to be announced properly. [Learn more about proper list structure.](#)

☐ The document does not use <meta http-equiv="refresh"> ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#)

☐ <object> elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#)

☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#)

☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#)

☐ <th> elements and elements with [role="columnheader"/"rowheader"] have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#)

☐ [lang] attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#)

■ Captured at Oct 29, 2025,  
3:27 PM GMT+3

■ Initial page load

■ Emulated Moto G Power with  
Lighthouse 12.8.2

■ Slow 4G throttling

■ Single page session

■ Using Chromium 141.0.0.0  
with devtools

Generated by **Lighthouse** 12.8.2 | [File an issue](#)