Project 1

---

1) MIPS Instruction Set

Use the attached cheat sheet (at the end of the assignment) in order to determine which
MIPS instructions appear in the program. Determine the instruction format for each instruction.

Determine the operands for each instruction. For registers determine both, the register
number and the symbolic register name.

There are conditional branches in the function. Determine to which instructions they
branch.

line	opcode	format	funct	MN	rs	rt	rd	imm	traduction
0	4	I		BEQ	4	0		0xD	**if (a0 = 0) then PC = PC + 4 + 4***
4									**nop**
8	32	I		LB	4	5		0x0	**a1 = memory[a0 + 0] as a byte**
c									**nop**
10	4	I		BEQ	5	0		0x7	**if a1 = 0 then PC = PC + 4 + 4*7**
14	0	R	37	OR	0	0	2		**v0 = 0**
18	9	I		ADDIU	4	4		0x1	**a0 = a0 + 1**
1c	14	I		XORI	5	3		0x20	**v1 = a1 XOR 0x20 : 6th byte flippe**
20	32	I		LB	4	5		0x0	**a1 = memory[a0] as a byte (we are**
24	0	R	43	SLTU	0	3	3		**v1 = (0 < v1) <=> (v1 != 0) as it**
28	5	I		BNE	5	0		0xFFFB	**if a1 != 0 then branch at PC + 4 +**
2c	0	R	33	ADDU	2	3	2		**v0 = v0 + v1**
30	0	R	8	JR	31				**Jump Register : PC = ra**
34									**nop**
38	0	R	8	JR	31				**Jump Register : PC = ra**
3c	9	R		ADDIU	0	2		0xFFFF	**v0 = 0xFFFF = -1**

What is the function actually doing? What is its return value?

This function takes a string as argument and returns :

- -1 if the string is a null pointer
- The number of char different than a space in the string otherwise.

1

2) MIPS Tool Chain

Write a C program matching the program from above.

```c
int f(char *s) {
    if(s == 0) return -1;
    char c = *s;
    if(c == 0) return 0;

    int r = 0;
    while(c != 0) {
        r += (c != ' ');
        c = *(++s);
    }
    return r;
}
```

Compile the program using the MIPS compiler installed on the lab machines using the
following command line:
```
mips-linux-gnu-gcc -mips1 -c -g -o mips-prog.o <input-file>
```

Disassemble the compiled program (mips-prog.o) with the objdump tool using the
following command line:
```
mips-linux-gnu-objdump -d mips-prog.o
```

Compare the resulting assembly code obtained from the objdump tool with the code
from above. Explain why the code looks so differently? The code contains many lw
instructions that use the register s8. What is the purpose of register s8? What are these
memory access instructions doing?

If we compile it without optimization. The assembly code is
quite different, much longer and most instructions are useless.
It uses register S8 which is the frame pointer. But here it is useless
as we know the size of the stack. Sp could have done the job, and here
sp = fp, so really it's useless. Moreover the code never uses other
register than v0 and it always store it's value in the stack (thanks to s8)
and load values from the stack.

Try to change the compiler options (enable/disable optimizations using the option -O0,
-O, or -O3) and see how this changes the code that you can see using the objdump
tool.

With some optimization we get better results, and we no longer use S8.
With -O2 optimization we have the exact same code. And with -Os we get even
a shorter code (but maybe less efficient).

---

3) MIPS Architecture

3.1 Program Flow

Provide a full list of instructions until the function terminates by
executing a jr instruction.

PC	instruction	a0	a1	v0	v1	explaination
0x0	beq a0, 0, 0xD	0x200	0x0	0x0	0x0	a0 != 0 so the branch is untaken
0x4	nop	0x200	0x0	0x0	0x0	no change
0x8	lb a0, a1, 0x0	0x200	0x0	0x0	0x0	read from memory[0x200] to a1 the value arrives in the next instruction
0xc	nop	0x200	0x61	0x0	0x0	no change wait for loading
0X10	beq a1, 0, 0x7	0x200	0x61	0x0	0x0	a1 != 0 so the branch is untaken
0x14	or v0, 0, 0	0x200	0x61	0x0	0x0	v0 <= 0
0x18	addiu a0, a0, 0x1	0x201	0x61	0x0	0x0	a0 <= a0 + 1
0x1c	xori v1, a1, 0x20	0x201	0x61	0x0	0x41	v1 <= a1 ^ 0x20
0x20	lb a0, a1, 0x0	0x201	0x61	0x0	0x41	read from memory[0x201] to a1 the value arrives in the next instruction
0x24	sltu v1, 0, v1	0x201	0x20	0x0	0x1	v1 <= (v1!= 0)
0x28	bne a1, 0, 0xfffb	0x201	0x20	0x0	0x1	a1 != 0 so the branch is taken. the next instruction is still executed
0x2c	addu v0, v1, v0	0x201	0x20	0x1	0x1	v0 <= v0 + v1 = 1
0x18	addiu a0, a0, 0x1	0x202	0x20	0x1	0x1	a0 <= a0 + 1
0x1c	xori v1, a1, 0x20	0x202	0x20	0x1	0x0	v1 <= a1 ^ 0x20
0x20	lb a0, a1, 0x0	0x202	0x20	0x1	0x0	read from memory[0x202] to a1 the value arrives in the next instruction

| PC	instruction	a0	a1	v0	v1	explaination
0x24	sltu v1, 0, v1	0x202	0x62	0x1	0x0	v1 <= (v1!= 0)
0x28	bne a1, 0, 0xfffb	0x202	0x62	0x1	0x0	a1 != 0 so the branch is taken. the next instruction is still executed
0x2c	addu v0, v1, v0	0x202	0x62	0x1	0x0	v0 <= v0 + v1 = 1
0x18	addiu a0, a0, 0x1	0x203	0x62	0x1	0x0	a0 <= a0 + 1
0x1c	xori v1, a1, 0x20	0x203	0x62	0x1	0x42	v1 <= a1 ˆ 0x20
0x20	lb a0, a1, 0x0	0x203	0x62	0x1	0x42	read from memory[0x203] to a1 the value arrives in the next instruction
0x24	sltu v1, 0, v1	0x203	0x0	0x1	0x1	v1 <= (v1!= 0)
0x28	bne a1, 0, 0xfffb	0x203	0x0	0x1	0x1	a1 == 0 so the branch is not taken
0x2c	addu v0, v1, v0	0x203	0x0	0x2	0x1	v0 <= v0 + v1 = 2
0x30	jr ra	0x203	0x0	0x2	0x1	end of function, returns. next instruction is still executed
0x34	nop	0x203	0x0	0x2	0x1	nop

3.2 Pipiline Diagram

Draw a pipeline diagram showing all the instructions executed by the function as determined
above. Assume a processor implementation as described above. Highlight
all forms of hazards that occur and graphically distinguish resolution mechanisms (e.g.,
forwarding, stalls, flushing).

PC	Instruction	Commentaries	Processor states
0x0	beq a0, 0, 0xD	reading a0	IF ID EX MEM WB
0x4	nop		IF ID EX MEM WB
0x8	lb a0, a1, 0x0	Reading a0 and in memory, writing in a1	IF ID EX MEM MEM WB
0xC	nop		IF IF ID EX MEM WB
0x10	beq a1, 0, 0x7	reading a1, branch untaken	IF ID EX MEM WB
0x14	or v0, 0, 0	writing in v0	IF ID EX MEM WB
0x18	addiu a0, a0, 0x1	writing in a0	IF ID EX MEM WB
0x1C	xori v1, a1, 0x20	reading a1, writing in v1	IF ID EX MEM WB
0x20	lb a0, a1, 0x0	Reading a0 and in memory, writing in a1	IF ID EX MEM MEM WB
0x24	sltu v1, 0, v1	writing in v1	IF IF ID EX MEM WB
0x28	bne a1, 0, 0xfffb	reading a1, branch untaken, next instruction executed, 2nd next flushed	IF ID EX MEM WB
0x2C	addu v0, v1, v0	reading v0 and v1, writing in v0	IF ID EX MEM WB
0x30	jr ra	flushed	IF
0x18	addiu a0, a0, 0x1	reading and writing a0	IF ID EX MEM WB
0x1C	xori v1, a1, 0x20	reading a1, writing in v1	IF ID EX MEM WB
0x20	lb a0, a1, 0x0	Reading a0 and in memory, writing in a1	IF ID EX MEM MEM WB
0x24	sltu v1, 0, v	writing in v1	IF IF ID EX MEM WB
0x28	bne a1, 0, 0xfffb	reading a1, branch untaken , next instruction executed, 2nd next flushed	IF ID EX MEM WB
0x2C	addu v0, v1, v0	reading v0 and v1, writing in v0	IF ID EX MEM WB
0x30	jr ra	flushed	IF
0x18	addiu a0, a0, 0x1	reading and writing a0	IF ID EX MEM WB
0x1C	xori v1, a1, 0x20	reading a1, writing in v1	IF ID EX MEM WB
0x20	lb a0, a1, 0x0	Reading a0 and in memory, writing in a1	IF ID EX MEM MEM WB
0x24	sltu v1, 0, v1	writing in v1	IF IF ID EX MEM WB
0x28	bne a1, 0, 0xfffb	reading a1, branch taken	IF ID EX MEM WB
0x2C	addu v0, v1, v0	reading v0 and v1, writing in v0	IF ID EX MEM WB
0x30	jr ra	end of function, returns. next instruction is still executed	IF ID EX MEM WB
0x34	nop		IF ID EX MEM WB

: stalling
: forwarding
: flushing

---

4) Processor design

4.1 Instruction Set Architecture

> Group instructions into binary formats, similar to the I-, J-, and R-format discussed for
> MIPS in the lecture. Illustrate the formats using figures in your report.

The first format is **R-format**, the 16-bits instruction is divided in 4 part of 4 bits :

0...3	4...7	8...11	12...15
opcode	Rs	R1	R2

(There are 16 registers, so register id are on 4 bits.)

The second format is **M-format**, used for memory access. The opcode is now on 3 bits, and the immediate value is on 5 bits :

0...2	3...6	7...10	11...15
opcode	Rs	Ra	immediate

And the last format is **I-format**. The opcode is on only 2 bits, and the immediate value is on 10 bits (register id are still on 4 bits) :

0...1	2...5	6...15
opcode	R	immediate

5

Describe each instruction of your processor. Explain what the instruction is doing, how it
can be written in human readable form (assembly), and how it is
encoded in binary form.

Assembly code	Format	Opcode	Traduction
ADD	R	0000	Rs <- R1 + R2
AND	R	0001	Rs <- R1 & R2
XOR	R	0010	Rs <- R1 ^ R2
JR	R	0011	PC <- Rs
LB	M	010	Rs <- SE(Mem[Ra + SE(immediate)]) (*)
SB	M	011	Mem[Ra + SE(immediate)] <- Rs[7:0]
MV	I	10	R <- SE(immediate)
BNN	I	11	If R != 0, then PC = PC + 2 * immediate (**)

*SE = Sign Extend.

** Instructions are on 16 bits, so PC should always be an even number.

Provide a sequence of instructions in assembly form that allows to
load the constant
65534 into a register using the instructions of your processor. Give a
short explanation of
each instruction and each intermediate result of your code.

In order to load 65534 (= 0xFFFE) into a register with those instructions, we
can do :

```
MV R0 0x3FF
ADD R0 R0 R0
```

The first line will set R0 to -1 = 0x3FF (on 10 bits). It means that after this
instruction, R0 has 0xFFFF value due to sign extension. Then the second
instruction do : R0 <= -1 + -1 = -2 (0xFFFF + 0xFFFF = 0xFFFE).

Translate the C-code from Question 1 to corresponding instructions
of your processor.
Assume that the input pointer is provided in the second register of
your processor and that
the result should be returned in the first register. The return address
is similarly provided
in register 15. Try to use the instructions of your processor as optimal
as possible in order
to minimize the number of instructions. There is no need to preserve
any register values
in your code, i.e., you can overwrite any register if needed.

6

Translation of C-code, we assume here that there is no pipeline in the processor yet.

```
00  BNN R1 3            //R1 = 0 -> return -1
02  MV  R0 0x3FF
04  JR  R15
06  MV  R0 0            //Initialization
08  MV  R3 0x20
0a  MV  R4 1
0c  LB  R2 R1 0
0e  BNN R2 2            //R2 = 0 -> return R0
10  JR  R15
12  XOR R2 R2 R3
14  ADD R1 R1 R4
16  BNN R2 2
18  BNN R4 0x3Fa       //Go back to 0c instruction
1a  ADD R0 R0 R4
1c  BNN R4 0x3F8       //Go back to 0c instruction
```

4.2 Pipelining

> Which kinds of hazards (data, control, or structural) can you encounter for your processor?
> Explain under which circumstances these hazards occur. How are these hazards
> resolved?

There are 3 types of hazards :

- data hazard
- control hazard
- structural hazard

We will treat them one by one.

Data hazard :

This hazard occure when a data is not available when it is needed for the next instruction.
The textbook exemple is when an instruction needs the result of an ALU operation. For example :

```
00 ADD R2 R3 R4
02 ADD R0 R1 R2
```

In this code the result of the first instruction is needed as an operand for the second one.
Nevertheless, in a pipelined CPU the result of an ALU operation might not be

written back in
the register file as soon as it is executed.

However in our pipelined CPU we only have three stages :

- Instruction Fetch (IF)
- Instruciton Decode (ID)
- Execute (EX)

The result of a ALU operation is written during the EX stage and is directly available. So this
result can be used for the next EX. This solves without any hazard the porblem of the codes like :

```
00 ADD R2 R3 R4
02 ADD R0 R1 R2
```

But the result of a EX instruction can be needed for a ID, typically :

```
00 ADD R0 R1 R2
02 BNN R0 0x08
```

Indeed, BNN (Branch Non Null) is done during the ID stage and thus needs the value of R0.
However this is not a hazard neither because we assume that the result of the ALU is
given so quickly that we have it for the ID directly.

As says the statement of the PR1 :

> Assume that the processor registers are written at the beginning of
> the EX stage and read
> at the end of the ID stage, i.e., values written in the EX stage are
> immediately available
> in the ID stage.

As a result, **a data hazard can only occure of there is a memory load**. This hazard is solved by **stalling the IF and ID stages**.

Control hazard :

A control hazard occure when the next PC is not correct. This happens when a branch is
mispredicted.

In our CPU we only predict untaken branch. This means **this hazard occures when a branch
is taken**. As a result **we must flush the IF stage**.

Structural hazard :

This hazard happens when a ressource is needed by several instructions at the same time. In our simple CPU, **This kind of hazard never occures**.

Does your processor need forwarding (as discussed in the lecture) for the instructions
in the EX stage? What about the conditional branch that is executed in the ID stage?
Explain for both cases why it is needed or why it is not needed.

Our CPU **does not need a forwarding for the EX stage**. Indeed, the result of the previous EX stage
is directly written back in the register file and available.

As for the ID stage, we assumed that the result of the EX stage is written back sufficiently quickly that it can be used in the same clock by the ID stage (for example for a branch instruction). This means that **we don't need to implement
a forwarding for this CPU**.