

ASSIGNMENT 5A – HOF ON LISTS

Advanced programming paradigms

In this assignment, you will apply different higher-order functions on lists to gain experience in those typical functional-oriented operations.

Question 1 – *Higher-order functions on lists*

Using only the `zip` and `map` higher-order functions, define the following functions that:

- (a) Returns a list of the length of each string of a list

Example:

```
lengthStrings(List("How", "long", "are", "we?")) returns List(3,4,3,3)
```

- (b) Produces a list with n identical elements of arbitrary type (don't use the `fill` method!)

Examples:

```
dup("foo", 5) returns List("foo", "foo", "foo", "foo", "foo")
```

```
dup(List(1,2,3), 2) returns List(List(1,2,3), List(1,2,3))
```

- (c) Multiplies element-wise two lists of values and create a new list

Example:

```
dot(List(1,2,3), List(2,4,3)) returns List(2,8,9)
```

Question 2 – *Folding functions on lists*

Now using folding (right or left) define a function that:

- (a) Determines if all logical values in a non-empty list are true.

Examples:

```
areTrue(List(true, true, false)) returns false
```

```
areTrue(List(true, true, true)) returns true
```

- (b) Determine the total length of the strings in a list

Example:

```
lString(List("Folding", "is", "fun")) returns 12
```

- (c) Returns the longest string of a list as well as its size

Example:

```
longest(List("What", "is", "the", "longest?")) returns (8, longest?)
```

- (d) Decide if a value is an element of a list of an arbitrary type

Examples:

```
isPresent(List(1,2,3,4), 5) returns false
```

```
isPresent(List(1,2,3,4), 3) returns true
```

- (e) Flatten a nested list structure of any type.

Example:

```
flattenList(List(List(1,1), 2, List(3, List(5, 8)))) returns List(1,1,2,3,5,8)
```