

Name: Max Copeland

Date: 9/22/17

Pledge: "I pledge my honor that I have abided by the Stevens Honor System"

For each function below, trace through it with reasonably small integer values. What does each function do?

HINT: You should assume integers are 8 bits for the purpose of this exercise.

```
int mystery1(int a, int b) {
    int c = a - b,
        d = (c >> 7) & 1,
        mystery = a - c * d;
    return mystery;
}
```

Trace: `mystery1(3, 7)` returns: 7

Trace: `mystery1(8, 7)` returns: 8

Summary: `mystery1` returns the larger of the two inputs.

```
void mystery2(int values[], int i, int j) {
    values[i] = values[i] ^ values[j];
    values[j] = values[i] ^ values[j];
    values[i] = values[i] ^ values[j];
}
```

Note: Improper C++ syntax found below.

Trace: `mystery2([1, 2, 3, 4], 0, 3)` values = [4, 2, 3, 1]

Trace: `mystery2([1, 2, 3, 4], 1, 2)` values = [1, 3, 2, 4]

Summary: `mystery2` swaps the integers in the `i` and `j` index

```
int mystery3(int x, int y) {
    int s, c;
    s = x ^ y;
    c = x & y;
    while (c != 0) {
        c = c << 1;
        x = s;
        y = c;
        s = x ^ y;
        c = x & y;
    }
    return s;
}
```

Trace: `mystery3(5, 7)` returns: 12

Trace: `mystery3(2, 8)` returns: 10

Summary: `mystery3` is a complicated function for adding inputs `x` and `y`