

Smart Parking API

Node-RED · SQLite · REST

ADMIN

GET	/api/admin/event-logs Event-Log-Einträge abrufen (filterbar)
Query-Parameters	eventtype, plate, from, to, limit (def. 100), offset (def. 0)
Response 200	Array: { id, timestamp, eventtype, source, message, parking_session_id }

GET	/api/admin/parking-sessions/open Alle offenen Parksessions
Response 200	Array: { id, plate, entry_time, amount_due, amount_paid }

GET	/api/admin/parking-sessions/:sessionId Session-Details per ID
Params	sessionId (integer)
Response 200	Einzelnes Session-Objekt (alle Felder)
Response 404	{ error: "Session nicht gefunden" }
Response 400	{ error: "Ungültige sessionId" }

PATCH	/api/admin/parking-sessions/:sessionId Session-Felder aktualisieren
Params	sessionId (integer)
Body (opt.)	amount_paid, payment_time, exit_valid_until
Response 200	{ success: true, session_id }
Response 400	Ungültige ID oder keine Felder angegeben

GET	/api/admin/rfid-admins Alle RFID-Admin-Einträge
Response 200	Array: { id, name, rfid_uid, role, active }

POST	/api/admin/rfid-admins Neuen RFID-Admin anlegen
Body	name* (string), uid* (string), active (bool, def. true)
Response 201	{ success: true }

Response 400	{ error: "name und uid erforderlich" }
-----------------	--

PATCH	/api/admin/rfid-admins/:uid RFID-Admin aktivieren / deaktivieren
Params	uid (rfid_uid string)
Body	active* (bool)
Response 200	{ success: true }
Response 400	{ error: "active erforderlich" }

GET	/api/admin/rfid-releases RFID-Schrankenfreigaben (mit Admin-Name)
Response 200	Array: { id, admin_id, admin_name, rfid_uid, parking_session_id, release_time }

PAYMENTS

GET	/api/payments/open-sessions Offene Sessions mit Live-Berechnung des fälligen Betrags
Response 200	Array: { session_id, plate, entry_time, amount_due, amount_paid, remaining_amount }
Hinweis	amount_due wird live berechnet (1 €/angefangene Stunde, min. 1 h)

GET	/api/payments/session/by-plate/:plate Aktive Session per Kennzeichen suchen
Params	plate (Kennzeichen, uppercase)
Response 200	{ session_id, plate, entry_time, amount_due, amount_paid, remaining_amount }
Response 404	{ error: "Keine aktive Session fuer dieses Kennzeichen" }

POST	/api/payments/pay Zahlung für aktive Session buchen
Body	plate* (string), amount_paid_now* (number > 0)
Response 200	{ success, plate, session_id, amount_due, amount_paid_total, remaining_amount, exit_allowed }
Hinweis	Bei vollständiger Zahlung: exit_valid_until = +15 min; PAYMENT_SUCCESS wird ins event_log geschrieben
Response 400/404	Fehlende Felder oder keine aktive Session

PATCH	/api/payments/session/:sessionId amount_paid direkt per Session-ID setzen
Params	sessionId (integer)

Body	<code>amount_paid* (number)</code>
Response 200	<code>{ success: true, session_id }</code>
Response 400	<code>{ error: "sessionId und amount_paid erforderlich" }</code>

MAP

GET	<code>/api/map/parking-spots</code> Alle Parkplätze mit Belegungsstatus
Response 200	<code>Array: { id, floor, spot_number, occupied } – sortiert nach Etage + Nummer</code>
GET	<code>/api/map/overview</code> Parkhaus-Übersicht (gesamt / frei / belegt)
Response 200	<code>{ total_spots, free_spots, occupied_spots }</code>