

PRELIMINARY

Secret Monero Bridge Proof-of-Concept XMR→sXMR Swap

18 March 2021

Preliminary Information:

Secret Monero Bridge Monero wallet address:

9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBA81QakWg83GCKibK

Step 1

User sends 1.0 XMR to the Secret Monero Bridge Monero wallet.

```
Starting refresh...
Refresh done, blocks received: 0
Untagged accounts:
  Account      Balance      Unlocked balance      Label
  *  0 A1uQoz    4.000000000000      2.000000000000      Primary account
-----
  Total    4.000000000000      2.000000000000
Currently selected account: [0] Primary account
Tag: (No tag assigned)
Balance: 4.000000000000, unlocked balance: 2.000000000000 (8 block(s) to unlock)
Background refresh thread started
[wallet A1uQoz]: transfer 9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBA81QakWg83GCKibK 1.0

Transaction 1/1:
Spending from address index 0
Sending 1.000000000000. The transaction fee is 0.000033700000

Is this okay? (Y/Yes/N/No): Y
Transaction successfully submitted, transaction <3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62>
You can check its status by using the 'show_transfers' command.
[wallet A1uQoz]:
```

User then collects the Monero proof-of-payment for the transaction:

```
[wallet A1uQoz]: get_tx_key 3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62
Tx key: a3017c8e43101abc1f6078971fe68ed4da7efd03caa732bdd3364bec9265d307
[wallet A1uQoz]:
```

Now the three pieces of information representing the Monero proof-of-payment have been obtained:

TXID: 3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62

TXKEY: a3017c8e43101abc1f6078971fe68ed4da7efd03caa732bdd3364bec9265d307

Payment Address:

9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBA81QakWg83GCKibK

Now the user can check the Monero proof-of-payment by submitting the **check_tx_key** command in his/her Monero wallet:

```
[wallet A1uQoz (out of sync)]: check_tx_key 3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62 a3017c8e43101abc1f6078971fe68ed4da7efd03caa732bdd3364bec9265d307 9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBAT81QakWg83GckibK
QHVNfVdcdmtbt5gFqCnBAT81QakWg83GckibK
9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBAT81QakWg83GckibK received 1.000000000000
000 in txid <3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62>
This transaction has 2 confirmations
[wallet A1uQoz (out of sync)]:
```

We can see that Monero wallet address:

9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBAT81QakWg83GckibK

received 1.000000000000 XMR in txid:

3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62

and that the transaction has had 2 confirmations.

The Secret Monero Bridge web application will then make a call to the locally running monero-wallet-rpc to verify the Monero proof-of-payment (similar to the curl call shown below):

```
waldo1@localhost:~$ curl http://127.0.0.1:18083/json_rpc -d '{"jsonrpc":"2.0","id":"0","method":"check_tx_key","params":{"txid":"3127ebdf7e3f69973326243eee8ef3e3e22ec958b7066b5b81fe9cfe52334f62","tx_key":"a3017c8e43101abc1f6078971fe68ed4da7efd03caa732bdd3364bec9265d307","address":"9yjuUbbdcFSXRKAoaCGfQQR9UkbkwVBhqYXihc1EcoPdin8YibndTrCbEgQHVNfVdcdmtbt5gFqCnBAT81QakWg83GckibK"}}' -H 'Content-Type: application/json'
{
  "id": "0",
  "jsonrpc": "2.0",
  "result": {
    "confirmations": 3,
    "in_pool": false,
    "received": 1000000000000
  }
}
wald01@localhost:~$
```

Note:

The Secret Monero Bridge web application will persist Monero proof-of-payment txids to ensure that no txid is processed more than once.

In this Proof-of-Concept we will wait for just 1 confirmation before proceeding.