```
❯ uv init --help
Create a new project

Usage: uv init [OPTIONS] [PATH]

Arguments:
  [PATH]  The path to use for the project/script

Options:
      --name <NAME>
          The name of the project
      --bare
          Only create a `pyproject.toml`
      --package
          Set up the project to be built as a Python package
      --no-package
          Do not set up the project to be built as a Python package
      --app
          Create a project for an application
      --lib
          Create a project for a library
      --script
          Create a script
      --description <DESCRIPTION>
          Set the project description
      --no-description
          Disable the description for the project
      --vcs <VCS>
          Initialize a version control system for the project [possibl
          values: git, none]
      --build-backend <BUILD_BACKEND>
          Initialize a build-backend of choice for the project [env:
          UV_INIT_BUILD_BACKEND=] [possible values: uv, hatch, flit,
          pdm, poetry, setuptools, maturin, scikit]
      --no-readme
          Do not create a `README.md` file
      --author-from <AUTHOR_FROM>
          Fill in the `authors` field in the `pyproject.toml` [possibl
```

```
          values: auto, git, none]
      --no-pin-python
          Do not create a `.python-version` file for the project
      --no-workspace
          Avoid discovering a workspace and create a standalone projec

Python options:
  -p, --python <PYTHON>
          The Python interpreter to use to determine the minimum
          supported Python version. [env: UV_PYTHON=]
      --managed-python
          Require use of uv-managed Python versions [env:
          UV_MANAGED_PYTHON=]
      --no-managed-python
          Disable use of uv-managed Python versions [env:
          UV_NO_MANAGED_PYTHON=]
      --no-python-downloads
          Disable automatic downloads of Python. [env:
          "UV_PYTHON_DOWNLOADS=never"]

Cache options:
  -n, --no-cache
          Avoid reading from or writing to the cache, instead using a
          temporary directory for the duration of the operation [env:
          UV_NO_CACHE=]
      --cache-dir <CACHE_DIR>
          Path to the cache directory [env: UV_CACHE_DIR=]

Global options:
  -q, --quiet...
          Use quiet output
  -v, --verbose...
          Use verbose output
      --color <COLOR_CHOICE>
          Control the use of color in output [possible values: auto,
          always, never]
      --native-tls
          Whether to load TLS certificates from the platform's native
          store [env: UV_NATIVE_TLS=]
      --offline
          Disable network access [env: UV_OFFLINE=]
      --allow-insecure-host <ALLOW_INSECURE_HOST>
          Allow insecure connections to a host [env: UV_INSECURE_HOST=
```

```
    --no-progress
        Hide all progress outputs [env: UV_NO_PROGRESS=]
    --directory <DIRECTORY>
        Change to the given directory prior to running the command
        [env: UV_WORKING_DIR=]
    --project <PROJECT>
        Discover a project in the given directory [env: UV_PROJECT=]
    --config-file <CONFIG_FILE>
        The path to a `uv.toml` file to use for configuration [env:
        UV_CONFIG_FILE=]
    --no-config
        Avoid discovering configuration files (`pyproject.toml`,
        `uv.toml`) [env: UV_NO_CONFIG=]
-h, --help
        Display the concise help for this command
```