

Ex1

OneCompiler

Upgrade

AI

JavaScript

Run

🔍

⚙️

💾 Save

🔑 Login

index.js

+

🔍

```
1 console.log(0.1 * 3 === 0.3);
2 console.log(9807199254748993)
```

🕒

⚙️

Console

I/O

AI Agent

156 ms

🟢

false

9807199254748992

Ready

Terminal

Light

Wiki

Internet

Ex2

OneCompiler

Upgrade

AI

Python

Run

🔍

⚙️

💾 Save

🔑 Login

main.py

+

🔍

```
1 palavra = "maçã"
2 print(len(palavra), len(palavra.encode())) # encode() usa UTF-8 por padrão
```

🕒

⚙️

Console

I/O

AI Agent

133 ms

🟢

4 6

Ready

Terminal

Light

Wiki

Internet

Ex3

The OneCompiler interface displays a Go program in the editor. The code defines a package 'main', imports 'fmt', and a function 'main' that declares a byte variable 'b' with value 255, increments it, and prints it. The console shows the output '0' and a status of '259 ms'.

```
1 package main
2
3 import "fmt"
4
5 func main() {
6     var b byte = 255
7     b++
8     fmt.Println(b)
9 }
10
```

Console: 0 259 ms

Ex4

The OneCompiler interface displays a Java program in the editor. The code defines a class 'Main' with a 'main' method that creates an integer array 'v' of size 3, prints its elements, and increments the second element. The console shows the output '0' and a status of '849 ms'.

```
1 public class Main {
2     public static void main(String[] args) {
3         int[] v = new int[3];
4         System.out.println(v[0]);
5         System.out.println(v[2]);
6     }
7 }
8
```

Console: 0 849 ms

Ex5

The OneCompiler interface displays a Rust program in the editor. The code uses 'let' to declare variables 's' and 't' and prints them. The console shows a compilation error: 'error: expected item, found keyword `let`'. The error message explains that 'let' cannot be used for global variables and provides a link to the Rust reference for items.

```
1 let s = String::from("oi");
2 let t = s;
3 println!("{}", s, t);
4
```

error: expected item, found keyword `let`
--> HelloWorld.rs:1:1
1 | let s = String::from("oi");
 | ^^^
 |
 | `let` cannot be used for global variables
 | help: consider using `static` or `const` instead of `let`
 |
= note: for a full list of items that can appear in modules, see
 <<https://doc.rust-lang.org/reference/items.html>>

error: aborting due to 1 previous error

Debug this error

Ex6

OneCompiler

Upgrade

AI

C

Run

Save

Login

Console

I/O

AI Agent

174 ms

1

2

3

4

5

6

7

8

#include <stdio.h>

int main(void) {

union { int i; float f; } u;

u.f = 1.0f;

printf("%d\n", u.i);

return 0;

}

1065353216

Reactor

Terminal

Light

Wiki

Internet