

Megamodel-driven Traceability Recovery & Exploration of Correspondence & Conformance Links

Bachelorarbeit

zur Erlangung des Grades eines Bachelor of Science
im Studiengang Informatik

vorgelegt von

Maximilian Meffert

Erstgutachter: Prof. Dr. Ralf Lämmel
Institut für Informatik

Zweitgutachter: Msc. Johannes Härtel
Institut für Informatik

Koblenz, im Juni 2017

Erklärung

Hiermit bestätige ich, dass die vorliegende Arbeit von mir selbständig verfasst wurde und ich keine anderen als die angegebenen Hilfsmittel – insbesondere keine im Quellenverzeichnis nicht benannten Internet-Quellen – benutzt habe und die Arbeit von mir vorher nicht in einem anderen Prüfungsverfahren eingereicht wurde. Die eingereichte schriftliche Fassung entspricht der auf dem elektronischen Speichermedium (CD-Rom).

Ja Nein

Mit der Einstellung der Arbeit in die Bibliothek bin ich ein- ☐ ☐
verstanden.

Der Veröffentlichung dieser Arbeit im Internet stimme ich ☐ ☐
zu.

.....
(Ort, Datum) (Maximilian Meffert)

Zusammenfassung

TBD.

Abstract

TBD.

Contents

1	Introduction	1
2	Related Work	2
3	Background	3
3.1	Mathematical Background	3
3.1.1	Relations	3
3.2	Formal Languages & Grammars	6
3.2.1	Context-Free Languages & Grammars	6
3.3	Traceability	6
3.3.1	Traceability Relationship	6
3.3.2	Traceability Link	6
3.3.3	Traceability Recovery	6
3.3.4	Traceability Exploration	6
3.4	Megamodeling	6
3.4.1	MegaL	6
3.5	Ontologies	6
3.6	Mereology	6
3.7	Program Analysis	7
3.8	XML Data Binding	7
3.8.1	Java Architecture for XML Binding (JAXB)	7
3.9	Object Relational Mapping	7
3.9.1	Java Persistence API (JPA)	7
3.9.2	Hibernate	7
3.10	Another Tool For Language Recognition (ANTLR)	7

4	Hypotheses	8
4.1	Fragments	8
4.2	Correspondence	8
4.3	Conformance	8
5	Methodology	9
5.1	The 101companies Human Resource Management System	9
5.2	Link Proper Part Ratio	9
6	Requirements	10
7	Design	11
8	Implementation	12
8.1	Context-Free Grammar Fragmentation	12
8.2	Name Correspondence Heuristic	12
9	Results	13
10	Conclusion	14

List of Figures

Chapter 1

Introduction

TBD.

Chapter 2

Related Work

TBD.

Chapter 3

Background

TBD.

3.1 Mathematical Background

3.1.1 Relations

A n -ary, $n \in \mathbb{N}$, relation is the subset of the Cartesian product of n sets:

$$R \subseteq A_1 \times \dots \times A_n = \{(a_1, \dots, a_n) | a_1 \in A_1 \wedge \dots \wedge a_n \in A_n\} \quad (3.1)$$

and a binary relation is the subset of the Cartesian product between two sets:

$$R \subseteq A \times B = \{(a, b) | a \in A \wedge b \in B\} \quad (3.2)$$

3.1.1.1 Homogeneous & Heterogeneous Relations

A relation $R \subseteq A \times B$ is called homogeneous if $A = B$, otherwise it is called heterogeneous. However, an arbitrary relation $R \subseteq A \times B$ is also homogeneous in the sense of:

$$R \subseteq A \times B \subseteq (A \cup B) \times (A \cup B) \quad (3.3)$$

3.1.1.2 Composition

The composition $S \circ R \subseteq A \times D$ of two binary relations $R \subseteq A \times B$ and $S \subseteq C \times D$ is defined as:

$$S \circ R := \{(a, d) \in A \times D \mid \exists x \in B \cap C : (a, x) \in R \wedge (x, d) \in S\} \quad (3.4)$$

3.1.1.3 Identity Relation

The relation I over a set A with:

$$I := \{(a, b) \in A \times A \mid a = b\} = \{(a, a) \mid a \in A\} \subseteq A \times A \quad (3.5)$$

is called identity relation.

3.1.1.4 Exponentiation

The n -th power R^n of a relation R with $n \in \mathbb{N}$ is the product of its composition n -times with itself:

$$R^n = \underbrace{R \circ \dots \circ R}_n \quad (3.6)$$

and can be recursively defined with:

$$R^0 := I \quad (3.7)$$

$$R^n := R \circ R^{n-1} \quad (3.8)$$

3.1.1.5 Properties

A relation R is called ...

Property	Requirement
bijjective	$\forall b \in B \exists! a \in A : (a, b) \in R$
function	$\forall a \in A \exists! b \in B : (a, b) \in R$
reflexive	$\forall a \in A : (a, a) \in R$
irreflexive	$\forall a \in A : (a, a) \notin R$
transitive	$\forall a, b, c \in A : (a, b) \in R \wedge (b, c) \in R \Rightarrow (a, c) \in R$
intransitive	$\forall a, b, c \in A : (a, b) \in R \wedge (b, c) \in R \Rightarrow (a, c) \notin R$
symmetric	$\forall a, b \in A : (a, b) \in R \Rightarrow (b, a) \in R$
asymmetric	$\forall a, b \in A : (a, b) \in R \Rightarrow (b, a) \notin R$
antisymmetric	$\forall a, b \in A : (a, b) \in R \wedge (b, a) \in R \Rightarrow a = b$

3.1.1.6 Closures

For a relation R over a set A its closure:

- $R \cup I$ is called *reflexive closure*
- $R^+ := R^1 \cup R^2 \cup R^3 \cup \dots$ is called *transitive closure*

$$(a, b) \in R^+ \Leftrightarrow (a, b) \in R^1 \vee (a, b) \in R^2 \vee (a, b) \in R^3 \vee \dots \quad (3.9)$$

$$\Leftrightarrow \exists n \in \mathbb{N} : n \geq 1 \wedge (a, b) \in R^n \quad (3.10)$$

$$\Leftrightarrow \exists n \in \mathbb{N} : n \geq 1 \wedge (a, b) \in R \circ R^{n-1} \quad (3.11)$$

$$\Leftrightarrow \exists n \in \mathbb{N} : n \geq 1 \wedge [\exists x \in A : (a, x) \in R \wedge (x, b) \in R^{n-1}] \quad (3.12)$$

$$\Leftrightarrow \exists n \in \mathbb{N} \exists x \in A : n \geq 1 \wedge (a, x) \in R \wedge (x, b) \in R^{n-1} \quad (3.13)$$

- $R^* := R^+ \cup I$ is called *reflexive-transitive closure*

$$(a, b) \in R^* \Leftrightarrow (a, b) \in R^+ \vee (a, b) \in I \quad (3.14)$$

$$\Leftrightarrow (a, b) \in R^+ \vee a = b \quad (3.15)$$

3.2 Formal Languages & Grammars

3.2.1 Context-Free Languages & Grammars

3.3 Traceability

[1] TBD.

3.3.1 Traceability Relationship

3.3.2 Traceability Link

3.3.3 Traceability Recovery

3.3.4 Traceability Exploration

3.4 Megamodeling

TBD.

3.4.1 MegaL

3.4.1.1 MegaL/Xtext

3.5 Ontologies

TBD.

3.6 Mereology

$$x \text{ partOf } x \quad (\text{Reflexivity}) \quad (3.16)$$

$$x \text{ partOf } y \wedge y \text{ partOf } x \Rightarrow x = y \quad (\text{Antisymmetry}) \quad (3.17)$$

$$x \text{ partOf } y \wedge y \text{ partOf } z \Rightarrow x \text{ partOf } z \quad (\text{Transitivity}) \quad (3.18)$$

TBD.

3.7 Program Analysis

TBD.

3.8 XML Data Binding

TBD.

3.8.1 Java Architecture for XML Binding (JAXB)

3.9 Object Relational Mapping

TBD.

3.9.1 Java Persistence API (JPA)

3.9.2 Hibernate

3.10 Another Tool For Language Recognition (ANTLR)

Chapter 4

Hypotheses

TBD.

4.1 Fragments

4.2 Correspondence

4.3 Conformance

Chapter 5

Methodology

TBD.

5.1 The 101companies Human Resource Management System

Description of the 101companies Human Resource Management System

5.2 Link Proper Part Ratio

The ratio between all proper parts of two artifacts and the proper parts of the same artifacts in a relationship.

$$\pi_{R,A_1,A_2} = \frac{|\{(p_1, p_2) \in R : p_1 \text{ properPartOf } A_1 \wedge p_2 \text{ properPartOf } A_2\}|}{|\{p : p \text{ properPartOf } A_1 \vee p \text{ properPartOf } A_2\}|}$$

Chapter 6

Requirements

TBD.

R1 asdf

R2 asdf

R3 asdf

R4 asdf

Chapter 7

Design

TBD.

Chapter 8

Implementation

TBD.

8.1 Context-Free Grammar Fragmentation

8.2 Name Correspondence Heuristic

Heuristics are quick and "simple" methods for finding good approximate solutions for complex problems. The Name Correspondence Heuristic determines correspondence between artifacts simply by finding similarities of names in those artifacts.

TBD.

Chapter 9

Results

TBD.

Chapter 10

Conclusion

TBD.

Bibliography

- [1] Stefan Winkler and Jens Pilgrim. “A Survey of Traceability in Requirements Engineering and Model-driven Development”. In: *Softw. Syst. Model.* 9.4 (Sept. 2010), pp. 529–565. ISSN: 1619-1366. DOI: [10.1007/s10270-009-0145-0](https://doi.org/10.1007/s10270-009-0145-0). URL: <http://dx.doi.org/10.1007/s10270-009-0145-0>.