


Can we implement good quantum LDPC codes on near-term devices?


Maxime Tremblay¹, Michael Beverland², Nicolas Delfosse²




Arute et al. Nature 574, 505–510 (2019)

The IBM Quantum heavy hex lattice

As of August 8, 2021, the topology of all active IBM Quantum devices will use the heavy-hex lattice, including the IBM Quantum System One's Falcon processors installed in Germany and Japan.



Near-term quantum computers will be locally connected.



Can we achieve large scale fault-tolerant quantum computing on locally connected devices?

Tradeoffs for reliable quantum information storage in 2D systems

Sergey Bravyi,¹ David Poulin,² and Barbara Terhal¹


¹*IBM Watson Research Center, Yorktown Heights NY 10598, USA*

²*Département de Physique, Université de Sherbrooke, Québec, Canada*

(Dated: September 11, 2018)


Long range interactions from local operations

Long range interactions from local operations




$$|\bar{0}\rangle \equiv |++\cdots++\rangle + |--\cdots--\rangle$$


Long range interactions from local operations




$$|\bar{0}\rangle \equiv |++\cdots++\rangle + |--\cdots--\rangle$$



Long range interactions from local operations



Long range interactions from local operations



Main results

Theorem

Let C be a Clifford circuit measuring computing Pauli operators S_1, \dots, S_r . Then, for any subset of qubits L , we have

$$\text{depth}(C) \geq \frac{n_{\text{cut}}}{64|\partial L|}.$$

Main results

Theorem


Let C be a Clifford circuit measuring commuting Pauli operators S_1, \dots, S_r . Then, for any subset of qubits L , we have

$$\text{depth}(C) \geq \frac{n_{\text{cut}}}{64|\partial L|}.$$

Corollary

For families of local-expander quantum LDPC codes of length n , a syndrome extraction circuit C implemented as a local Clifford circuit on a $\sqrt{N} \times \sqrt{N}$ grid of qubits satisfies

$$\text{depth}(C) \geq \Omega\left(\frac{n}{\sqrt{N}}\right).$$



References

- ❖ Bounds on stabilizer measurement circuits and obstructions to local implementations of quantum LDPC codes
[arXiv 2109.14599](#)
- ❖ Constant-overhead quantum error correction with thin planar connectivity
[arXiv 2109.14609](#)

Outline

1. Background and definitions
2. Proof of the main theorem
3. Circuit implementations
4. Numerical experiments

Background and definitions

Clifford circuit

- Preparations of $|0\rangle$ and $|+\rangle$ and classical bits.

Clifford circuit

- Preparations of $|0\rangle$ and $|+\rangle$ and classical bits.
- Single-qubit and two-qubit Pauli measurements.

Clifford circuit

- ❖ Preparations of $|0\rangle$ and $|+\rangle$ and classical bits.
- ❖ Single-qubit and two-qubit Pauli measurements.
- ❖ Single-qubit and two-qubit unitary Clifford gates.


Clifford circuit

- ❖ Preparations of $|0\rangle$ and $|+\rangle$ and classical bits.
- ❖ Single-qubit and two-qubit Pauli measurements.
- ❖ Single-qubit and two-qubit unitary Clifford gates.
- ❖ Classically-controlled Pauli operators.

Clifford circuit

- ❖ Preparations of $|0\rangle$ and $|+\rangle$ and classical bits.
- ❖ Single-qubit and two-qubit Pauli measurements.
- ❖ Single-qubit and two-qubit unitary Clifford gates.
- ❖ Classically-controlled Pauli operators.
- ❖ Output the parity of some subsets of measurement outcomes.

Clifford circuit




Local circuit


A b -local circuit is a circuit with qubits placed on a subset of the $\mathbb{Z} \times \mathbb{Z}$ grid such that any two-qubit operation acts on qubits at distance at most b from each other.

Local circuit



A b -local circuit is a circuit with qubits placed on a subset of the $\mathbb{Z} \times \mathbb{Z}$ grid such that any two-qubit operation acts on qubits at distance at most b from each other.



Connectivity graph



Connectivity graph



Stabilizer code

Stabilizer group

$$\mathcal{S} = \langle S_1, S_2, \dots, S_r \rangle \subset \mathcal{P}_n \setminus \{-I\} \text{ such that } S_i S_j = S_j S_i$$

Stabilizer code

Stabilizer group

$$\mathcal{S} = \langle S_1, S_2, \dots, S_r \rangle \subset \mathcal{P}_n \setminus \{-I\} \text{ such that } S_i S_j = S_j S_i$$

Stabilizer code

common +1 eigenspace of \mathcal{S}

$$\mathcal{C}(\mathcal{S}) = \{|\psi\rangle : S|\psi\rangle = \psi \forall S \in \mathcal{S}\}$$

Stabilizer code

Stabilizer group

$$\mathcal{S} = \langle S_1, S_2, \dots, S_r \rangle \subset \mathcal{P}_n \setminus \{-I\} \text{ such that } S_i S_j = S_j S_i$$

Stabilizer code

common +1 eigenspace of \mathcal{S}

$$\mathcal{C}(\mathcal{S}) = \{|\psi\rangle : S|\psi\rangle = \psi \forall S \in \mathcal{S}\}$$

Example

The five qubits code

$$\mathcal{S} = \langle XXZIZ, ZXXZI, IZXXZ, ZIZXX \rangle$$

Pauli measurement circuit

- Consider n -qubit independent commuting Pauli operators S_1, \dots, S_r .

Pauli measurement circuit

- Consider n -qubit independent commuting Pauli operators S_1, \dots, S_r .
- For $\mathbf{m} = (m_1, \dots, m_r) \in \mathbb{Z}_2^r$, denote $\Pi_{\mathbf{m}}$ the projector onto the common eigenspace of S_i with value $(-1)^{m_i}$.

Pauli measurement circuit

- ❖ Consider n -qubit independent commuting Pauli operators S_1, \dots, S_r .
- ❖ For $\mathbf{m} = (m_1, \dots, m_r) \in \mathbb{Z}_2^r$, denote $\Pi_{\mathbf{m}}$ the projector onto the common eigenspace of S_i with value $(-1)^{m_i}$.
- ❖ A Pauli measurement circuit maps a n -qubit state ρ to $\Pi_{\mathbf{m}}\rho\Pi_{\mathbf{m}}$ with probability $\text{Tr}(\Pi_{\mathbf{m}}\rho)$ and output \mathbf{m} .

Pauli measurement circuit

- ❖ Consider n -qubit independent commuting Pauli operators S_1, \dots, S_r .
- ❖ For $\mathbf{m} = (m_1, \dots, m_r) \in \mathbb{Z}_2^r$, denote $\Pi_{\mathbf{m}}$ the projector onto the common eigenspace of S_i with value $(-1)^{m_i}$.
- ❖ A Pauli measurement circuit maps a n -qubit state ρ to $\Pi_{\mathbf{m}}\rho\Pi_{\mathbf{m}}$ with probability $\text{Tr}(\Pi_{\mathbf{m}}\rho)$ and output \mathbf{m} .
- ❖ The circuit use $N = n + a$ qubits where a is the number of ancilla qubits.

Tanner graph

$$S = \{XXIII, ZXIZI, IIZZZ\}$$

Tanner graph

$$S = \{XXIII, ZXIZI, IIZZZ\}$$

$$T(S) = (V_Q \cup S, E)$$


$\{q_i, S_j\} \in E$ iff S_j acts
non-trivially on q_i

Tanner graph

$$S = \{XXIII, ZXIZI, I IYZZ\}$$

$$T(S) = (V_Q \cup S, E)$$

$\{q_i, S_j\} \in E$ iff S_j acts
non-trivially on q_i



Contracted Tanner graph

$$S = \{XXIII, ZXIZI, IIFYZZ\}$$

Contracted Tanner graph

$$S = \{XXIII, ZXIZI, I IYZZ\}$$


$$\begin{aligned}\bar{T}(S) &= (V_Q, \bar{E}) \\ \{q_i, q_j\} \in \bar{E} &\text{ iff } \exists S_k \text{ acts non-trivially on } q_i\end{aligned}$$

Contracted Tanner graph

$$S = \{XXIII, ZXIZI, I I YZZ\}$$

$$\bar{T}(S) = (V_Q, \bar{E})$$

$\{q_i, q_j\} \in \bar{E}$ iff $\exists S_k$ acts non-trivially on q_i



Quantum LDPC codes

A family of quantum LDPC codes $(Q_i)_i$ is a family of stabilizer codes such that the degree of the Tanner graph T_i are bounded by some constant independent of i .

Local-expansion

The Cheeger constant of a graph $G = (V, E)$ is defined as

$$h_\varepsilon(G) = \min_{\substack{L \subseteq V \\ |L| \leq \varepsilon |V|/2}} \frac{|\partial L|}{|L|}.$$

Local-expansion

The Cheeger constant of a graph $G = (V, E)$ is defined as

$$h_\varepsilon(G) = \min_{\substack{L \subseteq V \\ |L| \leq \varepsilon |V|/2}} \frac{|\partial L|}{|L|}.$$

A family of graphs $(G_i)_{i \in \mathbb{N}}$ is an (α, ε) -expander graph family if $h_\varepsilon(G_i) \geq \alpha$ for all i .

Local-expansion

The Cheeger constant of a graph $G = (V, E)$ is defined as

$$h_\varepsilon(G) = \min_{\substack{L \subseteq V \\ |L| \leq \varepsilon |V|/2}} \frac{|\partial L|}{|L|}.$$

A family of graphs $(G_i)_{i \in \mathbb{N}}$ is an (α, ε) -expander graph family if $h_\varepsilon(G_i) \geq \alpha$ for all i .

A family of quantum local-expander codes is a family of stabilizer codes with (α, ε) -expander contracted Tanner graphs.

Lemma

Let T be the Tanner graph of a stabilizer code with length n and with r stabilizer generators. Let \bar{T} be its contracted Tanner graph. Then, for all $\varepsilon \in [0, 1]$, we have

$$h_{\varepsilon'}(\bar{T}) \geq \frac{h_{\varepsilon}(T)}{\deg(T)}$$

where

$$\varepsilon' = \left(1 + \frac{r}{n}\right) \frac{\varepsilon}{1 + \deg(T)}.$$

➤ Show that

$$|\partial_{\bar{T}}L| \geq \frac{|\partial_T(L \cup N_T(L))|}{\deg(T)}.$$

➤ Show that

$$|\partial_T L| \geq \frac{|\partial_T(L \cup N_T(L))|}{\deg(T)}.$$

➤ If

$$|L \cup N_T(L)| \leq \varepsilon \frac{V(T)}{2},$$

then

$$|\partial_T(L \cup N_T(L))| \geq h_\varepsilon(T) |L \cup N_T(L)| \geq h_\varepsilon(T) |L|.$$

➤ Show that

$$|\partial_{\bar{T}} L| \geq \frac{|\partial_T(L \cup N_T(L))|}{\deg(T)}.$$

➤ If

$$|L \cup N_T(L)| \leq \varepsilon \frac{V(T)}{2},$$



then

$$|\partial_T(L \cup N_T(L))| \geq h_\varepsilon(T) |L \cup N_T(L)| \geq h_\varepsilon(T) |L|.$$

➤ Combine the two

$$\frac{|\partial_{\bar{T}} L|}{|L|} \geq \frac{h_\varepsilon(T)}{\deg(T)}.$$

$$|\partial_{\bar{T}} L| \deg(T) \geq |\partial_T(L \cup N_T(L))|$$



Review

- ❖ (Local) Clifford circuits
- ❖ Connectivity graphs
- ❖ Stabilizer codes and LDPC codes
- ❖ Pauli measurement circuits
- ❖ (Contracted) Tanner graphs
- ❖ Expander codes

Proof of the main theorem

Theorem

Let C be a Clifford circuit measuring commuting Pauli operators S_1, \dots, S_r . Then, for any subset of qubits L , we have

$$\text{depth}(C) \geq \frac{n_{\text{cut}}}{64|\partial L|}.$$

Corollary

For families of local-expander quantum LDPC codes of length n , a syndrome extraction circuit C implemented as a local Clifford circuit on a $\sqrt{N} \times \sqrt{N}$ grid of qubits satisfies

$$\text{depth}(C) \geq \Omega\left(\frac{n}{\sqrt{N}}\right).$$

Strategy

- Partition the circuit's qubits into two subsets L and R .

Strategy

- Partition the circuit's qubits into two subsets L and R .
- Lower bound the amount of correlation required between L and R to measure the Pauli operators.


Strategy

- Partition the circuit's qubits into two subsets L and R .
- Lower bound the amount of correlation required between L and R to measure the Pauli operators.
- Upper bound the amount of correlation introduced per operation.


Strategy

- Partition the circuit's qubits into two subsets L and R .
- Lower bound the amount of correlation required between L and R to measure the Pauli operators.
- Upper bound the amount of correlation introduced per operation.
- Combine both arguments to derive a lower bound for the depth of the circuit.

Measuring correlations




Measuring correlations



Mutual information

$$I(b_1; b_2) = 0$$

Measuring correlations




Mutual information

$$I(b_1; b_2) = 0$$

$$I(b'_1; b'_2) = 1$$


Measuring correlations




Mutual information

$$I(b'_1, b'_2, E_1; E_2) = 1$$

Measuring correlations



Measuring correlations



Classical operations can artificially boost mutual information.

Measuring correlations

- Build a circuit C' with the same action and similar depth as C by pushing all measurements and classical operations at the end.

Measuring correlations



- Build a circuit C' with the same action and similar depth as C by pushing all measurements and classical operations at the end.
- Consider the circuit $C' \circ E \circ C'$.

Measuring correlations

- ❖ Build a circuit C' with the same action and similar depth as C by pushing all measurements and classical operations at the end.
- ❖ Consider the circuit $C' \circ E \circ C'$.
- ❖ Compute the mutual information



$$I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}).$$

Circuit transformations





$$\text{depth}(C') \leq 4 \cdot \text{depth}(C) + 2$$

Circuit transformations





Circuit transformations







Both ancillas are the same node in the connectivity graph and in the same partition.






Circuit transformations




Circuit transformations




Circuit transformations



Circuit transformations




Circuit transformations



$$\text{depth}(U) \leq 4 \cdot \text{depth}(C)$$


Circuit transformations



$$\text{depth}(U) \leq 4 \cdot \text{depth}(C)$$

$$|\partial L| = |\partial L'|$$

The double measurement circuit



$$I(O_{\bar{L}}^{(2)}, E_{\bar{L}}; O_{\bar{R}}^{(2)}, E_{\bar{R}} | O^{(1)}) \text{ with } \bar{L} = L' \cup A_E$$

Bounds on the mutual information

Lower bound

For the double measurement circuit, we have

$$I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) \geq \frac{n_{\text{cut}}}{2}.$$

Bounds on the mutual information

Lower bound

For the double measurement circuit, we have

$$I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) \geq \frac{n_{\text{cut}}}{2}.$$

Upper bound

For the double measurement circuit, we have

$$I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) \leq 32|\partial L|\text{depth}(C).$$

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Note $M_{\bar{L}}^{(t)} = \{m_{i,\bar{L}}^{(t)} = \bigoplus_{o \in O_i^{(t)} \cap \bar{L}} o\}$ and similarly for $M_{\bar{R}}^{(t)}$.

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Note $M_L^{(t)} = \{m_{i,\bar{L}}^{(t)} = \bigoplus_{o \in O_i^{(t)} \cap \bar{L}} o\}$ and similarly for $M_{\bar{R}}^{(t)}$.

From the data processing inequality

$$I(O_L^{(2)}, E_{\bar{L}}; O_{\bar{R}}^{(2)}, E_{\bar{R}} | O^{(1)}) \geq I(M_L^{(2)}, E_{\bar{L}}; M_{\bar{R}}^{(2)}, E_{\bar{R}} | O^{(1)})$$

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Note $M_L^{(t)} = \{m_{i,L}^{(t)} = \bigoplus_{o \in O_i^{(t)} \cap \bar{L}} o\}$ and similarly for $M_R^{(t)}$.

From the data processing inequality

$$\begin{aligned} I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) &\geq I(M_L^{(2)}, E_L; M_R^{(2)}, E_R | O^{(1)}) \\ &= H(M_L^{(2)}, E_L | O^{(1)}) - H(M_L^{(2)}, E_L | M_R^{(2)}, E_R, O^{(1)}) \end{aligned}$$

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Note $M_L^{(t)} = \{m_{i,L}^{(t)} = \bigoplus_{o \in O_i^{(t)} \cap L} o\}$ and similarly for $M_R^{(t)}$.

From the data processing inequality

$$\begin{aligned} I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) &\geq I(M_L^{(2)}, E_L; M_R^{(2)}, E_R | O^{(1)}) \\ &= H(M_L^{(2)}, E_L | O^{(1)}) - H(M_L^{(2)}, E_L | M_R^{(2)}, E_R, O^{(1)}) \\ &= H(M_L^{(2)}, E_L, O^{(1)}) - H(O^{(1)}) - H(E_L) \end{aligned}$$

Proof of the lower bound

Note $m_i^{(t)} = \bigoplus_{o \in O_i^{(t)}} o$, the outcome for the measurement of S_i in circuit t .

Note $M_L^{(t)} = \{m_{i,L}^{(t)} = \bigoplus_{o \in O_i^{(t)} \cap L} o\}$ and similarly for $M_R^{(t)}$.

From the data processing inequality

$$\begin{aligned} I(O_L^{(2)}, E_L; O_R^{(2)}, E_R | O^{(1)}) &\geq I(M_L^{(2)}, E_L; M_R^{(2)}, E_R | O^{(1)}) \\ &= H(M_L^{(2)}, E_L | O^{(1)}) - H(M_L^{(2)}, E_L | M_R^{(2)}, E_R, O^{(1)}) \\ &= H(M_L^{(2)}, E_L, O^{(1)}) - H(O^{(1)}) - H(E_L) \\ &= H(M_L^{(2)} | E_L, O^{(1)}). \end{aligned}$$

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut}, \bar{L}}$ the operators $S_j \in S_{\text{cut}}$ for which m_j depends on at least one outcome in O_L .

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut}, \bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L}, \text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut}, \bar{L}}$.

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut}, \bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L}, \text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut}, \bar{L}}$.

From the data processing inequality

$$H(M_{\bar{L}}^{(2)} | E_{\bar{L}}, O^{(1)}) \geq H(M_{\bar{L}, \text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)})$$

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut}, \bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L}, \text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut}, \bar{L}}$.

From the data processing inequality

$$\begin{aligned} H(M_{\bar{L}}^{(2)} | E_{\bar{L}}, O^{(1)}) &\geq H(M_{\bar{L}, \text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}) \\ &\geq H(M_{\bar{L}, \text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \end{aligned}$$

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut},\bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L},\text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut},\bar{L}}$.

From the data processing inequality

$$\begin{aligned} H(M_{\bar{L}}^{(2)} | E_{\bar{L}}, O^{(1)}) &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}) \\ &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \\ &= H(m_i(E_{\bar{R}}) : S_i \in S_{\text{cut},\bar{L}} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \end{aligned}$$

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut},\bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L},\text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut},\bar{L}}$.

From the data processing inequality

$$\begin{aligned} H(M_{\bar{L}}^{(2)} | E_{\bar{L}}, O^{(1)}) &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}) \\ &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \\ &= H(m_i(E_{\bar{R}}) : S_i \in S_{\text{cut},\bar{L}} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \\ &= H(m_i(E_{\bar{R}}) : S_i \in S_{\text{cut},\bar{L}}) \end{aligned}$$

Proof of the lower bound

Note S_{cut} the operators with support on both L and R .

Note $S_{\text{cut},\bar{L}}$ the operators $S_i \in S_{\text{cut}}$ for which m_i depends on at least one outcome in O_L .

Note $M_{\bar{L},\text{cut}}^{(t)}$ the outcome of $M_{\bar{L}}^{(t)}$ corresponding to $S_{\text{cut},\bar{L}}$.

From the data processing inequality

$$\begin{aligned} H(M_{\bar{L}}^{(2)} | E_{\bar{L}}, O^{(1)}) &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}) \\ &\geq H(M_{\bar{L},\text{cut}}^{(2)} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \\ &= H(m_i(E_{\bar{R}}) : S_i \in S_{\text{cut},\bar{L}} | E_{\bar{L}}, O^{(1)}, M_{\bar{R}}^{(2)}) \\ &= H(m_i(E_{\bar{R}}) : S_i \in S_{\text{cut},\bar{L}}) \\ &= |S_{\text{cut},\bar{L}}|. \end{aligned}$$

Proof of the lower bound

By symmetry

$$I(O_{\bar{L}}^{(2)}, E_{\bar{L}}; O_{\bar{R}}^{(2)}, E_{\bar{R}} | O^{(1)}) \geq \max\{|S_{\text{cut}, \bar{L}}|, |S_{\text{cut}, \bar{R}}|\} \geq \frac{n_{\text{cut}}}{2}.$$