



Unified Messaging with OmniQueue

A Comprehensive Guide to Broker-Agnostic
Messaging Systems and Practical Implementations

Darius Max

Unified Messaging with OmniQueue

A Comprehensive Guide to Broker-Agnostic Messaging Systems and Practical Implementations

Darius Max

Table of Contents

Preface	1
Why This Book Exists	1
Who This Book Is For	1
What This Book Covers	2
Why OmniQueue?	2
A Note on Style	2
Reader Expectations	2
How This Book Is Organized	3
Our Promise	3
How to Use This Book	4
Reading Paths by Experience Tier	4
Part-by-Part Guide	4
Code Examples	4
Diagrams and Visuals	5
Cheat Sheets and War Stories	5
Cross-References	5
What You'll Need	5
Our Advice	6
1. Chapter 1: Introduction	7
1.1. The Role of Messaging in Modern Systems	7
1.2. Brokered vs. Brokerless Messaging	7
1.3. The Fragmentation Problem	7
1.4. Enter OmniQueue	8
1.5. A Simple Example	10
1.6. Who Uses OmniQueue?	11
1.7. What This Chapter Sets Up	11
2. Core Messaging Concepts	12
2.1. Messages, Queues, Topics, Streams	12
2.1.1. The Message Structure	12
2.1.2. Queues	12
2.1.3. Topics	13
2.1.4. Streams	13
2.1.5. Comparing Destinations	13
2.2. Brokers vs. Brokerless	15
2.2.1. What is a Broker?	15
2.2.2. Brokerless Messaging	16
2.2.3. Visual Comparison	16
2.3. Delivery Semantics	18

2.3.1. At-most-once	18
2.3.2. At-least-once	19
2.3.3. Exactly-once	19
2.3.4. OmniQueue Perspective	20
2.4. Reliability & Durability	22
2.4.1. Reliability	22
2.4.2. Durability	22
2.4.3. Durability in OmniQueue Context	23
2.5. Load Balancing & Consumer Groups	25
2.5.1. Consumer Groups	25
2.5.2. Consumer Group Dynamics	25
2.5.3. Load Balancing Patterns	27
2.6. Pub/Sub (Fanout) vs. Point-to-Point	27
2.6.1. Point-to-Point (P2P)	28
2.6.2. Publish/Subscribe (Fanout)	28
2.6.3. OmniQueue's Approach	30

Preface

Why This Book Exists

In the last decade, messaging systems have become the invisible backbone of modern software. From high-frequency trading platforms to e-commerce checkout flows, from IoT telemetry ingestion to social media fanout, **asynchronous message passing** underpins much of the world's critical software.

But there's a catch: the messaging landscape is **fragmented**. Each broker — RabbitMQ, Kafka, NATS, ActiveMQ, SQS, and so on — comes with its own API, terminology, quirks, and operational mindset. Switching from one broker to another can mean a complete rewrite of integration code, along with a steep re-learning curve for operations.

OmniQueue was born from a simple but ambitious idea:

“What if there was a single, unified API that could speak to any messaging system — brokered or brokerless — without sacrificing the power and unique features of each?”

— Founder's Notes

This book is the culmination of that idea.

It's **both** a deep dive into the theory and practice of messaging systems **and** the definitive guide to OmniQueue — a TypeScript-based, broker-agnostic messaging API.

Who This Book Is For

This book is written for engineers, architects, and operations teams who:

- Work with messaging systems regularly.
- Need to support multiple brokers across environments.
- Migrate between brokers due to scaling, cost, or vendor lock-in.
- Want to abstract messaging complexity without losing control.

We've structured the content so that:

- **Beginners (0–2 years)** gain a solid grounding in messaging fundamentals.
- **Intermediate practitioners (2–5 years)** learn deep operational patterns and broker-specific optimizations.
- **Senior engineers (5+ years)** explore high-scale, mission-critical messaging architecture and troubleshooting.
- **OmniQueue Mastery Mode** sections give you direct, in-depth knowledge to extend, tune, and contribute to the OmniQueue project.

What This Book Covers

We will explore:

- Core messaging concepts: queues, topics, routing, delivery semantics, and reliability.
- Detailed broker chapters for RabbitMQ, Kafka, NATS, JetStream, ActiveMQ, Artemis, ZeroMQ, BullMQ, AWS SQS/SNS, Azure Service Bus, and Apache Pulsar.
- OmniQueue’s architecture, design decisions, and implementation patterns.
- Mapping native broker concepts to OmniQueue’s unified API.
- Advanced OmniQueue usage: scaling, plugin development, observability, and disaster recovery.
- Real-world case studies, complete with war stories from production incidents.
- How to extend and contribute to OmniQueue.

Throughout the book, we’ll balance **conceptual clarity** with **practical hands-on examples**.

Why OmniQueue?

Traditional messaging integrations often fall into one of two traps:

1. **Tight coupling to a specific broker.** This limits future flexibility, creates vendor lock-in, and complicates migrations.
2. **Overly generic abstractions.** These hide broker-specific features, leading to lowest-common-denominator APIs.

OmniQueue aims to solve both problems:

- **Unified Core API** for sending, receiving, publishing, and subscribing.
- **Broker Adapters** that map directly to native features.
- **Optional Features** for advanced tuning, scaling, and recovery.
- **Plugin Architecture** for extending to new brokers or integrating custom logic.

A Note on Style

This book is written in the spirit of O’Reilly guides: technical, clear, and actionable — with just enough narrative to keep you awake during the heavy parts.

You’ll see **TypeScript code** for OmniQueue, **Mermaid diagrams** for system flows, and **cheat sheets** for quick reference.

Reader Expectations

- You don’t need to be a messaging expert — but some familiarity with distributed systems will help.
- You should be comfortable reading TypeScript and basic CLI commands.

- Expect real-world complexity: we'll talk about failures, quirks, and debugging nightmares.
- We'll show both the “happy path” and the “when it all goes wrong” path.

How This Book Is Organized

Part	Focus
I	Messaging fundamentals and OmniQueue core API.
II	Deep dives into individual brokers with OmniQueue mapping.
III	Advanced OmniQueue usage, scaling, and tuning.
IV	Real-world implementations and case studies.
V	Extending and contributing to OmniQueue.
Appendices	Quick references, glossary, and disaster checklists.

Our Promise

By the end of this book, you'll be able to:

- Understand the trade-offs between major messaging systems.
- Confidently implement broker-agnostic messaging in your projects.
- Operate and troubleshoot OmniQueue in production.
- Extend OmniQueue to support new brokers and patterns.

Messaging is not just about moving data. It's about shaping the **lifeblood** of your system — reliably, predictably, and with intent.

— From the Authors

How to Use This Book

This book is both a **reference** and a **journey**. You can read it cover-to-cover or jump directly to the sections that matter most to your work.

We've designed it with multiple entry points, so whether you are brand-new to messaging or a seasoned architect managing a multi-broker fleet, you'll find value.

Reading Paths by Experience Tier

We've tagged content for different levels of experience. If you identify your tier, you can follow the recommended path:

- **Beginner (0–2 years)** Start with Part I: **Messaging Fundamentals** (Chapters 1–3). These chapters introduce core concepts and get you hands-on with OmniQueue quickly. Then, read only the broker chapters (Part II) for the systems you'll use in your current work.
- **Intermediate (2–5 years)** You can skim Part I for a refresher, then dive deep into the broker chapters (Part II). Pay attention to **War Stories** and **Cheat Sheets** — they'll save you pain in production. Follow with Part III to learn scaling, monitoring, and advanced OmniQueue patterns.
- **Senior Engineer / Architect (5+ years)** Jump to the broker chapters you care about most, but don't skip Part III — it's packed with operational patterns for high-scale environments. Use Part IV's case studies for inspiration and validation of architectural decisions.
- **OmniQueue Mastery Mode** These sections are sprinkled throughout the book for readers who want to extend OmniQueue itself. You'll find them in both broker chapters and advanced sections.

Part-by-Part Guide

Part	How to Use It
I	Foundation for messaging concepts and OmniQueue basics. Best for new readers.
II	Broker-specific knowledge. Each chapter is standalone — read only what you need.
III	Advanced OmniQueue usage: scaling, observability, disaster recovery.
IV	Real-world case studies — learn from actual deployments and failures.
V	Contribution and extension — for those building on or contributing to OmniQueue.
Appendices	Quick-reference materials, glossary, and operational checklists.

Code Examples

All OmniQueue examples are in **TypeScript**. We assume you have basic familiarity with **npm**, **pnpm**,

or `yarn` and Node.js tooling.

Code listings are annotated with comments to explain **why** something is done, not just **how**. For example:

```
// Sending a message with OmniQueue
await omni.send({
  destination: 'orders',
  body: { id: '1234', status: 'confirmed' },
  group: 'order-processing', // Required for consumers
  ensure: true, // Create destination if it doesn't exist
});
```

Whenever we compare OmniQueue to a native broker API, we show them side-by-side for clarity.

Diagrams and Visuals

We use **Mermaid diagrams** for flows, topologies, and message lifecycles. These are rendered in the book, but if you're reading the raw AsciiDoc, you can copy the code into any Mermaid-compatible renderer to visualize it.

Cheat Sheets and War Stories

At the end of each broker chapter:

- **Cheat Sheet** — quick reference for commands, configs, metrics, and a **disaster checklist**.
- **War Stories** — short narratives of real-world incidents, failures, and their solutions.

Cross-References

Throughout the book, cross-references (e.g., “see <<_chapter_3>>”) help you connect concepts. We strongly encourage following them, especially when exploring advanced topics that build on earlier material.

What You'll Need

- **Node.js** 18+
- A package manager (`npm`, `pnpm`, or `yarn`)
- Docker (optional, but useful for running brokers locally)
- Basic terminal familiarity

You don't need to install every broker at once — we'll give setup instructions per chapter.

Our Advice

- **Don't just read — run the examples.** Messaging is best learned by sending and receiving real messages.
- **Experiment with failure.** Kill brokers, drop connections, overload queues — see how systems behave under stress.
- **Adapt patterns to your context.** There's no universal “right” way; use these patterns as starting points.

Chapter 1. Chapter 1: Introduction

1.1. The Role of Messaging in Modern Systems

Messaging is the circulatory system of distributed software.

Whether you are processing financial transactions, streaming telemetry from millions of IoT devices, or fanning out notifications to mobile users, **messages** are how your system communicates internally and externally.

Unlike synchronous HTTP calls, messaging systems decouple producers and consumers in **time** and **space**. This makes them a cornerstone of:

- **Scalability** — handle bursts by buffering messages in queues, logs, or streams.
- **Resilience** — retry failed deliveries without dropping data.
- **Loose coupling** — evolve services independently.
- **Asynchronous workflows** — free services from waiting on each other.

Modern architectures like **microservices**, **event-driven systems**, and **CQRS/ES** (Command Query Responsibility Segregation / Event Sourcing) rely heavily on messaging.

1.2. Brokered vs. Brokerless Messaging

Messaging systems come in two broad categories:

Type	Description	Examples
Brokered	Messages flow through a central server (the broker) that stores, routes, and delivers them.	RabbitMQ, Kafka, NATS JetStream, ActiveMQ Artemis, Azure Service Bus, Apache Pulsar
Brokerless	Producers send messages directly to consumers without an intermediary. Often implemented with peer-to-peer sockets.	ZeroMQ, nanomsg

Brokered systems offer durability, routing flexibility, and operational control. **Brokerless systems** excel in speed, simplicity, and deployment independence.

1.3. The Fragmentation Problem

Each broker ecosystem has its **own**:

- API shape and naming conventions
- Delivery semantics (at-most-once, at-least-once, exactly-once)
- Terminology: **queue** vs **topic**, **exchange** vs **stream**, **subject** vs **channel**

- Operational model and deployment pattern
- Performance characteristics and tuning knobs

Moving from RabbitMQ to Kafka isn't just a config change — it's often a **rewrite**. Even within the same organization, different teams may adopt different brokers for historical or domain-specific reasons.

This leads to:

- **Code duplication** — multiple code paths for different brokers.
- **Vendor lock-in** — hard to migrate away.
- **Operational complexity** — separate tooling, metrics, and expertise required.

1.4. Enter OmniQueue

OmniQueue addresses the fragmentation problem with a **unified, broker-agnostic API** centered on **publish/subscribe with mandatory consumer groups**.

Producers **publish** to a **topic**. Each **consumer group** subscribed to that topic receives a copy of every message; within a given group, only one consumer processes a given message.

Handlers acknowledge with `ack()` or `nack(requeue?: boolean)`.

```
Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3111:3111:0808/074022.326071:FATAL:content/browser/zygote_host/zygote_host_impl_linux.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074022.333121:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074022.333179:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x55af1c8023ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x55af20986504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7fb4b1c45330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7fb4b1c4527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7fb4b1c288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
#5 0x55af2097e535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
```

```

#6 0x55af20945a9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x55af20945a37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x55af1aa82ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x55af1b5c1a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x55af1ab68ef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x55af1ff43e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x55af1b4416b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x55af1b440d2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7fb4b1c2a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7fb4b1c2a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x55af1ce27b1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 000010b80013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
0000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007ffed86c8bc8
di: 0000000000000c27 si: 0000000000000c27 bp: 00007ffed86c8540 bx:
0000000000000c27
dx: 0000000000000006 ax: 0000000000000000 cx: 00007fb4b1c9eb2c sp:
00007ffed86c8500
ip: 00007fb4b1c9eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]

```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```

    at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
    at ChildProcess.emit (node:events:530:35)
    at ChildProcess._handle.onexit (node:internal/child_process:293:12)

```

flowchart LR

subgraph Producers

P1[Producer A] -->|publish| T[Topic: orders]

P2[Producer B] -->|publish| T

end

subgraph Consumers

G1[Group: order-service] -->|subscribe| T

```

    G2[Group: fraud-check] -->|subscribe| T
  end

  T -->|fanout copy| C11[Consumer 1 in order-service]
  T -->|fanout copy| C21[Consumer 1 in fraud-check]
  T -. work-sharing .-> C12[Consumer 2 in order-service]
  T -. work-sharing .-> C22[Consumer 2 in fraud-check]

```

With OmniQueue, your code can switch between brokers with minimal changes, while still leveraging advanced features through **broker adapters**.

1.5. A Simple Example

```

import { create } from '@omniqueue/core';
import '@omniqueue/rabbitmq'; // registers the "rabbitmq" adapter

// Create and init a broker instance
const broker = await create('rabbitmq', { url: 'amqp://localhost' });
await broker.init();

// Publisher: send one event to the topic "orders"
await broker.publish(
  'orders',
  {
    id: 'ulid-01JABCDEF...',
    body: { orderId: 'A123', status: 'confirmed' },
    headers: { 'x-source': 'checkout' },
  },
  {
    ensure: true, // lazily create the destination if missing
    // createOptions can pass through to the adapter (durable, partitions, etc.)
  }
);

// Subscriber: each GROUP receives a copy; work is shared inside the group.
await broker.subscribe(
  'orders',
  async (msg) => {
    try {
      console.log('Processing order', msg.body);
      await msg.ack();
    } catch (err) {
      await msg.nack(true); // requeue on error
    }
  },
  'order-service', // <-- mandatory groupId
  { ensure: true } // optional ConsumeOptions
);

```

```
// ...later, graceful shutdown  
await broker.close();
```

Switching to Kafka, NATS, Pulsar, or another supported broker means changing only the adapter import and connection config — your core logic stays the same.

1.6. Who Uses OmniQueue?

OmniQueue is designed for:

- **Polyglot microservice environments** — where different teams choose different brokers.
- **Hybrid cloud architectures** — where on-prem and cloud-native brokers must coexist.
- **Migration projects** — moving from one broker to another without downtime.
- **Prototyping and R&D** — quickly test message flows across multiple systems.

1.7. What This Chapter Sets Up

In the chapters ahead:

- **Chapter 2** will cover **Core Messaging Concepts** in detail — topics, routing, delivery guarantees, and reliability.
- **Chapter 3** will dissect **OmniQueue Architecture & Core API**, showing exactly how the abstraction is implemented with **publish/subscribe**.
- **Part II** will then dive deep into individual brokers.

The goal of this introduction is simple: Give you the “why” and the “what” before we explore the “how” and “when”.

Chapter 2. Core Messaging Concepts

2.1. Messages, Queues, Topics, Streams

At the heart of any messaging system is the **message**: a discrete unit of data that moves from producer to consumer.

2.1.1. The Message Structure

While brokers differ in terminology and features, most messages contain:

Field	Purpose
ID	Uniquely identifies the message. For durability and traceability, many teams use ULID or UUID v7. Some brokers provide their own sequence IDs (Kafka offset, Pulsar ledgerId/entryId, etc.).
Body	The actual payload. Often JSON for ease of debugging, but formats like Avro or Protobuf are preferred in high-performance or schema-validated environments.
Headers / Attributes	Metadata about the message (e.g., content-type , source service, trace IDs for distributed tracing, tenant identifiers). These can influence routing (e.g., header-based exchange in RabbitMQ) or serve for observability.



In OmniQueue, **body** is always JSON-serialisable to ensure adapter compatibility, but you can base64-encode binary payloads if needed.

2.1.2. Queues

A **queue** is a named, ordered collection of messages that delivers each message to exactly one consumer within a given group. When a message is acknowledged (**ack()**), it is removed from the queue (or marked processed).

Key characteristics:

- **FIFO order** by default, though some brokers allow priority or sharded ordering.
- **Work sharing** — multiple consumers in the same group share the load.
- **Backpressure** — unacknowledged messages accumulate in the queue.

Real-world usage:

- Task processing (image rendering, report generation).
- Decoupling request spikes from downstream processing.
- Buffering workloads when downstream systems are slow.

2.1.3. Topics

A **topic** is a named channel to which producers publish and consumers subscribe.

Key characteristics:

- **Fanout delivery** — every consumer group subscribed to a topic gets a full copy of the message stream.
- **Group semantics** — within a single group, messages are load-balanced to one consumer at a time.
- **Loose coupling** — producers don't need to know who consumes their messages.

Real-world usage:

- Event broadcasting (order events, user activity streams).
- Multi-service pipelines (analytics, fraud detection, notifications).
- Event sourcing feeds.

2.1.4. Streams

A **stream** is an append-only, immutable sequence of messages stored in durable storage. Consumers track their own **offset** (position) and can replay older messages at will.

Key characteristics:

- **Messages persist** for a retention period (e.g., 7 days) or indefinitely.
- **Multiple independent consumers** — each with their own offsets.
- **High throughput** by avoiding message deletion.

Real-world usage:

- Audit logging with replay.
- Rebuilding projections in CQRS systems.
- Time-series analytics pipelines.

2.1.5. Comparing Destinations

Type	Delivery Model	Storage & Retention	Replay Support
Queue	Point-to-point within a group	Message removed after ack	No
Topic	Publish/subscribe, fanout to groups	Broker-controlled, may persist temporarily	Sometimes (depends on broker)
Stream	Publish/subscribe with offset tracking	Long-term retention in log	Yes

```

Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3143:3143:0808/074022.824197:FATAL:content/browser/zygote_host/zygote_host_impl_linux.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074022.831203:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074022.831237:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x555c8b95c3ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x555c8fae0504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7f7afd645330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7f7afd64527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7f7afd6288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
#5 0x555c8fad8535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x555c8fa9fa9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x555c8fa9fa37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x555c89bdcee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x555c8a71ba49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x555c89cc2ef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x555c8f09de64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x555c8a59b6b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x555c8a59ad2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7f7afd62a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7f7afd62a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x555c8bf81b1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 000019a00013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
0000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007ffd04651f18

```

```
di: 00000000000000c47 si: 00000000000000c47 bp: 00007ffd04651890 bx:
00000000000000c47
dx: 0000000000000006 ax: 0000000000000000 cx: 00007f7afd69eb2c sp:
00007ffd04651850
ip: 00007f7afd69eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]
```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```
at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
at ChildProcess.emit (node:events:530:35)
at ChildProcess._handle.onexit (node:internal/child_process:293:12)
```

flowchart LR

```
subgraph Producer
  P[Producer] --> Q
end
```

```
subgraph Destinations
  Q[Queue]
  T[Topic]
  S[Stream]
end
```

```
Q -->|One message to one consumer| C1[Consumer]
T -->|Copy to each group| G1[Group A]
T -->|Copy to each group| G2[Group B]
S -->|Consumers pull by offset| C2[Consumer Offset 120]
```

2.2. Brokers vs. Brokerless

2.2.1. What is a Broker?

A **broker** is a dedicated server (or cluster) that:

- Accepts messages from producers via network protocols (AMQP, Kafka protocol, MQTT, HTTP).
- Routes them based on metadata (exchange bindings, partition keys, headers).
- Stores them (in memory, disk, or distributed logs) for durability and later delivery.
- Delivers them to consumers, tracking acknowledgements.

Examples: RabbitMQ, Kafka, NATS JetStream, ActiveMQ Artemis, Azure Service Bus, Apache Pulsar.

Advantages:

- **Durability** — messages survive restarts or crashes.
- **Routing flexibility** — fanout, topic filters, header matching, partitioning.
- **Operational visibility** — metrics, queues, consumer lag.
- **Security controls** — authentication, authorization, encryption.

Challenges:

- Operational cost — needs monitoring, scaling, patching.
- Latency vs. durability trade-offs — fsyncs, replication.
- Complexity — tuning partitions, queues, consumers.

2.2.2. Brokerless Messaging

In **brokerless** systems, producers send messages directly to consumers without an intermediary server. Typically, these use **peer-to-peer sockets** or multicast protocols.

Example: ZeroMQ's PUB/SUB, PUSH/PULL patterns.

Advantages:

- **Ultra-low latency** — no queue persistence or broker hop.
- **No single point of failure** — as long as consumers are reachable.
- **Lightweight deployment** — often just a library in your app.

Challenges:

- No inherent durability — offline consumers miss messages.
- No centralized management — must handle discovery, retries, ordering yourself.
- Difficult scaling for complex topologies.

2.2.3. Visual Comparison

```
Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3175:3175:0808/074023.360518:FATAL:content/browser/zygote_host/zygote_host_impl_linux
.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074023.367567:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
```

```

[0808/074023.367602:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x55939ca413ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x5593a0bc5504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7fab97a45330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7fab97a4527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7fab97a288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
#5 0x5593a0bbd535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x5593a0b84a9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x5593a0b84a37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x55939acc1ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x55939b800a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x55939ada7ef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x5593a0182e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x55939b6806b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x55939b67fd2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7fab97a2a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7fab97a2a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x55939d066b1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 000034500013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
0000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007ffe8bd98dc8
di: 0000000000000c67 si: 0000000000000c67 bp: 00007ffe8bd98740 bx:
0000000000000c67
dx: 0000000000000006 ax: 0000000000000000 cx: 00007fab97a9eb2c sp:
00007ffe8bd98700
ip: 00007fab97a9eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]

```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-

```
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
  at ChildProcess.emit (node:events:530:35)
  at ChildProcess._handle.onexit (node:internal/child_process:293:12)
```

flowchart TB

subgraph Brokered

P1 --> B[Broker Cluster]

P2 --> B

B --> C1

B --> C2

end

subgraph Brokerless

P3 --> C3

P3 --> C4

end

Brokered systems shine in reliability and complexity management. **Brokerless systems** shine in simplicity and speed — but require discipline in application design.



OmniQueue supports **both** worlds. A [@omniqueue/zeromq](#) adapter can connect directly between processes without a broker, while [@omniqueue/kafka](#), [@omniqueue/rabbitmq](#), and others leverage durable, clustered brokers.

2.3. Delivery Semantics

Delivery semantics define **how many times** a message is delivered to a consumer, and under what guarantees. They are a cornerstone of messaging design — the choice affects performance, complexity, and data correctness.

2.3.1. At-most-once

Definition:

A message is delivered **zero or one time**, but never more than once. If the delivery fails, the message is lost — no retries.

How it happens:

1. The broker (or producer in brokerless systems) sends the message without waiting for acknowledgement.
2. No redelivery is attempted if the consumer fails mid-processing.

Pros:

- Lowest latency — no ack/nack overhead.
- Simplest implementation.

Cons:

- Data loss possible under failures.
- Not suitable for critical workflows.

Real-world usage:

- Non-critical telemetry where occasional loss is acceptable (e.g., live UI metrics).
- High-frequency, low-value sensor data.

2.3.2. At-least-once

Definition:

A message is delivered **one or more times** until it is acknowledged. Duplicates may occur.

How it happens:

1. The broker stores the message until it gets an explicit ack from the consumer.
2. If ack is not received within a timeout or connection drops, the broker redelivers.

Pros:

- No message loss under normal broker persistence guarantees.
- The default for most brokers (RabbitMQ, SQS, NATS JetStream).

Cons:

- Requires **idempotent** consumers — they must handle duplicates gracefully.
- Potential extra load from duplicate processing.

Real-world usage:

- Payment processing (with idempotency keys).
- Order event processing.
- Logging pipelines.

2.3.3. Exactly-once

Definition:

A message is delivered **exactly one time** — no duplicates, no losses.

How it happens:

1. Requires transactional coordination between producer, broker, and consumer.
2. The broker and consumer commit offsets/state atomically.

Pros:

- Simplest for consumers — no deduplication logic.

Cons:

- High complexity, often broker-specific.
- Lower throughput due to transactional overhead.
- Often misunderstood — "exactly-once" guarantees are fragile in distributed systems.

Real-world usage:

- Financial transaction settlement (Kafka + idempotent producers + transactions).
- Highly sensitive event processing.

2.3.4. OmniQueue Perspective

OmniQueue does not enforce a delivery semantic by itself — it passes through the broker's native behavior. However:

- At-least-once is the most common.
- You can achieve effectively-once delivery by combining at-least-once brokers with idempotent consumer logic.
- Broker adapters may expose native exactly-once features (e.g., Kafka transactions) via `createOptions` or broker-specific APIs.

```
Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3207:3207:0808/074023.881008:FATAL:content/browser/zygote_host/zygote_host_impl_linux.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074023.888032:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074023.888067:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x560297c473ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x56029bdc504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7fe33c045330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7fe33c04527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7fe33c0288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
```

```

#5 0x56029bdc3535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x56029bd8aa9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x56029bd8aa37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x560295ec7ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x560296a06a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x560295fadef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x56029b388e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x5602968866b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x560296885d2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7fe33c02a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7fe33c02a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x56029826cb1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 000011c00013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
00000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007fffb42eff18
di: 0000000000000c87 si: 0000000000000c87 bp: 00007fffb42ef890 bx:
0000000000000c87
dx: 0000000000000006 ax: 0000000000000000 cx: 00007fe33c09eb2c sp:
00007fffb42ef850
ip: 00007fe33c09eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]

```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```

    at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
    at ChildProcess.emit (node:events:530:35)
    at ChildProcess._handle.onexit (node:internal/child_process:293:12)

```

sequenceDiagram

```

    participant P as Producer
    participant B as Broker
    participant C as Consumer

```

Note over P,C: At-most-once

```
P->>B: Send message
B-->>C: Deliver message
C <-->> B: No ack required
Note over B: If delivery fails → lost
```

```
Note over P,C: At-least-once
P->>B: Send message
B-->>C: Deliver message
C-->>B: Ack message
Note over B: No ack? Redeliver
```

```
Note over P,C: Exactly-once
P->>B: Send message (transaction)
B-->>C: Deliver message
C-->>B: Ack + commit atomically
```

2.4. Reliability & Durability

2.4.1. Reliability

Reliability is the ability of a messaging system to deliver messages as promised, even under faults. It depends on:

- **Acknowledgements** — explicit `ack()`/`nack()` calls.
- **Retries** — redelivery on failure.
- **Consumer groups** — work sharing without loss.
- **Dead-letter queues (DLQ)** — holding unprocessable messages for inspection.

Operational tips:

- Set sensible retry limits — infinite retries can overload systems.
- Use DLQs to capture poison messages (malformed or consistently failing).
- Monitor consumer lag — large lag indicates bottlenecks.

2.4.2. Durability

Durability ensures messages survive broker or system restarts. This requires **persistent storage** at the broker level.

Common strategies:

- **Disk persistence** — messages are written to disk (RabbitMQ durable queues, Kafka logs).
- **Replication** — messages are stored on multiple nodes (Kafka ISR, Pulsar BookKeeper).
- **Acknowledgement after fsync** — broker only acks after writing to stable storage.

Trade-offs:

- Durability often increases latency.
- Replication adds network cost but prevents data loss from node failure.

2.4.3. Durability in OmniQueue Context

OmniQueue's durability depends entirely on the broker adapter in use:

- **RabbitMQ Adapter** — durable queues + persistent messages.
- **Kafka Adapter** — log-based storage with configurable replication factor.
- **NATS JetStream Adapter** — file or memory storage with optional replication.
- **ZeroMQ Adapter** — no built-in durability (application must handle persistence).

You can influence durability in OmniQueue via `createOptions` when calling `publish()` or `subscribe()`, passing through broker-specific flags.

Example:

```
await broker.publish(
  'orders',
  { id: '1', body: {...}, headers: {} },
  { ensure: true, createOptions: { durable: true, replicationFactor: 3 } }
);
```

```
Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3239:3239:0808/074024.372607:FATAL:content/browser/zygote_host/zygote_host_impl_linux.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074024.379580:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074024.379616:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x564b112e83ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x564b1546c504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7ff7a5245330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7ff7a524527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7ff7a52288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
```

```

#5 0x564b15464535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x564b1542ba9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x564b1542ba37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x564b0f568ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x564b100a7a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x564b0f64eef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x564b14a29e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x564b0ff276b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x564b0ff26d2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7ff7a522a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7ff7a522a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x564b1190db1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 000002d00013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
00000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007ffd1653fea8
di: 0000000000000ca7 si: 0000000000000ca7 bp: 00007ffd1653f820 bx:
0000000000000ca7
dx: 0000000000000006 ax: 0000000000000000 cx: 00007ff7a529eb2c sp:
00007ffd1653f7e0
ip: 00007ff7a529eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]

```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```

    at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
    at ChildProcess.emit (node:events:530:35)
    at ChildProcess._handle.onexit (node:internal/child_process:293:12)

```

flowchart LR

```

P[Producer] -->|publish| B[Broker Storage]
B -->|write| D1[Disk: Log Segment]
B -->|replicate| N1[Replica Node A]
B -->|replicate| N2[Replica Node B]
D1 -->|ack| B

```

```
B -->|ack| P
B -->|deliver| C[Consumer]
```



If you don't configure durability in the broker, OmniQueue can't “make it durable” — always set it explicitly in `createOptions` when the workload demands it.

2.5. Load Balancing & Consumer Groups

In messaging systems, **load balancing** is about distributing work evenly among multiple consumers to improve throughput and avoid overloading any single consumer.

2.5.1. Consumer Groups

A **consumer group** is a named set of consumers that share the work of processing messages from a topic or queue.

Key characteristics:

- **Work-sharing:** Each message is processed by exactly **one** consumer in the group.
- **Isolation between groups:** Multiple groups can subscribe to the same topic, each getting its **own full copy** of the messages.
- **Scaling:** Adding more consumers to a group increases parallelism; removing consumers reduces throughput but not reliability.

OmniQueue enforces **mandatory consumer groups** — every `subscribe()` call must specify a `groupId`. This makes semantics explicit and avoids accidental fanout to unintended consumers.

Example with OmniQueue:

```
await broker.subscribe(
  'orders',
  async (msg) => {
    console.log(`[Worker] Processing order ${msg.body.id}`);
    await msg.ack();
  },
  'order-service',      // groupId
  { ensure: true }
);
```

2.5.2. Consumer Group Dynamics

- If a consumer in a group fails mid-processing: The broker reassigns its unacknowledged messages to other consumers in the same group.
- If more consumers join the group: The broker redistributes partitions or message streams to balance the load.


```

Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3271:3271:0808/074024.870117:FATAL:content/browser/zygote_host/zygote_host_impl_linux.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074024.877174:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074024.877207:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x55c8e7ec73ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x55c8ec04b504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7f5c44c45330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7f5c44c4527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7f5c44c288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
#5 0x55c8ec043535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x55c8ec00aa9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x55c8ec00aa37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x55c8e6147ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x55c8e6c86a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x55c8e622def6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x55c8eb608e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x55c8e6b066b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x55c8e6b05d2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7f5c44c2a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7f5c44c2a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x55c8e84ecb1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 00000b300013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
0000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007fff69b5c348

```

```
di: 000000000000cc7 si: 000000000000cc7 bp: 00007fff69b5bcc0 bx:
000000000000cc7
dx: 000000000000006 ax: 0000000000000000 cx: 00007f5c44c9eb2c sp:
00007fff69b5bc80
ip: 00007f5c44c9eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]
```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```
at ChildProcess.onClose (file:///home/runner/.npm-
global/lib/node_modules/@mermaid-js/mermaid-
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)
at ChildProcess.emit (node:events:530:35)
at ChildProcess._handle.onexit (node:internal/child_process:293:12)
```

flowchart LR

```
T[Topic: orders] -->|copy| G1[Group: order-service]
G1 -->|split work| C1[Consumer 1]
G1 -->|split work| C2[Consumer 2]
```

```
T -->|copy| G2[Group: fraud-check]
G2 -->|split work| C3[Consumer 3]
G2 -->|split work| C4[Consumer 4]
```

2.5.3. Load Balancing Patterns

1. **Static partition assignment** (Kafka, Pulsar): Each consumer gets a fixed set of partitions.
2. **Dynamic work stealing** (RabbitMQ, NATS JetStream): Consumers pull messages as they become available.
3. **Broker push with credit flow control**: Broker pushes messages but limits in-flight count per consumer.

Operational considerations:

- Monitor **consumer lag** per group.
- Keep consumer processing times balanced — slow consumers can cause uneven workloads.
- In idempotent systems, you can temporarily run the same consumer logic in multiple groups for migration or testing.

2.6. Pub/Sub (Fanout) vs. Point-to-Point

2.6.1. Point-to-Point (P2P)

In **point-to-point** messaging:

- A message is sent to a **queue**.
- Exactly one consumer within the target group processes it.
- Once acknowledged, the message is removed.

Pros:

- Ensures work is processed only once per group.
- Easy to reason about load balancing.

Cons:

- No automatic duplication to other consumers outside the group.

Real-world usage:

- Task queues (image processing jobs).
- Distributed workers for batch workloads.

2.6.2. Publish/Subscribe (Fanout)

In **publish/subscribe** messaging:

- Producers send to a **topic**.
- Each subscribed group gets a **full copy** of each message.
- Inside each group, messages are load-balanced.

Pros:

- Multiple services can independently react to the same event stream.
- Decouples event producers from consumers.

Cons:

- More storage and network usage if many groups subscribe.
- Need to manage schema and compatibility carefully.

```
Failed to generate image: mmdc failed:
Error: Failed to launch the browser process!
[3303:3303:0808/074025.369770:FATAL:content/browser/zygote_host/zygote_host_impl_linux
.cc:132] No usable sandbox! If you are running on Ubuntu 23.10+ or another Linux
distro that has disabled unprivileged user namespaces with AppArmor, see
https://chromium.googlesource.com/chromium/src/+main/docs/security/apparmor-usersn-
restrictions.md. Otherwise see
https://chromium.googlesource.com/chromium/src/+main/docs/linux/suid_sandbox_developm
```

```

ent.md for more information on developing with the (older) SUID sandbox. If you want
to live dangerously and need an immediate workaround, you can try using --no-sandbox.
[0808/074025.376730:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_cur_freq: No such file or
directory (2)
[0808/074025.376765:ERROR:third_party/crashpad/crashpad/util/file/file_io_posix.cc:145
] open /sys/devices/system/cpu/cpu0/cpufreq/scaling_max_freq: No such file or
directory (2)
Received signal 6
#0 0x55d3bf5833ba (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x6ad83b9)
#1 0x55d3c3707504 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac5c503)
#2 0x7f8e3ec45330 (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4532f)
#3 0x7f8e3ec4527e (/usr/lib/x86_64-linux-gnu/libc.so.6+0x4527d)
#4 0x7f8e3ec288ff (/usr/lib/x86_64-linux-gnu/libc.so.6+0x288fe)
#5 0x55d3c36ff535 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac54534)
#6 0x55d3c36c6a9d (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba9c)
#7 0x55d3c36c6a37 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xac1ba36)
#8 0x55d3bd803ee5 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4d58ee4)
#9 0x55d3be342a49 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5897a48)
#10 0x55d3bd8e9ef6 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x4e3eef5)
#11 0x55d3c2cc4e64 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0xa219e63)
#12 0x55d3be1c26b4 (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x57176b3)
#13 0x55d3be1c1d2f (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x5716d2e)
#14 0x7f8e3ec2a1ca (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a1c9)
#15 0x7f8e3ec2a28b (/usr/lib/x86_64-linux-gnu/libc.so.6+0x2a28a)
#16 0x55d3bfba8b1a (/opt/hostedtoolcache/setup-
chrome/chrome/stable/x64/chrome+0x70fdb19)
r8: 00001f300013c263 r9: 0000000000000001 r10: 0000000000000008 r11:
0000000000000246
r12: 0000000000000006 r13: 0000000000000264 r14: 0000000000000016 r15:
00007fffdc26d368
di: 0000000000000ce7 si: 0000000000000ce7 bp: 00007fffdc26cce0 bx:
0000000000000ce7
dx: 0000000000000006 ax: 0000000000000000 cx: 00007f8e3ec9eb2c sp:
00007fffdc26cca0
ip: 00007f8e3ec9eb2c efl: 0000000000000246 cgf: 002b000000000033 erf:
0000000000000000
trp: 0000000000000000 msk: 0000000000000000 cr2: 0000000000000000
[end of stack trace]

```

TROUBLESHOOTING: <https://pptr.dev/troubleshooting>

```
    at ChildProcess.onClose (file:///home/runner/.npm-  
global/lib/node_modules/@mermaid-js/mermaid-  
cli/node_modules/@puppeteer/browsers/lib/esm/launch.js:303:24)  
    at ChildProcess.emit (node:events:530:35)  
    at ChildProcess._handle.onexit (node:internal/child_process:293:12)
```

```
flowchart TB  
subgraph Point-to-Point  
P1[Producer] --> Q1[Queue]  
Q1 -->|one message to one consumer in group| C1[Consumer]  
Q1 -. ->|different message| C2[Consumer]  
end  
subgraph Publish/Subscribe  
P2[Producer] --> T[Topic]  
T -->|full copy| G1[Group A]  
T -->|full copy| G2[Group B]  
G1 -->|split work| C3[Consumer]  
G1 -->|split work| C4[Consumer]  
G2 -->|split work| C5[Consumer]  
end
```

2.6.3. OmniQueue's Approach

OmniQueue **always** uses publish/subscribe semantics at the API level:

- `publish(topic, message, opts?)` — send to a topic.
- `subscribe(topic, handler, groupId, opts)` — join a group to consume messages.

This allows:

- **Point-to-point** — by having only one group for a topic.
- **Fanout** — by having multiple groups subscribed to the same topic.

This design unifies the two models, and the behavior depends on how you name and organize your groups.

Example:

```
// Point-to-point: single group  
await broker.subscribe('orders', handler, 'order-service', { ensure: true });  
  
// Fanout: multiple groups get all events  
await broker.subscribe('orders', handler1, 'fraud-check', { ensure: true });  
await broker.subscribe('orders', handler2, 'analytics', { ensure: true });
```