Communication Complexity

Jake Kinsella and Max von Hippel

Northeastern University

April 9, 2021

If Alice knows x, and Bob knows y, how many bits of information must they communicate, in order for both Alice and Bob to know $f(x, y)$?

(Max)

Consider a two-party communication problem, in which the participants

(a) Alice

and

(b) Bob

participate to compute a function:

$$f : \underbrace{\mathbb{B}^n}_{\text{Alice's input}} \times \underbrace{\mathbb{B}^n}_{\text{Bob's input}} \rightarrow \underbrace{\mathbb{B}}_{\text{global output}}$$

(Max)

The players can come up with a *protocol* $\Pi = (p_1, \ldots, p_t)$, namely, for some natural $t \in \mathbb{N}$, a sequence of t-many functions $p_i : \mathbb{B}^* \to \mathbb{B}^*$ such that the communication between the players looks like this ...

(Max)

Alice is given input x.

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\texttt{p1}$.

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\mathtt{p1}$.

Bob is given input y.

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\texttt{p1}$.

Bob is given input y.

Thanks Alice. I can't reveal y, but $p_2(y, \texttt{p1})$ is $\texttt{p2}$.

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\mathtt{p1}$.

Bob is given input y.

Thanks Alice. I can't reveal y, but $p_2(y, \mathtt{p1})$ is $\mathtt{p2}$.

... yada yada yada ...

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\texttt{p1}$.

Bob is given input y.

Thanks Alice. I can't reveal y, but $p_2(y, \texttt{p1})$ is $\texttt{p2}$.

... yada yada yada ...

Pleasure doing business with you Bob. My final clue for you is that $p_{n-1}(x, \texttt{p1}, \ldots, \texttt{pn-2})$ is $\texttt{pn-1}$.

(Max)

Alice is given input x.

Hello Bob. I can't reveal x, but $p_1(x)$ is $\texttt{p1}$.

Bob is given input y.

Thanks Alice. I can't reveal y, but $p_2(y, \texttt{p1})$ is $\texttt{p2}$.

... yada yada yada ...

Pleasure doing business with you Bob. My final clue for you is that $p_{n-1}(x, \texttt{p1}, \ldots, \texttt{pn-2})$ is $\texttt{pn-1}$.

Rad. Then $p_n(y, \texttt{p1}, \ldots, \texttt{pn-1})$ is $\texttt{pn}$. TTFN!

(Max)

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

(Max)

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

Definition (Communication Complexity)

Suppose Π is a protocol for f in which at most t bits are communicated between Alice and Bob. Then the *communication complexity* of Π, denoted $C(\Pi)$, is t.

(Max)

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

Definition (Communication Complexity)

Suppose Π is a protocol for f in which at most t bits are communicated between Alice and Bob. Then the *communication complexity* of Π, denoted $C(\Pi)$, is t.

Definition ($C(f)$)

The communication complexity of f, denoted $C(f)$, is the minimum communication complexity achieved by any protocol for f.

Examples (Jake)

TODO

Methods

TODO

Fooling Set Method (Jake)

TODO

Tiling Method (Max)

TODO

2-Party Discrepency Method (Max)

TODO

Multi-Party Generalization (Jake)

TODO

Methods

TODO

Multi-Party Discrepency Method (Max)

TODO

Non-Deterministic (Jake)

TODO

Randomized (Max)

TODO