

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Communication Complexity

Jake Kinsella and Max von Hippel

Northeastern University

April 9, 2021

Communication Complexity

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If Alice knows x , and Bob knows y , how many bits of information must they communicate, in order for both Alice and Bob to know $f(x, y)$?

1 Introduction

■ Examples

2 Methods

■ 2-Party Problem

■ Fooling Set Method

■ Tiling Method

■ Discrepancy Method

■ Multi-Party Problem

■ Multi-Party Discrepancy Method

3 Other Variants

■ Non-Deterministic

■ Randomized

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Consider a two-party communication problem, in which the participants



(a) Alice

and



(b) Bob

participate to compute a function:

$$f : \underbrace{\mathbb{B}^n}_{\text{Alice's input}} \times \underbrace{\mathbb{B}^n}_{\text{Bob's input}} \rightarrow \underbrace{\mathbb{B}}_{\text{global output}}$$

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

The players can come up with a *protocol* $\Pi = (p_1, \dots, p_t)$, namely, for some natural $t \in \mathbb{N}$, a sequence of t -many functions $p_i : \mathbb{B}^* \rightarrow \mathbb{B}^*$ such that the communication between the players looks like this ...

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is $p1$.

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is p_1 .

Bob is given input y .

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is p_1 .

Bob is given input y .

Thanks Alice. I can't reveal y , but $p_2(y, p_1)$ is p_2 .

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is p_1 .

Bob is given input y .

Thanks Alice. I can't reveal y , but $p_2(y, p_1)$ is p_2 .

... yada yada yada ...

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is p_1 .

Bob is given input y .

Thanks Alice. I can't reveal y , but $p_2(y, p_1)$ is p_2 .

... yada yada yada ...

Pleasure doing business with you Bob. My final clue for you is that $p_{n-1}(x, p_1, \dots, p_{n-2})$ is p_{n-1} .

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Alice is given input x .

Hello Bob. I can't reveal x , but $p_1(x)$ is p_1 .

Bob is given input y .

Thanks Alice. I can't reveal y , but $p_2(y, p_1)$ is p_2 .

... yada yada yada ...

Pleasure doing business with you Bob. My final clue for you is that $p_{n-1}(x, p_1, \dots, p_{n-2})$ is p_{n-1} .

Rad. Then $p_n(y, p_1, \dots, p_{n-1})$ is p_n . TTFN!

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

Definition (Communication Complexity)

Suppose Π is a protocol for f in which at most t bits are communicated between Alice and Bob. Then the *communication complexity* of Π , denoted $C(\Pi)$, is t .

(Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

- The functions p_i can be *anything* so long as they are well-defined. E.g., could solve the Halting Problem.
- After the final message, *both parties* must know $f(x, y)$.

Definition (Communication Complexity)

Suppose Π is a protocol for f in which at most t bits are communicated between Alice and Bob. Then the *communication complexity* of Π , denoted $C(\Pi)$, is t .

Definition ($C(f)$)

The communication complexity of f , denoted $C(f)$, is the minimum communication complexity achieved by any protocol for f .

Parity (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (Are the number of 1s in xy even (0), or odd (1)?)

$f : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $(x, y) \mapsto \bigoplus xy$.

Parity (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (Are the number of 1s in xy even (0), or odd (1)?)

$f : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $(x, y) \mapsto \bigoplus xy$.

Example protocol Π :

$$P1 = \text{parity}(x).$$

Parity (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (Are the number of 1s in xy even (0), or odd (1)?)

$f : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $(x, y) \mapsto \bigoplus xy$.

Example protocol Π :

$$P1 = \text{parity}(x).$$

$$P2 = \text{parity}(y) \oplus P1$$

Parity (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (Are the number of 1s in xy even (0), or odd (1)?)

$f : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $(x, y) \mapsto \bigoplus xy$.

Example protocol Π :

$$P1 = \text{parity}(x).$$

$$P2 = \text{parity}(y) \oplus P1$$

Now both Alice and Bob know $f(x, y) = P2$. $C(f) \leq 2$ because $C(\Pi) = 2$ and Π implements f . But $C(f) \geq 2$ because f depends on x and y . Hence $C(f) = 2$.

Halting (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (A_{TM})

$H : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $\langle M, x \rangle \mapsto 1$ if M halts on x else 0.

Halting (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (A_{TM})

$H : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $\langle M, x \rangle \mapsto 1$ if M halts on x else 0.

Example protocol Π :

$P1 = y.$

Halting (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (A_{TM})

$H : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $\langle M, x \rangle \mapsto 1$ if M halts on x else 0.

Example protocol Π :

$P1 = y.$

$P2 = (M \text{ does/doesn't accept } y).$

Halting (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

Example (A_{TM})

$H : \mathbb{B}^n \times \mathbb{B}^n \rightarrow \mathbb{B}$ is precisely $\langle M, x \rangle \mapsto 1$ if M halts on x else 0.

Example protocol Π :

$P1 = y.$

$P2 = (M \text{ does/doesn't accept } y).$

Both players have unlimited computation power. We are only interest in communication complexity.

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.
What if we don't know any protocol Π ?

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.
What if we don't know any protocol Π ?

- Could we upper-bound $C(f)$ without knowing Π ?

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.
What if we don't know any protocol Π ?

- Could we upper-bound $C(f)$ without knowing Π ?

What if the only protocols we find seem really lousy?

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.
What if we don't know any protocol Π ?

- Could we upper-bound $C(f)$ without knowing Π ?

What if the only protocols we find seem really lousy?

- Could we lower-bound $C(f)$ without finding a better protocol?

Methods (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

If we find a protocol Π , then we know $C(f)$ is at most $C(\Pi)$.
What if we don't know any protocol Π ?

- Could we upper-bound $C(f)$ without knowing Π ?

What if the only protocols we find seem really lousy?

- Could we lower-bound $C(f)$ without finding a better protocol?

TL;DR: yup.

Fooling Set Method (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO

Tiling Method (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO

2-Party Discrepancy Method (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO

Multi-Party Problem (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO

Multi-Party Discrepancy Method (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

**Multi-Party
Discrepancy Method**

Other Variants

Non-Deterministic

Randomized

TODO

Non-Deterministic (Jake)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO

Randomized (Max)

Communication Complexity

Jake Kinsella
and Max von Hippel

Introduction

Examples

Methods

2-Party Problem

Fooling Set Method

Tiling Method

Discrepancy Method

Multi-Party Problem

Multi-Party

Discrepancy Method

Other Variants

Non-Deterministic

Randomized

TODO