

The Tiling Method

Max von Hippel

March 23, 2021

Consider a two-party communication problem, in which the participants



(a) Alice

and




(b) Bob

participate to compute a function:

$$f: \underbrace{\mathbb{B}^n}_{\text{Alice's input}} \times \underbrace{\mathbb{B}^n}_{\text{Bob's input}} \rightarrow \underbrace{\mathbb{B}}_{\text{global output}}$$

The players can come up with a *protocol* $\Pi = (p_1, \dots, p_t)$, namely, for some natural $t \in \mathbb{N}$, a sequence of t -many functions $p_i: \mathbb{B}^\times \rightarrow \mathbb{B}^\times$ such that the communication between the players looks like this:



Suppose that there is a protocol Π for f consisting of t messages, but, there does not exist any protocol $\Pi^{[r]}$ for f consisting of fewer than t messages. Then we say t is the *communication complexity* of f , and we write $C(f) = t$.

Given some such function f , it would be nice if we could automatically compute a reasonable lower bound on its communication complexity. One way to do this is with the *tiling method*. We will give the method immediately, and in tandem, we will illustrate the method using the function $f(x, y) = x < y$ where x, y are integers in $\mathbb{Z} \setminus \{0, 1, 2, 3\}$, encoded in \mathbb{B} oolean. First, let $M(f)$ be the *matrix of f* , namely, the $2^n \times 2^n$ matrix whose (x, y) th entry is the value $f(x, y)$.

	000	001	010	011	100
000 = 0	0	1	1	1	1
001 = 1	0	0	1	1	1
010 = 2	0	0	0	1	1
011 = 3	0	0	0	0	1
100 = 4	0	0	0	0	0

Table 1: The matrix $M(<)$ for inputs $x, y \in \mathbb{Z} \setminus \{0, 1, 2, 3\}$. Values of x are given in the rows, while values of y are given in the columns. False (i.e. 0) values are marked red for clarity.

A *combinatorial rectangle* in $M(f)$ is any submatrix of M . We say a rectangle $A \times B$ in $M(f)$ is *monochromatic* if for all $x, x^{[r]}$ in A and $y, y^{[r]}$ in B , $M_{x,y} = M_{x^{[r]},y^{[r]}}$.


	0	1	2	3	4
0	0	1	1	1	1
1	0	0	1	1	1
2	0	0	0	1	1
3	0	0	0	0	1
4	0	0	0	0	0

	0	1	2	3	4
0	0	1	1	1	1
1	0	0	1	1	1
2	0	0	0	1	1
3	0	0	0	0	1
4	0	0	0	0	0

	0	1	2	3	4
0	0	1	1	1	1
1	0	0	1	1	1
2	0	0	0	1	1
3	0	0	0	0	1
4	0	0	0	0	0

Figure 2: Some example rectangles of $M(<)$. The first rectangle, in **purple**, is monochromatically colored 0. The second rectangle, in **orange**, illustrates the flexibility of our rectangle definition, namely, that the rectangle does not actually need to be connected in the original matrix (although, the entries cannot be permuted). Neither the **second** nor **third** rectangle is monochromatic.

Without loss of generality, suppose the protocol Π begins with Alice sending a bit b . Then *certainly* $M(f)$ partitions into two rectangles L and R, where L considers all the scenarios where the bit Alice sent was 0, and R considers all the scenarios where the bit Alice sent was 1. Notice that L and R are strictly smaller than $M(f)$; in fact, the number of cells in L plus the number of cells in R equals the number of cells in $M(f)$. This is what we mean by a *partition*.



Consider the L branch.