CLI Output Screenshots: Router2 (show commands:ip ospf neighbor, interface brief, standby brief, ip bgp summary, ping)

```
ROUTER2>
ROUTER2>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet0/0     unassigned      YES unset  up                    up
GigabitEthernet0/0.10  unassigned      YES unset  up                    up
GigabitEthernet0/0.20  unassigned      YES unset  up                    up
GigabitEthernet0/1     10.0.0.2        YES manual up                    up
GigabitEthernet0/2     unassigned      YES unset  administratively down down
Vlan1                  unassigned      YES unset  administratively down down
ROUTER2>show standby brief
              ^
% Invalid input detected at '^' marker.

ROUTER2>show standby brief
              ^
% Invalid input detected at '^' marker.

ROUTER2>enable
ROUTER2#show standby brief
                     P indicates configured to preempt.
                     |
Interface   Grp  Pri P State    Active          Standby         Virtual IP
Gig         10   100   Active   local           unknown         192.168.10.254
Gig         20   100 P Active   local           unknown         192.168.20.254
ROUTER2#
ROUTER2#show ip bgp summary
BGP router identifier 10.0.0.2, local AS number 65002
BGP table version is 2, main routing table version 6
0 network entries using 0 bytes of memory
0 path entries using 0 bytes of memory
0/0 BGP path/bestpath attribute entries using 0 bytes of memory
0 BGP AS-PATH entries using 0 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
Bitfield cache entries: current 1 (at peak 1) using 32 bytes of memory
BGP using 32 total bytes of memory
BGP activity 0/0 prefixes, 0/0 paths, scan interval 60 secs

Neighbor        V    AS MsgRcvd MsgSent   TblVer  InQ OutQ Up/Down  State/PfxRcd
10.0.0.1        4 65001      39      40        2    0    0 00:14:48        4

ROUTER2#ping 192.168.10.254

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.10.254, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/0 ms

ROUTER2#
```