
# Surrogate modelling for GISAXS reconstruction




Maksim Zhdanov<sup>1</sup>, Lisa Randolph<sup>2</sup>, Marina Ganeva<sup>3</sup>, Thomas Kluge<sup>1</sup>, Christian Gutt<sup>2</sup> and Nico Hoffmann<sup>1</sup> Helmholtz-Zentrum Dresden-Rossendorf, <sup>2</sup> Universität Siegen, <sup>3</sup> Forschungszentrum Jülich

## Experimental setup



#### Inverse problem



#### Challenges

Inverse problem is ill-posed

Posterior distribution is complex due to ambiguities


Reconstruction via simulation is highly time-consuming

Uncertainty estimation is desired

## Solution: Approximate Bayes Computation + Surrogate model

**Posterior Acceptance criterion** Time **Prior** BornAgain [1] thickness 50k samples  $\mathbf{f}:\mathbf{y}\to\mathbf{X}$  $\mathbf{y} \sim \mathbf{Uniform}(0, \mathbf{I})$ 32 hours thickness sample roughness N times thickness 50k samples roughness 1 minute Surrogate model  $\mathbf{f}:\mathbf{y}, heta o \mathbf{X}$ roughness

#### Simulation



## Surrogate model

Convolutional neural network

Optimized via MSE loss

Wasserstein distance  $\mathbf{W_{|y|}(\mathbf{p_{BA}},\mathbf{p_{SM}})=0.03}$ 

## Summary

Interpretable and trustworthy reconstruction

Remarkable computation time reduction w.r.t.

BornAgain

[1] Pospelov, Gennady et al. "BornAgain: software for simulating and fitting grazing-incidence small-angle scattering." Journal of Applied Crystallography 53 (2020): 262 - 276.





