

Blockchains & Cryptocurrencies

Anonymity in Cryptocurrencies III / Scaling I



Instructors: Matthew Green & Abhishek Jain
Johns Hopkins University - Spring 2019

Housekeeping

- 3rd reminder: midterm Weds!
 - You can write a “cheat sheet”, handwritten, US letter sized paper, both sides
 - Includes today's lectures
- Assignment 2 due end of day

News?

News?

BITCOIN

Bitcoin [BTC] transaction numbers in Venezuela nosedive as country goes through acute power outage



Published 2 hours ago on March 11, 2019

By **Akash Anand** 

Review stuff (from last time)

Pedersen Commitments

- We need a cyclic group. $G = \langle g \rangle$ where it is hard to find x given (g, g^x) — AKA the “discrete log problem” (DLP) is hard
 - E.g., G can be a subgroup of a finite field $\{1, \dots, p-1\}$ where exponentiation/multiplication are modulo p
 - We also need two public generators: g, h
such that nobody knows the discrete log of g resp. h (vice versa)
 - Commitment to message: pick random $r \in \{0, \dots, groupOrder - 1\}$, compute: $C = g^m \cdot h^r$
 - To open the commitment, simply reveal (m, r)

Pedersen Commitments

- Why is this secure?
- **Hiding:** If g, h are generators, then h^r is a random element of the group, so. $C = g^m \cdot h^r$ is too
- **Binding:** Let q be the group order. Let $h = g^x$ for some unknown x . Assume an attacker can find $(m, r) \neq (m', r')$ such that $g^m h^r = g^{m'} h^{r'}$. Then it holds that:

$$g^m g^{xr} = g^{m'} g^{xr'} \quad \text{and thus,}$$

$$m + xr = m' + xr' \text{ mod } q$$

We can solve for x , which means solving the DLP!

Confidential Transactions

- Pedersen commitments are additively homomorphic:

- Commit to “m1”:

$$C_1 = g^{m_1} h^{r_1}$$

- Commit to “m2”:

$$C_2 = g^{m_2} h^{r_2}$$

- Now multiply the two commitments together:

$$\begin{aligned} C_3 &= C_1 \cdot C_2 \\ &= g^{m_1} h^{r_1} \cdot g^{m_2} h^{r_2} \\ &= g^{m_1+m_2} h^{r_1+r_2} \end{aligned}$$

Notice that C_3 is a commitment to the sum m_1+m_2
(under randomness r_1+r_2)

Confidential Transactions

- Introduced by Maxwell
 - Does not provide privacy for the identity of the input transactions, can be combined with CoinJoin or ringsides
 - Does allow you to hide the value of input transactions
 - Basic idea: use a Pedersen commitment to each transaction value, rather than revealing this in cleartext $C = g^v h^r$
 - Do a CoinJoin, and use additive property of Pedersen commitments to sum the values and then subtract each output commitment (board)

MimbleWimble (Grin)

- Combines CoinJoin with Confidential Transactions, provides both services in a single network

Zerocoin (MGGR14)


- Proposed as an extension to Bitcoin in 2014
 - Requires changes to the Bitcoin consensus protocol!
- I can take Bitcoin from my wallet
 - Turn them into 'Zerocoins'
 - Where they get 'mixed up' with many other users' coins
 - I can redeem them to a new fresh Wallet



Zerocoin

- Zerocoins are just numbers
- Each is a digital commitment to a random serial number
- Anyone can make one!

823848273471012983




Minting Zerocoin

- Zerocoins are just numbers
 - Each is a digital commitment to a random serial number SN
 - Anyone can make one!

$$C = \text{Commit}(SN; r)$$


$$C = g^{SN} h^r \bmod p$$

823848273471012983




Minting Zerocoin

- Zerocoins are just numbers
- They have value once you write them into a valid transaction on the blockchain
- Valid: has inputs totaling some value e.g., 1 bitcoin




Redeeming Zerocoin

- You can redeem zerocoins back into bitcoins
- Reveal the serial number & Prove that it corresponds to some Zerocoin on the chain
- In exchange you get one bitcoin (if SN is not already used)



Spending Zerocoin

- Why is spending anonymous?
- It's all in the way we 'prove' we have a Zerocoin
- This is done using a zero knowledge proof



Spending Zerocoin

- Zero knowledge [Goldwasser, Micali 1980s, and beyond]
 - Prove a statement without revealing any other information
- Here we prove that:
 - (a) there exists a Zerocoin in the block chain
 - (b) we just revealed the actual serial number inside of it
- Revealing the serial number prevents double spending
- The trick is doing this efficiently!

Spending Zerocoin

- Zero knowledge [Goldwasser, Micali 1980s, and beyond]
- Prove a statement without revealing any other information (other than that a statement is true)

Spending Zerocoin

- Zero knowledge [Goldwasser, Micali 1980s, and beyond]
 - Prove a statement without revealing any other information
- Here we prove that:
 - (a) there exists a Zerocoin (commitment) in the block chain
 - (b) the thing we revealed is the opening to that commitment
- Revealing the serial number prevents double spending
- The trick is doing this efficiently!

Spending Zerocoin

- Possible proof statement (not efficient, see CryptoNote):
 - Public values: list of Zerocoin commitments C_1, C_2, \dots, C_N
Revealed serial number SN

- Prove you know a coin C and randomness r such that:

$$C = C_1 \vee C = C_2 \vee \dots \vee C = C_N \\ \wedge C = \text{Commit}(SN; r)$$

- Problem: using standard techniques, this ZK proof has cost/size $O(N)$

Spending Zerocoin

- Zerocoin (actual protocol)
 - Use an efficient RSA one-way accumulator
 - Accumulate C_1, C_2, \dots, C_N to produce a short value A
 - Then prove knowledge of a short witness s.t. $C \in \text{inputs}(A)$
 - And prove knowledge that C opens to the serial number

Requires a DDL proof (**~25kb**)
for each spend. In the block chain.

Spending Zerocoin

- Zerocoin (actual protocol)
 - Use an efficient RSA one-way accumulator
 - Accumulate C_1, C_2, \dots, C_N to produce a short value A
 - Then prove knowledge of a short witness s.t. $C \in inputs(A)$
 - And prove knowledge that C opens to the serial number

Requires a DDL proof (**~25kb**)
for each spend. In the block chain.

Anonymity set comparison

- Anonymity set in CoinJoin:
 - **M**: where **M** is number of inputs in the transaction (bounded by TX size)
- Anonymity set in ByteCoin/RingCT:
 - **N**: where **N** is the number of inputs allowed in a transaction (bounded by TX size, 7-11 historically)
- Anonymity set in Zerocoin:
 - **P**: where **P** is number of total Zerocoins minted on the blockchain thus far* (independent of TX size)

Scaling

The problem

- Bitcoin transaction rate: 5-7 tx/sec
 - Bounded by block size (Segwit helps), TX size
 - All transactions must be globally verified, stored
- Ethereum: 15 transactions per second if they're small
- Visa: 24,000/sec peak (150M/day globally)
- WeChat 256,000/sec peak

Faster computers?

- Why not just build faster computers?

Faster computers?

- Why not just build faster computers?
 - Loss of decentralization
 - Eventually we saturate links, due to broadcast network
 - Replicated global state falls apart
 - Scaling is possible (see Visa, WePay etc.) but it requires dedicated, centralized servers

Can we do better?

Can we do better?

- Current ideas:
 - “Off chain”
 - “Sharding”
 - New consensus algorithms

Off-chain transactions (channels)

- In current Bitcoin-style networks, every transaction appears on the blockchain
 - This allows the whole network to verify financial integrity
 - I.e., we can't go off and do transactions elsewhere, accidentally/deliberately inflate the money supply
- But why does the network need to see every transaction?


Off-chain transactions (channels)

- Overarching idea:
 - If a transaction doesn't affect anyone else (except for the parties willing to risk money), chain doesn't need to see it
- Simplest example (but centralized):
 - Multiple parties deposit money into an exchange
 - Exchange is just a centralized bank, so everyone can quickly transmit money by adjusting balances
 - Only withdrawals need on-chain transactions

Off-chain transactions (channels)


- Off-chain exchange example still risks loss of funds
 - If the exchange disappears, your money goes with it
 - See e.g., QuadrigaCX
- The only benefit here is that the rest of the network can't lose money, e.g., due to inflation

Channels: Step 1




Channels: Step 2

* A pays B 0.2BTC




Channels: Step 2

* A pays B 0.2BTC




Channels: Step 3.....

* B pays A .5 BTC



Channels: Closure

- * Either party posts the most recent version of the transaction to the blockchain (all older versions get ignored)



Dispute resolution

- * What if someone posts an older, out-of-date version?
- * What if nobody signs the first “closure” transaction? How do you escape a payment channel in the worst case?