	Biomedical Limited, No 1 Ohimege Road, Industrial Estate, Ilorin Kwara State, PMB 1449			MASTER COPY STAMP HERE
	Title: **SOP for Cleaning and Operation of Semi-Automatic Filling Machine**			
Department	Unit:	**BML-PDF-PR-010**	**Revision No.:**	06
			Effective Date:	**April, 2025**
PRODUCTION	PROCESSING		**Next Review Date:**	**March, 2027**
Prepared By:		**Checked By:**	**Approved By:**	
Sign /date		**Sign /date**	**Sign /date**	

1.0 OBJECTIVE:

This SOP covers the procedure for cleaning and operating of computerized semi-automatic Filling Machine

2.0 SCOPE:

To provide written guidelines for cleaning and operating the computerized Semi-Automatic Filling Machine

3.0 RESPONSIBILITIES/ACCOUNTABILITIES:

Production Pharmacist, Production, Q.A Officer, Filling Machine Operators**.**

4.0 ABBREVIATION AND DEFINITIONS

N/A

5.0 PROCEDURES

Precaution:

- Always wear your proper overall in the Filling Room.
- Ensure that the machine is always clean and dry.
- Always mop up the floor.

Cleaning

-Put '**ON'** the switch from the mains.
-Then switch '**ON'** the machine.
-Press **'START'** button on the screen.
-Select 'English' Language Option.
-At the bottom left hand side of the screen press '**Cleaning Off**' button.
-Allow hot WFI to flow through the three nozzles for 5 minutes.
-Use a dedicated clean napkin soaked in 70% IPA to clean the body of the machine until clean.

Filling operation

-Calibrate the volume of the solution by pressing the '**CAPACITY'** button at the top left hand side of the screen (after selecting the 'English' button).
-Select **'1#channel set'** to set the volume of the first nozzle.

BIOMEDICAL LTD

- Select from numbers 1-8 the number that corresponds to the volume to be filled and enter the number in the Group box at the top left hand corner of the screen.
- Press Enter.
- Press Enter again at the bottom left hand side of the screen.
- Repeat this for the second and third nozzles by selecting **2#channel set** and **3# channel set** respectively.
- Set time interval for filling by pressing the '**INTERVAL**' button.
- Fix the bags on the nozzles.
- Then press the **'FILLING'** button to fill the bags with solution.
- Once the bag is filled, the solution will automatically stop.
- Remove the pouch, then cork with Stoppers provided within 2 seconds.
- Put the pouches in the container.
- Allow IPQC to check volume every 30 minutes of operation.
- Change filter after each batch filling.
- At the end of each operation, do line clearance, (See SOP for Line Clearance), and document.
- Record the total number of pouches filled.

6.0 REFERENCE AND ENCLOSURE

Manufacturer's Manual

7.0 TRAINING INVOLVEMENT

Production manager	Production pharmacist
Sectional heads	All production staff

8.0 DISTRIBUTION AND CONTROL:

MASTER COPIES	DOCUMENTATION UNIT
CONTROLLED COPIES	PRODUCTION DEPARTMENT

BIOMEDICAL LTD

9.0 CHANGE HISTORY

CURRENT REVISION	SUPERSEDE	REASON FOR REVIEW
00	Nil	First issue
06	05	• Change in sop format. • Inclusion of traceability of enclosures to parent SOP

BIOMEDICAL LTD