




Roadmaps ▾

AI Tutor ▾

Login

Sign Up

Top 100 Node.js Interview Questions and Answers

[Fernando Doglio](#)

A job interview (in any industry, but particularly in the development world) can be a thrilling and daunting experience at the same time.

It doesn't matter if you're an experienced developer or just someone getting started; a solid understanding of Node.js fundamentals, modern best practices, and the latest trends is key to your success.

This article is your ultimate guide, designed for both job hunters looking to get that job and hiring managers seeking to craft the perfect set of Node.js interview questions.

In this Article



Getting ready for your next interview

Test yourself with Flashcards

Questions List



If, on the other hand, you're looking for a more detailed guide on how to become a Node.js developer, you might want to check out [this roadmap](#) instead.

Getting ready for your next interview

Before diving into the full list of Node.js interview questions and answers, remember that a great interview is like a conversation between two friends. It's not just about what you know and what you can bring to the table, but also about what the company is looking for, what their expectations are, and the working environment they offer.

Here are some key areas to focus on in your preparation:

- **Master the fundamentals:** Make sure to review and master the core concepts like the event loop, asynchronous programming with callback functions, async functions, asynchronous operations, and Node.js's non-blocking I/O model.
- **Practice problem-solving:** This is going to be the main skill you'll use during your day-to-day, so be ready to demonstrate your skills with real-world coding challenges. Focus on how you approach a problem, break it down, and write clean, efficient JavaScript code.

- **Showcase your projects:** If you have any, be ready to discuss your past projects. Explain the architectural decisions you made, the challenges you faced, and how you solved them.
- **Stay current:** The Node.js (and JavaScript) ecosystem is constantly evolving. Familiarize yourself with the latest trends and tools, such as the rise of TypeScript, modern frameworks, and architectural patterns like Microservices and Serverless.

Test yourself with Flashcards

You can either use these flashcards or jump to the questions list section below to see them in a list format.

< 0 / 100 >

✓ Knew 0 Items ✨ Learnt 0 Items ▷ Skipped 0 Items ↺ ResetProgress

Beginner Questions

What is Node.js, and how is it different from a browser's runtime environment?

[Click to Reveal the Answer](#)

 Already Know that Didn't Know that Skip Question

Questions List

If you prefer to see the questions in a list format, you can find them below.

Beginner Questions

What is Node.js, and how is it different from a browser's runtime environment?

Node.js is a server-side JavaScript **runtime environment** that allows you to execute **code** outside of a web browser. While a browser's runtime is for front-end web development, Node.js is for building back-end services, command-line tools, and network applications.

Explain the purpose of the JavaScript engine (V8) in Node.js.

The V8 **JavaScript engine** compiles JavaScript code into machine code, allowing Node.js to execute it very quickly. It's the same engine used in Chrome, which is why Node.js is so fast.

Why is Node.js considered single-threaded, and how does the event loop handle async operations?

Node.js is single-threaded in that it has only one main thread for **code execution**. However, it handles **asynchronous operations** using the **event loop**. When an I/O operation (like reading a file) is requested, Node.js offloads it to a separate thread pool. The **event loop** then continues with

other tasks and, when the I/O operation is complete, a **callback function** is put on the **event queue** to be executed.

How do you create a simple web server using the built-in HTTP module?

You can create a simple **web server** by using the **http** module. You use **http.createServer()** to create the server and then **server.listen()** to start it on a specific port.

What's the difference between blocking and non-blocking code execution?

Blocking code execution stops the entire process until a task is complete. Non-blocking code execution, on the other hand, allows the process to continue with other tasks while an operation (like an I/O request) is being handled in the background.

How do you use the require() function to import a node module?

The **require()** function is used to load and cache node module files. For example, **const http = require('http');** imports the built-in module ("http") into your code.

What is Node Package Manager (NPM), and how do you use it to manage packages?

Node Package Manager (NPM) is a package management tool for Node.js. You use it via the command line interface to install, update, and manage dependencies for your projects.

Differentiate between local and global package installation using the command line interface.

A local installation (`npm install <package_name>`) installs the package in the `node_modules` folder of your current project, making it available only to that project. A global installation (`npm install -g <package_name>`) installs the package in a system-wide folder, making it available to all projects and accessible from the command line.

Explain the purpose of the package.json file.

The `package.json` file holds metadata about a project, including its name, version, and scripts. Most importantly, it lists the project's dependencies, making it easy to share and reproduce the project environment.

How do you handle error handling in asynchronous code with a callback function?

A common convention for error handling with a callback function is the "error-first callback" pattern. The first argument of the callback function is reserved for an error parameter, which will be `null` if the operation was successful.

What are Promises, and what problem do they solve with asynchronous code?

Promises are objects that represent the eventual completion or failure of an asynchronous operation. They address callback hell by providing a cleaner, more readable way to chain async functions.

Explain `async/await` and how it improves readability for `async` function calls.

`async/await` is a syntactic sugar built on top of Promises. It allows you to write asynchronous code that looks and behaves like synchronous code, making it much easier to read and maintain.

How do you use the `fs` module for FS operations?

The `fs` module provides api functions for interacting with the file system. For example, you can use `fs.readFile()` to read a file or `fs.writeFile()` to write data.

Explain the difference between synchronous and asynchronous file system operations.

Synchronous **file system operations** block the event loop until they are complete. Async operations, on the other hand, don't block the **event loop**; they take a **callback function** that is executed when the operation is finished.

What is a Buffer class in Node.js, and when would you use it for handling binary data?

The buffer class is used to represent a raw memory allocation outside the V8 heap. It's essential for handling binary data, such as images or encrypted information.

What is a stream, and when is it useful for writing data or handling large files?

A stream is an abstract interface for working with streaming data. It's particularly useful when dealing with large files or network communication, as it allows you to process data in small chunks rather than loading it all into memory at once.

Explain the role of the EventEmitter.

The EventEmitter is a class in Node.js that allows you to create custom events and listen for them. It's a key part of event-driven programming, enabling objects to communicate with each other through a notification mechanism.

What are `process.nextTick()` and `setImmediate()` in the context of the event loop?

`process.nextTick()` schedules a callback function immediately to be executed on the current event loop cycle, before any I/O. `setImmediate()` schedules a callback to be executed in the next cycle of the event loop.

How do you get and set environment variables in a Node.js application?

You can access env variables using the `process.env` object. For example, `process.env.PORT` would give you the value of the PORT environment variable. You can also take advantage of the `dotenv` module, which parses `.env` files in your local folder and turns their content into environment variables during the execution of your scripts.

What is a middleware function in the context of Express.js?

A middleware function is a function that has access to the request and response objects and can modify them or terminate the request-response cycle. It's often used for tasks like authentication, logging, and error handling.

How do you define a route in an Express.js application to handle an HTTP request?

You define a route using the `app.<method>(path, callback)` syntax, where `<method>` is the HTTP verb (get, post, put, delete, etc.), `path` is the URL, and `callback` is the handler for the HTTP request.

What is the difference between `exports` and `module.exports`?

`module.exports` is the actual object that is returned from a `require()` call. `exports` is a reference to `module.exports`. If you want to export a single object or class, you should use `module.exports`. If you want to export multiple things, you can add properties to the `exports` object.

Describe the read-eval-print loop (REPL) in Node.js.

The read-eval-print loop (REPL) is an interactive CLI tool that lets you execute code one line at a time. It's useful for testing small snippets of code and exploring the built-in Node object methods.

How would you debug a Node.js application?

You can debug a Node.js application using the built-in debugger (`node inspect`) or by using an integrated debugger in a code editor like VS Code.

List some common Node.js API functions.

Some common Node.js API functions include `fs.readFile()` , `http.createServer()` , `path.join()` , and `os.cpus()` .

What is an error-first callback, and what does the error object represent?

An error-first callback is a pattern used to create functions where the first argument is an error object. If an error occurred, that object will contain details about it; otherwise, it will be `null` . You can use this pattern when dealing with callback-dependent logic in your code.

What is the role of the event queue in the event loop?

This queue (also known as "callback queue") is where callback functions are placed after an asynchronous operation completes. The event loop checks the queue and executes these callbacks one by one when the main thread is free.

Explain how Node.js's single-threaded model handles multiple requests.

Node.js handles many requests at the same time efficiently because of its non-blocking I/O and the event loop. When an incoming request requires an asynchronous operation, Node.js doesn't wait; it offloads the task and processes the next request. The associated callback function for the first request is executed later, once the operation is finished.

How do you execute JavaScript code from a file?

You can execute code from a file by running the command **node** **<filename.js>** in your terminal.

What is a control flow function?

A control flow function is a function that manages the order of execution of other functions, especially in asynchronous programming, to ensure that tasks are performed in the correct sequence.

Mid-Level Questions

How would you avoid callback hell when making several asynchronous function calls?

The most effective way to avoid callback hell is to use Promises or **async/await**. These patterns allow you to chain async function calls in a much more readable, sequential manner, making the control flow of your application easier to manage.

Explain the concept of event-driven programming in Node.js.

EDP is a paradigm where the flow of a program is determined by events, such as user actions, sensor outputs, or messages from other programs. Node.js is naturally suited for this, as it uses the event emitter to fire events and allows other parts of the application to respond to them via event listeners.

Describe the phases of the Node.js event loop.

The event loop has several distinct phases: timers, pending callbacks, idle/prepare, poll, check, and close callbacks. The poll phase is the most important; it retrieves new I/O events and executes their callbacks.

How does the event loop prioritize different async function calls?

The event loop has a specific order of operation. For example, **`process.nextTick()`** callbacks are executed before any other events in the same cycle, while **`setImmediate()`** callbacks are executed in the subsequent cycle. Timers have their own queue and are executed as close as possible to their scheduled time.

What is the purpose of the libuv library?

Libuv is a C++ library that provides Node.js with its non-blocking I/O functionality. It's responsible for managing the pool of threads, which handles I/O tasks in the background, freeing up the main single thread to handle more requests.

Differentiate between `child_process.fork()` and `child_process.spawn()` in the child process module.

`child_process.spawn()` launches a new process with a specific command, streaming its I/O. **`child_process.fork()`**, on the other hand, is a special case of **`spawn()`** that's designed for Node.js modules. It establishes a communication channel between the parent and child processes, allowing them to exchange messages.

When would you use worker threads instead of a child process?

Worker threads are ideal for CPU-intensive tasks that would otherwise block the main single thread. Unlike child processes, they share memory, making it easier to exchange data, but they should only be used for computation, not I/O.

How does Node.js handle garbage collection?

Node.js uses the V8 engine's garbage collector. It works in two phases: the "Scavenge" phase for new objects and the "Mark-Sweep" and "Mark-Compact" phases for older, more persistent objects.

What are some common security vulnerabilities in Node.js applications, and how can you mitigate them?

Common vulnerabilities include cross-site scripting (XSS), SQL injection, and insecure dependencies. You can mitigate these by using security middleware, validating all user input, and regularly updating your node package manager dependencies.

How would you handle sessions and authentication in a Node.js application?

You can handle sessions and authentication using libraries like Passport.js. It's common to use JSON Web Tokens (JWT) for stateless authentication or session-based authentication with a session store like Redis.

What is CORS (Cross-Origin Resource Sharing), and how do you handle it with a Node.js HTTP server?

CORS is a security feature that prevents a web page from making requests to a different domain. You can handle it on a Node.js web server by setting specific HTTP headers or by using a middleware library like the **cors** package in Express.js.

Describe how to connect a Node.js application to a database.

You can connect to a database using a dedicated Node.js module for that database (e.g., **pg** for PostgreSQL or **mongoose** for MongoDB). These libraries provide an API to establish a connection, execute queries, and handle the results.

How do you assure consistent code style across a team using a linter?

You can use a linter like ESLint to automatically check for and report on code that doesn't follow a specific, consistent code style. It can be integrated into your development workflow and CLI tool to ensure everyone adheres to the same standards.

What are the advantages of using a framework like Express.js over the native HTTP module?

Express.js simplifies the process of building a web server by providing a robust set of features, including routing, middleware, and templating. It saves a lot of boilerplate work that would be required with the native HTTP module.

How do you handle errors gracefully in an Express.js application?

You can handle errors in Express.js using a dedicated error-handling middleware with four arguments: (**err** , **req** , **res** , **next**). This function is executed when an error is passed to **next()** , allowing you to centralize your error responses.

Explain the role of a router in Express.js.

A router in Express.js is a modular, mini-application that can handle specific routes. It helps you organize your application by grouping related routes and middlewares together, making your code more maintainable.

How do you process command-line arguments in Node.js?

You can access command line interface arguments through the **process.argv** array. The first two elements are the Node.js path and the script path, respectively; subsequent elements are the arguments passed by the user.

What is the purpose of process.env.NODE_ENV?

process.env.NODE_ENV is a crucial environment variable that signals to your application whether it's running in a development, production, or testing environment. Many node module dependencies and frameworks use this variable to optimize their behavior.

How do you manage secrets and configuration in a production Node.js application?

It's best practice to use env variables to store sensitive information like API keys and database credentials. You can use a library like **dotenv** for development, and a service like Vault or a cloud provider's secret manager for production.

Explain the concept of clustering in Node.js for handling multiple instances.

Clustering allows you to take advantage of multi-core systems by creating multiple instances of your Node.js application. The **cluster** module uses a master process to manage worker processes, distributing incoming load among them and ensuring high availability.

**How do you test a Node.js application?
Name some popular testing frameworks.**

You test a Node.js application by writing unit tests, integration tests, and end-to-end tests. Popular testing frameworks include Jest, Mocha, and Chai.

What is a Test Pyramid?

The Test Pyramid is a testing strategy that suggests you should have a large number of fast-running unit tests, a smaller number of integration tests, and a very small number of slow end-to-end tests. This approach ensures a quick feedback cycle while still providing full coverage.

What is GraphQL, and how does it compare to a traditional REST API for handling incoming requests?

GraphQL is a query language for your API. Unlike a **REST** API, which has fixed data structures for its endpoints, **GraphQL** allows the client to request exactly the data it needs, leading to more efficient endpoints and reduced over-fetching (when you request more information than what you actually need).

How would you implement a file upload feature in Node.js?

You would use a middleware designed for handling **multipart/form-data** requests, such as **multer**. **multer** parses the incoming request and makes the file available to your route handler, which can then save it to the file system.

What is a WebSocket, and when would you use it over a standard HTTP request?

A WebSocket provides a full-duplex communication channel over a single TCP connection. It's useful for real-time applications like chat apps or live dashboards, where you need a persistent connection and two-way communication without the overhead of repeated HTTP request cycles.

Explain how to manage asynchronous operations for multiple tasks.

You can use Promises with **Promise.all()** to run multiple tasks concurrently and wait for all of them to complete. This is much more efficient than waiting for one task to finish before starting the next.

Describe how Node.js communicates with external services.

Node.js typically communicates with external services via HTTP requests using the native **http** module or a JavaScript library like **axios** or **node-fetch**. You can also use other protocols like gRPC for high-performance communication.

What is the crypto module, and what is it used for?

The **crypto** module provides cryptographic functionality, including hashing, encryption, and decryption. It's used to secure sensitive data, such as user passwords and API tokens.

How does the thread pool fit into the Node.js architecture?

The thread pool is part of **libuv** and is used to offload blocking tasks into multiple threads, such as complex calculations or I/O operations, from the main single thread. This allows the event loop to continue processing other requests without being blocked.

Explain how Node.js's control flow can be managed using Promises and async/await.

Promises and **async/await** provide a structured way to manage control flow in an asynchronous programming environment. **async/await** allows you to write sequential-looking code that pauses execution until a Promise resolves, while Promises themselves allow for powerful chaining and parallel execution.

Advanced Level Questions

How would you architect a scalable and maintainable Node.js application?

I would use a modular architecture, breaking the application into smaller, single-purpose components. I would also leverage microservices or serverless patterns for scalability, use a message queue for inter-service communication, and implement a clear separation of concerns to ensure maintainability.

Explain the principles of Microservices and why Node.js is a good fit for this architecture.

Microservices is an architectural style where a large application is broken down into a collection of small, independent services. Node.js is a great fit because its event-driven programming model and efficiency with I/O-bound tasks allow it to handle many different requests and communicate between services effectively.

How do you handle inter-service communication in a microservices architecture?

There are several ways. You can use HTTP servers with RESTful endpoints, but for better performance and reliability, I prefer message queues (like RabbitMQ or Kafka) or a high-performance framework like gRPC.

Discuss the pros and cons of using a Serverless architecture with Node.js.

Pros: No server management, auto-scaling, and a pay-per-use model that can reduce costs. Cons: Vendor lock-in, cold start latency, and potential for more complex debugging and deployment.

How would you monitor and observe a production Node.js application?

I would use a combination of logging, metrics, and tracing. I would use a centralized logging service (e.g., Elastic Stack) to collect and analyze application logs, a metrics service (e.g., Prometheus) to track performance, and a tracing tool (e.g., OpenTelemetry) to trace requests across different services.

What are some best practices for handling CPU-intensive tasks in Node.js?

The best practice is to offload these tasks to other processes or services so they don't block the main single thread. I would use worker threads for in-process computation or a dedicated child process for more isolated tasks.

How would you optimize the performance of a high-traffic Node.js API?

I would start by implementing caching (at the application or database level), using clustering to utilize all available CPU cores, and optimizing database queries. I'd also ensure that I'm using non-blocking I/O and modern asynchronous programming techniques.

What are the benefits of using TypeScript in a Node.js project?

TypeScript adds static typing to your JavaScript syntax, which helps catch bugs early in development. It also provides better tooling, improved readability, and makes your codebase more robust and easier to refactor, especially in large-scale applications.

How would you set up a CI/CD pipeline for a Node.js application?

I would use a CI/CD platform like Jenkins, GitHub Actions, or GitLab CI. The pipeline would include steps to install dependencies, run tests, build a Docker image, and then deploy the container to a staging or production environment.

Describe the difference between a `fork()` and a `spawn()` process model.

`spawn()` launches a new process, and you get a stream to its stdin, stdout, and stderr. `fork()` is a special case of `spawn()` that is specifically for spawning Node.js processes. It includes a communication channel, allowing the parent and child to pass messages between them.

How do you prevent resource starvation in a Node.js application?

You can prevent resource starvation by ensuring that I/O operations have a timeout and that you handle them gracefully. Using a well-managed thread pool and load balancing across many different instances also helps.

How do you implement secure HTTP headers in an Express.js application?

You could use a middleware like `helmet` to automatically set a number of security-related HTTP headers, such as `X-Content-Type-Options` , `Content-Security-Policy` , and `Strict-Transport-Security` .

Explain what OpenTelemetry is and its role in modern applications.

OpenTelemetry is an open-source observability framework for generating and collecting telemetry data (metrics, logs, and traces). Its role is to provide a standardized way to instrument applications, making it easier to monitor and troubleshoot distributed systems.

What are the various ways to handle unhandled exceptions in a Node.js process?

You can use the `process.on('uncaughtException', ...)` event listener, but the recommended approach is to have a dedicated domain or middleware to catch errors and gracefully shut down the application.

How does the Node.js process model affect its scalability?

The Node.js single-threaded process model is great for I/O-bound applications, as it can handle a large number of concurrent connections efficiently. For CPU-intensive tasks, however, it can be a bottleneck, which is why we use clustering or worker threads to scale.

How does Node.js use the `require.resolve()` function, and when would you use it?

The `require.resolve()` function is used to find the full path to a module without actually loading it. It follows the same module resolution algorithm as `require()` but returns the resolved file path instead of the module itself. You would typically use `require.resolve()` in scenarios where you need to check if a module is available or to get its path for some other operation, such as dynamically loading a module or checking its location on the file system. This can be useful for tools or build systems that need to

locate dependencies without the side effects of loading the module immediately.

How do you ensure high availability and load balancing for a Node.js service?

You can use a load balancer (e.g., Nginx, HAProxy) to distribute multiple requests across different instances of your application. These instances would typically be running on different machines or containers to ensure high availability.

Explain the concept of a reactor pattern.

The reactor pattern is an I/O handling design pattern. It's a key part of how Node.js works, as it handles a large number of concurrent connections with a single thread by demultiplexing incoming events and dispatching them to their respective handlers.

What is the significance of the zlib module?

The **zlib** module provides compression and decompression functionality. It's significant because it's the module that Express.js's compression middleware uses to compress HTTP servers responses, which reduces bandwidth and speeds up page load times.

Describe the net and dgram modules.

The **net** module is for creating TCP servers and clients, allowing for streaming communication. The **dgram** module is for UDP datagram

sockets, which are useful for applications where data delivery isn't guaranteed, like gaming or streaming.

What is Docker, and how can it be used to deploy Node.js applications?

Docker is a containerization platform that packages your application and all its dependencies into a single, isolated container. You can use it to deploy Node.js applications by creating a Dockerfile that specifies how to build an image with your code and dependencies.

How would you implement rate-limiting on an API?

For rate-limiting an API, you could use a middleware such as **express-rate-limit** to restrict the number of requests a user can make to an API over a period of time. This prevents abuse, protects your resources, and ensures fair usage for all clients.

What are the key differences between Bun, Deno, and Node.js?

Bun is an all-in-one JavaScript runtime with a focus on speed and built-in tools. Deno is a secure runtime that uses TypeScript by default and has a different module system. Node.js is the original, most mature runtime with the largest ecosystem.

How would you handle a large number of database connections efficiently?

I would use a connection pool. A connection pool maintains a set of open connections to the database, allowing your application to reuse them

instead of creating a new connection for every request, which is much more efficient.

Discuss the use of a message queue (e.g., RabbitMQ, Kafka) with Node.js.

A message queue is useful for decoupling services. Instead of one service directly calling another, it can send a message to a queue. This is great for handling long-running or background tasks, as it prevents the event loop from being blocked.

What are some of the performance trade-offs of using `async/await`?

While `async/await` improves readability, it can sometimes be slightly less performant than raw Promises due to the overhead of generating the state machine. However, the performance difference is usually negligible, and the code clarity is well worth the trade-off.

How would you implement a simple caching layer in a Node.js application?

I would use an in-memory cache like `node-cache` or a more robust solution like Redis. You can implement a middleware function that checks the cache for a response before it hits your route handler and, if not found, stores the result after the handler completes.

What is esbuild, and how does it relate to Node.js?

esbuild is a very fast JavaScript bundler and minifier. It relates to Node.js as a tool for preparing your code for production, making it smaller and faster

to load.

Explain event delegation in an event-driven system.

Event delegation is a pattern where, instead of adding an event listener to every single element, you add one to a parent element. When a child element is clicked, the event bubbles up to the parent, and you can determine which child was clicked.

How does the V8 engine optimize JavaScript code?

The V8 engine uses Just-In-Time (JIT) compilation. It parses the JavaScript code and converts it into a lower-level intermediate representation. It then uses a fast compiler to generate unoptimized machine code. If a function is run often, it's passed to an optimizing compiler to generate faster, more efficient machine code.

What is JWT (JSON Web Token), and how does it work with Node.js?

JWT is a compact, URL-safe means of representing claims to be transferred between two parties. In Node.js, you would use a library like **jsonwebtoken** to create a JWT upon successful authentication. The token is then sent to the client, which includes it in subsequent requests for authorization.

How would you handle internationalization and localization?

I would use a Node.js module like **i18next** or **react-intl**. These libraries help you manage translations, format dates and numbers according to

different locales, and serve the appropriate content based on the user's language settings.

What is Server-Side Rendering (SSR) with Node.js, and why would you use it?

SSR is when a web page's HTML is generated on the server for each request. You would use it for better SEO (since search engine crawlers can easily read the content) and improved initial load times, especially for complex applications.

Discuss the trade-offs of a monolithic vs. microservices architecture for a new project.

A monolithic architecture is simpler to develop and deploy initially, but it can become harder to scale and maintain over time. A microservices architecture is more complex to set up but offers greater scalability, resilience, and maintainability in the long run.

How do you protect against DDoS attacks on a Node.js server?

You can protect against DDoS attacks by using a reverse proxy (e.g., Nginx) or a CDN (e.g., Cloudflare) to absorb and filter malicious traffic before it reaches your **http server**. Implementing rate-limiting is also a good practice.

What is the util module used for?

The **util** module provides utility functions for a variety of tasks, such as inspecting objects, converting **callback function**-based APIs to Promise-based APIs, and more.

Explain the concept of telemetry and its importance.

Telemetry is the process of collecting data about an application's performance, health, and behavior. It's crucial for understanding how your application is performing in production, identifying bottlenecks, and debugging issues.

What is the significance of the Promise.all() and Promise.race() methods?

Promise.all() is significant because it allows you to run multiple promises concurrently and wait for all of them to resolve before continuing.

Promise.race() is for executing multiple promises and acting on the first one that either resolves or rejects.

Explain the difference between setImmediate() and setTimeout(fn, 0).

setTimeout(fn, 0) schedules a task to be run as soon as possible after the current event loop cycle, but it's subject to a minimum delay.

setImmediate(), on the other hand, runs its task in the next cycle of the **event loop**, making it more predictable for I/O-based tasks.

How do you stay updated with the latest trends and best practices in the Node.js community?

I would follow the official Node.js blog and release notes, listen to podcasts, read articles from influential developers, and participate in community discussions and conferences.

Join the Community

roadmap.sh is the 6th most starred project on GitHub and is visited by hundreds of thousands of developers every month.

Rank **out of 28M!**

357K

GitHub Stars

★ **Star us on GitHub**
Help us reach #1

+90k **every month**

+2.8M

Registered Users

👤 **Register yourself**
Commit to your growth

+2k **every month**

48K

Discord Members

🗨️ **Join on Discord**
Join the community

[Roadmaps](#) [Guides](#) [FAQs](#) [YouTube](#)

📌 **roadmap.sh** by @nilbuild

Community created roadmaps, best practices, projects, articles, resources and journeys to help you choose your path and grow in your career.

THE NEW STACK

The top DevOps resource for Kubernetes, cloud-native computing, and large-scale development and deployment.

DevOps · Kubernetes · Cloud-Native

 [Cookie Settings](#)